structure assembly. Thus, the method emphasises non-local interactions rather than local ones. One of the advantage of the method is that the method can directly be applied to oligomer targets. We will report the detailed description of the method and the results of benchmark tests.

2PT003 配列順序に依存しない構造関係性を用いた長い挿入配列の構造モデリング

Modeling structure of large insertion regions in homology modeling by utilizing non-sequential structure relationship

Yuki Nakagawa, Shintaro Minami, Kengo Sawada, George Chikenji (*Grad. Sch. of Engineering, Nagoya Univ.*)

Homology modeling is a powerful method for predicting protein structures by using a template structure having a similar amino-acid sequence to the target protein. However, in the region where the amino acid sequence is very different between the target and the template or large insertions exist, the predicted structure for such a region remains unreliable. If such an unreliable region is so large that three or four secondary structures have to be constructed, de novo modeling is needed. Currently, such de novo modeling, however, does not always provide an accurate prediction. Here, we propose a new homology modeling method that can effectively generate reasonable structure candidates of such unreliable regions. The idea of the method is based on the observation that if we search similar structures of the reliable region of the target protein in PDB by a non-sequential structure alignment program, we almost always find good structure candidates of such unreliable regions. In the presentation, we will report the detailed description of method and results of benchmark tests.

2PT004 Common structural / sequence features of proteins that share non-sequential structural similarity

Kengo Sawada, Shintaro Minami, George Chikenji (*Dept. of eng., Nagoya Univ.*)

Recently, many researchers have reported interesting examples of non-sequential alignments such as circular permutations and domain or region swaps. For example, Alexj et al. conducted a comprehensive large-scale study of non-sequential alignments between available protein structures in Protein Data Bank (PDB) and found that 35.2% of all significant alignments are non-sequential [1]. Furthermore, Aysam et al. identified significant non-sequential structural similarity between some new folds and existing structures in PDB [2]. These observations suggest that appropriately utilizing non-sequential template enables us to predict new fold targets.

The goal of this research is to identify the structural and sequence features of proteins that share non-sequential structural similarity, in order to predict new folds utilizing non-sequential templates. In this work, we collected structures sharing non-topological similarity with one of the super-folds such as Ferredoxin-like fold, and found common features among them. We will report detailed description of the method and the results in the presentation.

[1] Alexj Abyzov and Valentin A Ilyin. 2007. BMC Structural Biology 7:78

[2] Aysam Guerler and Ernst-walter Knapp. 2008. Protein Science. 17:1374-1382

2PT005 PoSSuM: タンパク質の既知及び潜在的基質結合部位類似性検索のためのデータベース

PoSSuM: a database for searching similar pairs of known and potential ligand-binding sites in proteins

Jun-ichi Ito^{1,2,4}, Yasuo Tabei³, Kana Shimizu¹, Koji Tsuda^{1,3}, Kentaro Tomij^{1,2} (¹CBRC, ²AIST, ³Department of Computational Biology, Graduate School of Frontier Sciences, The University of Tokyo, ⁴Minato Discrete Structure Manipulation System Project, JST, ⁴National Institute of Biomedical Innovation)

We proposed a fast alignment-free method that can enumerate similar pairs from millions of ligand-binding sites in the Protein Data Bank (PDB). In our method, ligand-binding sites are first encoded as feature vectors based on their physicochemical and geometric properties of amino acid residues. Once feature vectors representing ligand-binding sites are converted to bit strings, called structural sketches, which is obtained by random projections of the vectors, a multiple sorting method is applied to the enumeration of all similar pairs in terms of the Hamming distance.

We have developed our new database, called Pocket Similarity Search using Multiple-sketchsorts (PoSSuM) to compile all similar pairs detected using our method as a relational database. In the latest version of our database, we used the following two datasets: 226,630 small ligand-binding sites obtained from protein-ligand complexes in the PDB, and 3,134,413 potential ligand-binding

sites identified using an existing pocket detection algorithm, ghecom. We applied our method to all-pair similarity searches for the 3.4 million known and potential ligand-binding sites. Consequently, we discovered ca. 24 million similar binding sites. Here we report those results including all the discovered pairs. Our database is expected to be useful for predicting protein functions and rapid screening of target proteins in drug design. The PoSSuM database is available at <http://possum.cbrc.jp/PoSSuM/>.

2PT006 サポートベクターマシンを用いた糖鎖結合部位予測手法の開発

Development of method for predicting carbohydrate binding site using support vector machine

Masaki Banno, Kentaro Shimizu (*Grad Sch Agricul. life sci., Univ Tokyo*)

Carbohydrate play an important roles in molecular recognition mechanism. Especially, carbohydrate-protein interaction are associated with important biological process such as cell to cell communication, cellular immunity and cell recognition. Recently, the number of carbohydrate binding proteins were achieved over 4000 structures. It is desired to extract new biological findings from these large amount of structural data. In this study, We have carried out data mining of the Protein Data Bank (PDB) to collecting carbohydrate binding proteins, and construct the prediction model of carbohydrate binding site in protein sequence using support vector machine. We analyzed binding site propensity for each types of carbohydrate. We also evaluated this prediction model for 5-fold cross validation. The sensitivity and specificity are achieved an 81% specificity of prediction at 64% sensitivity. Area Under Curve (AUC) were achieved 0.81.

2PT007 タンパク質における部位間での同時的補償的置換に基づく隣接残基対予測

Prediction of Contact Residue Sites Based on Concurrent and Compensatory Substitutions Between Sites in Protein Evolution

Sanzo Miyazawa (*Gunma Univ., Grad. Sch. Eng.*)

Structural and functional constraints originating in residue-residue interactions act on each amino acid in a protein, because a protein must fold into a unique three-dimensional structure and play a specific function. Selective constraints on amino acids in proteins are recorded in amino acid orders in homologous protein sequences and also in the evolutionary trace of amino acid substitutions. Thus, statistical analyses of amino acid orders and of the evolutionary trace of amino acid substitutions can provide information on residue pair couplings. A challenge is to extract direct dependencies between residue sites by excluding indirect correlations that originate from indirect interactions through other residues within a protein or even through other molecules. Recent attempts of disentangling direct from indirect dependencies of amino acid types between residue positions in multiple sequence alignments of proteins have revealed that the strength of inferred residue couplings is an excellent predictor of residue-residue proximity in folded structures. Here, we report an alternative attempt of inferring site couplings from concurrent and compensatory substitutions between sites at each branch of a phylogenetic tree. Accuracy of contact prediction based on the present method is comparable to that of the maximum entropy method.

2PT008 3DMET 構築のためのキュレーション支援システム

Supporting system for manual curation of the 3DMET database

Miki Maeda (*National Institute of Agrobiological Sciences*)

We have developed the 3DMET database, a three-dimensional structure database of natural metabolites. Automatic conversion from 2D- to 3D-structures causes conversion errors especially for chiral information. Thus, we applied automatic confirmation and manual curation to each 3D-structure. During the work, we need some supporting system and have developed.

"Structure-Checker" is a supporting system for self-judge of the conservation between two structures. The user interface is web browser and two MOL files are sent to the web server. In the server, the structures are converted to InChI and each columns are compared. If a column does not correspond to one structure, the color of the column is changed. Curators judged manually based on the results. To understand the results, curators need basic knowledge for the InChI description.

"Molecular Viewer" is a system for manual check of 3D-structures and literatures, developed for chemists not familiar to computer. The user interface of this system is also web browser. Book name, pages, and chemical name are