LETTER

TSV-based hairpin bandpass filter for 6G mobile communication applications

Fengjuan Wang^{1, a)}, Lei Ke¹, Xiangkun Yin², Vasilis F. Pavlidis³, Ningmei Yu¹, and Yuan Yang¹

Abstract Aimed at sixth-generation (6G) mobile communication applications, three fifth-order novel ultra-compact hairpin bandpass filter is proposed. Through-Silicon Via (TSV), a three-dimensional integration technology, is used to implement the arms of hairpin units, and some hairpin units consist of four arms. In this letter, the design method of the three proposed filters is introduced, and the filtering characteristics are verified by HFSS, an industry-grade simulator based on finite element method. The results reveal that the three proposed filter has the center frequency of 0.405 THz, 0.3915 THz, and 0.3955 THz with bandwidth of 0.1 THz, 0.077 THz, and 0.063 THz and exhibits an insertion loss of 2.0 dB and return loss over 12.4 dB, 13.4 dB, and 14 dB. The size of the three proposed filters is both $0.284 \times 0.0325 \text{ mm}^2$ ($1.29 \times 0.148 \lambda_g^2$).

Keywords: sixth-generation (6G) mobile communication, terahertz (THz) frequency band, hairpin bandpass filter, through-silicon via (TSV)

Classification: Electron devices, circuits and modules (silicon, compound semiconductor, organic and novel materials)

1. Introduction

With the high demands in wireless communications, sixth-generation (6G) mobile communication can provide efficient communication, unprecedented pace, and ubiquitous connectivity [1, 2]. Terahertz (THz) range can meet the increased bandwidth, improved efficiency, and high-reliability of 6G wireless communication [3]. Microstrip bandpass filters with compact size and lightweight need to be redesigned for high-performance functional in the channels of communication systems [4]. Microstrip hairpin filter with simple structure, and high integration [5, 6, 7, 8] has widely been utilized in microstrip bandpass filter at below 100 GHz. However, after entering the THz frequency band, the transmission loss of the microstrip line increases sharply, which no longer meets the performance requirements of the filter.

Fortunately, Through-Silicon Via (TSV) can achieve very good signal transmission function in the THz frequency band. TSV provides vertical electrical connections with low loss and, therefore, has been extensively investigated and developed [9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20,

21, 22, 23, 24, 25, 26, 27, 28, 29]. Therefore, a TSV-based hairpin bandpass filter at THz band is meaningful for 6G mobile communication.

The proposed filter is designed using odd-even mode analysis and coupling coefficient theory as described in Section 2. The results of the S-parameters and a performance comparison of relative THz bandpass filters are presented in Section 3. Finally, some conclusions are drawn in Section 4.

2. Design of TSV-based hairpin bandpass filter

In this section, the design method of the TSV-based four-arm hairpin filter is described. The TSV-based hairpin bandpass filter is consistent in the electronic circuit model given in Fig. 1 and topology structure given in Fig. 2. In this work, the substrate material in the TSV-based hairpin unit is assumed to be high-resistivity silicon. The high-resistivity silicon exhibits three important features, which are the dielectric constant of 11.9, dielectric tangent of 0.005 and resistivity of $1000 \Omega \cdot \text{cm}$. The four types of hairpin unit is modeled in High Frequency Structure Simulator (HFSS) software [30], which are shown in Fig. 3. As depicted in Fig. 4, the three main

Fig. 1 The circuit model.

Fig. 2 The topology of structure.

Fig. 3 The hairpin unit of HFSS model.

¹ School of Automation and Information Engineering, Xi'an University of Technology, Xi'an, Shaanxi 710048, China

² School of Microelectronics, Xidian University, Xi'an, Shaanxi 710071, China

³ Advanced Processor Technologies Group, Department of Computer Science, the University of Manchester, UK

^{a)} wfjxiao4@163.com

DOI: 10.1587/elex.18.20210247

Received June 8, 2021

Accepted June 29, 2021

Publicized July 9, 2021

Copiedited August 10, 2021

Fig. 4 Three HFSS models of hairpin filter.

Fig. 5 The comparison between S-parameter of three HFSS models.

structures of the fifth-order hairpin bandpass filter combines the input/output and internal coupling units.

3. Simulation results and comparison

The parameters of the proposed filters are listed in Table I. And the S -parameters are shown in Fig. 5. As the hairpin unit with four arms increase, the in-band return loss will increase. But the band width of the proposed filter will decrease.

A related THz hairpin filter and three related THz SIW filters are compared with the three proposed hairpin filters in Table II. With higher bandwidth, the filters in this work provides higher channel capacity for microwave signal transmission. Moreover, the size of the proposed hairpin filter is considerably smaller than the other hairpin filters, which shows that the structure of the proposed filters is more compact.

4. Conclusion

In this paper, based on TSV technology, a hairpin bandpass filter is first proposed for 6G mobile communications. The novel structure enhances the coupling effect and improves the returns the return loss characteristic in the hairpin bandpass filter.

Acknowledgments

This work was supported by the National Natural Science Foundation of China (61774127, 61771388), the Fok

Table I Structure parameters of proposed hairpin filter.

	Structure parameter	Symbol	Value (μm)
Feeder	Length	L_1	5.8
	Width	W	5.1
	Height	H_1	4
TSV	Diameter	D_2	5.1
	Length	L_2	26.5
RDL	Length	L_3	54.3
	Width	W	5.1
	Height	H_2	1
Distance	Adjacent TSV	D_1	12.3
	Signal RDL to GND RDL	D_3	8
	Type 1 hairpin unit to Type 2	S_1	2.5
	Type 2 hairpin unit to Type 1	S_2	3.6

Table II Comparison with different THz filters.

Filters	Type	CF (THz)	BW (THz)	IL (dB)	RL (dB)	Size	
						(mm^2)	λ_g^2
[26]	Hairpin	0.12	0.02	6.9	10	0.3×0.05	0.41×0.069
[27]	SIW	0.16	0.02	1.5	10	0.9×0.325	2.25×0.81
[28]	SIW	0.14	0.023	2.4	11	1.8×0.79	2.90×1.27
[29]	SIW	0.331	0.051	1.5	15	0.68×0.21	2.59×0.80
Model 1	Hairpin	0.405	0.1	2.0	12.4	0.284×0.0325	1.29×0.148
Model 2		0.3915	0.077	2.0	13.4	0.284×0.0325	1.29×0.148
Model 3		0.3955	0.063	2.0	14	0.284×0.0325	1.29×0.148

Ying Tung Education Foundation under Grant no. 171112, Shaanxi Innovation Capacity Support Project under Grant nos. 2020KJXX-093 and 2021TD-25.

References

- [1] Q. Qi, *et al.*: "Integration of energy, computation and communication in 6G cellular Internet of Things," *IEEE Commun. Lett.* **24** (2020) 1333 (DOI: 10.1109/LCOMM.2020.2982151).
- [2] B. Mao, *et al.*: "AI-based joint optimization of QoS and security for 6G energy harvesting Internet of Things," *IEEE Internet Things J.* **7** (2020) 7032 (DOI: 10.1109/JIOT.2020.2982417).
- [3] N.S. Ishak, *et al.*: "Frequency selective surface (FSS) realization in terahertz (THz) range for 6G initiative studies," *IEEE Asia-Pacific Conference on Applied Electromagnetics (APACE)* (2019) 1 (DOI: 10.1109/APACE47377.2019.9020831).
- [4] Y. Yu, *et al.*: "Ultracompact effective localized surface plasmonic bandpass filter for 5G applications," *IEEE Trans. Microw. Theory Techn.* **69** (2021) 2220 (DOI: 10.1109/TMTT.2021.3058535).
- [5] A. Zakharov, *et al.*: "Hairpin resonators in varactor-tuned microstrip bandpass filters," *IEEE Trans. Circuits Syst. II, Exp. Briefs* **67** (2020) 1874 (DOI: 10.1109/TCSII.2019.2953247).
- [6] V.N.R. Vanukuru, *et al.*: "CMOS millimeter-wave ultra-wideband bandpass filter with three reflection-zeros using compact single TFMS coupled-line hairpin unit," *IEEE Trans. Circuits Syst. II, Exp. Briefs* **67** (2020) 77 (DOI: 10.1109/TCSII.2019.2903324).
- [7] E. González-Carvajal, *et al.*: "Frequency and bandwidth tunable mm-wave hairpin bandpass filters using microfluidic reconfiguration with integrated actuation," *IEEE Trans. Microw. Theory Techn.* **68** (2020) 3756 (DOI: 10.1109/TMTT.2020.3006869).
- [8] T. Tsukushi, *et al.*: "Bandpass filter with flat passband and transmis-

- sion zeros using parallel-connected resistor loaded hairpin-shaped resonators,” *IEICE Electron. Express* **17** (2020) 20200320 (DOI: [10.1587/elex.17.20200320](https://doi.org/10.1587/elex.17.20200320)).
- [9] X. Yin, *et al.*: “Ultra-compact TSV-based L-C low-pass filter with stopband up to 40 GHz for microwave application,” *IEEE Trans. Microw. Theory Techn.* **67** (2019) 738 (DOI: [10.1109/TMTT.2018.2882809](https://doi.org/10.1109/TMTT.2018.2882809)).
- [10] X. Yin, *et al.*: “Metal proportion optimization of annular through-silicon via considering temperature and keep-out zone,” *IEEE Trans. Compon. Packag. Manuf. Technol.* **5** (2015) 1093 (DOI: [10.1109/TCPMT.2015.2446768](https://doi.org/10.1109/TCPMT.2015.2446768)).
- [11] V.F. Pavlidis, *et al.*: *Three-Dimensional Integrated Circuits Design* (Amsterdam, The Netherlands, Elsevier, 2017) 2nd ed.
- [12] L. Qian, *et al.*: “Through-silicon via-based capacitor and its application in LDO regulator design,” *IEEE Trans. Very Large Scale Integr. (VLSI) Syst.* **27** (2019) 1947 (DOI: [10.1109/TVLSI.2019.2904200](https://doi.org/10.1109/TVLSI.2019.2904200)).
- [13] L. Qian, *et al.*: “Investigating on through glass via based RF passives for 3-D integration,” *IEEE J. Electron Devices Soc.* **6** (2018) 755 (DOI: [10.1109/JEDS.2018.2849393](https://doi.org/10.1109/JEDS.2018.2849393)).
- [14] F.J. Wang, *et al.*: “A novel guard method of through-silicon via (TSV),” *IEICE Electron. Express* **15** (2018) 20180421 (DOI: [10.1587/elex.15.20180421](https://doi.org/10.1587/elex.15.20180421)).
- [15] X. Liu, *et al.*: “Electrical modeling and analysis of differential dielectric-cavity through-silicon via array,” *IEEE Microw. Wireless Compon. Lett.* **27** (2017) 618 (DOI: [10.1109/LMWC.2017.2711563](https://doi.org/10.1109/LMWC.2017.2711563)).
- [16] Q. Lu, *et al.*: “High-frequency electrical model of through-silicon vias for 3-D integrated circuits considering eddy-current and proximity effects,” *IEEE Trans. Compon. Packag. Manuf. Technol.* **7** (2017) 2036 (DOI: [10.1109/TCPMT.2017.2741340](https://doi.org/10.1109/TCPMT.2017.2741340)).
- [17] Q. Lu, *et al.*: “Wideband electromagnetic modeling of coaxial-annular through-silicon vias,” *IEEE Trans. Electromagn. Compat.* **60** (2018) 1915 (DOI: [10.1109/TEMC.2017.2771293](https://doi.org/10.1109/TEMC.2017.2771293)).
- [18] Q. Lu, *et al.*: “3-D compact 3-dB branch-line directional couplers based on through-silicon via technology for millimeter-wave applications,” *IEEE Trans. Compon. Packag. Manuf. Technol.* **9** (2019) 1855 (DOI: [10.1109/TCPMT.2019.2927553](https://doi.org/10.1109/TCPMT.2019.2927553)).
- [19] G. Katti, *et al.*: “Temperature dependent electrical characteristics of through-si-via (TSV) interconnections,” *IEEE International Interconnect Technology Conference* (2010) 1 (DOI: [10.1109/IITC.2010.5510311](https://doi.org/10.1109/IITC.2010.5510311)).
- [20] W.-S. Zhao, *et al.*: “Modeling and characterization of coaxial through-silicon via with electrically floating inner silicon,” *IEEE Trans. Compon. Packag. Manuf. Technol.* **7** (2017) 936 (DOI: [10.1109/TCPMT.2017.2678203](https://doi.org/10.1109/TCPMT.2017.2678203)).
- [21] J. Jin, *et al.*: “Investigation of carbon nanotube-based through-silicon vias for PDN applications,” *IEEE Trans. Electromagn. Compat.* **60** (2018) 738 (DOI: [10.1109/TEMC.2017.2737022](https://doi.org/10.1109/TEMC.2017.2737022)).
- [22] W.-S. Zhao, *et al.*: “Wideband modeling and characterization of differential through-silicon vias for 3-D ICs,” *IEEE Trans. Electron Devices* **63** (2016) 1168 (DOI: [10.1109/TED.2016.2516345](https://doi.org/10.1109/TED.2016.2516345)).
- [23] W.-S. Zhao, *et al.*: “Modeling of carbon nanotube-based differential through-silicon vias in 3-D ICs,” *IEEE Trans. Nanotechnol.* **19** (2020) 492 (DOI: [10.1109/TNANO.2020.3004825](https://doi.org/10.1109/TNANO.2020.3004825)).
- [24] T. Ni, *et al.*: “Architecture of cobweb-based redundant TSV for clustered faults,” *IEEE Trans. Very Large Scale Integr. (VLSI) Syst.* **28** (2020) 1736 (DOI: [10.1109/TVLSI.2020.2995094](https://doi.org/10.1109/TVLSI.2020.2995094)).
- [25] T. Ni, *et al.*: “A novel TDMA-based fault tolerance technique for the TSVs in 3D-ICs using honeycomb topology,” *IEEE Trans. Emerg. Topics Comput.* **9** (2020) 724 (DOI: [10.1109/TETC.2020.2969237](https://doi.org/10.1109/TETC.2020.2969237)).
- [26] S. Hu, *et al.*: “TSV technology for millimeter-wave and terahertz design and applications,” *IEEE Trans. Compon. Packag. Manuf. Technol.* **1** (2011) 260 (DOI: [10.1109/TCPMT.2010.2099731](https://doi.org/10.1109/TCPMT.2010.2099731)).
- [27] X. Liu, *et al.*: “Wideband substrate integrated waveguide bandpass filter based on 3-D ICs,” *IEEE Trans. Compon. Packag. Manuf. Technol.* **9** (2019) 728 (DOI: [10.1109/TCPMT.2018.2878863](https://doi.org/10.1109/TCPMT.2018.2878863)).
- [28] K. Wang, *et al.*: “Synthesis method for substrate-integrated waveguide bandpass filter with even-order Chebyshev response,” *IEEE Trans. Compon. Packag. Manuf. Technol.* **6** (2016) 126 (DOI: [10.1109/TCPMT.2015.2502420](https://doi.org/10.1109/TCPMT.2015.2502420)).
- [29] F. Wang, *et al.*: “Miniaturized SIW bandpass filter based on TSV technology for THz applications,” *IEEE Trans. THz Sci. Technol.* **10** (2020) 423 (DOI: [10.1109/TTHZ.2020.2974091](https://doi.org/10.1109/TTHZ.2020.2974091)).
- [30] HFSS software (2020) <http://www.ansys.com/Products/Electronics/ANSYS-HFSS>.