祝辞 Congratulations

On the special milestone of the 50th Anniversary of the founding of the Atomic Energy Society of Japan, this report describes the current status of the peaceful application of nuclear power in the United States (U.S.).¹⁾ It is particularly appropriate to do so at this time when there is a growing consensus that nuclear power can make a major contribution to reducing greenhouse gas emissions, there is a renaissance of interest and intense activity directed at building new nuclear power plants, and there is overwhelming public opinion in favor of extending operation of current nuclear power plants and in support of building new plants.

Performance of the 104 nuclear power plants (NPPs) operating in the U.S. has improved dramatically—from a capacity factor of about 70% a decade ago to 92% in 2007—producing very favorable economics. Operating safety has steadily improved—as measured by numerous performance indicators reported by the U.S. Nuclear Regulatory Commission (NRC) and the Institute for Nuclear Power Operations—and, no U.S. plant worker or member of the public has ever been injured or killed by an accident caused by nuclear power. Nuclear power is an emissions-free source of electricity—70% of all U.S. emissions-free electricity is generated by nuclear power. And, new NPP designs provide even greater improvements in construction and operation economics, reliability, and safety.

The U.S. Department of Energy (DOE) forecasts that by the year 2030 the U.S.'s demand for electricity will increase by 30%. Thus, just to maintain the same fraction of electricity from nuclear power would require about thirty new NPPs. Since the beginning of 2006 seventeen U.S. utilities have announced plans to file applications with the U.S. Nuclear Regulatory Commission (NRC) to build as many as thirty-three new NPPs. Seventeen of these applications for twenty-six NPPs are currently under review by the NRC. Numerous utilities have placed manufacturing orders for major components for these NPPs. And, two utilities have signed EPC (engineering, procurement, and construction) contracts for four NPPs. These are the first new NPP orders in the U.S. since 1978.

The nuclear renaissance in the U.S. began with the existing fleet of operating NPPs. During the past fifteen years power uprates and capacity factor improvements have increased the power output of U.S. NPPs by the equivalent of adding 26 new 1000 MWe NPPs to the grid. Additional power uprates of up to 15% for five additional NPPs are currently under review for approval by the NRC. And, the NRC has approved 20-year operating license renewals for 50 NPPs. (NPPs are initially licensed in the U.S. to operate 40 years.) Another 18 renewal applications are under NRC review, and letters of intent to renew for an additional 24 NPPs have been submitted to NRC. It is expected that the operating license of all 104 currently operating NPPs will be extended 20 years, and discussions are actively underway concerning the conditions to be met for an additional 20-year renewal.

Each of the new NPPs announced by U.S. utilities employ advanced designs compared to the current U.S. fleet of operating NPPs. Advanced features include new fabrication and construction techniques, digital control and safety systems, emergency systems with higher reliability, greater volumes of emergency cooling water,

W. バーチル氏

Dr. William E. Burchill

米国原子力学会(ANS)会長

イリノイ大学で博士号取得。コンバッションエンジニアリング社, エクセロン社勤務, テキサス大学学部長などを経て, 08年から現職。専門は原子力安全。

¹⁾ Statistics are cited as of December, 2008.

²⁾ ABWR—Advanced Boiling Water Reactor; EPR—European Pressurized Reactor; AP-1000—Advanced Pressurized water reactor, 1000 MWe; APWR—Advanced Pressurized Water Reactor; and ESBWR—Economical, Simplified Boiling Water Reactor.

and capability to use advanced nuclear fuels that produce more energy and less waste. As a group these designs are called ALWRs (Advanced Light Water Reactors). It is generally concluded in the industry that all commercial NPPs to be built in the U.S. during the next two to three decades will be ALWRs.

The five designs in all U.S. new NPP announcements to date are: the ABWR by General Electric/Hitachi, the EPR by Areva, the AP-1000 by Westinghouse, the APWR by Mitsubishi, and the ESBWR by General Electric/Hitachi.²⁾ The ABWR and the ESBWR are boiling water reactors; the EPR, the AP-1000, and the APWR are pressurized water reactors. Each of these designs achieves high reliability of its emergency systems, specifically the emergency core cooling system (ECCS). The ABWR, the EPR, and the APWR are called “evolutionary” designs, i.e., the ECCS has higher reliability because it has more systems in parallel—power supplies and water-delivery trains—than current designs, although the systems are similar to those in current designs. The AP-1000 and the ESBWR are called “passive” designs, i.e., the ECCS delivers water by gravity-feed systems which involve fewer electrically-powered pumps and valves. Reliability mathematics demonstrate that each approach produces a similar improvement in ECCS reliability compared to current ECCS designs.

There are several major challenges to making the nuclear power renaissance actually happen. Four are near-term. Perhaps the foremost challenge is to have sufficient labor, both skilled and degreed. During the last-nearly thirty years nuclear power has not been an attractive career objective for young people in the U.S. Nuclear power, along with many other U.S. heavy manufacturing industries, has an “aging workforce.” Recent estimates by the Nuclear Energy Institute project that about 50% of the U.S. nuclear power workforce will be eligible to retire within the next five years.³⁾ However, the recent slowdown of the overall U.S. economy may cause many retirements to be postponed.

Notwithstanding the retirement situation, skilled labor shortages—electricians, welders, pipefitters, machinists, radiation protection technicians—already confront the currently-operating nuclear power industry. Numerous trade schools have shut their doors during the past decade. Consequently, many utilities have individually or collectively established their own training programs, usually in collaboration with local community colleges. Another shortage involves nuclear engineers needed to design and to operate the plants. Undergraduate enrollments in U.S. nuclear engineering schools reached a low of about 700 students in 1998, and today only half as many U.S. universities offer this degree as twenty years ago. Another traditional source, the U.S. Navy, is producing sixty percent fewer former enlisted personnel as it once did.

Fortunately, the situation is improving rapidly. Utility programs to train new personnel in various labor skills are becoming more widely known and attended. University enrollments in nuclear engineering in Fall 2008 were more than double their number in 1998, and several schools have started, or are considering, new degree programs. The driving force producing these results is the aggressive hiring campaign being conducted by the reactor vendors, the NRC, and specific utilities. However, there still remains a gap by as much as a factor of three in the projected demand for nuclear engineering graduates compared to the number entering the nuclear power workforce.⁴⁾

The second near-term challenge is to re-establish the nuclear industry infrastructure in the U.S. This infrastructure is required to provide all of the structures, systems, and components needed in a NPP. The largest of these are the thick-walled steel vessels that house the nuclear reactors, the steam generators, pressurizers, and the piping that connects these components. The manufacturing technique with which the current fleet of operating reactors were manufactured involved bending thick metal plates and welding them together to form vessels or piping. This technique has been replaced in the design of all ALWRs with ultra-heavy forging in which major sections of a vessel or a complete length of pipe, including all connecting nozzles,

³⁾ “NEI Work Force Report,” Nuclear Energy Institute, December, 2007.

⁴⁾ “Innovative Education and Training Partnerships to Meet Manpower Demands of the Nuclear Renaissance in the United States,” William B. Burchill, presentation in Keynote Session 7, 16th Pacific Basin Nuclear Conference, Aomori, Japan, October 15, 2008.

are formed from a single metal billet by multiple pressing and boring steps. Unfortunately, there is no facility in the U.S. which can produce these very large forgings. The only such facilities in the world are in Japan, France, South Korea, and Russia. However, in late 2007 Areva and Northrup Grumman Shipbuilding announced the formation of a joint venture, Areva Newport News LLC, which will produce ultra-heavy metal forgings in a new facility to be built in the U.S. China also plans to build three ultra-heavy metal forging factories.

Another infrastructure issue concerns manufacture of pumps, pipes, valves, controllers, and other components. The quality of these components must be certified by an ASME (American Society of Mechanical Engineers) N-stamp which is held by the component's manufacturer in recognition of the quality of its manufacturing processes and products. A typical ALWR requires a large quantity of these quality components: about 2,500 valves, 250 pumps, 25,000 feet of pipe, 225 miles of electrical cable, and 90,000 electrical devices. During the construction of the current U.S. fleet of operating NPPs, about 600 companies held an N-stamp; today only about 100 companies are so qualified.

The Nuclear Energy Institute, an industry trade and policy organization based in Washington, DC, conducted three manufacturing workshops—Columbia, SC; Cleveland, OH; San Antonio, TX—during the first half of 2007 in order to stimulate U.S. industry to re-establish this lost manufacturing capability. The response during these workshops has been encouraging, but it is too early to tell the degree to which the U.S. manufacturing infrastructure will be re-established. Meanwhile, reactor vendors and utilities have thus far placed all orders for long-lead-time heavy components overseas, and it is expected that a high fraction of the quality components for the first several new plants will come from foreign sources.

The third near-term challenge is financing the cost of constructing a new NPP estimated to be about \$5 billion. The largest U.S. utility currently operating NPPs has a book value of about \$17 billion, and most are much smaller. Thus, committing to construct a new NPP is literally “betting the company.” To reduce this risk, the Energy Policy Act of 2005 provides three key incentives: a production tax credit of \$18 per megawatt-hour for the first 6000 megawatts of new NPPs, risk insurance against delays in commercial operation caused by licensing or litigation outside a utility's control, and loan guarantees up to 80 percent of the cost of projects.⁵⁾

Currently the financial community's opinion of nuclear power is quite positive since the operating cost of a NPP is below or competitive with any other electricity source, and the lifetime cost, including construction, is likewise positioned especially considering operation beyond an initial 40-year license. This was verified April 8, 2007, when Georgia Power Co. signed an EPC contract with Westinghouse and Shaw Group for two AP-1000 NPPs; it was further verified May 27, 2007, when South Carolina Electric & Gas also signed an EPC contract with Westinghouse and Shaw Group for two AP-1000 NPPs.

The fourth near-term challenge is the regulatory uncertainty associated with licensing a new NPP. The U.S. NRC has revised and streamlined its licensing process since the last U.S. NPPs were licensed. Under the new process the regulatory approval to construct and to operate a new NPP is issued based on an already-approved design (previously certified by the NRC) before construction is begun and significant expenditures are made. Thus, outrageous cost escalations which were experienced during regulatory delays in issuing an operating license following construction of many current U.S. NPPs should be precluded. However, the process is untested. Positive experience with the first several applications, including satisfactory public involvement, is required to build confidence and to reduce the level of uncertainty.

Three other longer-term challenges must be considered. First, NPPs must continue to be operated with the excellent safety record that has been demonstrated during the past two decades in order to maintain public confidence. Second, a long-term method of disposing of highly radioactive waste must be implemented. Third, security must be adequate to preclude diversion of materials that could be turned into nuclear weapons (so-called “proliferation”). The fact that the first of these challenges, operating safety, underlies all other

---

⁵⁾ These provisions are not unique to new NPPs, and similar ones are available to other projects that reduce greenhouse gas emissions.

considerations of nuclear power is widely acknowledged in the nuclear industry. The second and third of these challenges are closely related.

The form and volume of highly radioactive waste can be made much easier to dispose of by extracting it from used nuclear fuel by reprocessing. Reprocessing also allows the remaining nuclear fuel to be recycled to obtain its residual energy content (about two-thirds after its initial operation in a current NPP). During reprocessing security must be adequate to preclude materials diversion; currently this is accomplished using physical deterrents (frequently referred to as “guns, gates, and guards”). Outside the U.S. reprocessing and recycling of commercial nuclear fuel are conducted by France, England, Japan, and Russia for both their own NPPs and under contract for other countries NPPs. China has reprocessing/recycling facilities under construction. Although the U.S. formerly had such facilities, none currently exist at commercial scale.

The U.S. federal government, in response to the 1982 Nuclear Waste Policy Act, selected a deep geologic repository at Yucca Mountain in Nevada for disposal of highly radioactive waste from commercial NPPs. (Highly radioactive waste from defense facilities is disposed of in the Waste Isolation Pilot Project in New Mexico which has been operating successfully for eight years.) On June 3, 2008, the Department of Energy (DOE) submitted to NRC an application to operate the Yucca Mountain repository. Initial operation is forecast to begin as early as 2017. Currently, essentially all used nuclear fuel is securely stored at NPP sites either in spent fuel storage pools or in above-ground, dry casks.

Although the Yucca Mountain repository is currently designed to dispose of used nuclear fuel transferred directly from NPPs, it would be more efficient to reprocess the used fuel and to dispose of only the relatively low volume of highly radioactive waste in the repository. Furthermore, the used nuclear fuel from NPPs is increasingly being recognized as a valuable future asset for retrieval of its residual energy value. These conclusions are becoming widely accepted in the U.S. as they are already elsewhere in the world.

The U.S. DOE is also developing reprocessing and recycling methods which would be inherently proliferation-proof. Under the Advanced Fuel Cycle Initiative the DOE has developed methods in which elements, such as plutonium, which would be potentially attractive for diversion, are always combined with other elements which would make them useless for nuclear weapons. The results of this initiative are now a cornerstone of the Global Nuclear Energy Partnership under which the U.S. and other countries which currently have reprocessing/recycling capability would provide this service to the rest of the world thus reducing the volume of highly radioactive waste, recovering residual energy content of used nuclear fuel, and establishing security against proliferation.

Looking to the future beyond ALWRs, the DOE is leading an international program involving ten countries to design the next generation, called Generation IV, of NPPs. The design objectives of these NPPs include improved economics, safety, and security. Improved economics are expected due to much higher operating temperatures (about 1000°C) producing greater thermal efficiency. Safety is expected to be increased using melt-down proof materials (in some designs). Security is expected to be improved using proliferation-resistant fuels and fuel reprocessing/recycling methods. In addition, the Generation IV reactors include breeder reactor designs that produce more fuel than they consume. Clearly, whether any of these designs is ever considered for commercial application depends on the success of the renaissance which is beginning today with ALWRs.

The American Nuclear Society (ANS) congratulates the Atomic Energy Society of Japan (AESJ) on its 50th anniversary. ANS recognizes the very significant leadership role that AESJ provides in development and application of nuclear science, engineering, and technology both in Japan and worldwide. ANS is a not-for-profit, international, scientific and educational organization composed of approximately 11,000 engineers, scientists, administrators, and educators representing 1,600 plus corporations, educational institutions, and government agencies. Its professional, educational, and outreach activities are conducted through eighteen technical divisions with a wide range of technical focus including nuclear power operations, nuclear installations safety, environmental sciences, biology and medicine, robotics and remote systems, human factors, accelerator applications, fusion energy, and aerospace nuclear sciences.

(2008年 12月20日 記)