Nomenclature

$A_0, B_0, C_0, D_0, E_0, a, b, c, d, e, f, g, h, \alpha, \gamma$	= constants of the equation of state	
m_{ij}	= binary parameter for i and j components	[—]
P	= pressure	[atm]
R	= gas constant	[J·atm/mol·K]
T	= temperature	[K]
x	= mole fraction	[—]
ρ	= density	[mol/l]
<Subscripts>		
i	= component i	
j	= component j	

Literature Cited

1) ASHRAE: "ASHRAE Thermodynamic Properties of

Refrigerants," ASHRAE, New York (1969).

- Asselineau, L., G. Bogdanic and J. Vidal: *Chem. Eng. Sci.*, **33**, 1269 (1978).
- Brent, R. T.: "Algorithm for Minimization without Derivatives," Prentice-Hall, Englewood Cliffs, N. J. (1973).
- Fukuzato, R., Y. Tanigaki, N. Shiki, Y. Tomisaka, K. Arai and S. Saito: *J. Chem. Eng. Japan*, **15**, 167 (1982).
- Meskel-Lesavre, M., D. Richon and H. Renon: *Fluid Phase Equilibria*, **8**, 37 (1982).
- Mollerup, J. and A. Fredenslund: *J. Chem. Eng. Data*, **21**, 299 (1976).
- Nishiumi, H. and S. Saito: *J. Chem. Eng. Japan*, **8**, 356 (1975).
- Nishiumi, H. and S. Saito: *J. Chem. Eng. Japan*, **10**, 176 (1977).
- Piacentini, A. and F. P. Stein: *Chem. Eng. Prog., Symp. Ser.*, **63**, No. 81, 28 (1967).
- Stein, F. P. and P. C. Proust: *J. Chem. Eng. Data*, **16**, 389 (1971).

EFFECTS OF SEGREGATION ON FINE ELUTRIATION FROM GAS-FLUIDISED BEDS OF BINARY SOLID MIXTURE

HIROTOSHI TANIMOTO, TADATOSHI CHIBA AND HARUO KOBAYASHI

Department of Chemical Process Engineering, Hokkaido University, Sapporo 060

Introduction

In gas-fluidised beds, solid particles are ejected into the freeboard due to eruption of bubbles at the bed surface and are entrained by the freeboard gas flow. The variations of size distribution and of rate of entrainment of the ejected particles with the position of the freeboard have been widely investigated in terms of the transport disengaging height, TDH.^{3-10,13-18} In these investigations, it has been shown that the variations depend on the composition of fine particles as well as the solid properties and the bubbling bed characteristics. However, little attention has been paid to the composition near the bed surface and complete mixing of solid particles has been usually assumed throughout the whole bed, because most investigations have been concerned with elutriation in catalytic gas-fluidised bed reactors for which that assumption could be approximately accepted. In gas-fluidised beds for multi-component solid treatment such as coal and waste solid conversion processes, the size and density differences in mixture of solid particles cause appreciable solid segregation,¹² and the composition of lighter and finer particles near the bed surface is much higher than in the other parts

of the bed. In addition, recycle of elutriated particles or continuous solid feed affects the steady-state solid concentration profile in the bed. Hence, in the present work, the effect of solid segregation on fine solid elutriation has been experimentally examined under a condition where all elutriated particles are refluxed into the bed.

1. Experimental Apparatus and Procedure

A fluidised bed column of 0.10 m i.d. and 2.12 m height was made of transparent PMMA. The gas distributor was a 10 mm-thick perforated plate having 363 drilled holes of 0.5 mm dia. on a 5-mm triangular pitch. Humidified air (dew point = 279 K) was used as the fluidising gas to eliminate electrostatic effects. All experiments were carried out with beds consisting of binary solid mixture, one being fine and the other bulk bed particles. As the fine materials, 0.081-mm irregular silica gel particles and 0.053-mm spherical glass beads were used. Spherical glass beads of 0.163, 0.274 and 0.385 mm dia. were used as the bulk bed materials. Relevant properties of these particles are listed in **Table 1**. At the top of the column a conical section with a cone angle of 30 degrees was installed to delete unusual accumulation of fine particles in the upper part of the freeboard.

The elutriation rate was measured in a usual man-

Received August 30, 1982. Correspondence concerning this article should be addressed to H. Kobayashi. T. Chiba is at Coal Research Inst., Hokkaido Univ., Sapporo 060.

Table 1. Properties of particles used

Particle	d_p [mesh]	$\bar{d}_p$ [mm]	ρ_p [kg/m ³]	ρ_{mf} [kg/m ³]	U_{mf} [m/s]	ϵ_{mf} [—]	U_t^* [m/s]	Shape
SG81	−170+200	0.081	1200	470	0.0056	0.53	0.15	Irregular
GB53	−250+325	0.053	2520	1450	0.0085	0.43	0.22	Spherical
GB163	−80+100	0.163			0.025		1.29	
GB274	−48+60	0.274			0.076		2.17	
GB385	−35+42	0.385			0.128		3.02	

* Calculated values. GB, glass beads; SG, silica gel.

Fig. 1. Concentration profiles of fines for SG81/GB163 bed.

ner.¹¹⁾ After steady state of fluidisation was reached at a given gas velocity, the elutriated fine particles collected by a cyclone were sampled for a short time. Then the air flow was shut off rapidly and the fines were removed, weighed and returned into the bed. Horizontal bed sectioning was done to obtain the concentration profile of fines in the bed.²⁾

2. Results and Discussion

2.1 Completely mixed beds

Figure 1 shows concentration profiles of fine particles in the bed of 0.081-mm silica gel particles and 0.163-mm glass beads (SG81/GB163). In this case complete mixing of both particles is obtained at gas velocities greater than 0.165 m/s. For such completely mixed beds the elutriation rate, E , increases with static bed height, H_0 , as shown in Fig. 2. This tendency of increase of elutriation rate with bed height is quite similar to that observed in non-segregating beds which have been studied so far.⁷⁾ With increasing bed height the diameter of bubbles erupting at the bed surface becomes greater and this results in an increase of particles ejected into the freeboard.

In Fig. 3, the effect of the bulk bed composition of fines, $\bar{X}$, is examined for beds of the same particle mixture as above. Since in this case the minimum fluidisation velocity of the mixture, $\bar{U}_{mf}$, changes with $\bar{X}$, which in turn brings about a change of the bubble flow rate, $U - \bar{U}_{mf}$, the elutriation rates for different $\bar{X}$

Fig. 2. Effects of bed height on elutriation rate for completely mixed beds.

Fig. 3. Effects of bulk composition of fines on elutriation rate for completely mixed beds.

are compared by plotting them against the bubble flow rate. Here, the minimum fluidisation velocity of the mixture was calculated by an empirical equation.¹⁾ From the figure the elutriation rate is seen to increase with bulk bed composition as had been expected.

2.2 Partially or strongly segregated beds

The effect of bed height on the elutriation rate is illustrated in Fig. 4 for GB53/GB274 mixtures. The elutriation rate decreases with bed height. These results are definitely different from that for the SG81/GB163 mixtures shown in Fig. 2. For the GB53/GB274 mixtures, typical concentration profiles of the fines are shown in Fig. 5, which clearly indicates the

Fig. 4. Effects of bed height on elutriation rate for GB53/GB274 mixture.

Fig. 5. Variations of concentration profile of fines with bed height for GB53/GB274 mixture.

segregation of the fines towards the bed surface. The weight fraction of the fines, X , near the bed surface is higher in the lower bed than in the higher bed because mixing is less effective by the smaller bubbles in the lower bed. It has already been recognized, on the other hand, that the particles ejected from the bed surface increase with increasing bed height due to the greater size of erupting bubbles. Thus, with the increase in the height of segregating beds, the ejection of fine particles increases due to the greater size of erupting bubbles while it decreases due to the smaller concentration of fines near the bed surface. The result in Fig. 4 demonstrates, therefore, that in this case the latter effect of segregation on elutriation prevails over the opposite effect of the former.

Change in weight fraction of fines near the bed surface can also be expected to occur for different combinations of fine and bulk bed materials.^{2,12)} Figure 6 shows typical results which represent the effect of the diameter of bulk bed materials on the elutriation rate of fines (SG81) for a given bed height and bulk bed composition. Though the SG81/GB385 mixture has the highest minimum fluidisation velocity

Fig. 6. Effects of diameter of bulk bed material on elutriation rate.

Fig. 7. Variations of concentration profile with gas velocity for SG81/GB385 mixture.

and gives the smallest bubble diameter at a given superficial gas velocity, the elutriation rate for the mixture is greatest in accordance with the highest weight fraction of fines near the bed surface. For this mixture, it is also seen that the rate of increase in elutriation rate with gas velocity changes at about 0.200 m/s. As shown in Fig. 7, this corresponds again to the change of the concentration profile of fines near the bed surface. At gas velocities less than 0.200 m/s, the bed is almost completely segregated while it becomes partially segregated for $U < 0.200$ m/s. All these results show that the weight fraction of fines near the bed surface is considerably effective for the elutriation of fines, particularly from segregating beds.

Conclusions

Measurements of fine particle elutriation were carried out in fluidised beds of binary solid mixture. In segregating beds, the elutriation characteristics were much different from those in well-mixed beds. Different dependencies of elutriation rate for segregated and well mixed beds on bed height and superficial gas velocity were clearly shown and these could

be well explained through the change of weight fraction of fine particles near the bed surface.

Nomenclature

d_p	= particle diameter	[mm]
$\bar{d}_p$	= mean particle diameter	[mm]
E	= elutriation rate	[kg/m ² s]
h	= height from gas distributor	[m]
H_o	= static bed height	[m]
U	= superficial gas velocity	[m/s]
U_{mf}	= minimum fluidisation velocity of monocomponent particle	[m/s]
$\bar{U}_{mf}$	= minimum fluidisation velocity of binary particle mixture	[m/s]
U_t	= terminal velocity	[m/s]
X	= weight fraction of fine particles	[—]
$\bar{X}$	= bulk weight fraction of fine particles	[—]
Z	= dimensionless bed height	[—]
ϵ_{mf}	= voidage of incipiently fluidised bed	[—]
ρ_{mf}	= particle density of incipiently fluidised bed	[kg/m ³]
ρ_p	= particle density	[kg/m ³]

Literature Cited

- Cheung, L. Y.-L., A. W. Nienow and P. N. Rowe: *Chem. Eng. Sci.*, **29**, 1301 (1974).
- Chiba, S., T. Chiba, A. W. Nienow and H. Kobayashi: *Chem. Eng. Sci.*, **29**, 255 (1979).
- Geldart, D. and D. J. Pope: Preprints of AIChE 71st An. Meeting, Miami Beach (1978).
- Geldart, D., J. Cullian, S. Georghides, D. Gilvray and D. J. Pope: *Trans. Inst. Chem. Eng.*, **57**, 269 (1979).
- Guha, S. K., A. Kumer and P. Sen Gupta: *Can. J. Chem. Eng.*, **50**, 602 (1980).
- Horio, M., A. Taki, Y. S. Hsieh and I. Muchi: "Fluidization," ed. by J. R. Grace and J. M. Matson, p. 509, Plenum Press, New York (1980).
- Kunii, D. and O. Levenspiel: "Fluidization Engineering," Ch. 10, John Wiley & Sons, Inc. (1969).
- Leva, M. and C. Y. Wen: "Fluidization," ed. by J. F. Davidson and D. H. Harrison, Ch. 14, Academic Press (1971).
- Lin, L., J. T. Sears and C. Y. Wen: *Powder Technol.*, **27**, 105 (1980).
- Matsuno, Y., H. Kage, T. Nagamitsu, K. Higashitani, Y. Ideue and H. Yamaguchi: "Fluidization," ed. by M. Kwauk and D. Kunii, p. 47, Science Press (1982).
- Morooka, S., K. Kawazuishi and Y. Kato: *Powder Technol.*, **26**, 75 (1980).
- Nienow, A. W. and T. Chiba: *I. Chem. Eng., Symp. Ser.*, No. 65, p. S2/F/1 (1981).
- Sycheva, T. N. and E. V. Donat: *Int. Chem. Eng.*, **10**, 172 (1970).
- Sycheva, T. N. and E. V. Donat: *Int. Chem. Eng.*, **15**, 346 (1975).
- Tanaka, I. and H. Shinohara: *J. Chem. Eng. Japan*, **5**, 27 (1972).
- Tanaka, I., H. Shinohara, H. Hirose and Y. Tanaka: *J. Chem. Eng. Japan*, **5**, 51 (1972).
- Urabe, S., I. Hiraki, K. Yoshida and D. Kunii: *Kagaku Kōgaku*, **29**, 19 (1965).
- Zenz, F. A. and D. F. Othmer: "Fluidisation and Fluid-Particle Systems," Ch. 12, Reinhold, New York (1960).

(Presented at the 47th Annual Meeting of The Society of Chemical Engineers, Japan, at Tokyo, March 29, 1982.)

NUMERICAL METHOD FOR SOLVING STEADY THREE-DIMENSIONAL HEAT CONDUCTION PROBLEM IN SECTOR COLUMN

IKUHO YAMADA, SETSURO HIRAOKA, HAJIME NAKAMURA, SHIGEKATSU MORI, YOSHIHIRO MIZUTANI AND SATOSHI MATSUI

Department of Industrial Chemistry, Nagoya Institute of Technology, Nagoya 466

Generally, the partial differential equation, which describes the three-dimensional steady heat conduction problem by use of the cylindrical coordinate system, is given by the following equation.

$$\frac{\partial^2 T}{\partial z^2} + \frac{\partial^2 T}{\partial r^2} + \frac{1}{r} \frac{\partial T}{\partial r} + \frac{1}{r^2} \frac{\partial^2 T}{\partial \theta^2} = 0 \quad (1)$$

where the thermal conductivity is assumed to be constant. Using the relationship $y \equiv \ln r$, Eq.(1) can be transformed into the following equation.

$$e^{2y} \frac{\partial^2 T}{\partial z^2} + \frac{\partial^2 T}{\partial y^2} + \frac{\partial^2 T}{\partial \theta^2} = 0 \quad (2)$$

Then, the following 7-point finite difference equations (F.D.E. hereafter) for Eqs. (1) and (2) by means of the computational molecules, i.e.,

$$\left[\begin{array}{c} a_2 \\ a_5 \quad a_0 \quad a_6 \\ a_3 \quad a_1 \end{array} \right] T_{l,m,n} + O(\bar{k}^2) = 0 \quad (3)$$

Received April 19, 1982. Correspondence concerning this article should be addressed to I. Yamada. H. Nakamura is at Dept. of Mech. Eng., Daido Inst. of Tech. Nagoya 457.