Eng., 3, 342 (1980).

- 2) Fujie, K., M. Takaine, H. Kubota and Y. Miyaji: *J. Chem. Eng. Japan*, **13**, 188 (1980).
- 3) Hills, J. H.: *Chem. Eng. Journal*, **12**, 89 (1976).
- 4) Ide, K., S. Kawabata and H. Shinohara: *Kagaku Kogaku Ronbunshu*, **2**, 439 (1976).
- 5) Nishikawa, M., Y. Yonezawa, T. Kayama, K. Koyama and S.

Nagata: *J. Chem. Eng. Japan*, **9**, 214 (1976).

- 6) Ohkawa, A., Y. Shiokawa, N. Sakai and K. Endoh: *J. Chem. Eng. Japan*, **18**, 172 (1985).
- 7) Otake, T., S. Tone and K. Shinohara: *J. Chem. Eng. Japan*, **14**, 338 (1981).
- 8) Shah, Y. T., A. A. Kulkarni and J. H. Wieland: *Chem. Eng. Journal*, **26**, 95 (1983).

CORRECTION OF THE PAPER "SYNTHESIS OF DISTILLATION SEPARATION PROCESS WITH ENERGY INTEGRATION"

MASAAKI MURAKI AND TOYOHICO HAYAKAWA

Industrial Engineering Dept., Tokyo Institute of Technology, Tokyo 152

Dear Sir:

We wish to call attention to recently discovered errors in **Tables 5** and **7** and **Fig. 5** of the paper "Synthesis of Distillation Separation Process with Energy Integration," published in *J. Chem. Eng., Japan*, **14**, 233-238 (1981). These errors were caused by a bug in the computer program for subproblem optimization. Fortunately, these errors have no serious effect on the conclusion of that study, and the effectiveness of the synthesis method proposed therein does not change. Tables 5 and 7 and Fig. 5 are revised, and the following additional corrections are necessary.

Page	Column	Line	Erroneous	Should be read
			(b, bottom; t, top)	
237	1	24b	27	33
237	1	18b	2.70	3.39
237	1	17b	26.8%	8.0%
237	2	14b	26.8%	8.0%

We regret any trouble caused readers who had interest in our paper. We are grateful to Prof. Z. Fonyo for bringing some comments on our paper to our attention.

Table 5. Several solutions of the subproblems

Subproblem	Annual cost [10^5 \$/y]	
	Rathore <i>et al.</i>	This study
2- 8	1.7168	1.3888
4- 6	2.8900	2.2479
4- 9	2.4737	2.0664
4-14	2.6149	2.4936
4-15	2.6363	2.2014

Table 7. Calculation results of most economical subproblems

Subproblem		Cost reduction [10^4 \$/y]	Pressure [atm]			
			Without energy match		With energy match	
Column 1	Column 2		Column 1	Column 2	Column 1	Column 2
2	4	2.910	5.52	1.64	9.11	1.66
4	6	2.696	1.64	7.26	1.55	11.87
4	14	2.457	1.64	5.22	1.56	11.04
4	18	2.455	1.64	7.44	1.58	12.18
2	15	2.326	5.52	4.70	5.58	8.79

Fig. 5. An optimal distillation separation process with energy integration.