Article

Classifying Plantation Forests in a Snowy Region According to Cutting Age using GIS: A Case Study of Private Forests in Sanpoku Town, Niigata Prefecture

Satoshi Tatsuhara^{*1, 2} and Takeo Dobashi^{*3, 4}

ABSTRACT

Forest stands must be evaluated before making zoning or harvest plans. This paper evaluated the net income of managed sugi (Japanese cedar, *Cryptomeria japonica* D. DON) plantations in private forests in a snowy region and classified sugi plantations according to the probability of harvesting, using a geographic information system (GIS), in a case study of private forests in Sanpoku Town, Niigata Prefecture. The town includes both low coastal and mountainous inland areas and the snow depth varies markedly. Two transfer points were assumed: a timber market and a local wood-related complex. First, log production was predicted according to site quality, using an existing stand density management diagram, as well as height growth curves to obtain log volumes according to log length and top diameter class. Gross income was estimated from log prices and the predicted log production according to site quality. Then, the total cost from planting through to logging was estimated for standard conditions of productivity, necessary workforce and wages, using four factors: site quality, yarding distance, the deepest snow depth and slope angle. The cost of plantation forest management included the regeneration cost for establishing new plantations and the logging cost for final cutting. Forest net income was evaluated for three cutting ages: short, intermediate and long rotation. Finally, sugi plantations were classified according to the probability of harvest and the area of each class was obtained using GIS on the assumption of present, 10% higher and 10% lower log prices. Site quality was the more important factor in sugi plantation management; it was more important than yarding distance or the deepest snow depth. Prices 10% lower than present prices on the Niigata Timber Market were the minimum necessary to maintain timber production from sugi plantations in private forests, given present costs and subsidies.

Keywords: cutting age, net income, site quality, snow depth, sugi, yarding distance

INTRODUCTION

Many of the plantation forests in Japan were established after 1950, when natural hardwood forests were converted into coniferous plantations. The cutting area of these coniferous

plantations is expected to increase in the near future. However, low timber prices, increased wages and the reduction and aging of the forestry workforce have decreased the cutting area of coniferous plantations, especially in private forests. The final cutting of many coniferous plantations has been postponed. Simultaneously, high-performance forestry machines have been introduced to increase productivity and reduce harvest costs. Therefore, plantation forests should be classified according to management goals and harvests should be scheduled. Moreover, each stand should be evaluated before making decisions with regard to zoning and the scheduling of harvest, for example. Usually site quality and yarding distance are used to classify production forests.

IEHARA and KUROKAWA (1990) compared the profitability of hinoki cypress (*Chamaecyparis obtusa* (SIEB. et ZUCC.) ENDL.) reforestation for different site qualities, and HASEGAWA (2000) evaluated the profitability of sugi (Japanese cedar, *Cryptomeria*

^{*1}Institute of Natural Science and Technology, Niigata University, Niigata 950-2181, Japan.

^{*2}Present address: Graduate School of Agricultural and Life Sciences, the University of Tokyo, Bunkyo-ku, Tokyo 113-8657, Japan.

^{*3}Graduate School of Science and Technology, Niigata University, Niigata 950-2181, Japan.

^{*4}Present address: Argos Co., Ltd., 1-1 Toyo-cho, Myoko City, Niigata 944-0009, Japan.

japonica D. DON) plantations, taking into account the effect of site quality. IEHARA (1993) evaluated the profitability of long-rotation management of a hinoki cypress plantation. The economic evaluation of plantation forests using site quality and rotation-length can be simulated using existing growth models. However, it is relatively difficult to evaluate the differences between yarding distance classes, because the productivity of reforestation and harvest operations are difficult to model using yarding distance classes. Moreover, it is not clear how snow depth affects the profitability of sugi plantations in a snowy region.

Geographic information systems (GIS) have been used to make or simulate forest plans; these systems consider not only the sustainability of forest resources, but also the spatial distribution of forests. GIS plays an important role in spatial decision support systems (SDSS). For example, KILGOUR (1992) developed a computer-based information system for recording and retrieving data on plantation resources, predicting growth and yield and forecasting the future availability of sawlogs and roundwood. NÆSSET (1997) developed an SDSS for long-term forest management planning that coupled GIS and linear programming.

The objectives of this study were to evaluate the net income of sugi plantations in private forests in a snowy region and to classify sugi plantations according to the probability of harvest, using GIS, in a case study of private forests in Sanpoku Town, Niigata Prefecture. Site quality, yarding distance, slope angle and the deepest snow depth were considered. First, log production was predicted by simulating growth to obtain log volumes, according to log length and top diameter class. Gross income was estimated from the predicted log production and log prices. Then, the total cost from planting through to logging was estimated using standard conditions for productivity, labour and wages. Net income was evaluated for three cutting ages: short, intermediate and long rotation. Finally, sugi plantations were classified according to the probability of harvest and the area of each class was obtained using GIS.

STUDY AREA AND DATA

Study Area

The study area consisted of private forests in Sanpoku Town, Iwafune County, Niigata Prefecture (38° 21'33" N, 139° 27'43" E). Fig. 1 shows the location of Sanpoku Town in northernmost Niigata Prefecture, Japan. The total area of private forest is 23,175ha, which is 82% of the total area of the town. The main forest type in this area is sugi plantation, which covers 7,368ha. The elevation varies less than 1,000 m, as shown in Fig. 2. The average deepest snow depth between 1971 and 2000 ranges from less than 1m near the coast to up to 2m inland (JAPAN METEOROLOGICAL AGENCY, 2002), as shown in Fig. 3.

Fig. 1 Location of the study area

Fig. 2 Elevation of the study area

Fig. 3 The average deepest snow depth between 1971 and 2000 in the study area

Timber produced in private forests is sold in timber markets, especially the Niigata Timber Market in Niigata City, or to local sawmills. Recently, forest owners and timber dealers constructed *Sugitopia Iwafune*, a complex of sawmills, a laminated wood factory and wood products factories in Sanpoku Town, to produce standardized timber from sugi in this region. This study evaluated two cases: logs transported to Niigata Timber Market or to *Sugitopia Iwafune*.

GIS Data

ArcGIS 8.1.2 (ESRI, 2001b), including ArcInfo Workstation 8.1.2 (ESRI, 2001a), was used as the GIS for this study. Twenty-three 1:5,000 scale forest maps were input into the GIS by digitizing the boundaries of compartments, subcompartments, contours and roads. Attribute data, which were written in a forest book, were stored in a database table for each subcompartment. The attribute table included the area, forest conditions (*e.g.*, species and stand age) and site conditions (*e.g.*, soil type and surface geology). A digital elevation model (DEM) was created for the study area from the contours and the spot heights of mountaintops. The spatial resolution of the DEM was set at 5×5m, because many forest owners have

small stands. The deepest snow depth was interpolated from the “Mesh Climatic Data 2000” produced by JAPAN METEOROLOGICAL AGENCY (2002).

METHODS

Silvicultural Systems

Site index based on an index age of 40 years was classified into three categories: site quality 1 (good), ≥19.4m; site quality 2 (medium), 15.7-19.4m; and site quality 3 (poor), <15.7m. Yarding distance was classified into five categories at 200m intervals: 0-200, 200-400, 400-600, 600-800 and 800-1,000m. The deepest snow depth was classified into three categories: 0-1, 1-1.5 and 1.5-2m. Slope angle was classified into four categories: 0-15, 16-25, 26-35 and 36+ degrees.

Density at planting was set at 2,500 trees/ha for site quality 1 and 3,000 trees/ha for site quality 2 and 3. The regeneration operations shown in Table 1 were assumed. In the study area, snowfall bends stems in winter and the stems need to be straightened by tying them up with rope. Forest managers should perform this operation until the average tree height exceeds two and half times the deepest snow depth

Table 1 Standard amount of labour (mandays/ha) required for each regeneration operation

Stand age	Operation	Site quality		
		1	2	3
1	Site preparation	28.5	28.5	28.5
	Planting	35.1	42.0	42.0
2	Reinforcement planting	1.7	2.0	2.0
	Releasing	8.7	8.7	8.7
3	Releasing	11.5	11.5	11.5
	Straightening stems	15.5*	18.3*	18.3*
4	Releasing	11.5	11.5	11.5
	Straightening stems	15.5*	18.3*	18.3*
5	Releasing	11.5	11.5	11.5
	Straightening stems	15.5*	18.3*	18.3*
6	Releasing	11.5	11.5	11.5
	Straightening stems	18.8**	22.6*	22.6*
7	Releasing			11.5
	Straightening stems	18.8**	22.6**	22.6*
8	Straightening stems		22.6**	22.6*
9	Straightening stems		22.6**	22.6**
10	Straightening stems			22.6**
11	Straightening stems			22.6**
12	Veining	10.0	10.0	10.0
13	Cleaning	14.0	14.0	14.0
	Pruning	17.0	17.0	17.0
17	Pruning	25.4	25.4	25.4

Note: *, operations for the deepest snow depth ≥ 1m

**, operations for the deepest snow depth ≥ 1.5m

(NOOMOTE, 1988; 1989). The intermediate-grade thinning system was assumed for the thinning schedule and intensity. The thinning ratio was 25% in terms of density and thinning was carried out at the age of 20, 30, 40, 50 and 60 years.

Predicting Log Production and Gross Income

Log production was predicted by site quality to obtain log volumes based on log length and top diameter class (TATSUHARA and MINOWA, 1992). The existing stand density management diagram for sugi on the Japan Sea side of the Tohoku and Hokuriku regions, and height/age curves for sugi in Niigata Prefecture (EROSION CONTROL SECTION, 1980) were used. Gross income was estimated from the predicted log production and log prices. The growth of model stands was simulated according to the thinning system at five-year intervals, beginning at 20 years.

Predicting the average height of dominant and codominant trees

The average height of dominant and codominant trees was obtained from the height/age curve. Mitcherlich's formula was used as the height/age curve as follows:

$$\begin{aligned} h(t) &= 34.789\{1 - 1.0906 \exp(-0.0259 t)\} \text{ for site quality 1,} \\ h(t) &= 28.873\{1 - 1.0853 \exp(-0.0254 t)\} \text{ for site quality 2,} \\ h(t) &= 22.732\{1 - 1.0846 \exp(-0.0254 t)\} \text{ for site quality 3,} \end{aligned}$$

where t is age in years and $h(t)$ is the mean height in meters.

Site quality 1, 2 and 3 corresponded to site quality 1, 3 and 5, respectively, in the yield tables for Niigata Prefecture (EROSION CONTROL SECTION, 1980). Average height is as important as density, as it is required when using the stand density management diagram.

Predicting diameter distribution

Both mean diameter and the diameter distribution are necessary for predicting log products according to log length and top diameter class. The Weibull distribution was used for the diameter distribution. The mean diameter and quadratic mean diameter were predicted from stand density and average height, using the stand density management diagram. The variance of diameter V was obtained from the mean diameter D and quadratic mean diameter D_q as follows:

$$V = D_q^2 - D^2.$$

The mean and variation coefficient of diameter determined parameters b and c , using GARCIA'S (1981) approximation method. Parameter a , which expresses the smallest diameter in the stand, was estimated from age, t , and the number of trees per hectare, n , using the following equation developed by NAGUMO *et al.* (1981):

$$a = p t^q n^r,$$

where p , q and r are parameters.

Predicting the height curve

The height curve was used to obtain the height from the diameter class. This curve was predicted from the mean height and mean dbh using a dimensionless height curve (NAGUMO *et al.* 1981), in which height h and dbh d are treated as dimensionless quantities divided by the average as follows:

$$\frac{h}{H} = \left(\frac{d}{D} \right)^{0.5594 - 0.00178t}$$

where t is age, H is the mean height and D is the mean dbh.

Predicting the stem taper curve

The stem taper curve was used to estimate log volume for log length and top diameter class. The true stem form for the diameter class was predicted from the height and dbh for the relative stem taper curve. KUNZE's formula was used as the stem taper curve.

$$y^2 = p x^r,$$

where x is relative height, $(h - m)/h$, y is relative diameter, $d / d_{0.9}$, h is total height, d is diameter at height m above the ground, $d_{0.9}$ is diameter where relative height x is 0.9, p and q are parameters.

The stand form factor was predicted from the number of trees and mean height of dominant and codominant trees, using the stand density management diagram. Setting breast height form factor at the stand form factor, the parameters of the relative stem taper curve were obtained by solving the equations derived from the relative volume.

Predicting log volume based on log length and top diameter class

After estimating the diameter distribution, average heights for diameter class and stem forms for diameter class, the log cross-cutting strategy makes it possible to predict log numbers and log volumes, according to log length and top diameter class in a stand. First, as many 4-m logs with a minimum top diameter of 30cm as possible were cut from a tree. This was then repeated for 3.65-m logs with a minimum top diameter of 22cm, 3-m logs with a minimum top diameter of 18cm and 4-m logs with a minimum top diameter of 8cm. FLURY's diameter elliptic ratio was assumed to be 4.5%, to estimate the shortest diameter at the top end.

Predicting gross income

Gross income was estimated by multiplying log volume and log price for each log length and top end diameter class and summing these values. Log prices were set at the average log prices for 2002 on the Niigata Timber Market and *Sugitopia Iwafune*, as shown in Table 2. Log prices was declining gradually and the average log prices in 2000, two years before, was 10% higher than those in 2002. Thus log prices were also set at 10% higher and 10% lower than the prices in 2002 as a range of possible fluctuation. The log prices per m³ vary with log length and top end diameter class. The

Table 2 Log prices (Yen/m³) by log length and top end diameter class

	Log length	Top end diameter		
		Small	Intermediate	Large
Niigata Timber Market	4 m	10,380		28,880
	3.65 m		14,480	28,880
	3 m	10,380	13,600	
<i>Sugitopia Iwafune</i>	4 m	9,000		17,000
	3.65 m		16,000	17,000
	3 m	9,000	14,500	

Note: Small, intermediate and large top end diameter class include diameters of 6-13, 14-28 and 30+ cm, respectively

Niigata Timber Market charges a commission of 8% on sales, while the *Sugitopia Iwafune* does not.

Estimating Expenses

The cost of plantation forest management includes (1) the regeneration cost for establishing new plantations and (2) the logging cost for thinning and final cutting.

Regeneration cost

The regeneration cost includes costs for planting, releasing, veining, cleaning, pruning and straightening. The planting density was specified as 2,500 trees/ha for site quality 1 and 3,000 trees/ha for site qualities 2 and 3. The reinforcement planting density was assumed to be 5% of the planting density. The seedling price was set at 75 yen for planting and 90 yen for reinforcement planting. We assumed that stems were straightened with rope until the average tree height exceeded two and half times the deepest snow depth. The average height was estimated using the height/age curves for each site quality and the deepest snow depth was estimated from the "Mesh Climatic Data 2000". The price of rope was set at 1,000 yen/roll for 2.5-bu(7.5-mm)-thick rope, which was used in 3- to 5-year-old stands and 900 yen/roll for 3-bu (9-mm)-thick rope, which was used in 5- to 10-year-old stands.

Workers' wages were set at 11,000 yen/day (MHLW, 2003). The ratio of insurance to wages was assumed to be 27.325% (OGURA and OGURA, 1997) and included workmen's accident compensation insurance, health insurance, welfare annuity insurance and unemployment insurance. The standard amount of labour required for each regeneration operation, when calculating silvicultural subsidies, was used. It is summarized by site quality in Table 1. The actual amount of labour was estimated from the standard amount of labour multiplied by a distance coefficient *DI* (TAKAHASHI *et al.*, 1996). This coefficient was calculated as follows:

$$DI = 0.95858 + 0.01523 S + 0.00008 D,$$

where *S* is the slope class and *D* is the distance to the nearest road (m). Slope class was 1, 2, 3, or 4 for slope angles of 0-15, 16-25, 26-35, or 36+ degrees, respectively. Miscellaneous expenses were assumed to be 8.7% of wages and were added to the site preparation, releasing and cleaning costs.

Logging cost

Logging costs consist of (a) logging operation costs and (b) common logging costs required to install and remove a yarder and log deck, maintain the logging site and transport workers. Logging and common costs were estimated, mainly, using the methods described by UMEDA *et al.* (1982)

The conventional logging system was used to estimate logging costs because the conventional system is still used in Sanpoku Town. For final cutting, the following system was assumed:

Felling with a chain saw → cable yarding → bucking with a chain saw

For thinning, felling with a chain saw was assumed because thinning does not generate income and thinned trees are left in the forest in most cases.

1. Logging operation cost

The logging operation cost is the sum of the operation costs for felling, yarding and bucking, as well as transportation costs. The operation costs include four costs: the machine rental cost including attachment rental, fuel expenses, personnel expenses and miscellaneous expenses for each operation and are calculated as follows:

Machine rental cost per m³ = machine price × the rate of depreciation per hour × working hours per day / productivity,

Fuel expenses per m³ = the amount of fuel per day × fuel price / productivity,

Personnel expenses per m³ = wage × the number of workers / productivity.

where productivity means log volume produced for a day per person. The wages of loggers were set at 14,000 yen/day.

The ratio of insurance to wage was assumed to be 27.325%. Miscellaneous expenses were assumed to be 10% of the wage.

The transportation cost was estimated as the trucking fare per m³, dividing the truck fare by the load capacity. The nearest timber market, Niigata Timber Market, is about 110 km from Sanpoku Town, while the distance to *Sugitopia Iwafune* was set at 10 km. We assumed that 6-ton trucks were used and the fares were set at 40,050 and 13,900 yen, as the average fares for 110 and 10km, respectively, according to the Niigata Prefecture Trucking Association. Therefore, the cost was calculated at 6,675 and 2,317 yen/m³ for the Niigata Timber Market and *Sugitopia Iwafune*, respectively.

The logging operation cost per m³ without insurance, miscellaneous expenses and transportation cost was estimated from the productivity of felling and bucking, P_1 , and the productivity of yarding, P_2 , using the following equation:

$$\text{Logging operation cost per m}^3 \text{ without insurance, miscellaneous expenses and transportation cost (yen/m}^3\text{)} = 16,496 / P_1 + 67,708 / P_2 + 737.$$

Then, the total logging operation cost per m³, including these costs, was estimated using the following equation:

$$\text{Total logging operation cost per m}^3 \text{ (yen/m}^3\text{)} = 21,722/P_1 + 89,781/P_2 + 4112.$$

The total logging operation cost was evaluated by multiplying the total logging cost per m³ by log volume.

The productivity of felling and bucking depends on the volume per harvested tree and harvested volume per ha (UMEDA *et al.*, 1982). The productivity of felling and bucking was modelled from figures drawn by UMEDA *et al.* (1982) as follows:

$$\begin{aligned} P_1 &= 12.29472\sqrt{x} - 0.56379 \text{ for final cutting when the harvested volume} \geq 300\text{m}^3/\text{ha}, \\ P_1 &= 9.075685\sqrt{x} - 0.53892 \text{ for thinning when the harvested volume is between 50 and } 300\text{m}^3/\text{ha}, \\ P_1 &= 7.526339\sqrt{x} - 0.42195 \text{ for thinning when the harvested volume is between 30 and } 50\text{m}^3/\text{ha}, \\ P_1 &= 6.000566\sqrt{x} - 0.35033 \text{ for thinning when the harvested volume} < 30\text{m}^3/\text{ha}. \end{aligned}$$

The productivity of felling and bucking was estimated from the volume per harvested tree, x . Felling was assumed to contribute 30%, in the combination of felling and bucking. If thinning did not pay, bucking was not carried out. Therefore, the productivity was estimated by multiplying the above value by 10/3. The productivity of yarding depends on the volume per harvested tree, yarding distance and engine power (UMEDA *et al.*, 1982). The productivity of yarding was modeled from figures drawn by UMEDA *et al.* (1982) as follows:

$$\begin{aligned} P_2 &= 0.95 (58.273 x + 7.448) \text{ for yarding distance class =1,} \\ P_2 &= 0.95 (50.636 x + 6.679) \text{ for yarding distance class =2,} \end{aligned}$$

Table 3 The amount of labour (mandays) required to install and remove a yarder and log deck

Yarding distance class	1	2	3	4	5
Installing yarder	10	24	38	52	67
Removing yarder	3	4	11	16	20
Installing log deck	16	16	16	16	16
Removing log deck	5	5	5	5	5

Note: class 1, 0-200m; class 2, 200-400m; class 3, 400-600m; class 4, 600-800m; class 5, 800-1,000m

$$\begin{aligned} P_2 &= 0.95 (48.000 x + 4.100) \text{ for yarding distance class =3,} \\ P_2 &= 0.95 (44.636 x + 3.219) \text{ for yarding distance class =4,} \\ P_2 &= 0.95 (40.375 x + 2.197) \text{ for yarding distance class =5,} \end{aligned}$$

where 0.95 is a modification coefficient for a cable yarder with an intermediate (20-75 horsepower) to powerful engine. The productivity of yarding was estimated from the volume per harvested tree, x , and the yarding distance class, assuming that a cable yarder has a intermediate engine.

2. Common logging costs

Common logging costs include the costs for installing and removing the yarder and log deck, maintaining the logging site and transporting workers. The amount of labour required to install and remove a yarder and log deck is shown for yarding distance class in Table 3. The amount of labour required to install and remove a yarder increased with the yarding distance, while the amount of labour required to install and remove a log deck is constant, regardless of the yarding distance. The costs of installing and removing a yarder and log deck were estimated as personnel expenses. The wages of loggers and miscellaneous workers were set at 14,000 and 11,000 yen/day, respectively. The ratio of insurance to wages was assumed to be 27.325%. These costs do not depend on the cut area or harvested volume and the costs per m³ decrease with increasing yield. Other costs were estimated using the method of the Forestry Agency of Japan, as follows:

$$\begin{aligned} \text{Cost of maintaining a logging site (yen)} &= 0.0587 \times \text{stand volume} \times \text{wage}, \\ \text{Cost of transporting workers (yen)} &= x \times (8.1 - 3.4 \times \log(\text{int}(x / 1,000,000))) / 100, \end{aligned}$$

where x is the total cost at a logging site, *i.e.*, the logging cost and costs of installing and removing a yarder and log deck without insurance, miscellaneous expenses and transportation costs.

Subsidies

The central government and Niigata prefectural government subsidize silvicultural operations. Together, the two governments subsidize 40% of the cost of planting, releasing,

straightening, thinning and pruning; the prefectural government alone subsidizes another 30% of the cost of releasing, straightening, thinning and pruning. Note that the standard subsidy costs for both governments are higher than those for the prefectural government alone. The net income was calculated after considering subsidies.

GIS Processing

Site quality was estimated for each subcompartment from elevation, slope aspect, slope angle, soil type, sedimentation type, microtopography, surface geology and the deepest snow depth, using the model developed with type I quantification theory by the Niigata Prefectural Government (EROSION CONTROL SECTION, 1978). Elevation, slope aspect and slope angle were estimated from the DEM. Sedimentation type and microtopography were also estimated from the DEM, using the values for specific catchment areas calculated from the water flow direction on the DEM. Soil type and surface geology were obtained from the subcompartment attribute table and the deepest snow depth was from the "Mesh Climatic Data 2000". The site index was estimated for each cell of a raster layer, using the model, and then the average site index for each subcompartment was calculated from the cells on the raster layer using a zonal function of the GIS.

Yarding distance was estimated for each subcompartment from the road data, calculating the straight-line distance to a road. Cable yarding systems were used to carry logs from the stand to a road in the logging system. The horizontal distance to the road was used as an easy index of the yarding distance instead of the true yarding distance, because landing points are not fixed, but are chosen for each logging situation. The yarding distance was estimated for each cell in the raster layer and then the average yarding distance for each subcompartment was calculated from the cells in the raster layer using a zonal function of the GIS.

Larvae of the long-horned beetle (*Anaglyptus subfasciatus* Pic) sometimes bore into the trunk from dead branches and eat dead knots, reducing the value of the trunk because of resulting decay and discolouration. Plantations affected by gales are damaged more easily because more branches in these forests are broken by the wind. In this study area, strong northwesterly winds occur in winter. Therefore, the subcompartments exposed to the northwesterly wind were assigned a higher probability of damage, using the shaded relief function of the GIS. The solar azimuth and altitude were set at 315° and 0°, respectively.

Classifying Stands by Cutting Age using Net Income

Net income was evaluated for stand ages of 50, 60 and 80 years, which correspond to short, middle and long rotations, respectively, by subtracting expenses from the gross income and considering subsidies. The discount rate was set at zero,

based on forest rent theory, because most owners have small forests in Japan and tend to base harvest decisions on the net income, which is based, in turn, on harvesting profit and regeneration cost. This varies with site quality, yarding distance, slope class and the deepest snow depth. The subcompartments were classified into four classes: (1) Class A: stands where the net income becomes positive by age 50; these plantations could be harvested using a short rotation, (2) Class B: stands where the net income becomes positive between age 50 and age 60 and have a low probability of damage; these plantations could be harvested using an intermediate rotation, (3) Class C: stands where the net income becomes positive between age 60 and age 80 and have a low probability of damage; these plantations could be harvested using a long rotation and (4) Class D: stands where the net income is still negative at age 80 or where the net income is negative at age 50 and the probability of damage is high due to strong winds in winter; these plantations are not suitable for timber production.

RESULTS AND DISCUSSION

The site index was classified according to the three site qualities, as shown in Fig. 4. Yarding distance was classified according to the five categories, as shown in Fig. 5. The classification of sugi plantations into the four classes is shown in Fig. 6 and the areas of the sugi plantations in each class are shown in Table 4. The figure and table show three cases: (a) present timber prices, (b) 10% higher timber prices and (c) 10% lower timber prices.

For present timber prices, when transporting logs to the Niigata Timber Market, class D occupied about 70% and 30% belonged to classes B and C. The latter two classes are scattered around the southern coastal area, where the deepest snow depth is less than 1m and stands have good site quality. For logs transported to *Sugitopia Iwafune*, profitability was improved. The percentage of class D decreased, while those of the other three classes increased, and class C occupied about 40%. As a result, stands in the coastal area and stands of good quality belonged mainly to classes A and B and inland stands belonged mainly to class C.

For prices 10% higher than the present level, for logs transported to the Niigata Timber Market, the percentage in class D dropped dramatically and 65% belonged to class C. Some stands in the southern coastal area, where the deepest snow depth was less than 1 m, and some stands with good site quality, belonged to classes A and B. For logs transported to *Sugitopia Iwafune*, the percentage of classes C and D decreased and those of classes A and B increased. Class C constituted about half. Stands in the southern coastal area belonged mainly to class A and stands in other areas belonged mainly to class B.

For prices 10% lower than the present level, for logs transported to the Niigata Timber Market, most stands

Fig. 4 Site quality in the study area

Fig. 5 Yarding distance class in the study area
 Note: class 1, 0-200m; class 2, 200-400m; class 3, 400-600m; class 4, 600-800m; class 5, 800-1,000m

Table 4 Area of sugi plantations in the four classes

(a) Present timber prices

Transportation site	Class A		Class B		Class C		Class D	
	(ha)	(%)	(ha)	(%)	(ha)	(%)	(ha)	(%)
Niigata Timber Market	77.0	0.8	1286.2	14.1	1498.4	16.4	6258.9	68.6
<i>Sugitopia Iwafune</i>	1626.3	17.8	2120.8	23.3	3866.1	42.4	1507.3	16.5

(b) Timber prices 10% higher

Transportation site	Class A		Class B		Class C		Class D	
	(ha)	(%)	(ha)	(%)	(ha)	(%)	(ha)	(%)
Niigata Timber Market	997.4	10.9	581.0	6.4	5903.6	64.7	1638.5	18.0
<i>Sugitopia Iwafune</i>	2651.2	29.1	4866.2	53.4	899.0	9.9	703.9	7.7

(c) Timber prices 10% lower

Transportation site	Class A		Class B		Class C		Class D	
	(ha)	(%)	(ha)	(%)	(ha)	(%)	(ha)	(%)
Niigata Timber Market	0.0	0.0	835.9	9.2	594.6	6.5	7690.0	84.3
<i>Sugitopia Iwafune</i>	1282.8	14.1	433.9	4.8	2369.2	26.0	5034.6	55.2

Note: class A, short rotation; class B, intermediate rotation; class C, long rotation; class D, unsuitable for timber production

Fig. 6 Classification of sugi plantations into four classes

(a), present timber prices; (b), 10% higher timber prices; (c), 10% lower timber prices

Left, transporting logs to the Niigata Timber Market; Right, transporting logs to *Sugitopia Iwafune*

Note: class A, short rotation; class B, intermediate rotation; class C, long rotation; class D, unsuitable for timber production

belonged to class D. For logs transported to *Sugitopia Iwafune*, the percentage of class D increased to 55% and those of the other three classes decreased. Class B occupied about half. Class A, B and C stands occurred mainly in the coastal area and most inland stands belonged to class D.

Regeneration cost accounts for around half of the total cost. Fig. 7 shows the standard total regeneration cost and subsidies by site quality and snow depth class. The straightening of stems prostrated by snow is necessary in snow depth classes 2 and 3, but not in snow depth class 1. These operations cost 20 to 40% and 30 to 50% of the total regeneration cost for snow depth classes 2 and 3, respectively; the subsidy for this operation occupied a similar percentage of the total regeneration subsidies. If this operation is carried out annually until the average tree height exceeds two and half times the deepest snow depth, it places a large burden on plantation forest management. The simulation showed the disadvantage of the costs of forest management in deep snow areas. Moreover, about two thirds of the total regeneration cost were covered by the central and local governments. The government subsidies improved the profitability of plantation management, although site quality 3 (*i.e.*, poor sites) was still

Fig. 7 The standard total regeneration cost and subsidies by site quality and snow depth class
Note: SQ, site quality; DS, the deepest snow depth class.

Fig. 8 The net income at the age of 80 years for slope class 2 when logs are transported to the Niigata Timber Market (a), subsidized for snow depth class 1; (b), without subsidies for snow depth class 1; (c), subsidized for snow depth class 3; (d), without subsidies for snow depth class 3

unsuitable when regeneration was subsidized. Forest owners' profitability for different regeneration ages did not change much for site quality 1, because growth was quick; however, it was most affected at the deepest snow depth for site quality 3, because the trees grew slowly.

Fig. 8 shows the net income for stands at age 80 years for snow depth class 1 and 3, for slope class 2 and for logs transported to the Niigata Timber Market. According to this figure, site quality affected the net income more than did the yarding distance class, although the net income changed with both site quality and yarding distance class. Yarding distance class affects the cost of harvesting timber and site quality affects both gross income and the cost of harvesting timber. Fig. 8 (a) and (b) show the case of snow depth class 1, where snowfall does not nearly affect forest management. Timber to be harvested depends on site quality. Thus, in this case, site quality had an even larger effect on gross income than on regeneration cost. Fig. 8 (c) and (d) show the case of snow depth class 3, where the effect of snowfall on forest management appeared sensitively. Comparing with Fig. 8 (b) and (d), the operations of straightening stems increased regeneration cost and this effect became more sensitive for stands with lower site quality, because the operation of straightening stems needs carrying out for longer period. In subsidized cases, Fig. 8 (a) and (c), the effect of snowfall became smaller than that in unsubsidised cases, as shown in Fig. 7. Yarding/skidding distance is one of the two most important variables affecting logging operations (CONWAY, 1982). However, IEHARA and KUOKAWA (1990) showed that site quality greatly affected the profitability of a hinoki cypress plantation and that site quality should have priority when considering reforestation with hinoki cypress, although they considered logging cost, but not yarding distance. Therefore, site quality should take precedence over yarding distance class when choosing sites for plantation forests.

The geographic distribution of the four classes changed with fluctuating timber prices. Fig. 6 (c) showed that prices 10% lower than the present prices in the Niigata Timber Market are the minimum required to maintain timber production from sugi plantations in private forests, given the present costs and subsidies. The geographic distribution changes with fluctuations in wages and timber prices. HASEGAWA (2000) showed that the difference in the profitability of sugi plantations among site qualities increased with wages and that the profitability fell rapidly for stands with low site quality. Sugi plantations on low-quality sites are not profitable at the present wage level.

We assumed that the logs were transported to the Niigata Timber Market or *Sugitopia Iwafune*. It is more profitable to transport logs to *Sugitopia Iwafune* because the transportation costs are lower; in addition, the prices of small and intermediate logs were very similar at the two sites, as shown in Table 2. Fig. 6 shows that constructing *Sugitopia Iwafune* improved the profitability of sugi plantation management in

private forests. For large logs, however, the price at the Niigata Timber Market was higher than at *Sugitopia Iwafune*. Therefore, forest owners can sell large logs at the Niigata Timber Market and other logs at *Sugitopia Iwafune*, to maximize profitability. This selective selling improves profitability, especially for 80-year-old stands.

For private forests, the conventional logging system is still most commonly used and high-performance forestry machines are used only for about 30% of stands, although more high-performance forestry machines are being introduced to logging operations in private forests each year (FORESTRY AGENCY, 2003). The following logging system is possible for stands within 400 m of a road and slopes no steeper than 15 degrees.

Felling with a chain saw → yarding with a tower yarder → bucking with a processor

The productivity of logging systems using high-performance machines was 2.8 times that of the conventional logging system and the harvesting cost for the logging system with high-performance machines was 93% of that of the conventional logging system (FOREST POLICY SECTION, 1996). Therefore, it is possible to increase profitability by using high-performance machines for yarding distance classes 1 and 2. However, it is difficult to increase profitability for yarding distance class 3 because only a processor is available for bucking instead of chain saws.

CONCLUSIONS

The silviculture of sugi plantations using clearcutting was analyzed in terms of net income. Site quality proved to be the most important factor for sugi plantation management and was more important than yarding distance and the deepest snow depth. It was more important in a snowy region than other region in Japan because of the operation of straightening stems. The probability of harvesting sugi plantations in private forests in Sanpoku Town was classified. For present timber prices, when transporting logs to the Niigata Timber Market, 70% of sugi plantations, especially plantations affected by snowfall, were unsuitable for timber production and transporting logs to *Sugitopia Iwafune* proved to improve profitability. The recent decline in timber price decreased profitability of sugi plantation management rapidly in this town. Timber prices 10% lower than present prices at the Niigata Timber Market were the minimum required to maintain timber production from sugi plantations in private forests, given present conditions in terms of costs and subsidies.

Forest owners can base the probability of cutting their stands according to log prices using GIS to plan their harvest schedule and forestry officers can utilize this method to devise a regional forest plan. In addition, the net income included government subsidies, because the management of many plantation forests requires subsidies. This simulation would be useful for assessing the value of subsidies needed.

ACKNOWLEDGMENTS

We would like to thank Erosion Control Section, Department of Agriculture and Forestry, Niigata Prefectural Government for providing GIS data in forest maps and inventory records. We would also like to thank the Niigata Timber Market and *Sugitopia Iwafune* for providing timber price records.

LITERATURE CITED

- CONWAY, S., (1982): Logging practices; Principles of timber harvesting systems. Revised edition. Miler Freeman, San Francisco, 432pp
- EROSION CONTROL SECTION, DEPARTMENT of AGRICULTURE and FORESTRY, NIIGATA PREFECTURAL GOVERNMENT, (1978): Report on forest soil survey in private forests; Kubiki forest plan region. Niigata Prefectural Government, Niigata, 49pp (in Japanese)
- EROSION CONTROL SECTION, DEPARTMENT of AGRICULTURE and FORESTRY, NIIGATA PREFECTURAL GOVERNMENT, (1980): Yield tables. Niigata Prefectural Government, Niigata, 172pp (in Japanese)
- ESRI, (2001a): ArcInfo Workstation 8.1. Environmental Systems Research Institute, Inc., Redlands, CA, USA
- ESRI, (2001b): ArcGIS 8.1. Environmental Systems Research Institute, Inc., Redlands, CA, USA, 51pp
- FOREST POLICY SECTION, DEPARTMENT of AGRICULTURE, FORESTRY and, FISHERY, NIIGATA PREFECTURAL GOVERNMENT, (1996): Plan to promote the introduction of high performance forestry machines. Niigata Prefectural Government, Niigata, 33pp. (in Japanese)
- FORESTRY AGENCY, JAPAN, (2003): Annual report on trends of forest and forestry: fiscal year 2002. Japan Forestry Association, Tokyo, 284pp (in Japanese)
- GARCIA, O., (1981): Simplified method-of-moments estimation for the Weibull distribution. N. Z. J. For. Sci. **11**(3): 304-306
- HASEGAWA, H., (2000): Evaluation of sawn timber production profitability based on site quality in sugi plantation forest. J. Jpn. For. Eng. Soc. **15**(2): 143-154 (in Japanese with English summary)
- IEHARA, T., (1993): A profitability and economic evaluation of the forest management of hinoki in a long-rotation operation. J. Jpn. For. Soc. **75**: 34-40 (in Japanese with English summary)
- IEHARA, T. and KUROKAWA, Y., (1990): An economic evaluation for reforestation with hinoki on low-productivity forest sites. J. Jpn. For. Soc. **72**: 34-45 (in Japanese with English summary)
- JAPAN METEOROLOGICAL AGENCY, (2002): Mesh climatic data 2000. Japan Meteorological Business Support Center, CD-ROM
- KILGOUR, B., (1992): FRIYR: An integrated and computerized system for forest management and yield regulation. In: M. MINOWA and S. TSUYUKI (Editors), Proceedings of the symposium on integrated forest management information systems. Japan Society of Forest Planning Press, Tokyo, 57-65
- MINISTRY of HEALTH, LABOUR and WELFARE, JAPAN, (2003): Summary of the results of investigating forestry workers' wages by type of job in 2002. <http://www.mhlw.go.jp/toukei/itiran/roudou/chingin/ringyo/02gaiyo/kekka.html> (in Japanese)
- NÆSSET, E., (1997): A spatial decision support system for long-term forest management planning by means of linear programming and a geographical information system. Scand. J. For. Res. **12**: 77-88
- NAGUMO, H., SHIRAISHI, N. and TANAKA, M., (1981): Computer programming for the construction of a sugi local yield-table - program TUSYCS. In: M. NISHIZAWA (Editor), Proceedings of Forest Resource Inventory, Growth Models, Management Planning and Remote Sensing, XVII IUFRO World Congress, Kyoto: 103-114
- NOOMOTE, M., (1988): Growth processes and ultimate tree forms of planted sugi (*Cryptomeria japonica*) trees in heavy snowfall areas. Trans. 99th Ann. Meeting Jpn. For. Soc.: 293-294 (in Japanese)
- NOOMOTE, M., (1989): Silvicultural technique in heavy snowfall areas. X. Bull. Niigata Prefectural For. Exp. Sta. **31**: 19-25 (in Japanese)
- OGURA, Y. and OGURA, Y., (1997): Evaluating forest lands and standing trees: How to survey and buy forests. Seibunsha, Osaka, 430pp (in Japanese)
- TAKAHASHI, T., TATSUHARA, S., ZHENG, Y. and NAGUMO, H., (1996): Economic evaluation of area-based forest plans: A case study for the Tokyo University Forest in Chiba Prefecture. J. For. Plann. **2**: 5-11
- TATSUHARA, S. and MINOWA, M., (1992): Predicting log products in a newly established plantation area. In: M. MINOWA and S. TSUYUKI (Editors), Proceedings of the symposium on integrated forest management information systems. Japan Society of Forest Planning Press, Tokyo, 268-277
- UMEDA, M., TSUJI, T. and INOUE, K., (1982): Standard productivity tables and timber evaluation. Japan Forestry Investigation Committee, Tokyo, 234pp (in Japanese)

(Received 8 April 2005)

(Accepted 4 April 2006)