講

ON GYROSTABILIZER FOR SHIPS.

BY

演

Noboru Watanabe.

船用ジャイロス
タビライザーに
就いて

INTRODUCTORY REMARKS.

Generally speaking, the properties of a gyroscope are complex and obscure. But, the simplest of them only is applicable to practical instruments. This is the relation between Torque and Precession. Let me explain this relation briefly.

Take a well known type of a gyroscope shown in Fig. 1. Without revolving the wheel, hang the weight W on a hook at P . Then the angular accerelation at start will be given by $\frac{WL}{j}$, L being the half length of the axle and j the moment of inertia of the gyroscope about the axis RS . In this case, the particles of the wheel—e.g. A —will move in the direction AA' entirely according to the force W

WL is the moment of the tilting couple. Denoting this torque by C , we have

$$\text{angular accerelation} = \frac{C}{j} \quad (1).$$

Now if the wheel revolves with sufficient speed, the particle A will not be entirely under the influence of C on account of its own velocity.

Let AA'' in Fig. 2. be the velocity of the particle. If the weight acts on A along AA' , the direction of velocity changes into AA''' instead of moving along AA' . This change of direction will occur with every particle of the wheel, and produce rotation of the

一四二(横)

wheel about the vertical axis UV . This rotation is called “precession” It is quite evident that precessional velocity is proportional to the moment of tilting couple and inversely proportional to the angular velocity (in radians) of the wheel.

Ω = precessional velocity

$\Omega \propto \frac{C}{\omega}$, where C = moment of tilting couple or torque

ω = angular velo. of revolution.

By simple integration, it may be proved that the proportionality constant in the above equation is the moment of inertia of the wheel about its axis of revolution. So that, we have

$$\Omega = \frac{C}{I\omega} \quad (2)',$$

I being the moment of inertia of the wheel about its axis of revolution. The faculty of resisting change of direction can be expressed by either (1) or (2)' Usually, I and j are in about the same magnitudes. Therefore, we may give large resistance or stability to the wheel with a certain amount of ω .

$I\omega$ is called the angular momentum or strength of the wheel, and denoted by N , and is an important factor in the gyroscope designing. Equation (2)' can be written in the form

$$\Omega = \frac{C}{N} \quad (2).$$

From Figs. 1 and 2, the following law of the relation of senses of Ω , C and ω can be very easily proved.

“If you stand at one end of the axle of the gyroscope, it will precess in the same sense to the rotation of the wheel as seen by yourself. Here, the moment of force due to your own weight determines the tilting couple.”

(“Nature” Aug. 21 1915. p. 202),

If the precession is prevented by a brake or other means, the

motion of gyroscope is as given by (1) instead of (2). This means that the gyroscopic property is thrown out.

講

1. Principle of the Gyrostabilizer for Ships.

演

船用ジャイロス
タビライザーに
就いて

Among the applications of the property of the gyroscope to keep constant direction, the ship stabilizer has recently been one. The idea of stopping the rolling of a ship by spinning top, which does not fall down even with gravitation, is simple and ingenious. But until quite recent years there were practical difficulties. Dr. Otto Schlick in Germany was the first inventor to make experiments on board ship. A fairly good result on board the old German torpedo boat "Seebar" in 1906, gave the chance of beginning experiments on the Hamburg American liner "Silvana" and on the "Lochiel" in England. But, no general application followed.

In 1910, Mr. E. A. Sperry in N. Y., U. S. A., published his improvements on Schlick's idea. By the improvements, the ship can be rolled in still water by the gyroscope besides being stabilized on the rough sea. Mr. Sperry has called the Schlick gyroscope a passive type, his gyroscope an active type.

This evening I wish to explain the theory of the active type. But I will explain the passive type first to give a clear conception of the other. The details of the discussion of the active type will be found in my paper published in "Proceeding of the Tokyo Mathematico Physical Society 2nd Ser. Vol. IX. No. 1. 1918."

2. Schlick Type or Passive Type.

In this type, the gyroscope is suspended pendulously in such a manner that the axle of gyroscope keeps the vertical direction. The axle of the gyroscope can swing pendulously about an axis

athwartship as shown in Fig. 3. The torque about the rolling axis of the ship — X axis in the figure—tilts the ship and the gyroscope. But the gyroscope resists the torque by precessing about the athwartship axis — Y axis in the figure. Considered dynamically, the motions of the ship and gyroscope are coupled motions of the two bodies.

Let φ be the angle of inclination of the ship, and ψ be the inclination of the axle of the gyroscope to its vertical position. Then, the following can be very easily seen.

- (1) The velocity of change of ψ or $\frac{d\psi}{dt}$ is the precessional velocity of the gyroscope due to the torque produced by the wave upon the rolling ship.
- (2) The velocity of change of φ or $\frac{d\varphi}{dt}$ (the rolling velocity of the ship) is the precessional velocity of the gyroscope due to the gravitational force of the weight attached to the lower end of the gyroscope.

Therefore, the torque produced by the wave upon the rolling ship will tilt the axle of the gyroscope, lifting its weight and decreasing the roll of the ship. In turn, this lifted weight tilts the gyroscope round the axis of suspension Y , and the precession about the X axis due to this tilting results the rolling of the ship. Hence, the wave does not roll the ship directly but indirectly. The rolling of the ship and swinging of gyroscope occurring alternately in this way, we can not stabilize the ship unless the brake F consumes this rolling energy.

The motions of ship can be classified into Free rolling and Forced rolling.

3. Free Rolling with Schlick Gyroscope.

In this case, the ship is rolling in still water and there is no external force. To get the maximum effort of gyroscope, it is

necessary to give the maximum torque due to the gyroscope in an opposite direction to the rolling, at the instant when the rolling velocity of the ship is at a maximum.

The maximum torque of the gyroscope will be given by the maximum precessional velocity of the gyroscope. From this, it follows that the rolling of the ship and the swinging of the gyroscope should be in opposite phase.

To obtain this opposite phase, the necessity of the following two conditions may be proved mathematically.

- (1) The period of the still water rolling of the ship must be equal to the period of pendulous swinging of the gyroscope when not revolving.
- (2) Assuming the torque due to the brake action is proportional to the precessional velocity, the proportionality constant K has the following value.

$$K = 2N \sqrt{\frac{j}{\theta}},$$

where

θ means the moment of inertia of the ship round its rolling axis.

j , the moment of inertia of the gyroscope round the precessional axis Y .

N . The angular momentum of the gyroscope.

4. Forced Rolling with Schlick Gyroscope.

Now, the oscillating bodies, the ship and the gyroscope, are forced by the period of the wave. The ratio of the amplitudes of the rolling of ship and of torque due to the wave is a functions of the period of still water rolling, angular momentum of gyroscope, its period of pendulous suspension, force of the brake etc..

This relation can be clearly seen from the curve in Fig. 4. The ordinate is proportional to the square of that ratio, the abscissa being the ratio of the period of still water rolling to that of the wave, while K is proportional to the brake constant. From this, it is easily understood that the rolling of ship becomes enormously large for certain periods of the wave, when $K=0$ (i.e. when the brake is not applied) and $K=\infty$ (i.e. when an infinitely strong brake arrests the precession).

造船協會會報
第二十四號

5. Determination of the Size of Schlick Gyroscope.

Assuming that the rolling of the ship is sinusoidal, the inclination of the ship φ' is given in the form,

$$\varphi' = \varphi_0' \sin \sqrt{\frac{Qs}{\theta}} t,$$

where φ_0' is the amplitude of the rolling, Q the displacement of the ship, S the metacentric height, θ the moment of inertia about its rolling axis, and t the time. The maximum rolling velocity is $\varphi_0' \sqrt{\frac{Qs}{\theta}}$.

Let N be the required angular momentum of gyroscope to stabilize the ship, ψ_0 the maximum swing of the gyroscope.

If we desire to quench the rolling velocity $\varphi_0' \sqrt{\frac{Qs}{\theta}}$ during the swinging from $+\psi_0$ to $-\psi_0$, we have

$$\varphi_0' \sqrt{\frac{Qs}{\theta}} \theta = \int_{-\psi_0}^{\psi_0} N \cos \psi d\psi$$

$$\therefore N = \varphi_0' \sqrt{\frac{Qs\theta}{2 \sin \psi_0}} \quad \text{or} \quad N = \varphi_0' \frac{TQs}{4\pi \sin \psi_0}$$

T being the period of the still water rolling and being equal to

一四七(橫)

$2\pi\sqrt{\frac{\theta}{Q_s}}$. This gives the required value of N to quench the rolling of φ_0' . If we take $\phi_0=45^\circ$, we have $N=1.41\varphi_0'\sqrt{Q_s\theta}$. Let φ_0 be the amplitude of the rolling of ship in a sea. And put

$$\varphi_0' = m\varphi_0.$$

Here m is an experimental factor, which was taken 0.28 in Schlick's design, and φ_0 being taken $27^\circ \frac{1}{2}$, we have

$$N=0.00958\sqrt{Q_s\theta}, \text{ or } N=0.0153 TQ_s.$$

A being in tons, s in meter.

Next, the diameter, weight and revolutions of the gyroscope must be determined, but these depend upon the strength of material. The general procedure will be given in §7.

The data of strength of material used on "Silvana" were:—

Material:	Crucible cast iron
Breaking load:	36 ton / □"
Elongation:	20—20.5%
Elastic limit:	22.5 ton / □"

The dimensions e. t. c. actually adopted were as followings:—

	"Seebar"	"Lochiel"	"Silvana"
Length-Breath and Draught	$\overset{m}{35.6}$ — $\overset{m}{38.1}$ — $\overset{m}{1.14}$	$\overset{m}{41.6}$ — $\overset{m}{6.7}$ — $\overset{m}{2.75}$	$\overset{m}{62.5}$ — $\overset{m}{9.0}$ — $\overset{m}{27.1}$
Displacement	57 ton	360 ton	850 ton
Metacentric height	$\overset{m}{0.5}$	$\overset{m}{0.275}$	$\overset{m}{0.401}$
Proper period of oscillation	$\overset{m}{4.14}$	$\overset{m}{9.0}$	$\overset{m}{8.0}$
Longitudinal moment of inertia (k.g. $\overline{m}^2$)	12375	214000	552543
Diameter and Weight of gyroscope	$\overset{m}{1.00}$ —500 k.g.	$\overset{m}{1.20}$ —3000 k.g.	$\overset{m}{1.60}$ —5100 k.g.
Revolutions per minute	1600	1800	1800
Pericpherical velocity (m/sec.)	83	113	150.8

Angular velocity (radians/sec.)	167.55	188.6	188.6
Moment of inertia of gyroscope (k.g. m^2)	10.69	158.5	176.5
Angular momentum N	1789	11000	33300
Amplitude of precession	45°	75°	75°

造船協會會報

第二十四號

6. Sperry Type or Active Type.

There is no difference in the general principle of this type from the above, but the following improvements are added.

- (1) Adoption of a device to detect the direction of the rolling of ship.
- (2) By means of electric and mechanical devices connected with the above, the precession of the gyroscope is controlled by the motor named "precessional motor."
- (3) Control of the precessional speed by a governor or brake.

To detect the rolling of the ship, a small gyroscope named "controlling gyroscope" as shown in Fig. 5 is placed on the deck, its axle being athwartship. The controlling gyroscope can precess in a small angle about a vertical axis. At one end of the axis, there are a restitutional spring SS' and two electric contact cc' . The precessional motion is damped by means of a damper d . If the ship begins to roll to starboard for example, the controlling gyroscope begins to precess clockwise, but the precession is resisted by the tension of the spring S . If the rolling velocity exceeds a certain amount, the electric contact C is closed, because the travel of the end of the axle of the controlling gyroscope is proportional to the angular velocity of the rolling ship. The current through in C will control the precessional motion of the main or stabilizing gyroscope. If the ship begins to roll to port, the

一四九(續)

current through m' will control the stabilizing gyroscope in the opposite way to the above.

講

演

船用ジャイロス
タビリガーに就
いて

The brake is released by an electro-mechanical device whenever the precessional motor is started. If either the rolling velocity of the ship is under a certain value or the precessional motor speeds up over a certain limit, the brake is clamped. The speeding up of the precessional motor can be detected by means of a governor or other suitable device.

The operation of the above mechanism will be explained by the example of the yacht "Widgeon," the diagram of which is shown in Fig. 6. I was much pleased to have a chance to see this yacht, which was moored on lake Erie near Cleveland, Ohio, by the kind permission of Mr. E. A. Sperry and the owner of the yacht. Mr. E. G. Sperry took me on board. I took this opportunity to express my best thanks to these gentlemen.

Case 1. To stabilize the ship, the reversing switch being thrown to the right. Suppose the starboard side begins to go down.

The controlling gyroscope precesses clockwise and the lower electric contact is closed. The contact a of the relay switch are closed by the magnetic pull of the right electro magnet (1) excited by the current from the battery. The current from the d. c. ship supply source, passing the contact, releases the brake by the upward pull of the electro-magnet (2) and passing through the armature from above starts the precessional motor armature in some direction. The stabilizing gyroscope will be started in such a direction that the precession causes the couple to depress the port side. If the port side begins to go down, the current of the armature will flow from below, and the opposite revolution of the motor will produce a couple to depress the starboard side by starting the stabilizing gyroscope in the opposite direction.

If the rolling velocity of the ship does not exceed a certain limit, (I call this limit the sensibility of the controlling gyroscope), the contact of the controlling gyroscope is not made, and the brake is clamped, for there is no current through the electro-magnet (2).

If the precession of the stabilizing gyroscope exceeds its limit, the pivot on the gyro-casing cuts off the armature current by pressing the handle of knife switch and the brake comes into action.

Case 2. To roll the ship, the reversing switch being thrown to the left.

When the starboard side begins to go down, the left electromagnet (1) is excited instead of the right, because the reversing switch sends the current to the left in this case. For this reason, the direction of the precessional motor is the same as when in Case 1, the port side began to go down. The tilting couple produced by the gyroscope would depress the starboard side and increase the rolling.

7. Determination of the Size of Sperry Gyroscope.

According to experience, the amplitude of rolling of the ship increases wave after wave, and becomes as large as 20° or more. Let a_1 , a_2 and a_3 be three successive maximum angles of rolling, T and θ the complete period of still water rolling and the moment of inertia of the ship about the rolling axis respectively.

Then the angular momentum of ship at the instant, when the ship is in upright position between a_1 and a_2 , may be put approximately,

$$\frac{a_1 + a_2}{2} \cdot \frac{2\pi}{T} \cdot \theta.$$

At the next instant of upright position, this is

議
$$\frac{a_2 + a_3}{2} \cdot \frac{2\pi}{T} \cdot \theta.$$

The increase of the angular momentum during this interval is

演
$$\frac{a_3 - a_1}{2} \cdot \frac{2\pi}{T} \cdot \theta.$$

船用ジャイロス
タビリザーに就いて
Now let us put

Q = Displacement of ship in tons.

s = Metacentric height in meters.

N = Angular momentum of the gyroscope.

ψ = Angle of precession of the stabilizing gyroscope
reckoned from the starboard direction.

Then the moment of the stabilizing couple given by the
gyroscope is $N \frac{d\psi}{dt} \cos \psi$.

Let the revolving axis of the gyroscope precess between $\pm \psi_0$,
then the angular momentum given to the ship by the gyroscope
is

$$\int_0^t N \frac{d\psi}{dt} \cos \psi dt = 2 \int_0^{\psi_0} N \cos \psi d\psi,$$

between the two successive upright positions.

If the gyroscope can stabilize the ship, this should be equal
to the increment of the angular momentum of the ship.

$$\therefore \frac{a_3 - a_1}{2} \cdot \frac{2\pi}{T} \theta = 2 \int_0^{\psi_0} N \cos \psi d\psi$$

一五二(横)
or

$$a_3 - a_1 = \frac{2N \sin \psi_0 T}{\pi \theta}.$$

But, we have

$$T = 2\pi \sqrt{\frac{\theta}{Qs}}$$

or

$$\theta = \frac{T^2}{4\pi^2} Q_s$$

Therefore,

$$\frac{a_3 - a_1}{2} = 4\pi N \frac{\sin \phi_0}{Q_s T}$$

or

$$N = \frac{a_3 - a_1}{8\pi} \frac{Q_s T}{\sin \phi_0} = \frac{a_3 - a_1}{2} \frac{Q_s T}{4\pi \sin \phi_0}.$$

Taking $\frac{a_3 - a_1}{2}$ or the single roll increment to be $3^\circ.5$ and ϕ_0 to be 60° , we have

$$N = 0.0056 \times T Q S.$$

If we use more than one gyroscope, N will be divided between them.

Assume that the gyroscope has an annular form, the axial thickness being equal to the radial thickness and also to the internal radius. It is quite evident that the dimensions and weight of the gyroscope of required angular momentum depend upon the form of this profile. So the above is assumed for the sake of illustration.

Let this thickness be a . (see Fig. 7). The moment of inertia of such a disc is $\frac{15}{2} \delta \pi a^5$, δ being its density. The tensile stress due to the centrifugal force in the periphery of the gyroscope is $4\delta\omega^2 a^2$, ω being the angular velocity of the gyroscope.

Let L be the admissible working stress of the material of the gyroscope, then

$$4\delta\omega^2 a^2 = L.$$

But

$$N = \frac{15}{2} \delta \pi a^5 \omega.$$

From the above, we have

$$a = \sqrt[4]{\frac{4}{15} \frac{N}{\pi \sqrt{\delta L}}}.$$

Or,

$$\text{Diameter of the gyroscope} = 4 \sqrt{\frac{4}{15} \frac{N}{\pi \sqrt{\delta L}}}.$$

Then the mass of the gyroscope m is evidently

$$\delta 3 \pi a^3.$$

The forms of gyroscopes designed by Mr. Sperry differ from the above. The characteristics of some of them are shown in the following table.

船用ジャイロス
タビリガーに就いて

Displacement	40000 tons	10000	5000	430	165
Metacentric height	1.7 ^m	0.8	0.8	0.6	0.85
Rolling period	14"	13 [#]	12	8	5
Required angular Momentum ton $\overline{m}^2$	4 × 13200	2 × 2900	2 × 1325		374
Number of gyroscopes	4	2	1	1	1
Diameter of gyroscope	4.2	298	2.30	1.04	0.92
Weight, each	65 tons	23	13	13	0.90
„ total	260 tons	46	26	1.3	0.9
Revolutions per minute	605	855	1100	2600	2700
Percentage of whole instalation to displacement	1.1	0.80	0.95		0.96
Stabilizing pressure (See § 8)	90 tons	32	26		3.3

A comparison with antirolling tanks can be seen from the following table, which contains the data designed for the ice breaker “Ashtabula”

Displacement 4500 tons, $T=5''6-6''6$. $G.M.=4.8$

TANKS.*

Period of roll	Notes	Weight in tons			Percentage of displacement	Space required	Capacity for rolling ships.
		Water	Tanks	Total			
6	Two tanks 60' & 40'	784	95	897	19.8	Cn. Mr. 360	none
6 6	Two tanks 40' & 20'	490	65	555	12.4	626	„

* See “Active type of Stabiling gyro” by Mr. Sperry; “Proceeding of the Society of Naval Architects and Marine Engineers” Nov. 1912.

Complete gyro equipment.

Any period	One plan	0	0	51	1.1	64	8° to 10°
---------------	----------	---	---	----	-----	----	-----------

造船協會會報

第二十四號

8. The Pressure to Stabilize the Ship with Sperry's Gyroscope.

The moment of couple to stabilize the ship is given by

$$N \frac{d\phi}{dt}$$

ϕ being the angle of precession of gyroscope from the starboard line. To avoid excessive stress due to gyrostatic reaction, i.e. the stabilizing couple, it is quite beneficial to govern the precessional speed of the gyroscope.

Suppose this velocity is of such an amount that the gyroscope precesses between two limits during a half period of rolling, i.e.

$$\frac{d\phi}{dt} = \frac{2\phi_0}{T/2} = \frac{4\phi_0}{T}.$$

If we assume the length of the revolving axis of the gyroscope to be equal to its diameter, the gyrostatic pressure on the bearing of axle P is given by

$$P = N \frac{4\phi_0}{T} \frac{1}{D},$$

D being the diameter of gyroscope.

Taking $\phi_0 = 60^\circ$ or $\frac{2\pi}{3}$, we have

$$P = N \frac{4}{3} \frac{\pi}{T} \frac{1}{D}.$$

一五五(續)

9. Free Rolling with Sperry's Gyroscope.

For the sake of simplicity, I assume that the gyroscope precesses with its rated speed $\frac{4\phi_0}{T}$ as soon as the ship begins to

roll. This assumption is evidently not rigorous, but is sufficiently true to explain the character of the stabilizer. In this case, the constant couple $N \frac{4\phi_0}{T}$ is working opposite to the rolling. Therefore, it may be looked upon that the horizon tilts as much as $N \frac{4\phi_0}{T} \frac{1}{Q_s}$. And then, the rolling curve will be given as in Fig. 8. If the gyroscope determined in §7 is used, the displacement of the horizon $1^\circ.35$ about each half rolling.

10. Forced Rolling with Sperry Gyroscope.

I have assumed the wave is sinusoidal. The motion may be divided into three stages.

First stage. The ship begins to roll, but the stabilizer does not yet work, because the rolling velocity is under the sensibility of the controlling gyroscope.

Second stage. The stabilizer works, the gyroscope precessing.

Third stage. The stabilizer is clamped again after the rolling velocity decreases to the sensibility of the controlling gyroscope,

The rolling curve of the ship is shown in Fig. 9.

The periods of ship and wave are 12 sec. and 10 sec. respectively, and the rolling would reach 5° without the stabilizer. The sensibility of the controlling gyroscope is assumed to be $0^\circ.97$ per second.

Fig. 10 shows the same curve to a reduced scale.

Only a small part of the stabilization has been shown in the figure, but I think this is enough to illustrate the working of the gyroscope. Further discussion would have only mathematical interest.

11. Starting the Precession of the Gyroscope.

In the above discussion, it is assumed that the precession obtains its rated speed instantly, as soon as the rolling velocity attains the sensibility of the controlling gyroscope. I have discussed elsewhere* the precessional motion until it obtains the rated value. It is quite evident that this motion depends upon the nature of the couple of the precessional motor. I have assumed that the couple is constant. Even without a precessional motor, the gyroscope has the tendency to stabilize the ship by its precessional motion. This motor pushes the starting of precession and the precession reaches the rated speed more quickly.

The motions of ship and gyroscope are shown in Fig. 11. The similar discussion was given in the case to roll the ship.

12. Amplitude of Rolling Caused by the Gyroscope.

Still water rolling is usually expressed by the following formula.

$$\Delta\varphi = a\varphi + b\varphi^2$$

where a and b being constants.

The potential energy of the inclined ship being $\frac{1}{2}Qs\varphi^2$, the loss of potential energy during one complete roll is

$$\Delta(\frac{1}{2} Qs\varphi^2) = Qs\varphi \cdot \Delta\varphi = Qs(a\varphi + b\varphi^2)\varphi.$$

This loss increases with the amplitude of rolling. If this loss is equal to the energy supplied by the gyroscope during two complete precessions, the rolling reaches the limit. Let K be the couple of the precession motor, then the maximum rolling φ_0 is given by the following formula,

* See my paper referred in §1.

$$\varphi_0 Qs(a\varphi_0 + b\varphi_0^2) = K \cdot 2 \frac{2\pi}{3}$$

講 Let $K=10$ ton. meter, $a=0.100$ $b=0.010$,
 $Q=10000$ ton, $s=0.8$,

演 then $\varphi_0=9^\circ.5$.

The power of the motor will be given by

$$K.W = \frac{1}{75} K \times 1000 \times \frac{2\pi}{3}$$

In the above case, $K.W=43.2$.

13. Examples of the Gyrostabilizer.

The annexed photographs give the general idea of the gyroscopes practically used on board ship,

(1) Schlick gyroscope.

Fig. 12 shows the relative size of the ship “Silvana” and the gyroscope.

The gyroscope is revolved by means of a steam turbine, the blades of which are fixed on the axle of the gyroscope. The brake B controlled by the hydraulic piston can be seen in Figs. 13. and 14. In Fig. 15, the curves 1 & 2 are the declining angles of the still water rolling, the gyroscope being out of action; the curves 3 and 4 are those for the gyroscope in action. The rolling curves in a rough sea are given in Fig. 16. The gyroscope was in action from the instant marked B .

(2) Sperry type.

Figs. 17, 18 and 19 are the photographs of the gyroscope installed on the yacht “Widgeon.” The controlling gyroscope, relay switch etc. are clearly shown. The diameter of gyroscope is 3 feet. The rolling curve obtained on the lake Erie is given in

Fig. 20. The gyroscope was started to precess at the instant marked *B* and stopped at *A*.

Figs. 21 to 24 are photographs of the two gyroscopes and attachments as equipped on a steamer of 10000 tons displacement. They give a concise idea concerning the dimensions of ship and the gyroscopes. The diameter of gyroscope is 9 feet and weighs 23 tons, each.

討 論

講

○會長(寺野精一君) 唯今の渡邊君の御講演に對して御質問がございますれば、どうぞ御述べを願ひます。……御質問もございませぬければ、實驗をやつて戴きます。

演

〔是より實驗説明あり〕

船用
ジャイ
ロス
タビ
リザ
ーに
就
いて

Fig. 1.

Fig. 2.

Fig. 3.

Fig. 4.

Fig. 5.

Fig. 7.

Fig. 6.

Fig. 8.

Fig. 9.

Fig. 10.

Fig. 11.

Fig. 12.

Fig. 13.

Fig. 14.

Fig. 15.

Fig. 16.

Fig. 17.

Fig. 18.

Fig. 19.

Fig. 20.

Figs. 21 and 22.

Figs. 23 and 24.