Metropolitan-Vickers Rateau Marine Turbine.

By **H. L. Guy**, Esq. and **P. L. Jones**, Esq.,

[Read at the Meeting of the Society of Naval Architects of Japan,
in Autumn of 1922.]

The Authors, having been invited to contribute a paper upon the Metropolitan-Vickers Rateau marine turbine, have, in the following pages, endeavoured to indicate the process of evolution which has taken place in the development of this machine. Before dealing

Fig. 1.

with the considerations underlying the characteristic features of the turbine, it may be desirable to briefly describe its general construction.

Fig. 1 shows a typical longitudinal section of a high pressure cylinder, and Fig. 2

Fig. 2.

transverse section. Figs. 3 and 4 are corresponding sections for the low pressure turbine.

Steam is admitted to nozzle boxes RR which more usually are constructed to accommodate three blocks of nozzles, the number of nozzles in the blocks being different. Each block is controlled by a separate cut-out valve. After passing through these nozzles

Fig. 3.

the steam performs work on a two-row velocity wheel after which it passes through several Rateau stages A, leaving the high pressure cylinder by the exhaust C. Entering the low pressure cylinder at the steam belt D, the expansion is completed in several Rateau stages, after which the steam enters the condenser which is directly connected to the turbine cylinder.

Each Rateau stage consists of a stationary diaphragm containing nozzles and a wheel on which the blades are mounted. When the turbine is reversed, steam is shut off from the ahead turbine and is admitted to the astern nozzle blocks S, performing

work on the two-row velocity wheel F, and leaving the high pressure cylinder by the exhaust H. Entering the low pressure turbine at the belt B, it is completely expanded in two or more Rateau stages and thence passes to the condenser.

The nozzle boxes are pipe shaped steel castings; each box is inserted through a suitable circular hole provided in the cylinder, and is secured to the cylinder by means

Fig. 4.

of a flange at one end of the box only. The other end is free to expand and is provided with a guide pin to ensure that the plane of the nozzles is maintained parallel to that of the wheel and the nozzles themselves concentric with the wheel. Fig. 5 shows a set of these nozzle boxes.

Fig. 5.

It will be seen that they are of very stiff construction and well suited for withstanding deflection due to internal pressure. In the earlier designs of turbines a steam belt was provided at the high pressure end of the cylinder, this belt being cast in the cylinder itself. Suitable slots were cut through the walls of the belt and the nozzle box bolted up. This design is illustrated in Fig. 6, (A). It was found that as steam

Fig. 6.

pressures and temperatures were increased with this construction it was extremely difficult to prevent serious steam leakage from the belt at the horizontal joint. A further disadvantage lay in the fact that usually the steam conditions existing in front of the nozzles are such as to require that the steam belt is contained in a steel casting. With a steam belt cast integral with the cylinder this entailed either a complete cast steel cylinder or a cast steel portion at the high pressure end, thereby introducing undesirable circumferential joints. With the pipe design of nozzle box it is only necessary to make the boxes themselves of cast steel. These are small and very simple castings, and can therefore be easily and economically made and at the same time, thoroughly

satisfactory castings can be relied upon.

The first type of nozzle box adopted, and which is still used by other Makers, was inserted through a port of segmental or rectangular shape whose length was necessarily greater than that of the arc of the nozzles fed by it.

This design is illustrated in Fig. 6, (B).

In practice, such nozzle boxes were found to have certain disadvantages which became more serious as steam pressures and temperatures were increased. These arose principally from the fact that the relative expansion of the nozzle box and the cylinder to which it was attached, is $\frac{1}{1000}$ " for each inch length of opening for 150 degs. F. temperature difference between the nozzle box and the cylinder. If the fastening of the nozzle box to the cylinder was sufficiently rigid to wholly restrain this relative expansion, distortion of the cylinder or nozzle box usually resulted. If, on the other hand, the restraining forces were not sufficient to completely prevent the relative expansion, the joint between the nozzle box and the cylinder was ultimately sheared, and trouble arose from a leaky joint. It was difficult to make a good joint initially because of the elongated rectangular shape of the opening, and many methods which are successfully applied to making ordinary circular joints could not be used in this design. In the pipe type of nozzle box, the diameter of the circular opening necessary to introduce the nozzle box is only a fraction of the length of the nozzle arc fed by it and experience has proved that with the high steam pressures and temperatures now adopted, these joints can be successfully made and maintained tight.

It has been suggested that with the pipe type of nozzle box, difficulty may be experienced through the box tending to open out under the influence of steam pressure. In order to satisfy themselves on this point Metropolitan-Vickers carried out tests on several boxes of this type and the results obtained from one such test are shown in Fig. 7.

In a normal design the pressure existing in the nozzle box is of the order of 200 lbs/sq. in. gauge, and the pressure existing in the first stage of the turbine of the order of 50 lbs/sq. in. gauge. Measurements were taken of the change of the chord length and also of the change in the width of the slot opening. It will be observed that with

a pressure difference of from 150 to 200 lbs/sq. in. these changes are very small. It is to be observed further, that in these tests the slot openings were blanked off by means of a flexible copper joint which is equivalent to an expansion joint. The box, therefore, received no support such as would be received under normal operating conditions from the nozzle block which is bolted to it. With the nozzle block bolted on these deflections are materially reduced, particularly the slot opening.

One of the most characteristic features of the Rateau turbine is the method of fastening the blades to the wheel by rivetting.

Metropolitan-Vickers have experimented with and used a variety of blade fastenings and accumulated considerable experience with these types before the methods now adopted became their standard. In small turbines, and some of the earlier machines, blades were attached by caulking the packers into slightly dove-tailed grooves. This method was satisfactory for very low speeds only, and was early abandoned because of the difficulty inherent to all caulked attachments of being able to ensure that the caulking was sufficiently complete to prevent the blades breaking loose under running conditions.

A number of tests were carried out by us on the efficacy of dove-tail fastenings. These tests demonstrated that the jaw of the fastening was forced open perceptibly, concentrating the stress on the corners of the tongue, thus causing failure to take place at lower loads than would be expected from calculations based on the assumption that the load on the dove-tail was uniformly distributed over its bearing surface.

The critical speed of a blade depends not only on the rigidity of its attachment axially, but in any dove-tail fastenings, also on the extent to which a particular blade is backed up by the neighbouring blades or packers. While the backing up may be effective with the wheel stationary, its effect decreases as the speed increases, and may easily become zero at the normal running speed. This is a serious matter because there is always sufficient disturbance in a turbine to induce vibration in any member which is not rigidly fastened, and such vibration may ultimately cause a fracture. The critical speed of a blade with this type of fastening therefore, varies with the speed, and in consequence it becomes a very difficult problem to determine the critical speeds of the blades with sufficient accuracy to ensure that there is no danger of synchronous vibration being

stimulated at any of the running speeds.

Metropolitan-Vickers therefore, have adopted "T" root fastenings for short blades only, where the loading is comparatively very light, and the critical speed high under all conditions of running.

At one time welding appeared to offer an attractive means of attaching blades. Metropolitan-Vickers therefore investigated the possibilities in this direction and their experience was that while a very large percentage of welded blades when tested did not fracture at the weld, it was apparently impossible to ensure a good weld in every case, a certain percentage always failing at the weld, with a load only a fraction of that sustained by the good weld. An analysis of the tests showed that approximately 95% of the welds were good but 5% broke down with about half the load sustained by the others. In view of this fact and having regard to the very large number of welds which would be necessary if all the blades on a rotor were attached in this way welding was abandoned.

The rivetted fastening used to-day by Metropolitan-Vickers is identical with that used in the earliest turbines of this type built by them 14 years ago. As the necessary duty has changed in the development of the art, the rivetted fastening has been found to meet all requirements. It is always possible to design a rivetted root so that it is stronger than the active portions of the blade. In this case, the backing up which is such an important factor in stiffening the blade is provided by the rivets themselves. As the length of blades and their peripheral speed is increased, the number of forks on the blade have been increased so that the number of shears on the rivet are increased as illustrated in Fig. 27. In this way, blade fastenings have been manufactured for blades 17" long rotating with a tip speed of 840 ft/ second on a mean diameter of 63".

In considering blade fastenings, the importance of the rigidity of the fastening on the critical speed of the blade has already been referred to, and the conclusions stated are the results of experiments and experience.

It has long been the standard rule amongst Makers using methods of fastening other than rivetting, that the calculated critical speed of the blade must be at least 3.5 times

the running speed if failures of blades due to vibration troubles are to be avoided.

In order to ascertain the critical speed of blades, the apparatus shown in Fig. 8 has been employed by the Metropolitan-Vickers Research Department. In this, the blade A under test is attached to its holder C in exactly the same way as the blades are attached to the wheel in a finished turbine. By operating a switch, magnet B plucks the blade and starts it vibrating. At the same time, the magnet F releases the smoked plate E which falls against a stylus attached to the end of blade A. In this way a graph is scribed on the plate as shown in Fig. 9 from which the frequency of vibration can be calculated in the usual way. The results of tests taken in this way on two typical blades are as follows.

Blade.	Calculated C.S.	Test C.S. with rivetted root.	Difference per cent.	Test C.S. blade in vice.
1	5200	4578	13.7	5451
2	3070	2820	9	3228

The calculated critical speed was obtained by treating the active portion of the blade as a canti-lever and adopting the usual graphical construction. Such results illustrate the importance of the rigidity of the blade fastening, and in addition, show that with the rivetted fastening it is possible to calculate the critical speed very closely.

In choosing a material suitable for turbine blading several considerations have to be borne in mind:

High ultimate tensile strength and elastic limit are of first importance, because if the turbine dimensions are to be kept within reasonable limits the centrifugal stresses in the blades are considerable. It is not, however, sufficient to know the mechanical properties of the material at ordinary temperatures only. One must be sure that the strength of the material is maintained when operating at high temperatures, and is not permanently affected by repeated changes in temperature. Numerous tests have been carried out by different Experimenters on the strength of materials with varying temperatures.

In a paper contributed to the Paris Meeting of the Institution of Mechanical Engineers in June 1922, results of tests carried out by Professor F. C. Lea are given which confirm

Fig. 8.

1/8 3 7/8 ms Plate 2

Fig. 9.

the general results. From these it is apparent that the ordinary carbon and alloyed steels suffer only negligible decrease in strength at the maximum temperatures with which turbine blades are called upon to deal.

The case is, however, very different with bronzes, and Professor Lea shows the results of tests carried out on bronzes of five different compositions. In the case of a manganese bronze the ultimate tensile strength at 15 degs. C. is given as 35.7 tons/sq. inch, this being in the neighbourhood of the figure obtained with ordinary carbon steels. At 300 degs. C., however, the ultimate tensile strength of this bronze is only 17.7 tons/sq. inch. An aluminium bronze showed an ultimate tensile strength at 15 degs. C. of 37.48 tons/sq. inch, and only 10.42 tons/sq. inch at 300 degs. C.

Metropolitan-Vickers have experimented for many years with such materials as have been produced which appeared to offer some promise as blading material. Brass, phosphor bronze and monel metal were found to erode more readily than 5% nickel steel, and the two former suffer from deterioration in physical properties when subjected for long periods to strain under varying temperatures. For general work under average conditions, we have found 5% nickel steel, if suitably prepared, a very satisfactory material. It possesses a high ultimate tensile strength and elastic limit without being too hard to draw and maintains its mechanical properties throughout the ranges of temperature likely to be met with in turbine practice.

Tests extending over eight years have been carried out by Metropolitan-Vickers with blades constructed of rustless steel and iron. These materials have a chromium content of 13 to 14% and while they do not yet possess every desirable quality they appear to have, in a large degree, the property of resisting corrosion and erosion. Unfortunately, in order to obtain the best results from rustless steel, the material must be in a hardened condition and since it is not practicable to heat-treat the blades after machining the steel should be hardened before machining. This, however, results in material which is too hard to draw and work readily with ordinary machine tools, and in consequence, Steel Makers have recently concentrated on the production of rustless iron. This material closely resembles rustless steel except that it has a very low carbon content. It is claimed that rustless iron can be produced having similar anti-corrosive properties to that possessed

Fig. 10.

by rustless steel without being abnormally hard. At the present time, Metropolitan-Vickers have blades of one or other of these two materials in some thirty turbines.

An important feature of the Metropolitan-Vickers turbine is the design of the turbine spindle gland. One of these gland is illustrated in Fig. 10. It will be seen that it is arranged for operation either on steam sealing or water sealing. Normally, the turbine operates with a water seal. Water is supplied by means of the passage A to the periphery of the paddle wheel. The rotation of the paddle produces a centrifugal force at the periphery and it is necessary to supply the water under a certain head. In practice this head may vary from 5 to 25 feet. The centrifugal forces exerted on the water tends to maintain an equal length of water leg on each side of the paddle, but the difference in pressure between the inside and outside of the cylinder forces the water up the face of the paddle on the high pressure side until equilibrium is produced. Under normal conditions, a considerable portion of the outer face of the paddle is therefore not in contact with water. Experiments have been carried out on water paddles operating under a difference of pressure corresponding to that existing under service conditions, and also on water paddles wholly immersed in water. These experiments have shown that the power absorbed in rotating a paddle under operating conditions is considerably less than that required to rotate a paddle completely immersed and enclosed in a casing, at the same peripheral velocity. The work done in rotating a paddle in water is given by the following formula :

$$P = 6U^3D^2 \times 10^{-6}$$

where P is the power required in H.P.

U is the peripheral velocity in ft/second

D is the outside diameter in feet.

The actual power absorbed by a paddle under operating conditions is only about 50% of that given by this formula. In the case of a 3000 S.H.P. marine turbine, each paddle would absorb approximately 0.15% of the power developed in the turbine. The quantity of water required would be approximately 1½% of the total condensate. This water is not lost but returns to the condenser by passage B indicated in the Fig. 10.

The paddles are designed so that a water seal is formed at approximately $\frac{1}{3}$ rd. of the normal running speed. For lower speeds steam sealing is resorted to and the design of the gland is such that steam and water can both be on at the same time. It is customary when leaving port or when manoeuvring to work on steam seal, water sealing being resorted to as soon as the ship is on its normal course. When this gland is working under water sealed conditions no steam is blown into the engine room. This, while presenting a cleaner appearance than with steam sealed glands, has the very important advantage that steam cannot escape into the turbine pedestals and the possibility of this mixing with the oil and causing emulsification is eliminated. In none of the vessels fitted with this gland have any emulsification troubles been experienced.

As a result of the absence of steam blowing into the engine room, repeated observations in hot climates have shown that water sealing results in a cooler engine room than when steam sealing is adopted.

Of all the various considerations which have to be borne in mind in the construction of an impulse turbine, the design of the discs is of paramount importance.

A turbine disc has not only to withstand the centrifugal stresses arising from its own rotation together with additional stresses introduced by the centrifugal pull of the blades, but also stresses arising from difference in temperature between the periphery and the hub, stresses arising from forcing the wheel on to the shaft, and stresses arising from small vibrations. It is, therefore, of the first importance that the materials should be homogeneous and it is for this reason that while forged steel, rolled plate and cast steel have all been used by different Makers for turbine discs, the Metropolitan-Vickers Company have always confined themselves to the use of forged steel only.

The considerations just mentioned require that material used in disc construction should be the very best of its kind, and an elaborate technique of inspection has been built up by which very close watch is kept on those sources of possible trouble which have been revealed by our experience. Two kinds of steel are used by us for turbine discs, these having the following properties:

Material	a	b
Ultimate tensile strength—tons/sq. inch	40	48
Yield point—tons/sq. inch.	20	30
Elongation—per cent.	22	17
Contraction of area—per cent.	35	40
Phosphorus content—per cent.	Less than 0.05	Less than 0.05
Sulphur content—per cent.	"	"

The physical properties given in this table are minimum values.

The character of the centrifugal stress produced in a turbine disc is shown in Figs. 11 and 12, the former being for the type of wheel adopted in the first stage and the latter representing a typical wheel at the exhaust end of the turbine.

As is well known the stress on the hub varies as the square of the peripheral speed at the outer rim of the wheel and for any given revolutions per minute, the stress equations take the form shown on the right hand side of these Figs. on the assumption that the profile of the wheel follows a hyperbolic law. When the profile cannot be sufficiently closely approximated to by a single hyperbolic equation, it is necessary to treat the profile as made up of two or more such curves. The hub can be treated as a thick rotating ring loaded with the radial forces existing at the junction of the hyperbolic profile and the hub. The discontinuity in the stress curves in the Figs. is due to this method of treatment.

If, in place of rivetted fastenings, a dove-tail or "T" headed room is adopted, it is necessary to form a bulb rim of proportions indicated in dotted lines in Fig. 12 in order to limit the opening of the jaws to a permissible amount. This additional weight at the rim increases the stresses throughout the disc, the increased value of the tangential stress being indicated by the chain dotted lines. It might be argued that the stresses in the latter disc can be reduced to the value obtained with a rivetted fastening by increasing the axial dimensions of the disc. If such a course it adopted, the pitch of the discs on the shaft is naturally increased. Further, the weight of the disc is sensibly increased with the result that either the critical speed of the shaft will be brought much nearer the running speed or else the shaft diameter must be materially increased. Increasing

STRESSES IN VELOCITY WHEEL.

Radius of Wheel in Inches.

Fig. 11.

STRESSES IN A TYPICAL L.P. TURBINE WHEEL.

Fig. 12.

the diameter of the shaft is not always possible and in any case results in increased diaphragm gland losses. Further, the increased bore of the disc results in a further increase in stresses. One is, therefore, caught in a vicious circle which usually results either

in the speed of revolution being reduced or higher stresses being accepted. It is scarcely necessary to point out that the first critical speed of the turbine shaft should be kept at least 20% and preferably 30% above the speed at which the emergency governor is set, because marine turbines may be called upon to work for long periods at any lower speed. Further, those designs are to be preferred in which the turbine spindle is supported in two bearings only, because the critical speed can then be accurately determined. For this reason also the spindle should be attached to any other shaft by means of a flexible coupling.

In order to ensure that the wheels shall be tight on the shaft at maximum speed, they must be pressed on the shaft with an interference fit which is greater than the elastic expansion of the bore under centrifugal stresses at maximum speed. This condition can be fulfilled without the maximum stresses in the wheel being greater when the shaft is at rest than the centrifugal stresses at maximum speed, because when a wheel is pressed on a shaft, the bore of the shaft does not increase by the full amount of the difference between the diameter of the bore and the diameter of the shaft. With wheels and shafts of normal proportions about $\frac{2}{3}$ rds. of the pinch fit is taken up in expansion of the bore of the wheel and $\frac{1}{3}$ rd. in compression of the shaft. For instance, in the case of a wheel having a bore 10" diameter, and so proportioned that the maximum centrifugal stress is 8 tons/sq. inch at the tripping speed, the expansion of the bore under this condition will be 0.006". In order to ensure tightness the pinch fit must be at least 0.007" which will result in a stress when the wheel is stationary on the shaft of approximately 6.2 tons/sq. inch or about three-quarters of the centrifugal stress at maximum speed.

If this precaution is not adopted, and the wheels are loose by only a very small fraction of an inch at maximum speed, the bore of the wheel becomes extruded so that its diameter progressively increases until it is appreciably greater than the diameter of the shaft thus ultimately producing a loose wheel at all speeds.

Like all other elastic bodies, vibration can be set up in a turbine disc when the periodicity of an applied disturbing force synchronizes with one of the natural periods of vibration of the disc. A disc can vibrate in a great variety of ways. Vibration can take

Fig. 13.

Fig. 14.

Fig. 15.

place with any number of nodal circles or any number of nodal diameters. The forms of vibration which give most concern to Turbine Designers are the umbrella type, and also vibration about two, three or four nodal diameters. Figs. 13, 14 and 15 are reproductions of photographs taken of a disc vibrating about two, three and four nodal diameters respectively. The nodal areas are clearly shown up by the sand which runs from the vibrating portion to the stationary portion of the discs.

The critical frequency of a rotating disc is greater than that of a stationary disc on account of the righting effect of the centrifugal forces. In the case of a parallel disc without a hole, Lamb & Southwell have shown that the critical speed of a rotating disc can be obtained with very small error by a formula of the form.

$$N^2 = \alpha^2 \cdot \frac{h^2}{R^4} \cdot \frac{E}{\mu} + \beta \left(\frac{\omega}{2\pi} \right)^2$$

where h is half the thickness of the disc.

R is the radius of the disc.

E is Young's modulus.

μ is mass per unit volume.

α & β are numerical co-efficients.

ω is the angular velocity in radians per second.

N is the vibrations per second.

The values of α and β for steel discs obtained by Lamb & Southwell are given in the following table:

VALUES OF α

Number of nodal circles.	Number of nodal diameters.			
	0	1	2	3
0	—	—	0.5184	1.20
1	0.8669	1.977	3.353	5.133
2	3.823	5.564	8.153	10.42
3	8.693	11.55	14.74	18.345

VALUES OF β

Number of nodal circles.	Number of nodal diameter.		
	1	2	3
0	1.0	2.35	4.05
1	5.95	8.95	12.3
2	14.2	18.85	23.85
3	25.75	32.05	38.7

In the above formula for critical speed, the first portion is the square of the critical speed of the stationary disc, whereas the second portion is the square of the critical speed of the rotating disc neglecting its flexural stiffness. Professor Stodola has developed a graphical analysis by which the critical speed of rotating taper discs loaded with blades at the periphery can be obtained. For such discs the critical speeds can be expressed by a formula of the form :

$$N^2 = A \cdot \frac{h^2}{R^4} \cdot \frac{E}{\mu} + B \cdot \omega^2$$

where A and B are constants for any given disc whose value can be obtained by Stodola's method. For similar discs of the same material A and B are constants for the same type of vibration.

The frequencies of vibration of two discs calculated by Professor Stodola's method are exhibited in Fig. 16. The axial dimensions of the disc A are three-quarters of the axial dimensions of the disc B. The frequencies of a third disc C of uniform thickness have also been indicated. Two cases have been worked out for disc C. In the first, the disc has been treated as though it were rigidly fixed from the hub to a radius of 5.7''; in the second case, the disc has been assumed to be completely free. On the same figure, the frequency of the possible disturbing influences has been added. The relative immunity from any type of synchronous vibration is represented by the vertical intercept between the impulse curve and the vibration curves, e. g. in the case of the disc A it will be observed that the margin between the calculated critical speed with three nodal diameters, and the impulses likely to set up vibration of this character is only 11%, while the margin in the case of vibrations about four nodal diameters is 16%. In the

Fig. 16.

Fig. 17.

case of the disc B it will be noted that the margin is everywhere greater than 40%. It will be observed that in the case of disc C the vertical intercept between the frequency and the impulse increases very rapidly as the number of nodal diameters increases. It is therefore only necessary in discs of this type to investigate the vibration frequencies about one and two nodal diameters.

The way in which the critical speed is effected by the dimensions of the disc is illustrated by the following figures which apply to the discs just considered. If the diameter of the disc is kept constant, the following shows approximately the connection between the thickness of the disc and the critical speed.

Relative thickness.	1.0	1.1	1.2	1.3	1.4
Relative critical speed.	1.0	1.08	1.165	1.245	1.33

If, in series of discs rotating at the same angular velocity, the axial dimensions are the same at the inner and outer radii, and at all corresponding radial distances, the following table shows the relation between the outside diameter and the critical speed.

Relative outside diameter.	1.0	1.1	1.2	1.3	1.4
Relative critical speed.	1.0	0.855	0.735	0.635	0.550

The amplitude of the actual vibrations obtained during the tests illustrated by Figs. 13, 14 and 15 are plotted against the frequency of vibration in Fig. 17. The probable change in these vibrations caused by the centrifugal forces when the disc is rotating at normal speed is shown dotted in this Fig. This curve shows how closely the zones in which vibration can be set up adjoin one another, and it indicates the impracticability of running successfully between two critical speeds. The only safe course is to have an ample margin between any of the different critical speeds, and the impulse which can give rise to them. This margin should not be less than 30%.

The test results plotted on Fig. 17 are of additional interest, as recording the fact that vibration about one nodal diameter was distinctly observed. This case is usually neglected by mathematicians as being a type of vibration which cannot be set up.

If the temperature of a disc varies radially a stressed condition is set up in it owing to the tendency to expansion of certain rings in the disc being restrained by others a

lower temperature. When a turbine is warmed up before starting, or when the power developed by it is rapidly changed, or when in the case of a marine turbine it is reversed,

Fig. 18.

the temperature on the outer rim of the wheel is momentarily different from that of the hub. A gradient of temperature is therefore established along a radius. Professor Stodola has calculated the radial distribution of temperature in a typical turbine disc for various time intervals after a temperature difference of 150 degs. C. between the outer rim and the hub has been established by raising the temperature of the outer rim. These gradients of temperature are shown in Fig. 18 for a portion of the disc in the neighbourhood of the hub. The maximum stresses which can arise from this cause in the disc considered were also calculated by Professor Stodola and are shown in Fig. 19. In large discs,

Fig. 19.

stresses induced in this way may be sufficient to make the discs loose on the shaft, and even to overstress the material. In view of the time interval involved in changing conditions of operation of the turbine, it is improbable that temperature differences of as large an order as 150 degs. C. can be established in a disc, but there is no doubt that the stresses which can arise from this cause are by no means negligible, particularly in

large discs and in cases where they are additive to the normal centrifugal stresses.

In addition to the increased stresses which result from a gradient of temperature along a radius, there is the liability of an unstable condition being set up resulting in the disc kinking about two nodal diameters. The axial displacement of the extreme points on the kinked disc from their original position may be sufficient to bring these portions of the disc into contact with the diaphragms. Professor Stodola has shown that the critical temperature difference between the outer rim and the hub at which such kinking takes place depends on the ratio of the disc thickness to the radius and is connected by the relation :

$$T=A\left(\frac{h}{R}\right)^2$$

Where T =constant temperature difference.

h =half thickness of the disc.

R =outer radius of disc.

A =numerical coefficient.

The common practice of providing balance holes in turbine discs also has an important bearing on the question of disc vibration. When nozzles supply steam around the whole periphery of a disc a small difference of pressure is set up across it. This results from two causes :

- (1) The ejector action of the nozzles on the steam in the space between the disc and the diaphragm in front of it.
- (2) The leakage through the diaphragm gland which tends to build up pressure in this space, because there is no free exhaust from it.

These two actions oppose one another. The pressure difference which can be set up across a disc varies with the pressure existing at that stage. It is found by experience that in most of the low pressure stages in a normally designed turbine, the unbalanced force which can be set up is negligible. In the high pressure stages differences of pressure may cause appreciable end thrust and for this reason it is customary to provide means of communication, in order to pass steam from one side of the disc to the other, the object being to equalise the pressure across the disc. In those stages where nozzles

Fig. 20.

Fig. 21.

do not extend around the whole periphery, this means is provided by that portion of the circumference which is unoccupied by nozzles.

There are objections to drilling large holes through the face of the discs particularly in marine turbines, where the speed is not under the control of a centrifugal governor.

These objections are :

- (1) While the mean stress in a disc may be reasonable as shown by the curves in Figs. 11 and 12, at the place where the holes are drilled local stresses are introduced which may be two or three times as great as the mean.
- (2) The presence of balance holes increases the tendency of a disc to vibrate.

In the Metropolitan-Vickers marine turbine, these objections have been met by the provision of balance holes through the blades themselves. This construction is illustrated in Fig. 20. It is possible with this design to ensure that the stresses in the blades are not increased by providing such balance holes, i. e. the stresses at the portion of the blade affected can be kept less than in the working portion of the blade.

Until quite recently, while every care was taken in providing suitable passages to ensure that the steam moved smoothly along the prescribed path from entry at the first nozzles to leaving the last row of blades, it was allowed to pursue the tortuous path from the leaving edge of the last row of blades to the condenser tubes as best it could. This often resulted in a difference of pressure between the leaving edge of the last row of blades, and the top of the condenser of from $\frac{1}{2}$ " to 1" of mercury or more, corresponding to a loss in efficiency of from $2\frac{1}{2}\%$ to 6% . After making tests to ascertain the magnitude of the losses obtained in this way, Metropolitan-Vickers developed an exhaust construction whereby the steam is suitably guided on leaving the last row of blades and discharged sensibly uniformly over the whole area of the exhaust. In the marine turbine these exhaust guide blades are provided in the diaphragm shown in Fig. 21. That this object has been achieved has been demonstrated by measurements which have been taken on very large exhausts of this type. As the pressure differences are very small, differential gauges filled with paraffin were used. The results obtained on the exhaust of a large turbine when passing 228,310 lbs. of steam per hour into a condenser maintaining a vacuum of 28.62 Hg. (Bar. 30") at the turbine exhaust flange is shown in Fig. 22. In

Pressure differences around Exhaust Flange obtained
by means of Paraffin Differential Gauges.

Steam Quantity Lbs per Hour = 228310

Exhaust Area Sq. Feet = 96

Steam Velocity Feet per Sec. = 316

Fig. 22.

this case, the clear area through the turbine exhaust measured 16 ft. by 6 ft.

If a sufficient exhaust area to keep the loss down to small proportions is provided, it is of such a size that the continuity of the turbine structure is broken by it. In the exhaust construction illustrated in Figs. 3 and 4 it will be noted that certain of the guides Z run through the exhaust and at the forward end form walls of the turbine support, while at the aft end they are solidly knit up with the turbine barrel. These ribs, together with the outer walls of the exhaust, form a very strong box girder, with the result that the turbine can carry even the largest condenser with very small stresses being produced. It will further be noted that the steam is uniformly distributed over almost the whole length of the tubes. The exhaust diaphragm shown in Figs. 3, 4 and 21 has the further advantage that whether the ahead or the astern turbine is working, the steam from the last row of blades from the operating section is deflected so that it does not impinge on the last blades of the idle section. As the steam leaving the last row of blades contains a large percentage of water, if the blades on the idle section are not protected in this way they become eroded by the steam leaving the operating section. Further, if the steam from the operating section blows straight across to the idle section, negative work results from the impact and it has been demonstrated by test that this negative work can reduce the power developed by a reverse turbine, and therefore its efficiency, by as much as 15%.

In all Metropolitan-Vickers turbines, the condenser is placed immediately below the exhaust, and is carried by the low pressure cylinder. Considerable importance is attached to this, and the design of the turbine has been largely determined by it. Some of the advantages associated with this arrangement are as follows:—

- (1) An appreciably higher vacuum can be obtained behind the last row of blades as compared with those designs in which the condenser is connected to the turbine by even short pipes, particularly if these pipes take the form of bends.
- (2) The turbine is self-draining. The problem of draining a turbine with a top exhaust or with an exhaust in such a position that the lowest point in the flange leaving the turbine is above the bottom of the cylinder, is an exceedingly difficult one, and the Authors have not met a solution which is.

certain in its operation. The troubles which can and do arise from accumulations of water in a turbine cylinder are manifold.

- (3) The condenser is free to expand. In alternative arrangement the thrust which can result from the absence of free expansion of the turbine cylinder, condenser and connecting pipes can throw loads on to the turbine cylinder which may distort it and in other ways affect its alignment.
- (4) The construction and arrangement of the turbine and condenser seatings is simplified.
- (5) The condenser can be so arranged that the tubes can be withdrawn under the high pressure turbine cylinder resulting in a saving of space in the Engine room.

One of the distinctive differences between the marine turbine and one used for ordinary Power Station purposes is that the marine turbine is at one time operating and at another time rotating idly in the reverse direction to that in which it operates. Out of this difference arises a very serious difficulty which is naturally peculiar to marine turbines, and as a result it has long been recognised that reversing may be a dangerous condition. There is a good deal of misconception as to what really happens under this condition. Metropolitan-Vickers, having met with the usual difficulty with the first marine turbine they constructed when running on their Test Bed investigated the matter and arrived at conclusions which at that time were novel, but are now generally accepted. Imagine the position of things when the engines have been running ahead for some time and are then suddenly reversed. The different stages in the ahead portions have been operating at the temperatures shown in the dotted lines in Figs. 23 and 24, but immediately steam is shut off from them and they rotate in a direction opposite to the normal, their temperatures rapidly commence to rise. As is well known when a bladed wheel rotates in its normal direction in a stagnant atmosphere of steam, the blades whirl the steam about and an appreciable amount of work can be absorbed in this way. This is usually denominated the "windage loss". If the bladed wheel is rotated in the opposite direction the amount of work absorbed is increased from $1\frac{1}{2}$ to $4\frac{1}{2}$ times the exact amount depending on the nearness of the walls of the chamber in which the blades rotate to the blade itself.

Fig. 23.

In the case of a typical 3000 HP. marine turbine rotating at 3000 revolutions per minute, exhausting into 28" vacuum, approximately 50 BHP. is absorbed by the windage in the idle ahead turbine when running astern. The quantity of steam trapped in the cylinders is approximately 0.07 pounds. The temperature of this quantity of steam would, therefore, be raised at the rate of 1000 degs. F. per second provided no heat were radiated from the casing, and no steam is leaking into the idle turbine. The small amount of leakage steam which passes normally into the idle ahead turbine tends to limit the

Fig. 24.

maximum temperature which can be reached. In the normal case being considered, the maximum amount which may leak into the cylinder in this way is of the order of 0.07 lbs. per second, so that the limit of temperature fixed in this way should be approximately 1000 degs. F. Heat is, of course, also radiated from the casing which has the effect of reducing the maximum temperature obtained, but this effect is small. Observations of turbines operating under these conditions show that temperatures of 800 to 1000 degs. F. can be reached in an idle ahead turbine in about 15 minutes. When the direction of rotation is again changed, and the turbine is once more running in the ahead direction, steam will be admitted to a very hot turbine, and ultimately, the temperature distribution will again be that shown by the dotted lines, but now the reverse turbine will

begin to heat up in its turn. The chain dotted line in fig. 24 shews the estimated temperature distribution in the L. P. ahead turbine when running astern if no provision for cooling is made other than that produced by leakage steam from the astern to the ahead turbine. Very large temperature changes which take place in this manner can result in serious distortion which may bring the moving and rotating parts of the machine into contact, with disastrous results. Further, repeated heating and cooling in this way has a very ill effect on many of the materials used in the construction of the turbine such as iron castings or any parts made of bronze or brass, and it is a fact that serious trouble has been experienced arising from this cause. The difficulty has been surmounted in Metropolitan-Vickers marine turbines by a simple automatic arrangement which admits sufficient steam at low temperature into the idle turbine to carry away the heat generated, and at the same time, limits the temperature rise to a permissible amount. The steam used for

Fig. 25.

this purpose has already done work in the operating turbine. Its temperature is therefore low and as it has performed work before it is used for cooling, the loss in efficiency can be reduced to very small proportions. The full lines in figures 23 and 24 shew the estimated temperature distribution in the idle elements when provision is made for cooling these elements in the manner adopted by the M. V. Co. In Fig. 25. this cooling arrange-

ment is shown in a typical case. Steam is taken from the astern turbine after it has performed work in the high pressure section, and passes through the non-return valve A which opens under the difference of pressure between the operative and the idle stages of the turbine connected by the pipe B. Cooling arrangements of this type have been fitted to all Metropolitan-Vickers marine turbines and no difficulties have been experienced in operation through rapid or continual reversal, although the trouble which this device guards against is now very generally recognised as being the cause of many of the mysterious accidents which have occurred in marine turbines.

It may be suggested that the limiting temperature could be reduced to reasonable proportions by increasing the quantity of leakage steam. Unfortunately, the amount of steam which leaks from the ahead turbine into the astern turbine when the former is operating is approximately three times as great as that which flows from the astern turbine to the ahead turbine when running in the reverse direction. On the other hand, the amount of heat generated in the ahead turbine when running idle is from three to four times as much as that of the astern turbine running idle at the same speed. Thus, if the leakage is increased sufficiently to reduce the final temperature in the idle ahead turbine to safe limits, three times this amount of steam will leak from the ahead turbine to the astern turbine when the former is operating, thus resulting in a permanent loss in efficiency of considerable amount. Thus, supposing the leakage across the dividing diaphragm is to be sufficient to ensure that the maximum temperature in the ahead turbine when running idle will not be greater than 500 degs. F. the quantity of leakage steam required for this purpose will be approximately 0.22 lbs/second. Hence, when the ahead turbine is operating the leakage steam from the ahead turbine to the astern turbine will be approximately 0.65 lbs/second. However, in the case of the 3000 S.H.P. turbine being considered, this leakage would represent 5.7% loss of work in the ahead turbine, and in addition, the negative work performed by this leakage steam in the low pressure astern stages would be of the order of 1%. It will, therefore, be seen that the total loss, which it should be observed is a permanent loss, would be approximately 6.5%.

From the considerations effecting design which have just been reviewed, the balance of safety and therefore reliability obviously lies in constructing a turbine for a given duty

FIG. 26 a.

with as small a mean diameter of the blades as possible consistent with efficiency.

As the out-put to be developed at a given number of revolutions per minute increases, the main difficulty lies in providing adequate area through the last row of blades. The difficulty lies in reconciling reasonable stresses in the blades with the desirability of keeping the losses represented by the kinetic energy of the steam leaving the last row of blades within permissible limits.

If these two conditions are to be met the design at the exhaust end must be such that the longest permissible blade is used on the smallest possible diameter. Therefore those designs permit of the greatest extension in which the last step in expansion is performed in several rows of blades on several wheels.

The most obvious development along this line is the double flow exhaust, but this is inflexible, in that the change in economic output is from 2 to 1 and 2 to 1 only. Further in practical designs a number of stages are duplicated unnecessarily.

The "Baumann" multi-exhaust turbine was evolved to solve this problem, and this solution results in a system of turbine construction which is so flexible that it presents great manufacturing advantages.

Figs. 26 a & 26 b taken from Baumann's paper on "Large Steam Turbine Practice"* illustrate the principle of this construction.

The last stage of the normal turbine is replaced by the two diaphragms J and GE.

The steam leaving what in the normal turbine is the last but one row of blades D is split into two portions by the ring dividing the diaphragms into two rings G and E.

That portion of the steam passing through the outer ring of diaphragm blades E is fully expanded down to the exhaust pressure and operates in the ring of blades F which are of the normal impulse type.

Moving blade HF like the diaphragm GE in front of it is divided into two rings of blades H and F.

That portion of the steam which passes through the inner ring of diaphragm blades G is expanded through a small drop of pressure only and passes into the inner row of moving blades H. Here the steam is further expanded, the action being similar to that

* Journal of the Institution of Electrical Engineers Vol. 59. No. 302. June 1921.

in reaction blades. Leaving the moving blade H the steam is expanded right down to the exhaust pressure in diaphragm J and operates on the moving blades K.

It will be noticed in the figure that 58% of the total steam quantity passes through the moving blades K while 42% passes through the blades F, thus by the addition of one multi-exhaust stage the permissible output of the turbine is increased by over 70% by the addition of one diaphragm and wheel.

The principle can be extended to more than two exhaust rows. In Fig. 27 the principle is extended to the provision of 3 rows of moving blades each exhausting steam to the condenser.

This turbine which runs at 3000 rpm. was designed for a maximum output of 22,000 B.H.P. when exhausting into a vacuum of 28", and has been in successful operation for some time.

It will be noted that as the mean diameter of the blades in this turbine relatively to its output is very small, and as a large shaft diameter is necessary to ensure that the normal running speed is adequately below its first critical speed, the discs become rings, and are made of ample strength by rivetting them to the shaft itself.

With this construction it is claimed that a smaller mean diameter of blading can be adopted at the exhaust end than with any known alternative method, with the advantages that :—

- (1) The peripheral velocity is the lowest possible and therefore centrifugal stresses are relatively low.
- (2) The risks resulting from uneven temperature in the discs are reduced.
- (3) The critical speeds of the discs can be kept well above the periodicity of any possible exciting forces.
- (4) The shaft can be constructed with its critical speed well above the maximum running speed.
- (5) The diaphragms can be made of greater strength and rigidity.

In many turbine installations in spite of the higher efficiency of the prime mover relative to reciprocating engined vessels, the overall results have been prejudiced by the large amount of steam necessary for auxiliary services.

In ordinary mercantile practice with steam driven auxiliaries of the usual type, it is found that there is normally a considerable amount of auxiliary exhaust steam surplus over that which can be utilised in the feed heater.

If this surplus steam is passed to the auxiliary condenser or to the main condenser a considerable thermo-dynamic loss results. In the Metropolitan-Vickers turbine provision is made for the surplus auxiliary steam to be utilised in the low pressure turbine. For this purpose it is convenient to make a connection on the ahead interconnecting pipe. A large number of vessels are now at sea in which the auxiliary surplus steam is utilised in the above manner without any difficulties arising.

As an example of what the adoption of this arrangement may mean it should be realized that with the present design of the ship's auxiliaries driven by separate steam engines, the total consumption of auxiliary steam for an installation of 2,500 to 3,000 S. H.P. may easily be as high as 25% of the main steam quantity. It is rarely possible to utilize more auxiliary steam in the feed heater than approximately 10 to 12% of the main steam supply. If the surplus exhaust steam is led into the low pressure turbine, each pound of steam performs approximately half of the work which is done by a pound of high pressure steam admitted to the turbine in the ordinary way. It is thus apparent, that by the use of the surplus auxiliary exhaust connections as above described, it may be possible to realise an improvement of the order of 5% to 6% on overall consumption of fuel as compared with those installations in which the surplus steam is taken direct to the condenser.

From the first, in all Metropolitan-Vickers turbines the revolutions per minute of both high pressure and low pressure elements have been made the same. Owing to the nature of the design adopted it has been possible to do this without it being in any way necessary to compromise other elements in the design. In such a machine if the power is equally divided between the two cylinders the torque transmitted by each spindle is the same. As a consequence, those elements in the construction which are determined by the torque are duplicates on the two sides. The principal of these are the bearings, couplings, pinions and gear wheels. As the parts are interchangeable between the two sides, either the number of spares can be reduced or the utility of such spares as are carried is doubled. It will be appreciated that such duplication has considerable manu-

FIG. 27.

facturing advantages also.

Resulting from the fact that the revolutions per minute are the same on both sides, and also from the fact that with the Metropolitan-Vickers construction the mean diameter need not be determined by the requirements of the ultimate step in expansion, the same mean diameter of the blades can be used in the low pressure cylinder as is desirable in the high pressure cylinder. In this way many of the disc forgings are common to high pressure cylinders and low pressure cylinders, and many of the jigs used in the manufacture of these discs and blading are common to the two cylinders.

Further, due to the type of design adopted for the turbine glands and to the fact that the revolutions of the high pressure and low pressure turbines are the same, it follows that the four turbine glands required for the complete turbine can be made identical.

The authors desire to acknowledge the assistance given to them in the preparation of this paper by Mr. K. Baumann, and also Mr. L. S. Robson, M.Sc. (Tech.) who made the calculations of the critical speeds of discs upon which Fig. 16 is based. Their thanks are also due to the Metropolitan-Vickers Electrical Co. Ltd., for permission to publish the data contained in this paper.

Discussion.

Mr. K. Yokoyama:—The paper is very interesting and valuable to the turbine designers and users. I do not hesitate to agree that the Metropolitan Vickers Rateau Marine Turbines have so many specialities than other kind of turbines.

Fastening of blades by rivetting fork shaped blade roots to the wheel rim is so rigid that the exhaust part would bear still higher peripheral speeds. I think, indeed, there is no other means by which we can secure blades to the disc more rigidly than that used in the Rateau Turbines. In this method of fastening, all blades are unable to have equal strength, while, in the other case, the blades near the stopper are reduced in strength to a considerable degree owing to thinning of blade roots. But this method is too complicate and the cost of the turbine will be increased. In order to find the best form of blade roots more simple and practicable, a number of tests carried out by us in our firm, but

I regret to say we could not come to any conclusion.

It is very wise method to strengthen the blade by enlarging its width instead of thickness. In the latter, a considerable loss must be introduced by chocking the steam passages. With this shape of the blade root, the rim of the disc may be made very light, so we can reduce the stress of the disc to a considerable degree. Usual case of troubles in turbines are due to breaking down of blades. So, the turbine designers have to consider the strength of blades above all. But, we can not neglect to consider the strength of other parts, such as discs and spindles. All parts must be in a good proportion, that is, we can never allow to make a part very strong, while the other remains weak. From this point of view, I think, this method of the Rateau turbines is the most suitable one.

As for the blade materials, the writers recommended 5% nickel steel than others, the reason being less erosive than brass, phosphor bronze or monel metal. We have learned by test that nickel steel resists to rust more than non-ferreous alloys in steam of a high temperature, but I doubt that if it is more rust-proof in a marine turbine which is intermittently used, and, the writers have shown that an alminium bronze showed an ultimate strength of only 10,42 tons per square inch at 300 degrees C. But, I know that another kind of alminium bronze showed an ultimate tensile strength more than $27\frac{1}{2}$ tons per square inch at 400° C. I think, nickel steel must be avoided to be used for turbine blades as possible, and monel metal or some others are more preferable. Indeed, the improvement of steam turbines are depended on blading materials and it is an urgent requirement that we must have most suitable material for turbine blades.

The arrangement of multiple exhaust blading is very ingenious and seems that most of the advantages claimed are well founded. The problem in obtaining the maximum leaving area is indeed fundamental. But, we must consider that, in increasing the leaving area, the care should be taken that advantages obtained through the reduction of leaving losses are not out-weighed by losses due to splitting up of the steam flow, into two or more parts, I think that the multiple exhaust arrangement will introduce serious new losses in endeavour to reduce the leaving losses. Though losses in this arrangement are calculated in the paper, friction losses through extra blades and nozzles and clearance

losses will bring total losses to an amount which would compensate for a considerable increase in leaving losses in a commonly designed machine. It is not essential for high efficiency, to design too low leaving losses, as the steam has to be brought from the blade exits to the condenser, and either this is accomplished by the remaining velocity in the steam itself, or such velocity has to be created by the difference in pressure between blade exits and condenser. So, I think, it is a better way to consider the method of utilizing the leaving velocity in leading the steam to the condenser. I doubt how much steam consumption we can reduce. I am disappointed that the writers did not show any result of actual tests. It will be very interesting to compare this arrangement with ordinary single exhaust or double flow turbines. This arrangement will substantially increase the length of the machine, so the weight will become greater. There will be no considerable difference of weight between this arrangement and that of an increased diameter to have a sufficient leaving area with a preferable blade length.

It seems that the reason why makers adopted the low speed is not only to reduce leaving losses, but to overcome defects which has been experienced directly or indirectly to the use of high blade speeds. Of course, high blade speeds decrease the reliability of turbines to a great extent. Reliability is what the user has to consider first and next the thermodynamic efficiency, but this should not be developed at the expense of reliability. In the development of the modern steam turbine, it is noticeable tendency to have increased blade speeds, thus to have a smaller number of stages. I think, good design and suitable material will be able to eliminate all difficulties due to high blade speeds. It may be said with confidence that troubles are not general, but are rather limited to certain makes and can be avoided. As the consequence of low peripheral speeds, makers are obliged to adopt very long blades. In using long blades, two fundamental losses are introduced, one due to variation of speed ratio and the other due to variation of the pitch length along the blade length. It will be very interesting to compare the thermodynamic efficiency of turbines with low speeds and long blades and those with high speeds and short blades.

Let us assume two steam turbines developing 10,000 S. H. P. one with a blade speed of 550 ft. per sec. and a blade height ratio of 3.5 and the other with a blade speed of 700 ft. per sec. and a blade height ratio of 5.7. These figures are selected to give same

amount of stress in parallel blade due to centrifugal force only, in both turbines. The steam pressure is taken at 200 lbs. per sq. in. abs. and superheated 200°F. and vacuum in condenser to be 28 inches.

The following table shows the particulars and losses calculated.

Turbines No.	1	2
Blade height ratio $\frac{D}{h}$	3.5	5.7
Stress of parallel blade due to centrifugal force	8.8 tons.	8.8 tons.
No. of stages.	13	8
Mean diameter.	49"	54"
Blade height.	14"	9.5"
Blade tip diameter.	63"	63.5"
Leaving loss in percent.	2.05	3.35
Disc loss in percent.	1.17	1.6
Nozzle loss in percent.	7.5	6.6
Loss due to variation of speed ratio in percent.	.207	.0625
Loss due to variation of pitch length in percent.	1.5	1.12
Total loss in percent.	12.427	12.7325

In the above, the losses due to variation of speed ratio and pitch length along the blade length may be considered to be limited to one or two stages at exhaust side. So, limiting to the last stage only, I have calculated percentage losses for the whole turbine. Another losses, such as bearing, diaphragm and gland losses may be considered to be nearly same in both turbines. Thus, we have losses depend on blade speeds and sizes of blades and discs, as mentioned above. In above comparison, we know the difference of the thermodynamic efficiency between two turbines is very little and, if we consider that leaving speed may be utilized in leading exhaust steam to condenser, it may be said that the steam turbine with high blade speed has more efficiency. With regard to size and weight, it will be said that there is a great gain in the turbine with the high blade speed as we find from the above table that, the number of stages is reduced from 13 to 8, while the blade tip diameters remain nearly same.

But, application of the multiple exhaust arrangement reduces the turbine diameter to a considerable degree. So, this arrangement is applicable in such a case in which the space is not allowed to install a steam turbine of large diameter, as in the case for certain kind of war ships, although it is accompanied with some other disadvantages.

The introduction of the exhaust steam in regular stream lines along the whole length of the condenser is one which I most agree. It is very important to lead the exhaust steam in simple flow to the condenser, considering from the point that the leaving speed must be utilized. In most cases, the exhaust steam is choked in a plane at horizontal joint of casing, so we must be very careful to make the steam flow easily at this part. It is misunderstood that we are satisfied by giving plenty area for steam passage and not to take in consideration the nature of stream line. In a marine turbine, it is very necessary to put a guide for exhaust steam. Penetration of exhaust steam into astern blades, in many cases, causes turbine troubles.

Lastly, I repeat that this turbine has so many specialities than the other kind of turbines.

But I would like to say that improvement of turbines are mostly dependent on increase of peripheral speeds and it is done only by improvement of materials as well as the most careful design and workmanship well founded on theory.

Messrs. Guy and Jones:—The Authors wish to express their pleasure at the appreciative remarks of Mr. Yokoyama. There are certain points in his contribution with which the Authors would like to deal.

In regard to blading material, the position as the Authors outlined was that at the time of writing the paper; none of the usual blading materials could be regarded as entirely satisfactory in all circumstances. Metropolitan-Vickers have used nearly all the blading materials which have been produced but as stated in the paper, in the vast majority of cases based on long experience, the 5% nickel steel has proved the most generally satisfactory material. For the last nine years they have experimented with rustless irons and rustless steels and are using them to an increasing extent. These materials can now be regarded as satisfactory commercial materials and are now used to

a large and increasing extent in Metropolitan-Vickers standard turbines.

Some doubt has existed as to the suitability of such materials for marine conditions, but the Authors' experience in this respect has been uniformly satisfactory. The following table of relative corrodibility of 5% nickel steel and various grades of rustless iron and rustless steel was obtained as the result of long experiments by the Metropolitan-Vickers Research Department on the corrodibility of these specimens in an atmosphere of steam generated from sea-water into which regulated quantities of oxygen were introduced.

Relative Corrodibility.

5% N. S.	Rustless Irons and Steels.					
	Sample A.	Sample A. Air hardened.	Sample B.	Sample B. Air hardened.	Sample C.	Sample C. Air hardened.
523	127	100	119	137	127	100

The Authors have had experience with Monel metal blades but found that Monel metal was subject to erosion in a relatively high degree.

Mr. Yokoyama has doubts as to the efficiency of the multi-exhaust blading.

The Authors cannot present a more fitting reply to his fears than to reproduce the tests taken on two turbines fitted with multi-exhaust blading in the Dalmarnock Power Station of the Glasgow Corporation. The summary figures given are extracted from the report of Mr. Mitchell, the Chief Electrical Engineer of the Glasgow Corporation.

Glasgow Corporation. Dalmarnock Power Station.

Set No. 3. in the Station.

Nominal load—Kw.	18750	15000	11250
Date		11.1.23	
Duration of test—hrs.	1.718	2.14	1.0018
Approx. load at alt. terminals—Kw.	18200	15650	11800
Actual conditions:			
S. V. press. lbs/sq. in. g.)	250	254	254
S. V. temp. degs. F.	643	618	610
Vac. 30" bar. Inches Hg.	29.25	29.31	29.34
Cons. as run—lbs/Kw. hr. (power measured at alt. terms.)	10.222	10.218	10.374
Cons. corrected to design conditions (power measured at alt. terminals.)	10.293	10.207	10.333

Cons. corrected to design condns. (power measured at H. T. side of transf.)	10.398	10.303	10.421
Average consumption—lbs/Kw. hr.		10.335	
Guaranteed average consumption.		10.440	

**Glasgow Corporation. Dalmarnock Power Stn.
Set No. 2. in the Station.**

Nominal load—Kw.	18750	15000	11250
Date		19.7.23	
Duration of test—hrs.	1.194	1.543	1.178
Approx. load at alternator terminals—Kw.	19000	16400	12500
Actual conditions:			
S. V. press. lbs/sq. in. g.)	258.2	257.4	257.0
S. V. temp. degs. F.	712	711	693
Vac. 30" Bar.—Inches Hg.	28.71	28.89	29.02
Cons. as run—lbs/Kw. hr. (power measured at alt. terminals.)	9.733	9.745	9.982
Cons. corrected to design condns. (power measured at alt. terms.)	9.903	10.00	10.235
Cons. corrected to design condns. (power measured at H. T. side of transf.)	10.00	10.088	10.317
Average consumption—lbs/Kw. hr.		10.106	
Guaranteed average consumption.		10.44	

In regard to these tests it is of interest to add that the test on No. 3 set was taken 17,649 hours after the set was first installed during which time it had generated 42,195,400 Kw. hours. The tests on No. 2 set were taken 26,737 hours after the set was first put on commercial service, during which time it had generated 204,559,800 Kw. hours.

It should be noted that the steam consumptions of these two turbines as run in terms of shaft-horse-power measured at the turbine coupling are 7.22 lbs/SHP. in the case of No. 3 set and 6.92 lbs/SHP. in the case of No. 2 set. The steam conditions on the two tests, are of course different. From additional information supplied to him by Mr. Mitchell, Mr. H.M. Martin presented an analysis of the tests on No. 3 set in "Engineering" August 31st 1923, from which he deduces that the efficiency of the multi-exhaust blading is over 80%. He concludes "It is thus evident that the adoption of

the multi-exhaust has not involved any material reduction in the efficiency of the turbine. Indeed as far as the tests go they indicate that the efficiency of the last stage is much the same as the efficiency of those preceding it."

It is notable that the tests referred to were taken with the extraordinarily high vacuum of 29.31" (barometer 30") on a turbine which was designed for a vacuum of 29.1". The volume of steam to be handled by the multi-exhaust blading during the test was therefore 30% greater than under the designed condition and the fact that the Makers were willing to carry out tests at this unusual and extraordinarily high vacuum exhibits their confidence in the efficiency of the multi-exhaust blading, a confidence which is amply justified by the test result.

The Authors do not agree with Mr. Yokoyama's suggestion that if a large leaving velocity is permitted in a turbine this can be utilised in conducting the steam from the last row of blades to the condenser. They have taken many tests on the matter and their observations lead them to believe that the whole of the leaving velocity is definitely lost and that a fresh velocity has to be generated to carry the steam down through the exhaust. If one considers the exceedingly tortuous path through which the steam is to pass through the last row of blades to the condenser, this fact can be readily appreciated.

Mr. Yokoyama states that the weight and length of a machine having multi-exhaust blading will be greater than that of a normal turbine apparently of either larger diameter or double flow construction. The fact that the capacity of a 10000 HP. turbine can be increased 60% to 16000 HP. on a 3000 rpm. unit by increasing the length of the turbine by 13½" is, we think, a sufficient index that the increased capacity is obtained by very small total increase in total weight and dimensions with a consequent material saving in weight per SHP.

The Authors do not quite agree with the table representing a comparison between two turbines, one 49" mean diameter and the other 54" mean diameter given by Mr. Yokoyama. They would expect from tests on losses in turbines made by Metropolitan-Vickers over a number of years that the net gain for the smaller diameter turbine would be at least 2.02% as compared with the larger diameter turbine. Compared with the

losses as given by Mr. Yokoyama they are of opinion that the disc loss is underestimated unless this represents disc friction alone, in which case there is no item in his table to cover windage of the blades. Taking windage and disc friction together they would expect the loss to be 2.78% in the case of the 49" mean diameter turbine and 3.8% in the case of the 54" diameter turbine, a difference of 1.02%. They would also expect the nozzle loss to be the same in both turbines.