$$\begin{aligned} P_{\xi} - iP_{\eta} &= -i\rho V\Gamma e^{-i\alpha}, \\ M &= -2\pi\rho V^2 c_1^2 \sin 2(\alpha - \gamma) \\ &\quad + \rho V\Gamma c_2 \cos(\alpha - \delta), \end{aligned}$$

where

$$\begin{aligned} V &= \sqrt{u_0^2 + v_0^2}, \quad \alpha = \tan^{-1}(v_0/u_0), \\ \alpha_0 &= c_0 e^{i\delta}, \quad a_1 a_{-1} = c_1^2 e^{i2\gamma}. \end{aligned}$$

The hydrodynamical force and moment are the same as those, in which the cylinder is placed in a uniform flow with velocity components u_0 , v_0 , as they ought to be.

2). If we assume

$$\zeta = \frac{1}{2}(z + R^2 z^{-1})$$

instead of (6), the cylinder is a flat plate. When the flat plate, without translation, rotates about an axis through the mid-point of the section, no circulation may exist, and therefore $u_0 = v_0 = \Gamma = 0$, and we get, inserting these into (18) and (19), $P_{\xi} - iP_{\eta} = 0$, $M = 0$.

The results, also, ought to be.

3). If we assume

$$\zeta = \frac{1}{2}z + l + \frac{1}{2}\frac{R^2}{z},$$

in which l is supposed to be real, this also is a flat plate. Let us consider the case, in which the flat plate rotates about an axis distant l from the mid-point of the plate and in the plane of the

plate. In this case a circulation may exist so that the farther edge from the axis of rotation may be always a stagnation point, which is determined by (15) as

$$\Gamma = -2\pi\omega R(R+l).$$

The force and moment are

$$P_{\xi} = -2\pi\rho\omega^2 l R(R+l), \quad P_{\eta} = 0, \quad M = 0.$$

The hydrodynamical force is always directed towards the axis of rotation. This means that the fluid may be repulsed outwards as in centrifugal pump.

6. **Conclusion.** The method treated in this paper is particularly convenient in the case when an airfoil has both the translational and angular velocities, or an angular velocity in a special flow such as an outward flow from a source situated at the origin. The theory of centrifugal pump, in which there are a number of airfoils, will be treated in a subsequent paper by the writer.

References.

- 1) H. Lamb : Hydrodynamics, 6th ed., p. 20.
- 2) Tomijiro MORIYA : J. Soc. Aeron. Sci. Japan, 8 (1941), p. 576.
- 3) Rosa M. Morris : Phil. Mag., 23 (1937), p. 757.

The Geometry of the Perfect Tension Field. II*

By Kazuo KONDO, University of Tokyo

Part 2. The Geometry of Deformation.

§ 3. The Definition of the Path.

We have seen that each tension trajectory is a geodesic of the two-dimensional variety, curved or flat as the case may be, of the tension field as Theorem 2 or its extension shows it. Its differential equation is given by (2.8). But we can prove that it can be written in other forms than (2.8). For example, we can obtain such a sort of transformation as follows. According to the ordinary principle of the projective transformation of the paths in the geometry of connection, any system of one-dimensional varieties defined by a differential equation of the second order of

the type

$$\frac{d^2 u^i}{dt^2} + \Gamma_{(1)jk}^{(i)} \frac{du^j}{dt} \frac{du^k}{dt} = 0, \quad (3.1)$$

called the "path" where $\Gamma_{(1)jk}^{(i)}$ are the coefficients of connection of the field of such paths, coincides as a whole with the system defined by

$$\frac{d^2 u^i}{ds^2} + \Gamma_{(2)jk}^{(i)} \frac{du^j}{ds} \frac{du^k}{ds} = 0, \quad (3.2)$$

* Read at the 5th session of the Japan Society for Applied Mechanics, Sep. 10, 1948, as a continuation to the Report I, (1) of the References. Received on April 20, 1949.

where

$$\Gamma_{jk}^i = \Gamma_{jk}^{(1)} - \delta_j^i \phi_k - \delta_k^i \phi_j \quad (3.3)$$

and ϕ_j is a covariant vector which satisfies

$$2\phi_j \frac{du^j}{ds} = \frac{d^2 s}{dt^2} \left/ \left(\frac{ds}{dt} \right)^2 \right. \quad (3.4)$$

Both systems (3.1) and (3.2) mutually inter-related by (3.3) and (3.4) afford the same system of paths.

Now, let us perform the projective transformation to the geodesic system defined by (3.1) of the tension field, such as

$$\Gamma_{jk}^i = \{j^i_k\} - \delta_j^i \phi_k - \delta_k^i \phi_j \quad (3.5)$$

and

$$2\phi_j \frac{du^j}{ds} = \frac{d^2 s}{ds^{*2}} \left/ \left(\frac{ds}{ds^*} \right)^2 \right. \quad (3.6)$$

and let

$$\phi_i = \frac{\partial \psi}{\partial x^i},$$

where

$$\psi = \frac{1}{2} \log(1 + \varepsilon), \quad (3.7)$$

ε being the strain of elongation in the direction of the tension line. Then we get

$$\frac{d^2 u^i}{ds^{*2}} + \Gamma_{jk}^i \frac{du^j}{ds^*} \frac{du^k}{ds^*} = 0 \quad (3.8)$$

as the defining equation of the same system of path for the whole tension field.

But we have, by virtue of (3.6),

$$2 \frac{d\psi}{ds} \frac{ds}{ds^*} = \frac{d^2 s}{ds^{*2}} \left/ \frac{ds}{ds^*} \right.,$$

whence by (3.7)

$$1 + \varepsilon = \frac{ds}{ds^*} \quad (3.9)$$

by taking the constant of integration suitably.

The equation (3.9) shows that the length ds^* is identically equal to the original length of the line element of the path with the length ds , so far as the path is along the tension line. Hence we can conclude that the equation (3.8) is satis-

fied by the line which has originally formed the set of the material points of the tension trajectory before the deformation. We can name, therefore, the line defined by (3.8) and (3.9) on the original curved surface before deformation the "path of tension," taking the parameter s^* equal to the length along the line.

The deformation of the tension field can therefore be treated from the point of view of the projective geometry of path.

§ 4. The Completely Geodesic Tension Field.

Since the behaviours of the paths just defined depend on the distribution of the quantity ε , we cannot apriori, before the deformation takes place, know of what sort they will be. But there are certain cases in which their characters especially those depending on the coefficients of connection can be determined apriori in spite of the possible variety of the deformations. Let us call such systems of paths the "paths apriori" and the field the "tension fields apriori".

The simplest example of such cases may be that in which the paths coincide with the geodesics of the original surface. We shall call such paths of tension the "geodesic tension trajectories".

The necessary and sufficient condition for the geodesic tension trajectory is that

$$\Gamma_{jk}^i \frac{du^j}{ds^*} \frac{du^k}{ds^*} = \{j^i_k\}^* \frac{du^j}{ds^*} \frac{du^k}{ds^*}, \quad (4.1)$$

where $\{j^i_k\}^*$ is the Christoffel 3-index symbol for the original curved surface with the fundamental differential form

$$ds^{*2} = g_{ij} du^i du^j \quad (4.2)$$

expressed by the same variables of the coordinates.

From (4.1) and (3.5), we get

$$[\{j^i_k\}^* - \{j^i_k\} + \delta_j^i \phi_k + \delta_k^i \phi_j] \frac{du^j}{ds^*} \frac{du^k}{ds^*} = 0. \quad (4.3)$$

Now, let the path in question be coincident with one of the parametric line, namely $u^2 = \text{const.}$, in order to simplify the further treatments. The expression of the above criterion (4.3) is then reduced to

$$\{1^1\}^* = \{1^1\} + 2\delta_1^1 \phi_1 \quad (4.3.1)$$

because we have

$$\frac{du^j}{ds^*} \frac{du^k}{ds^*} = 0$$

for all the cases when at least one of j, k is different from 1.

Applying orthogonal curvilinear coordinates, we get further

$$g_{11}^* = g_{21}^* = 0, \quad g_{12} = g_{21} = 0$$

$$\{1^1\} = \frac{\partial}{\partial u^1} \log \sqrt{g_{11}}, \quad \{1^2\} = -\frac{1}{2g_{22}} \frac{\partial g_{11}}{\partial u^2},$$

$$\{1^1\}^* = \frac{\partial}{\partial u^1} \log \sqrt{g_{11}^*}, \quad \{1^2\}^* = -\frac{1}{2g_{22}^*} \frac{\partial g_{11}^*}{\partial u^2}$$

The equation (4.3.1) becomes then

$$\frac{\partial}{\partial u^1} \left(\log \sqrt{\frac{g_{11}^*}{g_{11}}} \right) + \frac{\partial}{\partial u^1} (1 + \varepsilon) = 0 \quad (4.4)$$

and

$$\frac{1}{2g_{22}^*} \frac{\partial g_{11}^*}{\partial u^2} = \frac{1}{2g_{22}} \frac{\partial g_{11}}{\partial u^2} \quad (4.5)$$

of which the former (4.4) is satisfied identically.

For further simplification, let the real length of the tension line be equal to du^2 , then

$$g_{11} = 1$$

and (4.5) becomes

$$0 = \frac{\partial(1 + \varepsilon)^2}{\partial u^2} = \frac{\partial g_{11}^*}{\partial u^2}$$

or

$$\frac{\partial \varepsilon}{\partial u^2} = 0,$$

whence we see that ε is a function of u^1 only. Thus we get

(Theorem 3) The uniaxial tensile strain of the tension field on the parametric line perpendicular to the stress vectors is stationary at the point where it crosses a geodesic tension line. If we shall call the uni-axial field, the whole of which is filled up with geodesic tension lines, the "completely geodesic tension field", we get

(Theorem 3-1 The uni-axial tensile strain of the completely geodesic tension field is the same, for any point on any parametric line which is perpendicular to it and vice versa.

For example, we shall mention some simple cases. The conical surface which is formed as a free system produced by stretching any surface of revolution in the direction of the axis is completely geodesic. We will prove later that the hyperboloid of revolution of one sheet formed by free torsion of the circular cylindrical surface with finite length is completely geodesic and, therefore, that the paths of the tension are the helices on the original cylindrical surfaces.

Especially it is evident that the uniform tension field for which ε is constant everywhere is completely geodesic. The uniform tension field can be flat or curved.

At last we shall not fail to notice that the condition (4.3.1) of geodesic tension line may not be identical with the more severe one that all the geodesics on the deformed surface should be geodesic on the original surface also which is expressed by

$$\{i^j\}^* = \{i^j\} - \delta_i^l \chi_j - \delta_j^l \chi_i,$$

where χ_i is a covariant vector.

§ 5. Geodesic Approximation.

Of the principal components of strain, the one tangential to the stress vector is due to the elastic elongation of the material line while the other perpendicular to it is due to the formation of wrinkles. It follows therefore, that the former is small compared with the latter when the elastic resistance of the material against tension is large, so small that it may be disregarded in comparison with the considerable large deformation due to the wrinkling. If the curvature of the original surface is finite, it must necessarily be accompanied by finite deformations, when it is stretched as a free system into a ruled surface. The lateral contraction, for which we have not any reason that finite deformations are prohibited,

can grow large enough. We may neglect then the elastic strain and write

$$\sqrt{g_{11}} = \sqrt{E} = 1 + \varepsilon = 1 = \text{const.} \quad (5.1)$$

for such cases, being led to a sufficient condition for a completely geodesic tension field. Therefore,

(Theorem 4) The tension field produced by the free deformation of a surface whose curvature is finite can, approximately, be regarded to be a completely geodesic tension field, by neglect of the elastic strain.

We shall call the approximation thus introduced the "geodesic approximation". The neglect in view of this approximation cannot be valid, if the contractive strain is of the same order as the tensile strain. But the contractive strain also may be so small as the elastic strain that we may safely neglect at all the change of the metric properties due to the deformation and apply the same fundamental tensor for both states before and after the deformation, if the curvature of the original curved surface is sufficiently small. The paths of tension can then be regarded as straight lines or geodesics of the surface.

Even if the original form is flat, the paths of tension do not coincide with the straight line, the geodesics in the original plane. But they can approximately be regarded as straight if the deformation is small. The same is true for the case of the flat tension field, which presents a plane form after the deformation.

§ 6. Variational Expression.

We know that the strain energy stored in the tension field must be smallest, when it really occurs, among those of all the possible states of deformation of the elastic system in question under the same given boundary conditions. We know, moreover, that no change of the state of strain and the strain energy stored should take place even if we cut the elastic membrane in a uni-axial state along any tension trajectory.

But it should be otherwise if we cut it not along but across tension trajectories. The line

along which we cut the field must then be uni-axial, for it forms a free boundary. There should therefore be produced a new distribution of stress lines. The strain energy should then be minimum for the new system thus produced, with the cut along the line mentioned above. It should be smaller than any other state which has no cut and therefore is constrained along that line. That is to say that the strain energy of the membrane of the tension field without any cut must have the largest strain energy stored in it compared with any system with a cut.

Hence we may conclude that

(Theorem 5) Among the states of strain under given boundary conditions of the elastic systems produced by cutting into many slender slices from the original membrane, what really occurs is the tension field and has the largest strain energy.

This is an extension of the interesting theorem of maximum strain energy due to Mr. T. Iai, which we have been calling in connection with his name since that time when he found it for the plane tension field as early as 1936. It is no contradiction to the principle of minimum energy but a transform of the same.* We hope we shall have opportunity to treat this problem more detailly in future.

Practical application of this theorem will naturally be carried out by the variational method. But the rigorous solution is not so easy, because the equation of the path along which we shall cut the field, contains the coefficients of affine connection which are themselves functions of the strain and so we cannot apriori know the possible paths. It can be easily performed and be useful only in the case of completely geodesic fields as well as of the geodesic approximation. We have to con-

*) Mr. S. Moriguchi has pointed out that it is a typical example of the involute transformation whose general features have been enunciated by K. Friedrichs (3), (4).

ついている。このときには Kaurit W と Kaurit WHK で接着剤の厚さ 1 mm のものとを比較しているが、大体に於て同じ位の剪断強度が出ている。著者はこの程度の試験だけでは余り決定的なことは未だ判らぬが、試験条件が厳であり、また木口の影響が甚しいから試験結果が非常に散ばっていること、そして接着面近くでの水分の変動を防止するだけに有効な防湿処置が是非必要であること、トウヒ(これから類推して針葉樹)では乾燥状態に戻れば接着強度が比較的良好になること、しかしブナでは著しく弱いこと、それで木口の防湿処理が特に重要であることなどの諸点を結論として掲げている。(倉西正嗣)

計 測

11. 組合應力による大きな塑性変形測定用の歪計
Strain Gages for Large Plastic Strains and Combined Stresses, J. Marin, ASTM Bulletin., No. 161, 1949/10, 28/31頁(学会), 円筒形試験片が組合応力を受けて生ずる比較的大なる塑性範囲の歪を測るために試作した歪計2種についてその構造性能等を述べたものである。その一つは軸力と振りを受ける時の試片の伸びおよび振り角を機械的に同時に測るもので、試片の

標点距離に2箇の円輪をばね付きの紙で止め、振り角はその両円輪の相対的回転角を円輪附属の指針で読み、軸歪は両円輪の軸方向の相対的変位を円輪の一方に固定したダイヤルゲージで読み取る。円輪をばねによって試片に取付けることによつて、試片が軸応力により径を変えても計器が狂うことなく、大きな塑性変形が精密に計れる点がねらいである。他の一つは円筒形試験片が内圧と軸力を同時に受ける時の軸方向および直徑または円周方向歪を同時に測る電気式の歪計である。即ち SR-4 計を貼り付けた薄い燐青銅製ばねクリップを同じく薄い燐青銅製の円輪2箇の間に橋渡しして、円輪を試験片の標点間に紙で取付ける。試片の塑性伸びに伴う両円輪間の比較的大きな変位はばねクリップに貼り付けた SR-4 計に比較的小さな伸歪を生じ、これを歪指示計(電気メータ)に導いて軸歪を読み取る。また試片の円周方向歪は試片の外周に緊縮した薄い帯金に矢張り SR-4 計を貼り付けたばねクリップを取付け、帯金の伸縮を SR-4 計の小さな歪に直してメータ読みと試片の眞の軸歪、円周歪間の関係の精密なキャリブレーションの方法も述べてある。(鶴戸口英善)

(16 頁よりつづく)

sider for such cases the variation in connection with the possible geodesic systems.

The simplest case is the plane field with small strain, for which we have to consider the variation by cutting off in connection with the system of straight lines as has been studied by Iai.

References.

- 1) K. Kondo : The geometry of the perfect tension field - I.
- 2) T. Iai : Method of solution by means of the theorem of maximum strain energy of the

problems of elasticity (in Japanese). The Journal of the Society of Aeronautical Sciences of Nippon. 10/96 (1943). p. 276.

- 3) K. Friedrichs : Ein Verfahren der Variationsrechnung das Minimums eines Integrals als das Maximum eines anderen Ausdruckes darzustellen. Göttinger Nachrichten (1929). S. 13-20.
- 4) R. Courant-D. Hilbert : Methoden der Mathematischen Physik I (Zweite Auflage). Berlin, Springer (1931). Kap. V.

(18 頁よりつづく)

に於て、航空時代の昔とかわらざる情熱を以て、再建に健闘する人々を見出すことは力強い限りである。

日本の将来は主として中小工業に頼らざるを得ないが今後如何なる中小企業の形態を以て如何にして優秀な近代工業製品を作り、國際的に競争し得る技術水準を維持発展せしめていくかが重大な問題である。その場合最も重大な欠陥は、現在に於ても既に顕著であるが、巨費を投じて基礎的研究を行い製品の改良、発明、発見等に役立つような設備、機関を各企業体としては殆んど持ち得ないということである。この点に於て各大学の研究機関、僅かに残されている民間研究機関および学会の使命は愈々重大となりつゝある。この間、

元航空関係者をその会員の約6割にもつ日本応用力学会は昭和22年創立以来各学会を横に連絡する廣い視野に立つて多くの業績をなしてきた。学会を通して各研究者の研究は技術発展のオアシスとして直接間接に我が工業に與える影響力の大きいことを強調したい。各大学研究所に於ける現在までの多くの研究成果の工業におよぼした影響も亦大きいものがあつたと信ずる。

総合工業であつた航空工業の基盤をなす関係学問および技術分野は廣く深い。戦後のおくれを急速にとりもどしつつある現在の我が工業にとつて、進歩の性格の航空技術者が各部門に入つて行つてゐることは、必ずや大きなプラスをもたらさずにはおかぬであらう。