Generation in Machine Translation: the right place to choose between translation equivalents

John D. Phillips[†]

This paper looks at the problem of choosing between alternative lexical translation equivalents in machine translation. It argues that the knowledge base used for making choices between alternative translations is part of the target language grammar and that it should be applied and the translation chosen as part of generation of the target language text. This contrasts with previous work on the problem, which has assumed that these choices should be made in analysis or transfer. Various types of knowledge base could be used to make the choice between alternatives. The method outlined here uses information about stereotypical contexts of use of words, stored as part of an ontological network.

KeyWords: *machine translation, lexical choice, DRT, knowledge representation*

1 Introduction

Lexical choice in machine translation divides into two rather separate parts, the choice of what to say and the choice of how to say it. The latter is the problem, common to most applications involving text-generation, of choosing between alternative morphological and syntactic ways of expressing the same literal meaning. Examples in English are the choice between verb or nominalisation, active or passive clause, adjective or relative clause. The lexical choice here is the choice between alternative realisations of the same lexeme. The factors involved in these choices are mostly poorly understood, and often the internal representation of such alternations in a natural language processing system will be the same at some level. A separate and prior problem is the choice of what literal meaning to express. In machine translation, what to say is specified by the source text, but there will be many possible interpretations of the source text. As a consequence, in machine translation, this problem manifests itself as the selection of one of many possible translation equivalents for each source-language morpheme or non-compositional structure. It is to this latter problem that this paper is addressed.

Usually, machine translation systems make the choice between lexical translation equivalents either by setting up target-language-dependent word senses in the source language or interlingua and making the choice during analysis, or else by putting constraints on transfer rules. This paper will argue that both theoretically and practically the best place to make

[†] Department of Linguistics, Yamaguchi University

the choice is in generation. The paper will go on to discuss methods of making the choice and will present one method in detail.

2 An example

Most of the examples in this paper will concern translation from English into Japanese. This is because the work began in an English-Japanese machine translation project, and because those parts of the system here described which have been implemented use these two languages. None of the examples depend on special properties of English or Japanese.

The most straightforward type of example to which this paper addresses itself is one where a single source-language word has many possible translations into the target language. The English word *paper* for instance has a couple of dozen translations into Japanese in a medium-sized dictionary. Some of them are

<i>kami</i>	the substance paper	<i>mondaiyousi</i>	an exam question paper
<i>ronbun</i>	an academic paper or thesis	<i>touan</i>	an exam answer paper
<i>sinbun</i>	a newspaper	<i>binsen</i>	letter-writing paper
<i>sinbunsya</i>	a newspaper company	<i>kabegami</i>	wallpaper
<i>syorui</i>	papers, documents	<i>sindansyo</i>	a doctor's paper (medical certificate)

In most contexts, none of these Japanese translations are interchangeable. Though an English speaker will very often call a newspaper a paper, *kami* is not used in this sense in Japanese, and neither *kami* nor *sinbun* can be used to refer to a newspaper company, for instance in translating the question “Which paper do you work for?” Thus, though *kami* translates the most central meaning of *paper*, it cannot be used as a general-purpose translation equivalent; the most suitable translation equivalent must be chosen on each occasion of use.

Looking up the content words of a couple of pages of Japanese text in a medium-sized Japanese-English dictionary showed that the dictionary gave most words at least three translations, on average about seven translations for each word. The same experiment with German and English gave about six translations for each word on average, showing that the problem is not confined to words with a particularly wide semantic range, or to translation between culturally distant languages.

3 Current techniques

Current commercial machine translation systems ignore the problem of lexical choice by allowing only one translation to be specified for each source-language content word. Even

where a system contains several dictionaries (e.g. for different subject fields), the dictionaries simply mask each other so that only one translation for each word will be available in the processing of any particular text. This approach has obvious limitations. It works reasonably well for a technical text concerned with a narrow subject area, because many words will be technical terms with only one sensible translation in that subject area. Because most machine translation to date has dealt with such texts, lexical choice has not been seen as a central problem. However even in technical texts, many everyday words with multiple possible translations are used and once the constraints on text type are removed, lexical choice becomes the main problem for translation.

Solutions to the problem of lexical choice have generally taken one of two forms. An approach with a long history is that of selectional or collocational restrictions (e.g. (Lehrberger 1982)). In this approach, a source-language word with many translations is treated as so many homographs. The English word *paper*, for instance, in translating into Japanese, would be treated as ambiguous between *paper*₁ (= Japanese *kami*), *paper*₂ (= *ronbun*), *paper*₃ (= *sinbun*), ... , *paper*₁₀ (= *sindansyo*). In the English grammar then, predicates are syntactically restricted as to the types of argument they are allowed to take. For instance in a translation system intended for use with texts about conferences, verbs such as *submit*, *present*, and *publish* would have their syntactic objects restricted to *paper*₂ (amongst other things), so that the only syntactically acceptable analysis of a verb phrase such as *submit a paper* will contain *paper*₂. '*A4 paper*' though would be analysed as containing *paper*₁ due to selectional restrictions on *A4*, and '*travel papers*' would be analysed as containing *paper*₅ due to selectional restrictions on *travel*. Generation of the correct translation equivalent is then trivial since each predicate of the source-language analysis corresponds to a single target-language lexeme.

This method is an improvement on having just a single translation available, presumably just *ronbun* in the example, but there are both theoretical and practical objections to it. A major practical objection is that the source-language grammar and lexicon must be different for each target language and for each direction of translation: there can be no multilingual or reversible translation. It is also difficult to make selectional restrictions work in practice: the grammar rules must make them void in some contexts, e.g. some negatives and intensional contexts, and allow them to be overridden in metaphors etc. It is often difficult to decide what the appropriate restrictions are — in the *paper* example above, there is no reason why someone should not publish an examination paper or submit it to a conference, but if selectional restrictions allow this collocation, they will not produce a unique analysis of the example. From a theoretical point of view, this type of analysis of a source language, involving word senses

based on target-language lexemes, has no linguistic justification at all. It might be argued that the word senses actually used are mostly intuitively sensible ones anyway, and could be justified monolingually, but really this is unlikely to be the case. (Jorgensen 1990) argues that the division of the range of meaning of a word into many discrete senses is psychologically unfounded to start with: subjects asked to classify examples of the use of words generally divide them into only two or three senses, and the classification varies from subject to subject, and from day to day with the same subject.

An interlingua can be seen as a multilingual extension of this approach using homographs. An interlingua will contain enough predicates to represent all possible lexical translation equivalences in the languages of the world. But apart from the difficulty of designing an adequate interlingua, there is the problem then that any analysis of a source language in order to translate into a target language will be massively redundant — senses will be distinguished in the interlingual representation of the source language text which are distinguished in other languages but irrelevant for translation into the target language.

An alternative to stating selectional restrictions in the source lexicon is to state the same information in the form of conditions on transfer rules. (Pentheroudakis 1990) presents a recent example. One of Pentheroudakis' examples is the following pair of rules for translating the English verb *draft* into Korean:

draft $\Leftrightarrow$ cingcipha- *iff the patient is human* (e.g. 'draft a secretary to another department')
draft $\Leftrightarrow$ koanha- *iff the patient is abstract* (e.g. 'draft a letter')

Though the source-language grammar and lexicon are here freed from dependence on the target-language lexicon, the knowledge base for lexical choice must still be reformulated for each pair of languages in each direction of translation: the information still seems to be used in the wrong way.

4 Lexical choice in generation

The knowledge used in lexical choice is in reality part of the target language. In Pentheroudakis' example above, the type of object usual with the Korean verbs *cingcipha-* and *koanha-* is a fact about Korean, not about the relationship between Korean and English (which is how Pentheroudakis treats it) or about English (which is how it would be treated in the homograph approach). Intuitively, the knowledge base for lexical choice belongs in the description of the target language, in that the knowledge is about the semantic relationships between target-language words. Of course there is also a practical advantage to making this knowledge part of the description of the target language: it need only be stated once regardless of the

number of languages and directions of translation. Furthermore, the same knowledge base will be useful for other types of natural language processing as well as in machine translation.

It follows that in machine translation, lexical choice must be part of generation. Take a standard machine translation system consisting of three parts, analysis, transfer, and generation. If word senses are not distinguished in the source language, or at least are distinguished only as far as can be justified on grounds internal to the source language, the output of analysis will contain only genuine source-language predicates. In transfer, each of these predicates will presumably have many possible target-language equivalents, all of which must be output. It will be the job of the generation component to apply the target-language knowledge base to choose between the many possible translations suggested by the transfer module. The same sequence of operations will apply in the type of partly interlingual system argued for by (van Eynde 1992) and partly implemented in Eurotra, where lexical items are treated by transfer but grammatical structure and relations are treated interlingually.

The target-language knowledge base used in generation for lexical choice could take a variety of forms. Stochastic methods immediately spring to mind of course, either the purely statistical language model described by (Brown, Cocke, Pietra, Pietra, Jelinek, Lafferty, Mercer, and Roossin 1990), or the type of mixed linguistic and statistical data which could be derived from linguistically analysed corpora such as the Penn Treebank. Simple selectional restrictions stated in the target-language grammar would also do the job. However, the method to be outlined below is a preference mechanism similar to that of (Wilks 1975), but incorporating some more recent results from psycholinguistics and formal logic.

First, an outline of the system architecture assumed in subsequent discussion and examples.

5 A framework for machine translation

The framework assumed here for machine translation is diagrammed in Figure 1. The double lines between *parsing* and *disambiguation*, and between *transfer* and *lexical choice*, represent possible multiple outputs. *LF* is the indexed logic described below, also used for the knowledge bases. The module with which this paper is concerned is *lexical choice*. The task of the *lexical choice* module is to produce from the output of *transfer* (see (Phillips and Nakano 1993; Phillips 1993b)) a single, non-disjunctive logical form from which a target-language sentence can be straightforwardly generated using the algorithm described by (Phillips 1993a) and improved by (Lager and Black 1994).

For purposes of exposition here, a simple logical formalism is used, representing a sentence as a network of semantic dependencies. The basic units of the formalism are *indices*, *proper-*

Fig. 1 The proposed framework

ties, and *relations*. A logical form consists of an unordered set of *terms*; each term is either a property predicated of an index, or a relation between two indices. The written notation depicts properties and relations as unary and binary functors, respectively, and indices as their arguments, i.e. within brackets. A logical form representing ‘John saw Mary’ might be

$$e : \text{john}(j) \ \& \ \text{see}(e) \ \& \ \text{mary}(m) \ \& \ \text{tense}(e, \text{past}) \ \& \ \text{actor}(e, j) \ \& \ \text{patient}(e, m)$$

It can be seen that the concepts or entities mentioned in the sentence are labelled with indices, and the semantic relationships specified in the sentence to hold between them are shown by relations. Properties show the natural language classes the English names of which were used to refer to the entities in the sentence. The indices will serve as discourse referents when the logical form is incorporated into a discourse representation (Kamp 1981). The root node of the network is specified at the beginning of the representation, in this case e , the node representing the seeing event. In terms of discourse representation theory, e is the discourse referent of which the logical form is a description. Figure 2 depicts the same dependency network as a feature structure.

The advantages of using indexed logic for semantic representation have been widely recognised at least since Kamp proposed its use for the representation of discourse anaphora. Kamp’s paper dealt only with nominal discourse entities, but for an adequate representation situational discourse entities, introduced by verbs, adjectives and perhaps prepositions, are also needed — the case for this is well put by (Parsons 1990), and from a different point

$$e \left[\begin{array}{l} \text{predicate : see} \\ \text{tense : past} \\ \text{actor : } j [\text{predicate : john}] \\ \text{patient : } m [\text{predicate : mary}] \end{array} \right]$$

Fig. 2 Feature-value representation of ‘John saw Mary’

of view by (Asher 1993).

The logical form above is simplified, mainly in that the predicate *tense* here stands for what should be a complex representation of tense and aspect, related anaphorically to the preceding discourse. A similarly simplified representation of the Japanese translation of the example, ‘Jon ga Mearii wo mita’, might be

$$e : \text{jon}(j) \ \& \ \text{kouisya}(e,j) \ \& \ \text{mearii}(m) \ \& \ \text{judousya}(e,m) \ \& \ \text{miru}(e) \ \& \ \text{tense}(e,\text{past})$$

Again this is a description of an event *e*, involving two other discourse entities, *j* and *m*, described as *jon* and *mearii* respectively. The event *e* is a seeing event (*miru* is the Japanese verb); *j* stands in the *kouisya* (actor) relation to it, and *m* in the *judousya* (patient) relation.

What is required for machine translation is not an accurate representation of ‘meaning’, whatever that may be, but an unambiguous representation of the entities involved in the discourse (objects, events, etc.) and the relations between them. This is the purpose of the representation we use here; it is important that the indices, properties, and relations are justifiable in the language being represented.

Properties in the formalism are simply the contentful (open-class, lexical) morphemes of the language. This follows from what was said above, though there can of course be no objection to differentiating senses where there is justification in the language being described.

Relations are a different matter, representing not morphemes but grammatical structure. The purpose of analysing a source text is to make explicit the semantic relationships between its parts, so that a translation can be made which specifies the same relationships (or translationally equivalent ones) between the same discourse entities. The relations of the formalism represent these semantic relationships, in the sense that they instantiate demonstrable grammatical concepts of the language being represented. So the relations *actor* and *patient* in the example are not implication-based thematic roles of the type rejected by (Dowty 1989) but are grammatical relationships which can be justified on syntactic grounds, using such tests as literal synonymy between sentences of different grammatical structure (e.g. passive and active voice).

For representing ambiguity, disjunction of atoms is used. $\{see;saw\}(e)$ means that *e* is either a seeing event or a sawing event. $with(\{m;e\},t)$ states a relation between *t* and either

m or *e* (e.g. in the analysis of *John saw Mary with a telescope*). These disjunctions are purely abbreviatory, a way of representing multiple outputs succinctly.

For transfer, the English and Japanese logical forms shown above can be related declaratively by rules such as

$$\begin{aligned}\text{kouisya}(X,Y) &\Leftrightarrow \text{actor}(X,Y) \\ \text{miru}(E) &\Leftrightarrow \text{see}(E)\end{aligned}$$

The use of this type of rule reflects the basically compositional nature of translation and works well for probably a large majority of the basic structures and morphemes of any pair of languages. With some translation examples, compositional translation initially seems inadequate, but on closer inspection the analysis required on language-internal grounds enables compositional translation at the level of syntactic or semantic analysis, although the surface structures seem different. For instance there are many cases where arguments to a verb, absent in one language, must be provided in another language. Welsh, like many other languages, uses resumptive pronouns: *the man I spoke to* is *y dyn y siaredais ag ef*, ‘the man that I spoke to him’, the preposition having an explicit object. The Japanese sentence *kesa atta* might be translated *I met him this morning*, although neither of the pronouns is explicit in the Japanese either lexically or in the morphology of the verb. It is uncontroversial that the absent noun-phrase in the Welsh case is implicitly present and that the reference should be made explicit during analysis; the same seems true in the Japanese case (e.g. (Gunji 1987) assumes a ‘zero pronoun’ analysis of this type of sentence without comment). Once the referents are made explicit, translation becomes compositional.

There are though, as is well-known, as number of cases where a compositional treatment is inadequate. Some of these cases are just extensions of examples of non-compositionality in monolingual analysis. An adequate monolingual analysis, even though it is non-compositional, will carry over into translation. Idioms, for instance, are essentially non-compositional: in a monolingual analysis, an idiom must at some level be treated as a single unit. Likewise in translation, translation equivalence must be defined between the idiom and an equivalent idiom or literal word or phrase in the other language. Rather similar are problems with the monolingual analysis of phrasal verbs (e.g. *look up* in ‘look a word up in a dictionary’), and with support verbs (e.g. *have* in ‘have a bath’). Such cases must, for obvious semantic reasons, be treated as a unit in monolingual analysis, and likewise translated as a unit.

However in other cases, there is no language-internal basis for anything other than a compositional analysis, but the compositional analyses of translationally-equivalent units correspond only partly between languages: in other words, these examples show a lack of compositionality specifically in the process of translation and must be dealt with in transfer. (Lindop and

Tsujii 1991) have collected and classified a large number of examples of what they call ‘complex transfer’, i.e. non-compositional translations. Examples showing non-compositionality specifically in the process of translation fall into a small number of discrete classes. To exemplify here how such cases can be handled in our formalism, we look at three possible German translations of the English verb *like*: the verbs *mögen* and *gefallen*, and the adverb *gern*.

Mögen is an unproblematic translation of *like*: we can translate *I like Mary* as *ich mag Maria* using the transfer rule

$$\text{like}(E) \Leftrightarrow \text{mögen}(E)$$

In Figure 3, the relevant parts of the translation are lined up to show the domains of application of separate transfer rules, i.e. five rules are used.

me(me)	]	[	ich(me)
like(l)	]	[	mögen(l)
actor(l,me)	]	[	actor(l,me)
patient(l,m)	]	[	patient(l,m)
mary(m)	]	[	maria(m)

Fig. 3 The translation of *like* as *mögen*

Gefallen requires its arguments in a different order to those of *like*:

$$\text{like}(L) \ \& \ \text{actor}(L,A) \ \& \ \text{patient}(L,P) \Leftrightarrow \text{gefallen}(L) \ \& \ \text{actor}(L,P) \ \& \ \text{patient}(L,A)$$

In the translation *Maria gefällt mir*, Mary is the syntactic subject and I am a dative object. Again, Figure 4 shows the relevant parts of the logical forms aligned. This time three transfer rules are used.

me(me)	]	[	ich(me)
like(l)	]	[	gefallen(l)
actor(l,me)	]	[	patient(l,me)
patient(l,m)	]	[	actor(l,m)
mary(m)	]	[	maria(m)

Fig. 4 The translation of *like* as *gefallen*

Finally, if *like* is translated as *gern*, an adverb, e.g. in *ich schwimme gern*, ‘I like swimming’, the *actor* of English *like* is the *actor* of *like*’s *patient* in the German:

like(L) & actor(L,A) $\Leftrightarrow$ gern(L) { hs(L,E) & patient(L,E) }

The forms in curly brackets { } are conditions on the transfer, to be verified relative to the discourse record when the transfer rule is used, but not forming part of the discourse record. *Hs*, mnemonic for ‘head-switch’, is defined in such a way that the emboldened indices in the alignment in Figure 5 are translated non-compositionally.

know]	[wissen(k)
patient(k,l)]	[patient(k,s)
me(me)]	[ich(me)
like(l)]	[gern(l)
actor(l,me)]	[{ hs(l,s) & patient(l,s) }
patient(l,s)]	[patient(l,s)
swim(s)]	[schwimmen(s)
actor(s,me)]	[actor(s,me)

Fig. 5 The translation of *to know that I like swimming* as *wissen daß ich gern schwimme*

The effect of *hs* is to shift the head of the embedding structure: the condition *hs(E,F)* requires that any relation of the form $P(X,E)$ in the logical form to which the left-hand side of the transfer rule relates, corresponds to $P(X,F)$ in the logical form to which the right-hand side relates. This is a development of the type of rule used by (Watanabe 1990).

Detailed discussion and examples of the treatment of various types of non-compositional translation in this formalism are presented by (Phillips and Nakano 1993), (Antona and Tsujii 1993), and (Phillips 1993b).

6 A method for choosing between alternative translations

Given the above framework, the transfer component might be expected to produce some output such as

... {kami;ronbun;sinbun;sinbunsysa;syorui;mondaiyousi; touan;binsen;kabegami;sindansyo}(p)
& teisyutu(s) & patient(s,p) & recipient(s,j) & zassi(j) & ...

when set to translate the English *I'd like to submit a paper to the journal* into Japanese. (*Zassi* is ‘journal’, *teisyutu* is ‘submit’ in this sense — of course in reality there would be other possible translations of these words as well.) The problem is, how to choose between

the several translations of *paper*. The basic idea is that the translation including *ronbun*, ‘an academic paper or thesis’, describes the most stereotypical situation in the context and is therefore the right translation. The correct translation is the most stereotypical one. Translation is equated with interpretation, and the correct interpretation is the most stereotypical one. Had the speaker or writer intended any other meaning, he would have had to be more specific or his original English sentence would have been misinterpreted by its recipient.

If “stereotypical” can be taken to be roughly the same as “statistically commonest” (which of course it is not) then a stochastic algorithm can be used to choose the best translation based on a language model derived from a statistical analysis of a large corpus of Japanese text. If the language model was based on a linguistically analysed corpus, it would be applied to logical forms to choose the most likely combination of relations between indices with particular properties. That is, the language model would be based on probabilities of particular relations between indices with particular properties. Alternatively, a language model based on unanalysed corpora would be used during generation of the target-language from the logical form to choose the most likely target-language output.

However, “stereotypical” and “common” do not mean the same thing, and the method to be outlined here uses a quite different idea of stereotypicality. Each of the source and target languages is provided with a lexical knowledge base in which are entered stereotypical links between the contentful morphemes of the language — i.e. the *properties* of the logical form. For the example logical form above, in the system’s Japanese knowledge base is stated a stereotypical connexion between the logical predicate *zassi* (‘journal’) and the predicate *ronbun*, a connexion which does not exist for the other translations of *paper*. The discourse entity *j* is an instance of *zassi* and if *p* is an instance of *ronbun* the stereotypical link is verified via *s*, an instance of *teisyutu* (‘submit, present’). If *p* is an instance of any of the alternatives to *ronbun*, the stereotypical link cannot be verified.

The justification for the above comes from Grice’s work on the pragmatics of linguistic communication. (Grice 1975) proposed several generalised conversational implicatures, or maxims of conversation. Grice’s second Maxim of Quantity tells a speaker (or writer) “Do not make your contribution more informative than is required.” The hearer (or listener) will flesh out the text using knowledge of stereotypical or default situations where it is underspecified. (Levinson 1987) has re-formulated the maxim as follows.

Speaker’s Maxim: the **Maxim of Minimisation**

‘Say as little as necessary’, i.e. produce the minimal linguistic information sufficient to achieve your communicational ends (bearing the first maxim in mind).

Recipient's Corollary: the *Enrichment Rule*

Amplify the informational content of the speaker's utterance, by finding the most SPECIFIC interpretation, up to what you judge to be the speaker's m-intended point.

Specifically:

- (a) Assume that stereotypical relations obtain between referents or events, UNLESS (i) this is inconsistent with what is taken for granted, (ii) the speaker has broken the maxim of Minimisation by choosing a prolix expression.
- (b) ...
- (c) ...

To Levinson's *Enrichment Rule*, it seems reasonable to add a direction that words are used in stereotypical meanings. Caveat (i) of the rule ensures that the context will be taken into account in deciding on any actual interpretation, so the effect of the rule is that a word is interpreted with a sense as stereotypical as the context will allow. Hence if there are several possible interpretations (i.e., for our purposes, translations) of a text, the most stereotypical is to be preferred.

7 Knowledge base — content

It has often been observed that human translators need not be experts in the subject matter of the texts they translate, though they do need a certain amount of background knowledge. This observation can be interpreted as meaning that a translator need not acquire any deep understanding of a text to translate it, the translator needs only knowledge of the way language is used in discussing the text's subject area. I myself have worked as a conference interpreter, and a large part of the knack of the job initially is in learning not to understand and absorb what is said consciously. This claim, that a very shallow level of 'understanding' of text is sufficient for translation, is supported by the work of (Gerloff 1989). She studied professional translators at work and found them to translate mechanistically by and large, using just local structures and local context. Her subjects used deliberate understanding and explicit reference to larger units of text only when they experienced conscious difficulty.

Just this type of shallow processing for initial interpretation of text is posited by the psycholinguistic theory of Naive Semantics (Dahlgren, McDowell, and Stabler 1989; Dahlgren 1988). Part of the claim of Naive Semantics is that there exists a discrete level of cognitive understanding of word meaning, corresponding roughly to the idea behind selectional restrictions, but expressed in a more general way as stereotypical relations between words. The following quotation is from (Dahlgren et al. 1989):

The reader of a text actively constructs a rich picture of the objects, events, and situation described. The text is a vague, insufficient, and ambiguous indicator of the world that the writer intends to depict. The reader draws upon world knowledge to disambiguate and clarify the text, selecting the most plausible interpretation from among the infinitely many possible ones. In principle, any world knowledge whatsoever in the reader's mind can affect the choice of an interpretation. Is there a level of knowledge that is general and common to many speakers of a natural language? Can this level be the basis of an explanation of text interpretation? Can it be identified in a principled, projectable way? Can this level be represented for use in computational text understanding? We claim that there is such a level, called Naive Semantics, which is common-sense knowledge associated with words. Naive semantics identifies words with concepts, which vary in type. Nominal concepts are categorisations of objects based upon naive theories concerning the nature and typical description of conceptualised objects. Verbal concepts are naive theories of the implications of conceptualised events and states. Concepts are considered naive because they are not always objectively true.

It is claimed that there is a coherent, discrete level of speakers' understanding of the meanings of words, and that it is this knowledge which a reader draws upon to disambiguate and clarify a text and select the most plausible interpretation from among the many possible ones. While in the last resort any background knowledge can be made use of in interpreting a text, this does not happen unless the naive semantics fail to produce a coherent interpretation, in which case conscious difficulty is experienced in understanding the text. The naive semantic knowledge is attached to individual lexical items and includes such things as typical contexts of use, attributes, preconditions, results, and ontological information. The knowledge base originally comprised information elicited experimentally from subjects. An example (from (Dahlgren et al. 1989), p. 154) is shown in Figure 6.

```
buy(  {
      whatEnabled(can(afford(subj,obj))),
      how(with(X) & money(X)),
      where(in(Y) & store(Y)),
      cause(need(subj,obj)),
      whatHappenedNext(use(subj,obj))
    },
    {
      goal(own(subj,obj)),
      consequenceOfEvent(own(subj,obj)),
      selectionalRestriction(sentient(subj)),
      implies(merchandise(obj))
    })
```

Fig. 6 Naive Semantic knowledge associated with 'buy'

Figure 6 (figure 10 of (Dahlgren et al. 1989)) shows the information associated with the verb *buy*. There are two lists of features, the first giving typical properties of the word, the second inherent properties. Dahlgren's implemented system has a total of forty-eight possible features, of which about fifteen appear on a typical lexical item. Constraints which naturally obtain in the generic knowledge mean that most features are irrelevant to most words. For instance, only the features *cause*, *goal*, *whatEnabled*, *whatHappenedNext*, *consequenceOfEvent*, *where*, *when*, *implies*, *how*, *selectionalRestriction* can appear on verbs; the features *sex* and *behaviour* are relevant only with animate objects. The lexical frames fit into an ontological structure which also specifies generic information on higher concepts (such as *sentient* and *merchandise* in Figure 6) — this aspect of the system is described by (Dahlgren 1988). The amount of information required in the lexicon is large, but not inordinately so: it is probably comparable in quantity with the syntactic information required for reasonably full coverage of a language.

As far as this paper is concerned, the important claims of Naive Semantics are (i) that such a database can in practice be compiled, (ii) that it contains a manageably small amount of information, and yet (iii) that it can represent all the information that is likely to be needed to interpret a text (iv) using only the local context, i.e. the sentence currently being processed. Though the propounders of the theory apply it only to the analysis of text, it obviously has wider applications in natural language generation and in machine translation. In particular, for machine translation, if we equate interpretation of a text with translation (i.e. translation into Japanese rather than *mentalese*), a Naive Semantic database should be able to make the choices between alternative translations (i.e. interpretations) of lexical items.

8 Knowledge base — representation

(Thomason and Touretzky 1992) present a formalisation of a monotonic inheritance network with roles, where the roles are inheritable partial functions from individuals to individuals. Query answering in a network of this type corresponds to parsing a fragment of the network with a context-free grammar whose non-terminals are inference rules and whose terminals are links in the network. Such a proof system is tractable and the resulting networks are easily comprehensible, or 'picture-able' as Thomason and Touretzky put it. This type of network seems ideal for the representation of the stereotypical knowledge needed for lexical choice.

Naive Semantics provides an ontology of concepts corresponding to monolingually justifiable word senses. The English word senses in the published literature on Naive Semantics

are in fact skewed towards particular technical applications and the ontology could be much simplified for translation applications. Anyway, the ontology can form the backbone of an inheritance network, constructed by the IS (=ISA) links of the network. Typical and inherent properties of nodes in the network are represented as roles and relations of various sorts.

Figure 7 shows the part of the network relevant to showing that journals stereotypically have papers associated with them.

Fig. 7 ‘Journals have papers in them’

A distinction is drawn in the network between individuals (boxes) and kinds (ellipses), and between independent (white) and dependent (shaded) nodes, where a dependent node is one that is created by a role attachment. The ontology, then, consists of the white nodes only: shaded nodes are there to show relations between kinds in the ontology. Links in the network representing roles are marked with the name of the role, crossed links represent identity (e.g. in Figure 10), other links are IS links. Both inherent and stereotypical properties are represented by roles in the network: links representing inherent properties are solid, those representing stereotypical properties are broken. In Figure 7, *zassi* and *ronbun* are names of kinds, *j* and *p* are individual entities, i.e. a specific journal and paper, and *zr* is a node showing a stereotypical relationship between *zassi* and *ronbun* (*zr* is mnemonic for ‘*zassi*’s *ronbun*’).

Although the network contains representations of both inherent and stereotypical properties, it remains monotonic and queries can be answered efficiently by context-free parsing. This is because the difference between the two types of role — inherent and stereotypical — is used only to divide the network into two parts which can be queried separately or to-

gether. Queries can be of two types: ‘does the whole network support this fact?’ and ‘does the network excluding stereotypical links support this fact?’ In the first case, the query is a question about whether something is stereotypically so, and is answered by parsing the network treating inherent and stereotypical links as though they were identical. In the second case, the query is a question about whether something is inherently so and is answered by parsing the network excluding stereotypical links. In both cases, inheritance is monotonic. Stereotypical links are stereotypical because of the way the translation system uses answers to queries involving them, not because of the way they are treated in the network.

Looking at the relevant part of the logical form for the ‘*submitting a paper to a journal*’ example,

... {kami;ronbun;sinbun;sinbunsya;syorui;mondaiyousi;touan;binsen;kabegami;sindansyo}(p)
& teisyutu(s) & patient(s,p) & recipient(s,j) & zassi(j) & ...

it can be seen that we need to find some link between one of the alternative translations of *paper* and some other predicate in the logical form. From the piece of network in figure 7, it can easily be shown that *ronbun* are typically associated with *zassi*, or alternatively, that if *j* and *p* are attached into the network as shown in the figure, a stereotypical link exists between them. The proof of the former uses two context-free ‘network structure’ rules, Thomason & Touretzky’s rules 21 and 24 (Thomason and Touretzky 1992):

$$21: \theta(ff,x,G,y) \Rightarrow x \xrightarrow{f} z \quad \theta(F,z,G,y)$$

$$24: IS(\emptyset,x,\emptyset,p) \Rightarrow x \rightarrow p$$

In the rule notation, ‘phrasal’ categories are written with a link type (*IS* in rule 24, θ , a variable ranging over non-role link types in 21) and four arguments: a sequence of role links, the node at the beginning of that sequence, another sequence of role links, the node at the beginning of that sequence. ‘Lexical’ categories are actual links in the network

(e.g. *zassi* $\xrightarrow{\text{haspart}}$ *zr* in Figure 7). Variables *F* and *G* range over sequences of roles, *f* over roles, *x*, *y*, and *z* over nodes, and *p* over kind nodes. Hence rule 21 says that if you have an *f*-role link from *x* to *z* in the network, and can prove some relation (i.e. θ) between *z*’s *F* and *y*’s *G*, then you have the same relation between *x*’s *ff* and *y*’s *G*. In the case of the example, and referring to Figure 7, we have a *haspart* role link from *zassi* to *zr*, and can prove an *IS* relation between *zr* and *ronbun*, therefore we have the same *IS* relation between *zassi*’s *haspart* and *ronbun*. The relevant parse tree is shown in Figure 8.

Hence we can show that stereotypically there is a *haspart* relation between *zassi* and *ronbun*. Further, we can relate the *haspart* relation to a state of *having-a-part*, a hyponym of *have*, as shown in Figure 9. In other words, if we know that stereotypically there is a *haspart* relation between *zassi* and *ronbun*, we know that stereotypically *zassi* have *ronbun*.

From the piece of network in Figure 10, it can be shown that a similar link is actually

Fig. 8 Parse tree for 'zassi's *haspart* is a *ronbun*'

Fig. 9 Relating the *haspart* role to the state of *having*

described by the example sentence. The submitting event s , being a type of giving event, has by inheritance a postcondition the actor of which is the same as the recipient in s . In other words, as a consequence of submitting the paper to the journal, the journal will have the paper.

Hence the choice of *ronbun* gives a logical form describing a more stereotypical situation than would choosing one of the other possible translations which have no stereotypical association with *zassi*.

In fact of course, this example is oversimplified. In reality the English word *journal* also has several possible translations, as does *submit*. It would of course be possible just to take

Fig. 10 The consequences of *submitting* something

each possible combination of choices in turn and compare the number of stereotypical links found for each. Where there are more than two sets of choices, it will be more efficient to use a modification of a constraint-satisfaction algorithm to iterate through the possible combinations non-redundantly. In the example, links would be found between *zassi* and *ronbun*, and between *teisyutu* and those translations of *paper* which refer to privately produced documents, since *teisyutu* is most typically, though not invariably, used of handing in or presenting a document one has prepared oneself. The most stereotypical sentence would therefore be the one containing *ronbun*, *zassi*, and *teisyutu*.

9 Discourse representation

Using the local context in determining word choice is appropriate only for the first reference to a discourse entity. On subsequent reference, the same translation will be used. Imagine (12) as a reply to (11)

(11) I'd like to submit a paper to the journal.

(12) What is the paper about?

'The paper' in (12) refers to the paper mentioned in (11). There is little context in (12) itself to help in deciding the translation of 'paper', but the fact of coreference between the papers in (11) and (12) determines the ontological type, and therefore the translation, of 'paper' in (12).

To handle examples of this type, intersentential cohesive links (anaphora, ellipsis, etc.) must be analysed and explicitly represented. This can be done using techniques derived from discourse representation theory ((Kamp 1981), (Asher 1993) and much other work). During translation, as analysis and generation progress, two *discourse records* are built up, one each for the source and target languages. As each new logical index is used in the source-language analysis and target-language generation, it is noted in the respective discourse record along with its ontological type. This will ensure that the translation of coreferring expressions is consistent. Of course the discourse record will contain other information as well: information on topic structure and on the syntactic and thematic structure of the immediately preceding clause and sentence will be needed to handle anaphora and ellipsis in analysis and to produce appropriate sentence types in generation. The use of a discourse record allows translation to proceed clause-by-clause or sentence-by-sentence, syntactic, semantic, and pragmatic continuity between successive translation units being maintained using the discourse record.

When (12) is translated in the context of (11), the index associated with the ‘paper’ will already appear in the target-language discourse record, along with a note of its ontological type. The correct translation as *ronbun*, ‘academic paper’, will therefore be the only possible one. In fact, were the ontology implemented as sorted indices, this translation would be forced automatically at the transfer stage, rather than having to be checked explicitly subsequently, as part of lexical choice.

Even when the local context suggests otherwise, an anaphoric noun phrase will always have its translation determined by the discourse record. In (13), if the definite noun phrase *the paper* is taken to be anaphoric, say to an examination essay just discussed, *touan* ‘exam paper’, rather than *ronbun* ‘academic paper’, will be the correct translation despite the local context.

(13) I’d like to submit the paper to a journal.

In other examples, an anaphoric link may provide the local context for choosing the translation of another word. In (14), the fact that, in the Japanese translation, the reflex of ‘it’ refers back to the *ronbun* ‘academic paper’ will ensure that an appropriate translation of *accept* is selected.

(14) I have submitted a paper to the the journal. When will I know if it has
been accepted?

Accept has a large number of translations into Japanese, for example

<i>uketoru</i>	accept, take delivery	<i>kanju</i>	accept (fate), submit tamely to
<i>junou</i>	accept (a gift)	<i>junnou</i>	accept (a rule), conform
<i>judaku</i>	accept (a suggestion), agree	<i>saiyou</i>	accept (an article or paper)
<i>ukeireru</i>	accept, enlist, take in, enregister	<i>ukeru</i>	accept, suffer, be given
<i>mitomeru</i>	accept, approve, recognise		etc.

Choice between many of the translations seems to be largely determined by the ontological type of the patient — here an academic paper.

Relational nouns can be seen as another relevant form of anaphora. (15) shows that choice of the correct translation of the noun can depend on the anaphoric link.

(15) A car crashed. The driver was killed.

In (15), it is understood that the *driver* is the driver of the car mentioned in the first sentence. If (15) is translated into Japanese, a choice must be made between half a dozen translations of *driver*:

<i>gyosya</i>	driver of a horse-drawn carriage	<i>usioi</i>	driver of cows
<i>untensyu</i>	driver of a motor vehicle	<i>umakata</i>	driver of horses
<i>kikansyu</i>	driver of a train	<i>doraibaa</i>	driver of a computer peripheral

If the relational noun *driver* is given an analysis of the form *driver of it*, where *it* refers to the car, the translation follows naturally.

Ellipsis is relevant in examples such as (16).

(16) Last night Mr. J. Smith gave a recital on the harpsichord. The harpsichord was a particularly beautiful antique instrument with paintings of children at play on the lid. Mr. Smith played for two hours ...

The translation of the first occurrence of *play* is dealt with as above. The translation of the second occurrence into Japanese should be *hiku* ‘to play a stringed instrument’, but could in general be

<i>fuku</i>	play a wind instrument	<i>suru</i>	play a sport
<i>tataku</i>	play a percussive instrument	<i>enjiru</i>	play a role
<i>asobu</i>	amuse oneself	<i>kakeru</i>	play a record
			etc.

None of the mechanisms so far mentioned could provide a correct translation in this case, since the local context gives no clues at all. Indeed the previous sentence gives a misleading clue. It may be that a correct analysis of the rhetorical structure of the text could show that the second sentence was an aside, and that the use of Mr. Smith’s name in the third sentence marked a return to the main subject, allowing a complex inference to relate *play* to *harpsichord* via Mr. Smith as a musician. A simpler way of looking at the relation between *play* and the first sentence, in the framework proposed here, is to see the third sentence as containing an ellipsis: ‘Mr. Smith played [the harpsichord] for two hours.’ If the lexical rule making an intransitive verb out of the basically transitive verb *play* marked it as having an elided object, the link

with which would be established during analysis, the correct translation could be obtained in the normal way, using the local context and semantic network, though in this case, as in (14), the ‘local’ context would be an anaphoric link to information in the discourse record.

10 Conclusion

This paper has tried to do two things. Firstly, it has tried to convince the reader that the best time to make choices between alternative lexical translation equivalents is during or immediately preceding target-language generation, not during analysis of the source-language text or during transfer or by using an interlingua. It has argued for this point of view on the theoretical grounds that semantic relationships between target-language words are a matter for the target-language grammar, not for source-language analysis rules or for transfer rules, and on the practical grounds that making this information part of the description of the target language means less work when a machine translation system is built.

Secondly, the paper has tried to sketch a particular linguistically and psycholinguistically based method of making lexical choices in generation. Whether or not this method has been here adequately justified is quite independent of whether or not lexical choice is best done as part of generation. The basic approach is to choose the most plausible of several possible target-language sentences in context, and many other good methods exist for doing this. In the short term, for the same amount of effort expended by system builders, a stochastic approach, based on statistics gleaned from large corpora, is likely to give better results. A simple system of semantically based syntactic selectional restrictions can also give good results with restricted text types. In both these cases, no explicit choice need be made between alternative translations, there need be no separate ‘lexical choice’ module: the sentence generator will either stochastically prefer one generated sentence over the others, or it will fail to generate any sentences not permitted by the selectional restrictions. Neither of these methods can in the end take context fully into account. Yet another possibility is a combination of methods: the method described in this paper will sometimes fail to produce a unique preferred translation, either because the source text is ambiguous or because of deficiencies in the system’s knowledge base, and in such cases it would be convenient to choose between the presented alternatives stochastically.

Reference

Antona, M., and Tsujii, J. (1993). “Treatment of tense and aspect in translation from Italian

- to Greek — an example of treatment of implicit information in knowledge-based transfer MT.” In *TMI-93*.
- Asher, N. (1993). *Reference to Abstract Objects in Discourse*. Kluwer.
- Brown, P., Cocke, J., Pietra, S. d., Pietra, V. d., Jelinek, F., Lafferty, J., Mercer, R., and Roossin, P. (1990). “A statistical approach to language translation.” *Computational Linguistics*, 16(2). §2.
- Dahlgren, K. (1988). *Naive Semantics for Natural Language Understanding*. Boston : Kluwer.
- Dahlgren, K., McDowell, J., and Stabler, E. P. (1989). “Knowledge representation for commonsense reasoning with text.” *Computational Linguistics*, 15(3).
- Dowty, D. R. (1989). “On the semantic content of the notion of ‘thematic role’.” In Chierchia, G., Partee, B. H., and Turner, R. (Eds.), *Properties, Types and Meaning*, Vol. 2. Kluwer.
- Gerloff, P. A. (1989). “From French to English: A look at the translation process . . .” Reviewed in *Computational Linguistics*, 15.
- Grice, H. P. (1975). “Logic and conversation.” In Cole, P., and Morgan, J. (Eds.), *Syntax & Semantics 3: Speech Acts*. Academic Press.
- Gunji, T. (1987). *Japanese Phrase Structure Grammar*. Reidel.
- Jorgensen, J. C. (1990). “The psychological reality of word senses.” *Psycholinguistic Research*, 16.
- Kamp, H. (1981). “A theory of truth and semantic representation.” In Groenendijk, J. et al. (Ed.), *Formal Methods in the Study of Language*. Amsterdam: Mathematical Centre Tracts, University of Amsterdam.
- Lager, T., and Black, W. J. (1994). “Bidirectional incremental generation and analysis with categorial grammar and indexed quasi-logical form.” In *7th International Workshop on Natural Language Generation*. Kennebunkport, Maine.
- Lehrberger, J. (1982). “Automatic translation and the concept of sublanguage.” In Kittredge, R., and Lehrberger, J. (Eds.), *Sublanguage*. Berlin : de Gruyter.
- Levinson, S. C. (1987). “Pragmatics and the grammar of anaphora.” *Linguistics*, 23.
- Lindop, J., and Tsujii, J. (1991). “Complex transfer in MT: a survey of examples.” In *Assessment of Computational Linguistic and Machine Translation Formalisms*, Vol. 3 of *Studies in Machine Translation and Natural Language Processing*. Commission of the European Communities.
- Parsons, T. (1990). *Events in the semantics of English*. MIT Press.
- Pentheroudakis, J. E. (1990). “Complex bidirectional transfer in the ECS English-Korean system.” In *Seoul International Conference on Natural Language Processing*, pp. 108–119.

Language Research Institute, Seoul National University, Korea.

- Phillips, J. D. (1993a). "Generation of text from logical formulae." *Machine Translation*, 8(4).
- Phillips, J. D. (1993b). "Structural misalignment in machine translation." In *Natural Language Processing Pacific Rim Symposium*.
- Phillips, J. D., and Nakano, H. (1993). "Structural change in machine translation between Japanese and English." Vol. 93(26). Information Processing Society of Japan.
- Thomason, R. H., and Touretzky, D. S. (1992). "Inheritance theory and networks with roles." In Sowa, J. F. (Ed.), *Principles of Semantic Networks*. Morgan Kaufman.
- van Eynde, F. (1992). "Machine translation and linguistic motivation." In *Linguistic Issues in Machine Translation*. Pinter.
- Watanabe, H. (1990). "A model of a transfer process using combinations of transfer rules." In *PRICAI*.
- Wilks, Y. (1975). "A preferential pattern-seeking semantics for natural language inference." *Artificial Intelligence*, 6(1).

John D. Phillips: John Phillips graduated from the University of Wales in 1978. After working first as a translator and interpreter then as a computer programmer, he joined the staff of Edinburgh University's Department of Artificial Intelligence as a Research Associate in 1983, where he worked on the Alvey NL Tools and speech recognition projects. In 1988 he moved to the Seminar für Natürliche-sprachliche Systeme of Tübingen University, and in 1990 to the University of Manchester Institute of Science & Technology's Centre for Computational Linguistics. Since 1992 he has lived and worked in Japan, holding first a JSPS Fellowship at the National Language Research Institute in Tokyo, and currently an Associate Professorship at Yamaguchi University. His current research interests include discourse representation theories, and both linguistic and stochastic MT.

(Received August 1, 1996)

(Revised October 13, 1996)

(Accepted December 12, 1996)