INFLUENCE OF TRACK SHAPE RATIO ON TURNING CHARACTERISTICS OF A TRACKED VEHICLE RUNNING ON FRESH CONCRETE

Dang Thai TRAN¹, Tatsuro MURO², Soichiro KAWAHARA³ and Manabu HIRAKAWA⁴

¹ Student member of JSCE, M. Eng., Postgraduate Student, Graduate School of Science and Eng., Ehime University
(3 Bunkyo-cho Matsuyama 790-8577, Japan)

² Fellow member of JSCE, Dr. Eng., Professor, Dept. of Civil and Environmental Eng., Ehime University
(3 Bunkyo-cho Matsuyama 790-8577, Japan)

³ Member of JSCE, Dr. Eng., Research Associate, Dept. of Civil and Environmental Eng., Ehime University
(3 Bunkyo-cho Matsuyama 790-8577, Japan)

⁴ Member of JSCE, M. Eng., Engineer, Hitachi Kenki Co. Ltd,
(650 Kamitachi-cho, Tsuchiura 300-0013, Japan)

A simulation method was developed to investigate the possibility of economical adaptation of ordinary machinery to the work on fresh concrete by changing only track shape ratio. The simulation is then verified by an experiment on a model vehicle running on fresh concrete of slump of 5.5 cm with different traction force and with steering ratio of 1.6. Using the simulation, the influence of the track shape ratio on turning characteristics of tracked vehicle was investigated. The result of the investigation shows that, for a typical turning motion, the effective tractive effort decreases while the turning radius and turning moment increases with the increment of the track shape ratio.

Key Words: *shape ratio, turning characteristics, tracked vehicle, fresh concrete*

1. INTRODUCTION

The aim of the research is to investigate on a method to adapt ordinary tracked vehicle to a very soft terrain such as fresh concrete, soft sandy terrain or muddy terrain. As have been known, running characteristics are not only influenced by contact pressure but also by track shape ratio¹⁾. Consequently, it can be expected that the most efficient and economic way to adapt ordinary tracked vehicle to weak terrain is to change only the vehicle undercarriage to reduce mean contract pressure. However, to further adapt the vehicle to super weak terrain, besides reducing mean contact pressure, there is a need to choose proper track shape ratio for that reduced mean contact pressure. By the selection of both the proper mean contact pressure and proper track shape ratio, with roughly the cost of the new track, it is expected that the vehicle can be adapted to a work requiring turning motion on very soft terrain environment. This paper presents the result of investigation of the effect of track shape ratio on turning characteristics of tracked vehicle while keeping reduced mean contact

pressure unchanged by keeping constant mean contact area. Moreover, the track shape ratio was changed keeping the same grouser high and grouser pitch. Except for the change on track shape ratio by mean of change on track width and track length, other vehicle dimensions remain unchanged.

The comparison between turning proprieties of a model tracked vehicle running on the same fresh concrete with different track shape ratios shows that the track shape ratio has considerable effect on the running proprieties of tracked vehicles especially on the turning moment and turning radius. Based on the result of the investigation, it can be concluded that proper selection of the track shape ratio can improve the vehicle's workability on super weak terrain.

2. SIMULATION

(1) Forces and moment acting to turning vehicle

The vehicle is subjected to land locomotion resistances acting to outer and inner track T_{2o} and T_{2i} . The direction of these forces is considered to be

Fig. 2 Forces and moment acting to turning vehicle

longitudinal. The direction of thrust of outer and inner track, T_{3o} and T_{3i} is considered to be on the contact plane of the tracks. The resultant ground reactions P_o and P_i are considered having a normal direction to the contact plane of the tracks. The vehicle is subjected to lateral forces F_o and F_i caused by lateral bulldozing and lateral shear resistance. The turning moment M is occurred to overcome the moment exerted by the resultant lateral force. The vehicle is also subjected to effective tractive effort T_4 and naturally to its own weight W . Fig. 1 shows the forces and moment acting to the turning vehicle. The equilibrium equations can be written as:

Force balance in the horizontal plane in longitudinal direction [Fig. 1(a)]:

$$(T_{3o} + T_{3i}) \cos \theta_t - (T_{2o} + T_{2i}) - (P_o + P_i) \sin \theta_t - T_4 \cos \alpha = 0 \quad (1)$$

Force balance in the vertical direction [Fig. 1(b)]:

$$W - [(P_o + P_i) \cos \theta_t + (T_{3o} + T_{3i}) \sin \theta_t] \cos \theta_{lat} - (F_o + F_i) \sin \theta_{lat} = 0 \quad (2)$$

Force balance in the horizontal plane in lateral direction [Fig. 1(a)]:

$$T_4 \sin \alpha + (F_o + F_i) \cos \theta_{lat} - (P_o + P_i) \cos \theta_t \sin \theta_{lat} = 0 \quad (3)$$

Moment balance written for point U [Fig. 1(b)]:

$$\frac{C}{2} [(P_o - P_i) + (T_{2o} - T_{2i}) \sin \theta_t] - W H_g \sin \theta_{lat} \cos \theta_t + T_4 H_{dp} \sin \alpha \cos \theta_{lat} = 0 \quad (4)$$

Moment balance in horizontal plane [Fig. 1(a)]:

$$M + (T_{2o} + P_o \sin \theta_t - T_{3o} \cos \theta_t) \frac{C}{2} \cos \theta_{lat} - (T_{2i} + P_i \sin \theta_t - T_{3i} \cos \theta_t) \frac{C}{2} \cos \theta_{lat} + T_4 \sin \alpha \cos \theta_t [L_{dp} - (e_o + e_i) \frac{d}{2}] + T_4 \cos \alpha H_{dp} \sin \theta_{lat} = 0 \quad (5)$$

Where

T_{2o}, T_{2i} : Land locomotion resistance of outer and inner track

T_{3o}, T_{3i} : Thrust of outer and inner track.

P_o, P_i : Ground reaction of outer and inner track.

M : Turning moment.

T_4 : Effective tractive effort.

Fig. 2 Simulation flow chart

(2) Simulation method and flow-chart

For tracked vehicle with rigid suspension system the set of equations describing the state of steady turning can be collapsed into the set of 5 equilibrium equations (1) ~ (5) with 5 independent unknowns^{2), 3)}. The independent unknowns are sinkage of front idler and rear sprocket of inner track S_{fi} , S_{ri} , lateral inclination angle θ_{lat} , slip ratio of outer track i_o (or effective tractive effort T_4) and slip ratio of inner track i_i . For flexible tracked vehicle with rigid suspension system, all other characteristics in the set of equilibrium equations; turning moment M , thrusts of outer and inner track T_{3o} , T_{3i} , lateral forces F_o , F_i , land locomotion resistances T_{2o} , T_{2i} , ground reactions P_o , P_i , turning radius R , eccentricities e_o , e_i , angle of inclination of vehicle θ_t , can be computed from the above 5 independent unknowns. Consequently, the balance conditions for the arbitrary set of the unknowns can be investigated and the unknowns can be methodically modified to satisfy the balance conditions. Using this approach, the problem of predicting turning characteristics can be expressed as problem of finding out which combination of the position of the vehicle at steady turning state (specified by S_{fi} , S_{ri} and θ_{lat}) and operating conditions (specified by i_o (or T_4) and i_i) satisfies the equilibrium equations. The answer to this problem is to solve the set of 5 equilibrium equations for the 5 unknowns S_{fi} , S_{ri} , θ_{lat} , i_o (or T_4) and i_i . Newton-Raphson method for a set of nonlinear equations is used as a solving method of this set of nonlinear equations⁴⁾. As a result, the flow chart of the simulation is as shown in Fig.2.

At first, the design parameters of vehicle, terrain-track system constants and steering ratio are inputted into the simulation. Then the initial guess of S_{fi} , S_{ri} , θ_{lat} , i_o (or T_4) and i_i are selected and inputted into the program. As the next steps the sinkage distribution $S(i)$, distribution of longitudinal and lateral amount of slippage $J_{lon}(i)$ and $J_{lat}(i)$, pressure distributions $p(i)$, longitudinal and lateral shear distribution τ_{lon} , τ_{lat} are calculated. Based on the above calculated values all the characteristics that appear in the set of equilibrium equations; M , T_{3o} , T_{3i} , F_o , F_i , T_{2o} , T_{2i} , P_o , P_i , R , e_o , e_i , θ_t , are computed using basic equations of terrain-track interaction and other equations of geometrical relationship between those characteristics⁵⁾. The equilibrium conditions of the set of the guess of S_{fi} , S_{ri} , θ_{lat} , i_o (or T_4) and i_i can then be investigated by replacing the above calculated characteristics into the left hand side of the equilibrium equations. If the equilibrium conditions are not satisfied the

Table 1 Properties of artificial fresh concrete

Max. Aggr. (mm)	Air cont. (%)	Water-Cement Ratio (%)	Admixt-ures ratio (%)	Slump (cm)
13	2.5	53	52	5.5
Water content (kg/m ³)	Clay Content (kg/m ³)	Admix-tures content (kg/m ³)	Aggreg-ate content (kg/m ³)	Stabili-zer (kg/m ³)
203.6	307.5	897.8	831.9	1.158

corrected values of the guessed unknown are then computed using Newton-Raphson method. Using the above corrected values of S_{fi} , S_{ri} , θ_{lat} , i_o (or T_4) and i_i the calculation is repeated until convergence.

3. EXPERIMENT

The experiment on model vehicle turning on fresh concrete was carried out to verify the simulation analysis. Artificial fresh concrete using clay instead of cement is used to avoid hardening of the material during experiment. Table 1 shows properties of the artificial concrete.

Fig. 3 shows the outline of the model vehicle. The model vehicle is 1/10 scale model of the 40kN bulldozer running on soft sandy terrain. The model vehicle is made for the purpose of verification of the simulation analysis, therefore, the exact modeling is not of first priority. The track mean contact pressure was modified to the pressure of 0.483 N/cm² which is lower then that for super weak terrain to make the vehicle suitable for running on fresh concrete of slump of 5.5 cm. It must be noted that the above contact pressure is selected to investigate the effect of track shape ratio for that pressure and the thorough investigation on appropriate selection of mean contact pressure is not of concern of this paper. Each of the tracks of the vehicle is driven independently by a 90W AC motor through chain transmission. Rotary speed of the main shaft of the motors can be set at fixed value by speed regulators so that steering ratio could be adjusted. Three road rollers support each of the track belts. The dimension of model vehicle is shown in Table 2.

Table 3 shows the terrain-track system constants determined by plate loading unloading and traction test⁴⁾. The constants k_1 , n_1 , k_2 , n_2 determined the

Fig. 3 Outline of model vehicle

Table 2 Model vehicle dimension

Vehicle weight W (N)	638	Grouser height H (cm)	1.7
Height of hitch point H_{dp} (cm)	15	Grouser pitch P (cm)	2.55
Dist. cent. of grav.-hitch point L_{dp} (cm)	30	Grouser thickness G_t (cm)	0.3
Initial track tension H_o (N)	196	Maximum track deflection (cm)	1
Height of center of gravity H_g (cm)	10	Radius of front idler R_f (cm)	6.5
Contact length D (cm)	33	Radius of rear sprocket R_r (cm)	6.5
Track width B (cm)	20	Radius of road rollers R_m (cm)	1.9
Mean contact pressure (kPa)	4.83	Number of road rollers	3
Track gauge C (cm)	33	Road roller interval R_i (cm)	6

relationship between contact pressure p and slip sinkage s as in the following formula for the case when there is no rebound sinkage:

$$p = k_1 s^{n_1}$$

Where p contract pressure
 s sinkage of track

For the case when there is rebound sinkage, the relationship between contact pressure and sinkage is determined by:

$$p = k_1 s^{n_1} + k_2 (s - H)^{n_2}$$

Where H is the sinkage of the beginning of the rebound process ⁴⁾.

The terrain-track system constants determined from traction test, m_c , m_f and a , c_0 , c_1 , c_2 , describe the relationship between shear resistance and amount of slippage and relationship among slip sinkage, contract pressure and amount of slippage as in the following formulas:

Table 3 Terrain-track system constants

	m_c (N/cm ²)	m_f	a (1/cm)
Lon.	0.0157	1.0170	0.1531
Lat.	0.1236	1.0170	0.1225
k_1 (N/cm ^{n₁+2})	n_1	k_2 (N/cm ^{n₁+2})	n_2
0.2276	1.2130	8.5445	0.8010
c_0 (cm ^{1+2c₁-c₂/N^{c₁})}	c_1	c_2	
0.9262	0.9151	0.6006	

$$\tau = (m_c + m_f \cdot p)[1 - \exp(-a \cdot j)]$$

$$s = c_0 p^{c_1} j^{c_2}$$

Where τ shearing resistance
 p contact pressure
 j amount of slippage
 s amount of slip sinkage

Fig. 4 Turning experiment

The vehicle is run in a soil bin with steering ratio of 1.6 (Fig. 4). The steering ratio is defined by the ratio of circumferential speed of outer to that of the inner track. The experiment was carried out for three cases of effective tractive effort of 0, 69 and 147 N. The soil bin has a width and length of 270 mm and depth of 30 mm. Due to the fact that, for all the cases of experiment, front idler of both tracks are in state of floating above concrete, the effect of reaction force from boundary of soil bin due to bulldozing resistance can be ignored.

Directly measured parameters are sinkages, traveled distances covered by each track, time during which these distances are covered, effective tractive effort, and rotary speed of each track. The sinkages were measured using a depth gauge while the traveled distances by a distance measurer. The sinkage was measured immediately after the vehicle is stopped to reduce errors between moving and stopped vehicle due to rebound of fresh concrete. The developed traction force is recorded using a load cell and a universal memorizer. The rotary speeds are measured using a speed measurement device. From the directly measured parameters the turning radius and the slip ratio of each track were determined.

4. RESULTS AND DISCUSSION

(1) Research conditions

The experiment was carried out with only one case of track shape ratio k of 1.650 while the simulation was carried out for different track shape ratios k defined as:

$$k = \frac{D}{B}$$

Where B is the track width and D is the track contact length (Fig. 3).

Table 4 Track shape ratio cases

B (cm)	D (cm)	k	$p_{\text{mean}} = W/2BD$ (N/cm ²)
12.50	52.80	4.224	0.483
13.75	48.00	3.491	0.483
15.00	44.00	2.933	0.483
16.00	41.25	2.578	0.483
20.00	33.00	1.650	0.483

Fig. 5 Influence of track shape ratio k on slip ratio of inner track i_i for different slip ratios of outer track i_o

Table 4 shows the cases of investigated track shape ratio. The simulation was carried out with the track shape ratio k of 4.244, 3.491, 2.933, 2.578 and 1.650. The mean contact pressure P_{mean} is kept unchanged by keeping constant mean contact area $B \times D$. Except for the change of the track width B and the contact length D to modify track shape ratio k , other vehicle specifications are unchanged. For each of the track shape ratio k the simulation was carried out to compute turning characteristics of the vehicle turning with steering ratio of 1.6 for slip ratio of outer track i_o ranging from 0 to 1 with step of 0.01.

(2) The effect of the track shape ratio on running characteristics

The change of the track shape ratio k will bring about the change of the actual contact area even if the mean contact area $B \times D$, which is used as one of the important design parameter, remains unchanged. The track shape ratio k exerts its influences on turning characteristics of tracked vehicle through its effect on the change of actual contact area and through its effect on land locomotion resistance.

Fig. 5 shows the influence of the shape ratio k on slip ratio of inner track i_i for different slip ratios of

Fig. 6 Influence of track shape ratio k on amount of sinkage of front idler of outer track S_{fo} for different slip ratios of outer track i_o

outer track i_o . The slip ratio of outer track i_o and inner track i_i are slip ratios in horizontal direction. The slip ratio of inner track i_i increases with the decrement of track shape ratio k , i.e. increment of track width B . Moreover, the degree of influence of track shape ratio k decreases as the slip ratio of outer track i_o increases. For smaller range of slip ratios of outer track i_o the influence of the track shape ratio k is considerable while from the slip ratios of outer track i_o of about 0.6 this influence becomes very small. The figure also shows the comparison between measured and calculated values of the slip ratio of inner track i_i for the case of the track shape ratio k of 1.650. The comparison shows good match between computed and measured values.

Fig. 6 shows the influence of the track shape ratio k on the sinkage of front idler of outer track S_{fo} for different slip ratios of outer track i_o . The influence of the track shape ratio k on the sinkage of front idler of outer track S_{fo} can be said rather complex as can be seen from the figure. For a bigger range of slip ratio of outer track i_o , the sinkage of front idler of outer track S_{fo} decreases. The figure also shows the comparison between measured and calculated values of the sinkage of front idler of outer track S_{fo} for the case of shape ratio k of 1.650. The figure shows that the measured and calculated values agree well with each other.

Fig. 7 shows the influence of the track shape ratio k on the sinkage of rear sprocket of outer track S_{ro} for different slip ratios of outer track i_o . In general the sinkage of rear sprocket of outer track S_{ro}

Fig. 7 Influence of track shape ratio k on amount of sinkage of rear sprocket of outer track S_{ro} for different slip ratios of outer track i_o

Fig. 8 Influence of track shape ratio k on lateral inclination angle θ_{lat} for different slip ratios of outer track i_o

increases with the increment of slip ratio of outer track i_o . Moreover, the sinkage of rear sprocket of outer track S_{ro} increases with the increment of shape ratio k , i. e. with decrement of track width B . The degree of influence of track shape ratio k on the sinkage of rear sprocket of outer track S_{ro} is significant and increases with the increment of slip ratio of outer track i_o . The figure also shows the verification result of the simulation program by experimental results for the case of shape ratio of 1.650.

Fig. 8 shows the influence of the track shape ratio k on lateral trim angle θ_{lat} for different slip ratios of

Fig. 9 Influence of track shape ratio k on effective tractive effort T_4 for different slip ratios of outer track i_o

Fig. 10 Influence of track shape ratio k on thrust of outer track T_{30} for different slip ratios of outer track i_o

outer track i_o . The figure shows that the influence of track shape ratio k on lateral trim angle θ_{lat} is rather complex. The figure also shows the comparison between measured and calculated values of lateral trim angle θ_{lat} for the case of track shape ratio of 1.650. The comparison shows good match between measured and calculated values.

Fig. 9 shows the influence of the track shape ratio k on the effective tractive effort T_4 . In general, the tractive effort T_4 decreases with the increment of the track shape ratio k , i.e. decrement of the track width B for a typical turning motion corresponding to the region of smaller slip ratio of outer track i_o . Contrary, the tractive effort T_4 increases with the increment of the track shape ratio k , i.e. decrement of the track width B in the region of bigger slip ratio of outer track i_o . The figure shows there exists maximum effective tractive effort T_4 for all the cases of the track shape ratio k . The figure also shows the comparison between measured and computed values of the effective tractive effort for the case of track shape ratio of 1.650, i.e. track width of 20.00 cm. The comparison shows rather good match between simulation and experimental results.

Fig. 10 shows the influence of the track shape ratio k on the thrust of outer track T_{30} for different slip ratios of outer track i_o . The thrust of outer T_{30} achieves maximum values for all the cases of the track shape ratio k . Moreover, the thrust of outer track T_{30} decreases with the decrement of shape ratio k , i.e. the increment of track width B . The influence of the track shape ratio k on the thrust of outer track T_{30} is considerable, considering that the change on the track shape ratio k is relatively small.

Fig. 11 Influence of track shape ratio k on thrust of inner track T_{3i} for different slip ratios of outer track i_o

Fig. 11 shows the influence of the track shape ratio k on the thrust of inner track T_{3i} for different slip ratios of outer track i_o . In the larger zone of the slip ratio of outer track i_o the thrust of inner track T_{3i} decreases with decrement of the track shape ratio k , i.e. increment of the track width B . In the smaller zone of the slip ratio of outer track i_o , however, the reversed tendency can be observed, i.e. the thrust of inner track T_{3i} increases with decrement of the track shape ratio k , i.e. increment of the track width B . The figure shows that the track shape ratio k exerts considerable effect on the thrust of inner track T_{3i} .

Fig. 12 Influence of track shape ratio k on ground reaction force of outer track P_o for different slip ratios of outer track i_o

Fig. 12 shows the influence of the track shape ratio k on the ground reaction force of outer track P_o for different slip ratios of outer track i_o . The influence of the track shape ratio k on ground reaction force of outer track P_o is complex and different depending on the value of the slip ratio of outer track i_o . In the region of larger value of the slip ratio of outer track i_o the ground reaction force of outer track P_o increases with the increment of the track shape ratio k , i.e. decrement of the track width B . Contrary, for a region where the slip ratio of outer track i_o has smaller values the ground reaction force of outer track P_o increases with decrement of the track shape ratio k , i.e. decrement of the track width B . The figure shows considerable effect of the track shape ratio k on the ground reaction force of outer track P_o .

Fig. 13 shows the influence of the track shape ratio k on the ground reaction force of inner track P_i for different slip ratios of outer track i_o . Similarly to the case of the ground reaction force of the outer track P_o , the ground reaction of inner track P_i decreases with increment of the slip ratio of outer track i_o for all the cases of track shape ratio k . Furthermore, the ground reaction of inner track P_i increases with increment of the track shape ratio k , i.e. decrement of the track width B .

Fig. 14 shows the influence of the track shape ratio k on the turning moment M for different slip ratios of outer track i_o . The track shape ratio k exerts considerable influence on the turning moment M in the region of typical turning motion with smaller slip ratio of outer track i_o . Furthermore, the turning

Fig. 13 Influence of track shape ratio k on ground reaction force of inner track P_i for different slip ratios of outer track i_o

Fig. 14 Influence of track shape ratio k on turning moment M for different slip ratios of outer track i_o

moment M increases with the increment of the track shape ratio k , i. e. decrement of the track width B . This phenomenon can be explained by decrease of arm length and lateral bulldozing resistance due to the decrease of the contact length when the track width increases. The maximum turning moment M can be observed for all the cases of the track shape ratio k . The turning moment M of track shape ratio of 4.244, i.e. track width of 12.5 cm is about from 2 to 3 times that of the turning moment M of track shape ratio of 1.650, i.e. track width of 20 cm. As a result, it can be concluded that the track shape ratio

Fig. 15 Influence of track shape ratio k on turning radius R for different slip ratios of outer track i_o

k plays a very important role in the design of tracked vehicles working on a soft terrain.

Fig. 15 shows the influence of the track shape ratio k on the turning radius R for different slip ratios of outer track i_o . For better comparison between turning radius R of different track shape ratios k , the range of turning radius R is limited to the range from 0 to 30 m. The turning radius R increases with the increment of the track shape ratio k , i. e. the decrement of the track width B . From the figure, it can be observed that the track shape ratio k exerts considerable influence on the turning radius R especially in the larger range of the slip ratio of outer track i_o . The figure shows the minimum value of turning radius R can be observed for all the cases of shape track ratio k . It is obvious that the turning radius R increases very rapidly from certain slip ratio of outer track i_o . The figure also shows the comparison between measured and calculated turning radius R for the case of the track shape ratio k of 1.650, i.e the track width B of 20 cm. The comparison shows that the measured and calculated values of turning radius R agree well with each other.

Fig. 16 shows the influence of the track shape ratio k on the input energy E_1 for different slip ratios of outer tracks i_o . For better comparison between input energy E_1 of different track shape ratios k the range of slip ratio of outer track i_o was limited from 0.2 to 1. The figure shows that for the bigger range of slip ratio of outer track i_o the input energy E_1 increases with increment of track shape ratio k , i.e. with the decrement of track width B . For the small range of slip ratio of outer track, however, the

Fig. 16 Influence of track shape ratio k on the input energy E_1 for different slip ratios of outer track i_o

Fig. 17 Influence of track shape ratio k on the tractive energy E_4 for different slip ratios of outer track i_o

tendency is reverse, i.e. the input energy E_1 increases with decrement of track shape ratio k .

Fig. 17 shows the influence of the track shape ratio k on the effective tractive effort energy E_4 for different track shapes ratio k . Similarly to the case of the input energy, the effective tractive energy increase with increment of the track shape ratio k , in the larger range of slip ratio of outer track i_o . The optimum slip ratio of outer track can be found around slip ratio of outer track i_o of 0.5 for all the cases of the track shape ratios. It can be observed from the figure that the optimum slip ratio of outer track is larger at smaller track shape ratio k , i. e. larger track width B . It can be concluded that the

Fig. 18 Influence of track shape ratio k on distribution of lateral amount of slippage of outer track J_{lat} for the case of slip ratios of outer track i_o of 0.3

Fig. 19 Influence of track shape ratio k on distribution of lateral shear resistance of outer track τ_{lat} for the case of slip ratios of outer track i_o of 0.3

track shape ratio k exerts relatively larger effect on the tractive energy E_4 .

Fig. 18 and Fig. 19 show the influence of the track shape ratio k on the distribution of lateral amount of slippage and lateral shear resistance respectively for the case of slip ratio of outer track i_o of 0.3. For better comparison the track shape ratio is limited to only three cases of $k = 1.650, 2.933$ and 4.224 . From the figures it can be observed that the track shape ratio k exerts considerable effect on distribution of lateral amount of slippage and lateral shear resistance.

Fig. 20 shows the influence of the track shape ratio k on the pressure distribution of the inner track for the case of the slip ratio of outer track i_o of 0.3. The figure shows for this case of the slip ratio of outer track i_o the pressure of the inner track tends to concentrate on rear wheel as track shape ratio k increases.

Fig. 20 Influence of track shape ratio k on the ground contact pressure distribution of inner track for the case of slip ratio of outer track i_o of 0.3

5. CONCLUSION

The simulation was developed to predict turning characteristics of tracked vehicle turning on fresh concrete. The experiment on the model vehicle running on fresh concrete was then carried out to verify the simulation. The effect of track shape ratio at the same mean contact pressure was investigated and the followings can be concluded for a given fresh concrete-model vehicle:

- (1) In general, the tractive effort T_4 decreases with the increment of the track shape ratio k , i.e. decrement of the track width B for a typical turning motion corresponding to the region of smaller slip ratio of outer track i_o .
- (2) The turning radius R increases with the increment of the track shape ratio k , i.e. the decrement of the track width B .

(3) The track shape ratio k exerts considerable influence on the turning moment M in the region of typical turning motion with smaller slip ratio of outer track i_o . Furthermore, the turning moment M increases with the increment of the track shape ratio k , i. e. decrement of the track width B .

REFERENCES

- 1) Bekker, M. B.: Theory of land locomotion, the mechanics of vehicle mobility, University of Michigan press, pp. 280-282
- 2) Muro, T and Thai, T.D.: Turning Characteristics of a Bulldozer under Traction on a Weak Sandy Terrain, Proceedings of 7th European ISTVS Conference, pp. 102-109, 1997.
- 3) Muro, T. and Thai, T.D.: Numerical Analysis to Predict Turning Characteristics of Rigid Tracked Vehicle under Traction on Loose Sandy Soil, TERRAMECHANICS, Volume 18, The Japanese Society for Terramechanics, pp. 41-48, 1998.
- 4) William H. Press, Saul A. Teukolsky, William T. Vetterling and Brian P. Flannery: Numerical Recipes in C, the art of scientific computing- second edition, Cambridge University Press, pp. 379-393, 1995.
- 5) Tran Dang Thai and Tatsuro Muro: Numerical analysis to predict turning characteristics of rigid suspension tracked vehicle, Journal of Terramechanics, Volume 36, No.4, pp.183-196, October 1999.

(Received March 10, 1999)

フレッシュコンクリート上を走行する履帯式車両の旋回特性に及ぼす 履帯形状比の影響

トラン ダン タイ ・ 室 達 朗 ・ 河原 荘 一 郎 ・ 平 川 学

本研究は、履帯式車両の履帯形状比が、フレッシュコンクリートなどの軟弱地盤上での旋回走行に与える影響について調べることを目的としている。本報は、実験と解析結果より、軟弱地盤上での履帯式車両の旋回特性として、沈下量、有効牽引力、旋回半径、旋回モーメントおよび車両傾斜角に履帯形状比が及ぼす影響について示している。その結果、履帯幅が狭く履帯長が長くなる程旋回モーメントが大きく旋回半径が大きくなることが判明した。