536.25 : 532.529 : 536.44

Experimental Study of Homogeneously Dispersed Two-phase Critical Flow*

By Yukio SUDO**

To verify the principle of the occurrence of the critical flow, a homogeneously dispersed two-phase flow is tactfully realized in an experiment. Air and water are used as fluids of the two-phase flow and water is blown into the gas stream as minute droplets. The concrete critical flow condition is carefully obtained by measuring the thrust of the two-phase flow outside the exit plane of the duct. The critical conditions obtained at the experimental result are well coincident with the theoretical ones. At the same time the factors governing the critical conditions of the homogeneously dispersed two-phase flow are also made clear.

1. Introduction

In this study, the critical conditions of the homogeneously dispersed two-phase flow are studied experimentally. This homogeneously dispersed two-phase flow having a definite flow pattern is one of the typical two-phase flows.

Although various complicated two-phase flows, of course, exist in reality, the homogeneously dispersed two-phase flow treated here is restricted almost to an ideal case that gas and liquid particles are each flowing with uniform velocities at each cross-section of the duct. Accordingly, only the case that a comparatively small volume of the liquid particles constitutes the gas stream is dealt with.

Especially in the experiment, the thrust of the two-phase flow is measured at the outside of the testing duct exactly to grasp the flow conditions at the exit plane of the duct. The characteristic features of the critical conditions of the dispersed two-phase flow which occur in the experiment are at the same time made clear.

This study compares the experimental critical state obtained from the thrust measurements with the theoretical state obtained by applying the general principle of the occurrence of the critical flow to this flow. Thus, in this study the two are compared to verify the theory on the occurrence of the critical flow.

In addition, it seems that the reports on the dispersed two-phase critical flow are very rare although the ones on the separated two-phase critical flow are numerous.

2. Experimental Critical State

2.1 Experimental apparatus and procedure

(A) Outline of the experimental apparatus:

* Received 4th April, 1973.

** Research Fellow, Japan Atomic Energy Research Institute, Tokai, Ibaragi.

The experimental apparatus is shown schematically in Fig. 1, where both an air-supply system and a water-supply system are connected with the testing duct. Air and water are used as the gas and liquid of the two-phase flow in the present experiment and are mixed as a "homogeneously dispersed two-phase flow". The water-supply system includes the floating rotor meter to measure the flowrate of the liquid and the guiding pipe to the testing part, while the air-supply system includes three compressors, regulating valves, reservoir tank and the measuring part of the flowrate of the gas.

The testing duct is composed of the testing part of the straight duct (70mm in length, 7mm I.D.) in which gas and liquid flow as a dispersed two-phase flow, two guiding pipelines to send water and air and the apparatus to blow minute liquid droplets into the testing part of the duct under uniform pressure through four holes (1mm I.D.).

Fig.1 Schematic diagram of the experimental apparatus

The mechanism to blow the liquid droplets into the testing part of the duct is shown in Fig. 2. The pressure reduction along the duct wall is measured with pressure taps (0.3mm I.D.) located at the

positions of 0.5, 5, 10, 20 mm each from the outlet section of the duct. Apart from the above-mentioned pressure measurements, the pressure reduction along the flow on the centerline of the duct is also measured. The apparatus for it is composed of a stainless steel tube (2mm O.D.) with two static pressure holes (0.3mm Dia.) on its surface and a mechanism which holds one end of the stainless steel tube and makes it move along the flow slightly and a pressure gauge. The pressure reduction along the flow is continuously measured on the centerline of the duct far outside the duct by removing the position of the static pressure holes with this apparatus. An optical apparatus is also furnished to observe the flow conditions in the neighborhood of the outlet section of the duct as well as an apparatus to measure the local flowrate of liquid droplets through the cross-section at the exit of the testing duct of 7mm I.D. by traversing a pitot tube of 0.6mm I.D. (with a sharp edge at the top) at intervals of 0.5mm along a vertical line passing through the center of the duct in order to examine whether the homogeneously dispersed two-phase flow is established. An apparatus by which the thrust of the two-phase flow is measured in order to investigate the flow conditions at the outlet of the duct, especially to investigate the critical flow conditions, is also furnished.

The thrust of two-phase flow is measured by measuring with a platform scale the force acting on a flat disk against which the two-phase flow strikes. This measuring technique has been well checked with a single-phase flow beforehand.

(B) Experimental procedure: At the time of experiment, flowrates of water and air are first regulated before the fluids enter the testing part and then the total flowrate is gradually increased under the condition of the constant quality x . When the flowrate reaches the maximum capacity of the experimental apparatus, the series of the runs at the constant quality is broken off and then the same procedure is repeated after a new value of quality is taken. In the runs, the pressure reductions both on the centerline of the duct and on the duct wall along the flow, the pressure in the reservoir tank of gas and the thrust of the two-phase flow are at the same time measured. From these measurements, the flow conditions at the outlet section of the duct are calculated from the subcritical region to the critical region.

Fig. 2 Concrete conditions for mixing the liquid droplets and the gas.

2-2 Experimental results

(A) Flow conditions and the pressure reduction on the centerline of the duct: In the real flows, it is important to examine if the liquid droplets are in reality uniformly dispersed across the sections of the duct or if the droplets flow partially to an extreme degree when the critical state occurring in the experiment is compared with the theoretical analyses. In this experiment it was confirmed beforehand that, as the blowing-in method of liquid droplets the method of blowing water in the vertical direction to the gas stream from the wall into the duct through the holes is better than that of blowing water in parallel with the gas stream on the centerline of the duct. The local flowrate of liquid droplets is measured on the cross-section at the exit of the testing duct to check if a dispersed flow has been realized. The experimental result shown in Fig. 3. In the figure, the flowrate of water is gradually increased under a constant flowrate of air ($W_g=1.0$ kg/min.). Strictly speaking the local flowrate of water loses the uniformity as the flowrate of water becomes large, but it can be assumed that the flowrate distribution over the section of the duct is approximately uniform within this degree.

No.	W_g (kg/min)	W_L (kg/min)	x
1.	1.0	1.5	0.40
2.	1.0	0.77	0.59
3.	1.0	0.30	0.77
4.	1.0	0.10	0.91

Fig. 3 Example of the flow rate distribution of the liquid droplets in the radial direction.

The static pressure reduction along the flow on the centerline of the duct is shown in Figs. 4-7 with the quality as a parameter when the total flowrate is increased under the constant quality. The pressure is normalized with the stagnation pressure in the reservoir tank P_0 . Figure 4 shows the case of a single-phase flow of air without water for comparison. The horizontal line at the exit of the duct in the figure shows the value of back pressure ratio P_b/P_0 . In the case of a single-phase flow of air, the exit pressure is equal to the back pressure and the pressure reduction within the duct is very small when the flow rate is comparatively small. When the flow rate is gradually increased, the dimensionless static pressure P/P_0 becomes lower and an abrupt pressure reduction occurs in the neighborhood of the

exit of the duct although the stagnation pressure P_0 in the tank and the static pressure P at each cross section of the duct both rise. When the flow rate is increased furthermore and when the flow rate exceeds a certain value, the dimensionless static pressure reduction profiles are fixed constant in the duct and the exit pressure at the same time becomes higher than the back pressure. After this, the critical state is realized in the flow. In the critical flow the perturbation of the static pressure in the neighborhood of the back pressure becomes visible outside the duct and the amplitude of perturbation becomes larger as the flow rate is increased. That the flow state of gas at the critical point (that is, at the outlet of the duct) is expressed as the Mach number $Mg=1$, can be shown later from the coincidence of the theoretical relation between the exit pressure and total flow rate with the experimental results. The exit pressure ratio P_e/P_0 is lower than the value (0.528 in case of air) when Mg becomes unity under the isentropic change, as the flow change is not isentropic because of the friction loss between the gas stream and the duct wall.

Next, the pressure reductions in case of the dispersed two-phase flow are shown in Figs.5-7. The situation when the total flow rates are increased under the constant quality x , is similar to that of the above-described single-phase flow, but the numerical values are much different between the two as the droplets are contained in the flow. That is, when the total flow rate is increased, the dimensionless pressure reduction P/P_0 in the duct is almost fixed and the exit pressure P_e becomes higher than the back pressure P from over a certain flow rate, and then, at last, this dispersed two-phase flow also reaches the critical flow. The characteristic of the dispersed flow is that the flow is much affected by the quality. When the quality x is smaller, the fixed static pressure ratio P/P_0 at each cross section in the duct becomes lower especially in the critical flow. When the quality becomes closer to unity the situation becomes much more similar to that of the single-phase flow. The amplitudes of the static pressure perturbation outside the exit of the duct become smaller and the pressure reduction biases along the flow in the neighborhood of the exit become less steep as the quality becomes smaller.

Fig. 4

Fig. 5

Fig. 6

Fig. 7

Fig.4-7 Examples of the static pressure reductions along the flow-direction on the centerline of the duct (experimental).

(B) Flow regions which can be judged from the exit pressure ratio P_e/P_0 : The flow state of the dispersed two-phase flow moving from the subcritical flow to the critical one can be characterized by the relation between the exit pressure ratio P_e/P_0 and back pressure ratio P_b/P_0 with the quality as the parameter. In Fig. 8, the experimental results are shown in case of $D=7\text{mm}$, $L/D=10$. As seen from this figure, whatever the quality may be, the exit pressure P_e is almost equal to the back pressure P_b in the subcritical region, and whatever the back pressure ratio, P_e becomes higher than P_b and at the same time the exit pressure ratio P_e/P_0 becomes almost constant in the critical region. Especially it should be noticed that, when the quality is near unity, the boundary

between the subcritical region and the critical one is remarkably divided and that, on the other hand, when more water droplets are contained in the flow and then, where the quality becomes smaller, the boundaries between the two regions become obscure and the transition regions appear, where the flows don't reach the critical state although the exit pressure is higher than the back pressure. It is clearly shown in Fig. 8 how the constant value of P_e/P_o at the critical state changes when the quality becomes smaller than unity.

Fig. 8 Exit conditions of the homogeneously dispersed two-phase flow (relations of the exit pressure ratio and the back pressure ratio).

(C) The comparison of the static pressure on the centerline of the duct with the one on the duct wall: Both of the static pressures, P_ϕ and P_w measured on the centerline of the duct and on the duct wall are shown in Fig. 9 to Fig. 11. The differences between the two pressures P_ϕ and P_w are related intimately to the appearance of the transition region described above. Especially in Fig. 9, the case of the single-phase flow is illustrated as a reference. In this case the pressure on the centerline of the duct is almost coincident at the same cross section of the duct with the pressure on the duct wall far toward the neighborhood of the outlet section of the duct (the distance between the pressure tap located on the wall and the outlet section is limited for technical reasons). But, in the case of the dispersed two-phase flow, although the differences between the two static pressures, P_ϕ and P_w are small upstream by more than one diameter of the duct from the outlet section even if the quality becomes as low as 0.35, the pressure on the centerline of the duct becomes much higher than the pressure on the wall and the differences of the two become remarkable between the exit plane of the duct and about one diameter upstream from it especially when more water droplets are contained in the flow. From the results of these measurements, it is understood that the transition region appears because the pressure on the centerline of the duct becomes higher than on the duct wall at the same cross section in the neighborhood of the exit plane and the approximation of one-dimensionality that the pressure is uniform over across the section of the duct ceases to be valid gradually.

Fig. 9

Fig.10

Fig.11

Fig.9-Fig.11 Comparison of the static pressure reductions measured on the centerline of the duct and on the duct wall.

(D) Critical conditions: In the preceding sections, transition conditions from the subcritical flow to the critical one in case of the dispersed two-phase flow, that is, how different the critical flow state is from the subcritical one has been investigated and described. And in addition to this, it is pointed out that the problem of the two-dimensionality of the flow arises also in the dispersed flow although the degree is much smaller. Here, the flow state at the critical conditions is investigated in detail.

D-1. Relation between the critical flow rate and the critical pressure: In Fig.12, the relations between the total flow rate W and the exit pressure P_e and shown, taking the quality x as the parameter. In the figure, the positions of the arrow indicate the back pressure P_b (which is the atmospheric pressure and is constant in this experiment). Also in this figure, the transition region appears where the exit pressure P_e is a little higher than

the atmospheric pressure. As the exit pressure becomes higher enough than the back pressure, the total flow rates become proportional to the increase of the exit pressure under the constant quality. The nearer to unity the quality is, the more remarkable this proportionality is. The experimental relation between the flow rate and the exit pressure in case of air (single-phase flow) is illustrated with the -mark on the same figure and the thick, solid line indicates the theoretical relation of the two at the critical state as a reference. The more water is contained in the flow, the higher the exit pressure becomes under the condition of the same flow rate of air. The case that the quality comes infinitely closer to unity in the dispersed two-phase flow coincides with the case of the single-phase flow. In other words, the flow state when the water droplets are mixed in the gas flow can be understood as a state in the continuous change of the flow state from the single-phase flow. The arranging method of the experimental results described above has been very often adopted till now and this method is very convenient for the results of the experimental data can thus be very well understood. This arrangement is, however, insufficient for the purpose of investigating the critical condition concretely as it cannot be made clear in what states the two phases are at the critical conditions. Then the thrust of the dispersed two-phase flow is measured in the outside of the duct and the velocities of the gas and liquid U_{ge} , U_{le} at the outlet section of the duct are calculated to investigate the condition of the two phases at the critical state in detail.

Fig.12 Experimental relations of the total flowrate and the exit pressure.

D-2 The exit conditions (especially the critical state) obtained from the thrust measurements:

(a) The calculation of exit conditions: In the case of the homogeneously dispersed two-phase flow, a difficulty occurs precisely to grasp the flow state in the duct unlike in the case of a completely separated two-phase flow. It is very difficult to grasp the condition of the gas

directly or to know the diameters, velocities and temperatures of the water droplets and then, the whole flow state cannot be understood easily as minute droplets are dispersed with high velocities in the gas stream in this flow. By the way, the difference between the droplets temperature T_d and the static temperature of air T_g may be considered small at each cross section of the duct and then, the assumption of $T_g/T_d=1$ may be valid approximately at the outlet section under the following experimental conditions:

Stagnation temperature of the gas $T_{0g}=300^\circ\text{K}$

Water temperature entering the duct $T_{0d}=293\text{--}295^\circ\text{K}$

as the droplets are very minute and the duct is comparatively long. Under the above-described assumptions of $T_g/T_d=1$, the flow state of the two phases at the outlet section is calculated from the thrust measurements to compare the critical states in the experimental results with the theoretical conditions. As the total momentum flux along the flow is kept constant outside of the duct, the following equation is introduced involving the thrust F of the two phases of gas and liquid which acts on the flat disk as shown in Fig. 13.

Fig.13 Control volume for the calculation of the exit condition from thrust measurements of jet.

$$(W_g U_{ge} + W_l U_{le})/g_c + A_e P_e + (A - A_e) P_b = F + A P_b. \quad (2-1)$$

Where, A is the area of the control volume projected in the direction of the flow, g_c is the converting factor of force, W_g and W are the flowrates of the gas and the liquid and A_e is the area of the duct exit and where the two-phase jet is assumed to flow away smoothly in the vertical direction to the flow without rebounding on the disk of the platform scale.

Eqn.2-1 is simplified as follows.

$$W\{(1-x)U_{ge} + xU_{le}\}/g_c = F - A_e(P_e - P_b). \quad (2-2)$$

Continuity eqn. at the outlet section of the duct is,

$$W(1-x)/g_c \rho_{ge} U_{ge} + Wx/g_c \rho_{le} U_{le} = A_e \quad (2-3)$$

Energy eqn. between the entrance and the outlet of the duct is,

$$W\{(1-x)C_{pg} \bar{T}_e + xC_{pl} \bar{T}_g\} + W\{(1-x)U_{ge}^2/2 + xU_{le}^2/2\}/g_c J = H_0$$

Where, ρ_{ge} and ρ_{le} are the densities of the gas and the liquid, C_{pg} and C_{pl} are the specific heats at the constant pressures of the gas and the liquid, J is the mechanical equivalent of heat and H_0 is the total enthalpy at the entrance of the duct.

From $\bar{T} = \bar{T}_g = \bar{T}_l$,

$$\bar{T}_e \{ (1-x) C_{p\ell} + x C_{pg} \} + \{ (1-x) U_{\ell e} + x U_{ge} \} / 24cJ = H_0/W. \quad (2-4)$$

State eqn. of the gas is,

$$P_e = \rho_{ge} g_c R \bar{T}_e. \quad (2-5)$$

From the above four equations (2-2), (2-3), (2-4), (2-5) the flow conditions at the outlet section of the duct (u_{ge} , $U_{\ell e}$, T_e , ρ_{ge}) are easily obtained through the measurements of total flow rate W , quality x , thrust F and exit pressure P_e .

(b) Exit conditions of the flow by thrust measurements: First, the results of the thrust measurement are shown in Fig. 14. In Fig. 15, the velocities of gas and liquid U_{ge} , $U_{\ell e}$ are shown. From this figure, the following characteristics are understood when the total flow rate is increased under the constant quality.

Fig.14 Example of the result of thrust measurements.

Fig.15 Exit velocities of gas and water droplets obtained from thrust measurements.

- (1) In the transition region where the exit pressure is a little higher than the back pressure (atmospheric pressure) the velocities of each phase increase with an increase of the exit pressure.
- (2) In the critical region where the exit pressure is higher enough than the back pressure the velocity of each phase is kept constant approximately. The characteristic of the critical conditions appears here.

The sonic velocities indicated at the right shoulder of the figure are the sonic velocities of the gas at each experimental

condition a, b, c and d. That is, the critical velocities of the gas approximately coincide with the sonic velocity of the gas at the state. On the other hand, the constant velocities of the water droplets under the constant quality x becomes gradually lower at the critical conditions as the volume of the water droplets in the flow becomes larger relatively, that is, when the quality x becomes smaller.

3. Verification of the Theory on the Critical Flow

3-1 Theoretical state of the critical flow of the homogeneously dispersed flow: The theoretical state of the critical flow which should occur in the homogeneously dispersed flow shown in Fig.16 is characterized as follows.

Here, a two-phase flow composed of the compressible gas and the incompressible liquid droplets such as air and water is treated on account of easiness of the experiment and furthermore, a dispersed two-phase flow in the adiabatic duct of which the cross-sectional area is constant is treated under the following assumptions.

Fig.16 Flow model of the homogeneously dispersed two-phase flow for analyses (adiabatic, constant-area duct).

- (1) The liquid droplets neither combine into one nor separate in the gas stream.
- (2) The droplets are distributed uniformly at each cross section in the duct.
- (3) The diameters of the droplets are the same, that is, both the evaporation from the surfaces of the droplets and the condensation to the surfaces are ignored.
- (4) The droplets are incompressible and very small.

Basic equations: The variation of the variables in the infinitesimal distance dZ between the two control surfaces is considered first.

(Continuity eqn.) The droplets and the gas which are contained in the infinitesimal control volume are respectively,

$$(\pi/6)d^3nAdZ, \quad \{1-(\pi/6)d^3n\}AdZ.$$

where d is the diameter of the droplet, n the number of the droplets per unit volume, A the cross section area of the duct, Z the distance along the flow. Then,

$W(1-x) = (\pi/6)d^3nA\ell g_c U_{\ell}$, $Wx = \{1-(\pi/6)d^3n\}A g_c U_g$.
where W is the total flow rate, ρ the density, u the velocity, g_c the conversion factor of force. The subscripts ℓ and g show liquid and gas phases respectively. By eliminating $(\pi/6)d^3 \cdot n$ from both

equations and then, differentiating it,

$$\frac{1-x}{\rho_g U_g^2} dU_g + \frac{x}{\rho_g U_g} dU_l + \frac{x}{\rho_g U_g} dU_g = 0. \quad (3-1)$$

(Momentum eqn.) As the droplets are minute, the following expression is established for one droplet moving in the gas stream.

$$\frac{\pi}{6} d^3 \frac{dU}{dZ} + \frac{\pi}{6} d^3 \rho_l U \frac{dU}{dZ} = F_d. \quad (3-2)$$

where F_d designates the friction force per unit length and is in general a function of the velocity difference $u_g - u_l$. For the whole of the flow, the following expression is obtained. This is independent of the above. The interference between the droplets and the duct wall is considered to be zero.

$$A \frac{dP}{dZ} + \frac{\pi(1-x)}{g_c} \frac{dU_l}{dZ} + \frac{\pi x}{g_c} \frac{dU_g}{dZ} = -F_w. \quad (3-3)$$

where F_w is the wall friction per unit length along the flow.

(Energy eqn.) For the whole of the flow,

$$x d h_g + (1-x) d T_e + \frac{x}{g_c} U_g d U_g + \frac{1-x}{g_c} U_l d U_l = 0. \quad (3-4)$$

For the temperature change of the incompressible droplets in the gas stream,

$$(\pi/6) d^3 \rho_l c_p U_l \frac{dT_e}{dZ} = \pi d^2 \alpha (T_g - T_e). \quad (3-5)$$

As P , ρ_g and h_g are the thermodynamic state properties.

$$dP_g = (\partial P / \partial P) dP + (\partial P / \partial h_g) d h_g.$$

By substituting the above relation into Eqn. (3-1),

$$\left(\frac{x}{\rho_g U_g} \right) \left(\frac{\partial P}{\partial P} \right) \frac{dP}{dZ} + \left(\frac{x}{\rho_g U_g} \right) \frac{dU_l}{dZ} + \left(\frac{x}{\rho_g U_g} \right) \frac{dU_g}{dZ} + \left(\frac{1-x}{\rho_g U_g} \right) \frac{dU_l}{dZ} + \left(\frac{1-x}{\rho_g U_g} \right) \frac{dT_e}{dZ} = 0. \quad (3-6)$$

Eqns. (3-2)-(3-6) are formally expressed as follows.

$$\begin{aligned} A_{11} \frac{dP}{dZ} + A_{12} \frac{dU_l}{dZ} + A_{13} \frac{dU_g}{dZ} + A_{14} \frac{dT_e}{dZ} &= A_{15} \\ A_{21} \frac{dP}{dZ} + A_{22} \frac{dU_l}{dZ} + A_{23} \frac{dU_g}{dZ} + A_{24} \frac{dT_e}{dZ} &= A_{25} \\ A_{31} \frac{dP}{dZ} + A_{32} \frac{dU_l}{dZ} + A_{33} \frac{dU_g}{dZ} + A_{34} \frac{dT_e}{dZ} &= A_{35} \\ A_{41} \frac{dP}{dZ} + A_{42} \frac{dU_l}{dZ} + A_{43} \frac{dU_g}{dZ} + A_{44} \frac{dT_e}{dZ} &= A_{45} \\ A_{51} \frac{dP}{dZ} + A_{52} \frac{dU_l}{dZ} + A_{53} \frac{dU_g}{dZ} + A_{54} \frac{dT_e}{dZ} &= A_{55} \end{aligned} \quad (3-7)$$

where

$$\begin{aligned} A_{11} &= \left(\frac{x}{\rho_g U_g} \right) \left(\frac{\partial P}{\partial P} \right), A_{12} = \left(\frac{x}{\rho_g U_g} \right), A_{13} = \left(\frac{x}{\rho_g U_g} \right), A_{14} = \left(\frac{x}{\rho_g U_g} \right), A_{15} = 0, \\ A_{21} &= \left(\frac{x}{\rho_g U_g} \right) \left(\frac{\partial P}{\partial h_g} \right), A_{22} = 0, A_{23} = 0, A_{24} = 0, A_{25} = 0, \\ A_{31} &= \left(\frac{x}{\rho_g U_g} \right) \left(\frac{\partial P}{\partial h_g} \right), A_{32} = 0, A_{33} = 0, A_{34} = 0, A_{35} = 0, \\ A_{41} &= \left(\frac{x}{\rho_g U_g} \right) \left(\frac{\partial P}{\partial h_g} \right), A_{42} = 0, A_{43} = 0, A_{44} = 0, A_{45} = 0, \\ A_{51} &= \left(\frac{x}{\rho_g U_g} \right) \left(\frac{\partial P}{\partial h_g} \right), A_{52} = 0, A_{53} = 0, A_{54} = 0, A_{55} = 0. \end{aligned}$$

Here, the determinant made of the coefficients in the left-hand sides of eqn. (3-7) is put as Δ .

$$\Delta \equiv \begin{vmatrix} A_{11} & A_{12} & A_{13} & A_{14} & A_{15} \\ A_{21} & A_{22} & A_{23} & A_{24} & A_{25} \\ A_{31} & A_{32} & A_{33} & A_{34} & A_{35} \\ A_{41} & A_{42} & A_{43} & A_{44} & A_{45} \\ A_{51} & A_{52} & A_{53} & A_{54} & A_{55} \end{vmatrix}. \quad (3-8)$$

dP/dZ , du/dZ and so on are expressed as follows.

$$\frac{dP}{dZ} = \frac{1}{\Delta} \begin{vmatrix} A_{25} & A_{26} & A_{27} & A_{28} & A_{29} \\ A_{35} & A_{36} & A_{37} & A_{38} & A_{39} \\ A_{45} & A_{46} & A_{47} & A_{48} & A_{49} \\ A_{55} & A_{56} & A_{57} & A_{58} & A_{59} \end{vmatrix}, \text{ etc.} \quad (3-9)$$

According to the above equations the

flow state changes in the duct. As the critical flow is considered to occur as a limited change in the continuous flow state in the duct, the flow condition at the critical position is determined from such relation that the denominator becomes zero while the numerator equals to zero. Now, as it can be assumed for simplicity that the gas state changes according to the state equation of the ideal gases,

$$M_g^2 = 1 + \epsilon, \quad \epsilon \equiv \frac{\frac{1-x}{x} \left(\frac{P_g}{P_l} \right) \left(\frac{U_g}{U_l} \right)^2 + (x-1)}{1 - (x-1) \frac{1-x}{x} \left(\frac{P_g}{P_l} \right)}. \quad (3-10)$$

from the relation that the denominator equals to zero.

As the value of ϵ becomes positive in the above equation ($0 < x < 1$ in case of the dispersed two-phase flow), it can be readily understood that the gas is supersonic at the critical position of this two-phase flow (that is, $M_g > 1$).

To what degree the gas becomes supersonic at the critical position depends on the magnitude of ϵ , which shows the characteristics of the critical flow which occurs in the dispersed two-phase flow. Eqn. (3-10) involves also the relation of the critical state ($M_{ge}=1$) in case of the single-phase flow ($x=1$). Also from this fact, it can be readily understood that, in the experimental results of the relation between the total flow rate W and the exit pressure P_e , the relation when the quality approaches infinitely unity in the dispersed two-phase flow coincides with the case of the single-phase flow.

3-2 The theoretical verification of the critical conditions:

(A) Relative velocities between the gas and the liquid. It may be without serious error assumed that the temperature of the gas is approximately the same as that of the water droplets at the outlet section of a long duct when the droplets are infinitesimal in the two-phase flow. Besides, the possibility exists at least that the velocities of the gas and the droplets are of the same magnitude at the outlet of the duct because the droplets are accelerated enough in the long duct by the gas stream when the volume of the droplets is relatively small. In Fig. 17, the calculated values of the velocity ratios ($k=(U_g/U_l)e$) are shown especially at the critical conditions to investigate the possibilities described above. This figure is made from Fig. 15, in which the critical velocities of the gas and the liquid (U_{ge} and U_{le}) are shown by calculating from the thrust measurements. When the total flow rate W is increased gradually under the constant quality x , the exit pressure becomes more higher at the critical conditions and on the other hand, the velocity ratio k of the gas and the liquid is kept almost constant, whatever the exit pressure is. The velocity differences between the gas and the liquid droplets decrease, and the velocity ratio approaches unity when the quality approaches unity (that is, the liquid flow rate becomes relatively small). The

possibility described above is now proved. Inversely, when the relative volume of the water droplets is increased, the droplets are not accelerated by the gas stream in the real flow and then, the velocity ratios k become larger at the critical states.

Fig. 17 Critical velocity ratio of gas and water droplets.

(B) The relation between the total flow rate W and the exit pressure P_e at the critical condition: The nearer the quality x approaches unity, the better the experimental relation between the critical flow rate W and the exit pressure P_e coincides with the theoretical relation which is obtained under the assumption that the velocities and the temperatures of the gas and the liquid are the same at the outlet section of the duct, that is, using one of the extreme relations. When the quality deviates far from unity, the experimental flow rates, however, become lower than the theoretical ones. This is caused mainly by the magnitude of the velocity ratio and then, may be caused by the fact that the droplets are not fully accelerated by the gas stream even in the long duct when the volume of the droplets becomes larger in the flow. This tendency that the critical velocity of the droplets becomes lower when the volume of the droplets is relatively large appears markedly in Fig. 17.

The semi-theoretical relations between the critical flow rate W and the critical exit pressure P_e which have been calculated using both the almost constant velocity ratio k shown in Fig. 17, and the assumption of $T_g/T_l=1$, are shown in Fig. 18 with the $\square$ -marks. These semi-theoretical values completely coincide with the experimental results in the critical regions in which the exit pressure is higher enough than the back pressure. On the other hand, in the transition region in which the exit pressure is a little higher than the back pressure, small differences occur between the two.

(C) The critical velocity of the gas: In Eqn. (3-10), the quality x , the density ratio (ρ_g/ρ_l) of the gas and the water and the velocity ratio k directly affect the magnitude of ϵ and by the magnitude of these values the critical Mach number of the gas is decided.

Next, let's investigate roughly the magnitude of these factors which affects ϵ in this experiment. The velocity ratio k is in the range of 3~5 as shown in Fig. 17 and the density ratio ρ_g/ρ_l is at most 2×10^{-3} within the pressure range of this experiment. Then, with the quality x from 1 to 0.3,

$$\epsilon = 10^{-2}$$

Accordingly, within the experimental range of this dispersed two-phase flow, the characteristic parameter is sufficiently small compared to unity and then, Eqn. (3-10) of the critical condition which indicates the flow rate at the critical point is expressed as,

$$Mg \doteq 1$$

The critical velocity of the gas at the critical point becomes equal to the sonic velocity of the gas at the flow state of the gas. On the other hand, judging from Fig. 15 in which the exit velocities U_{ge} and U_{le} of the gas and the liquid are shown, the gas velocities are nearly equal to the sonic velocities indicated at the right shoulder of the same figure when the exit pressure P_e is higher enough than the back pressure P_b and furthermore, the critical gas velocity is substantially represented by the relation $Mg=1$, even if the experimental errors exist in the experimental measurements. In other words, the theoretical critical state is in good agreement with the experimental state with regard to the gas velocity. It is, however, noticed here that the critical flow does't always occur under the same condition of the critical gas velocity being the sonic velocity in such a dispersed two-phase flow but that the relation of $Mg=1$ occurs as the density ratio ρ_g/ρ_l of the gas and the liquid becomes larger. At the same time, since the velocity ratio becomes in general large when the system pressure is very high and the duct is short, it can be fully considered that the magnitude of ϵ becomes large and then, that Mg becomes larger than unity at the critical point when quality x is small. In this sense, the magnitude of ϵ is very important and the critical state in case of the dispersed two-phase flow could be estimated to a certain extent from the magnitude of ϵ if it can be guessed in advance.

Fig. 18 Comparison of the experimental relation between the total flow-rate and the exit pressure with the theoretical one.

4. Conclusions

In this study, an experiment of a dispersed two-phase flow which is one of the typical flow patterns in various two-phase flows and at the same time has a

definite flow condition, is carried out and both the comparison and discussion of the theoretical state of the critical flow with the experimental results are done.

The following results are obtained as the result of the experiment in which the volume of the water droplets is small compared to that of the gas and in which a comparatively long duct is used.

(I) First according to the result of the experiments,

(1) when the total flow rate W is increased under the condition of constant quality, the gas velocity becomes almost constant at the critical state and is nearly equal to the sonic velocity. The constant gas velocity at the critical state is different depending on the magnitude of the quality x .

(2) The critical water droplets velocities also become constant depending on the magnitude of the quality. The nearer the quality is to unity, the larger the constant velocity becomes at the critical states.

(3) When the flow state moves from the subcritical region to the critical region, a transition region appears in the domain that the quality x is small. This transition region is caused by the two-dimensionality of the flow.

(II) According to the results of the theoretical analyses,

(1) with regard to the critical velocity of the gas, it is shown to become nearly equal to the sonic velocity and these theoretical results are coincident with the experimental results.

(2) With regard to the critical velocity of the water droplets, it can be shown that the semi-theoretical relation between the critical flow rate and the exit pressure obtained by using the experimental ratio k of the liquid and the gas is in good coincidence with the experimental relations.

(III) To sum up, the coincidence between the experimental results of the critical state and the theoretical ones is very good and accordingly it can be considered that the aim of this study is fully attained.

Acknowledgements

The author would like to express his sincere thanks to Professor Yoshiro Katto of the University of Tokyo for his discussions and most valuable suggestions. Thanks are also due to Mr. T. Sato, and Mr. T. Nagasaka for their valuable assistances in the experiment.

References

- (1) Hijikata, K. et al., Trans. of Japan Soc. Mech. Engrs. (in Japanese) Vol.37, No.295 (1971),
- (2) Mori, Y. et al., Trans. of Japan Soc. Mech. Engrs. (in Japanese) Vol.37, No.295 (1971),
- (3) Katto, Y. and Sudo, Y., Bulletin of the JSME, Vol.16, No.101 (1973) p.1741.
- (4) Sudo, Y. and Katto, Y., Theoretical and Applied Mechanics, Vol.22 (1972), p.67.
- (5) Katto, Y., Bulletin of the JSME, Vol. 11, No.48 (1968), p.1135.
- (6) Katto, Y., Bulletin of the JSME, Vol. 12, No.54 (1969), p.1417.
- (7) Katto, Y., Jour. Japan Soc. Mech. Engrs. (in Japanese), Vol.72, No.602 (1969) p.355.
- (8) Sudo, Y. and Katto, Y., Trans. of Japan Soc. Mech. Engrs. (in Japanese), Vol.41, No.342 (1975), p.18.
- (9) Sudo, Y. and Katto, Y., Trans. of Japan Soc. Mech. Engrs. (in Japanese), Vol.41, No.342 (1975), p.30.