THE ENERGY BALANCE OF THE ELECTRO-HYDRAULIC LINEAR ACTUATION SYSTEM

Mika HERRANEN, Kalevi HUHTALA and Matti VILENIUS

Dept. of Intelligent Hydraulics and Automation, Tampere University of Technology, P.O.Box 589, 33101
 Tampere, Finland

ABSTRACT The variable gas exchange valve actuation systems have been developed in order to improve the efficiency of the combustion process. The electro-hydraulic valve actuation (EHVA) systems have good power to weight ratio, high maximum force and good controllability. The disadvantages are limited frequency bandwidth and energy recovery. Each component of the EHVA system has certain energy consumption, which is characteristic to the component. In this study the power consumptions of the components are investigated by means of the simulation. The investigated components are a hydraulic pump, a hydraulic accumulator, a control valve, and hydraulic lines connecting the components.

The pressure losses caused by the oil flow are most significant in the control valves, 50-60% of the total energy consumption. If the stored kinetic energy of the actuator and moving oil masses could be reused, the energy consumption could be up to 25% better.

Keywords: Energy, consumption, electro-hydraulic, variable valve train.

1. INTRODUCTION

The EHVA systems have fully flexible opening time and lift events. Thus the fuel efficiency of the combustion process can be controlled better under the varying load conditions. The EHVA system can be a useful device to reduce the emissions too. However, the total energy consumption shouldn't be much higher than the conventional cam driven valve actuation system. In the Figure 1 the example of the friction distribution of the conventional engine is shown. In the EHVA system has no cam/follower contact or the camshaft journals, which reduces the friction significantly [1].

Figure 1 Valve train friction loss percentage [1]

Until now, the most of EHVA studies have concentrated to the properties or function of the actuation system. Accurate comparison of the energy balance or the energy consumption has been rarely published. The investigated EHVA system can be built without the return spring of the gas exchange valve, which could change the energy balance as well. However, the hydraulic control valve consumes the electric energy and this will add the

EHVA total energy consumption. Also the pressure drop caused by the flow of the hydraulic fluid decreases the efficiency. The energy taken by the hydraulic pump is dependent on the flow rate and pressure. If the pressure or the flow rate could be taken down while no movements are needed, energy saving would be considerable [2].

In the EHVA system the potential energy stored in the pressurized fluid is converted to the kinetic energy of the gas exchange valve system. The problem in the EHVA system is how the kinetic energy could be recovered to the pressure energy.

2. EHVA SYSTEM

Preliminary energy consumption calculation of the different hydraulic systems has been made in earlier study [3]. In this paper, the previously chosen best hydraulic circuit with return spring is taken under investigation. Comparable hydraulic system without the spring had worse energy consumption, but it could have some other benefits, and is therefore chosen.

2.1 Hydraulic circuits

In the Figure 2 and Figure 3 the simplified schematic pictures of the studied hydraulic systems are shown. In Figure 2 the constant hydraulic pressure is affecting to the circular area in the bottom of the actuator. When the pressurized fluid is directed to the above of the actuator, the actuator opens the gas exchange valve and compresses the return spring. The circular area also pushes the pressurized fluid to the accumulator. When the upper chamber is connected to the tank, the spring and the pressurized circular area closes the gas exchange valve. The circular area helps to move only the actuator faster; it cannot draw the gas exchange valve to close direction.

Figure 2 Hydraulic circuit of the return spring system

In another hydraulic circuit (Figure 3) the pressure of the circular area is controlled also, and no return spring is applied. The opening and closing of the gas exchange valve is done only by means of hydraulic pressure forces. The closing sequence is performed by actuator only via the fixed coupling between the actuator and gas exchange valves.

Figure 3 Hydraulic circuit of the system without return spring

2.2 Hydraulic components

Each hydraulic component has a certain efficiency which may be originated from mechanical and flow friction, compressibility of the medium, and leakages. Some components need the electric power in order to operate. All these energy sinks degrades the total efficiency of the EHVA system.

The power consumptions of the hydraulic control valve and the hydraulic line between the valve and the actuator are investigated.

The hydraulic pump is sized by the average flow demand, but it must be oversized slightly in order to compensate the leakages and to maintain the pressure. The additional flow is directed through the pressure relief valve to the tank, and is producing pure waste energy. The amount of extra flow is depended on the type of the pump and the hydraulic circuit. The variable displacement pump can adjust the changes in average flow rate. The comparison between two pump types is done.

The momentary flow demand of the system is much higher than average flow. It's not reasonable to size the fixed hydraulic pump according to max. flow, and the change is faster than variable pump can follow, so the extra flow peak is utilized either the hydraulic/gas accumulator or the compressed fluid volume.

3. SIMULATIONS

The simulations are made by the AMESim (LMS International) program which is complete 1D simulation suite to model and analyze multi-domain, intelligent systems, and predict their multi-disciplinary performance [4]. The flow and pressure are investigated before and after every component. Due the differences between the hydraulic systems, the control parameters had to be tuned in order to achieve closely identical displacement curves. The stroke event is shown in Figure 4. The effect of the cylinder pressure is modeled too.

Figure 4 Stroke event of the actuator

The hydraulic energy taken during the stroke is calculated by integrating the multiply of the hydraulic pressure and flow rate to the actuator chamber. This is the amount of energy which is eventually needed to produce the stroke of the electro-hydraulic gas exchange valve system. The energy is calculated separately in open (Eq. (1)) and close direction. After that the energy loss/consumption over any component is compared to the total hydraulic energy produced by the pump Eq. (2), and the relational energy consumption is calculated.

$$E_{hyd\ open} = \int_0^{t_{stroke}} p_+ \times Q_+ dt \quad (1)$$

$$E_{hyd\ total} = \int_0^{t_{stroke}} p_{pump} \times Q_{pump} dt \quad (2)$$

3.1 Hydraulic circuit comparison

In the system with the return spring, the energy stored in the spring produces the return stroke, and therefore any extra closing energy is futile. However the actuator has to push out the hydraulic fluid from above of the actuator and this needs some energy. The returning flow adds the energy need in all cases. The energy of the opening and closing events include the energy needed to overtake energy losses in returning hydraulic lines and components.

Without the return spring, the actuator has to draw whole gas exchange valve system to the upper position, and therefore the energy consumption is much higher.

The needed energy levels are presented in Table 1. The difference in overall energy rate is explained by higher flow rate of the non-return spring system.

Table 1 Energy rates of the systems

Energy	Return spring	No Spring
Opening (hydraulic)	179 J	132 J
Closing (hydraulic)	28 J	116 J
Pressure relief valve	2 J	12 J
Energy from the pump	309 J	410 J
System Efficiency	67 %	60 %

3.2 Hydraulic components

Control valve. The hydraulic control valve has significant effect to the system efficiency. In Table 2 there is shown the relatively energy losses over the control valve, compared to the energy produced by the pump during the event.

Table 2 Energy loss in the control valve

	Return spring	No spring
P-->A	35 %	21 %
A-->T	23 %	27 %
B-->T	-	8 %
P-->B	-	10 %
Total	58 %	66 %

Hydraulic lines. The length of the hydraulic lines between the components can produce some energy losses. The length of the line has straight effect to the acceleration pressure force needed in the beginning of the stroke. The l/d ratio has effect to the viscous friction of the fluid flow. In the simulations, the basic pipeline length between the control valve and the actuator is 0,2 m and diameter 10 mm. Then the length of the line is altered. In Figure 5 the energy consumption during the stroke in that specific hydraulic line is presented.

Figure 5 Energy consumption in hydraulic line (control valve ↔ actuator)

The energy consumption is increased linear when the l/d -ratio increases. As a percentage the single line energy consumption is under 1% from the total energy consumed. The energy consumption is higher in lines between the control valve and pump/tank, because higher l/d ratio (length of the pipe 2m, diameter 19mm). Total energy

consumption of the pipe lines can be assumed to be around 7-8% in both investigated hydraulic circuits. The flow rate without the return spring is losing less energy in single line, but total energy consumption is nearly the same because the flow goes in parallel to two lines during the stroke. The non-return spring system has higher total flow rate from the pump, and energy consumption between the pump and the control valve is higher. The return spring system has, however, high flow rate peak to the tank line while the non-return spring system the flow is more evenly distribute during the stroke. This also balances the difference between the systems.

Hydraulic pump. The hydraulic pump should produce only required amount of pressurized fluid. The fixed displacement pump takes all the time nearly fixed amount of energy, when running. If the gas exchange valve lift is decreased, the rise of the waste energy directly corresponds the decreased actuator lift (Table 3). The relatively efficiency decreases, but so does the difference between the systems. This is partially due to control valve losses, which are now 28% (return spring) and 31% (non-return spring cases) from the total energy losses. With the variable displacement pump, the EHVA system efficiencies would be 68% (return spring) and 66% (non-return spring) though the actuator lift would be reduced. The controller of the variable displacement pump takes some energy when the displacement is altered. This, however, is not taken into account in this study. Also must keep in mind that the efficiency of the pump will decrease, when partial displacement is used. The reduction of the pump efficiency will be ca. 6 percentage points if the displacement is halved.

Table 3 Energy rates of the systems, 50% actuator lift, fixed pump

Energy	Return spring	No Spring
Opening (hydraulic)	98 J	76 J
Closing (hydraulic)	15 J	59 J
Pressure relief valve	160 J	218 J
Energy from the pump	320 J	414 J
System Efficiency	35 %	33 %

Intentional pressure drop (hiccough). Previous results are simulated ensuring that pressure before the control valve remains near maximum. This is done by modeling large accumulator and volume in the pressure line. This means that pressure in the pressure line of the pump is staying near the maximum. In Figure 6 and Figure 7 the simulated pressures are shown (non-return spring case).

Figure 6 Pressure in the pressure line of the control valve, during the stroke

Figure 7 Pressure in the pressure line of the pump, during the stroke

Next, only the relatively small hydraulic accumulator is placed before the control valve. After that pressure amplitude increases. The pressure must be kept in range that ensures that the movement of the actuator is unchanged. This could need the change of the controller parameters too. After the accumulator resizing the pressure in the pump pressure line is shown in Figure 8. The lower pressure demand causes that energy consumption from the pump decreases from 410 to 318 J (22% lower). Nearly similar decreasing (17%) is detected in return spring case. This is, however achieved only if constant pressure pump is used. The variable displacement pump can typically adjust the flow/pressure demand within the 40-150 ms [5] and thus “ruin” the purposed pressure drop. The gas exchange valve can be lagging easily if environmental parameters are changed. The usage of rail (compressed volume) instead of accumulator should be slightly better; because of no back and forth flow is needed. However the used simulation model did not find significant difference between them.

Figure 8 Lowered pressure in the pressure line of the pump, during the stroke

Also, the previous simulations aren't notifying the interference of the parallel cylinder or the actuators. The pressure in the pump pressure line can be significantly different in real, multi-cylinder case. The pressure needed in the actuator chamber during the stroke is presented in Figure 9. However, this can be only achieved if actuator based pressure or flow control is applied [2].

Figure 9 Pressure in actuator upper chamber (return spring)

3.3 Energy recovery

The nominal required energy is defined by multiplying the force affecting to the actuator and the velocity of the actuator. Multiplying is done only at the moment when the acceleration is positive to the moving direction. Then the momentary product is integrated as shown in Eq.(3). This is the amount of energy needed to make the open stroke. On the contrary, the deceleration part of the stroke can be assumed to be the energy which could be recovered. In this way the estimation of the recovered energy is better brought out. Because the frictions, the actuator will need some energy during the constant movement (and during the minor deceleration), but this matter is ignored in this study. The recovery partition includes the energy needed to transfer fluid in return line also. The energy needed to compress the return springs during the deceleration is subtracted from the opening recovery part. The maximum recovered energies during the stroke are presented in Table 4.

$$E_{nom\ open} = \int_0^{t_{open}} F_{act} \times v_{act} dt, \quad (3)$$

where $F_{act} = F_{act}$ if $a_{act} \geq 0$
 $F_{act} = 0$ if $a_{act} < 0$

Table 4 Energy in acceleration and deceleration phase of the actuator

Energy	Return spring	No spring
Opening	118 J	85 J
Closing	36 J	49 J
Recovery in opening	9 J	45 J
Recovery in closing	47 J	71 J

For comparison, if the gas exchange valve system would be displaced without any mechanical or viscous friction, the need of the energy would be around 60 J in opening direction (the return springs applied). In closing direction the springs can give all the energy needed. The energy stored in the two return spring is ca. 17 J. If the system is without return spring (mass only), the needed open/close energy is only 5/9 J.

3.4 Energy distribution

Energy distributions in both cases are presented in Figure 10. The efficiency of the hydraulic pump is now also included. The calculated actuator energy is the energy what is left after the wasted energy sources. Thus the recovered energy calculated could be even higher than residual actuator energy, because recovered energy includes part of the wasted energies.

Figure 10 Energy balance of the EHVA systems

4. CONCLUSIONS

The simulations showed that the largest energy loss (50-60%) is caused by the hydraulic control valve. This is predicted because the all deceleration energy is applied by pressure difference over the valve. Control valve with the better flow/pressure drop ratio would improve the situation.

The hydraulic circuit has strong effect to the total amount of energy which EHVA system consumes. The usage of the constant return pressure and/or the return spring is lowering the hydraulic flow rate, and thus lowering the pressure/energy losses up to 25%. The system efficiency of the non-return spring system is also lower due the multiple pressure losses over the hydraulic control valve.

If the system flow demand is varying due the rpm of the valve lift, variable displacement pump should be used. In that case the efficiency of the system will alter only amount of changes of the hydraulic pump efficiency.

If the pressure could be adjusted to the demand of the actuator, significant energy saving up to 35% could be achieved. The variation of the pressure/flow demand is altering fast, and it could be hard to apply a simple and functional hydraulic system. The displacement control of the closed hydraulic circuit would have better efficiency than the throttle control of the open hydraulic circuit.

There is up to 25% of energy which could be recovered, but this would need complex hydraulic systems and perhaps smart controlling system.

5. FUTURE WORK

Different hydraulic circuit with different control valves, are taken under investigation. The valve performance is essential to the moderate or good energy consumption.

The actuator is slightly oversized and could apply more force than the system requires. Thus the pressurized area could be decreased. The simulation model should be verified with the measurements.

6. NOMENCLATURE

A	Actuator port of the hydraulic control valve
a_{act}	Acceleration of the actuator
B	Actuator port of the hydraulic control valve
$E_{hyd\ open}$	Hydraulic energy needed to open the gas exchange valve
$E_{hyd\ total}$	Hydraulic energy during the stroke produced by the pump
$E_{nom\ open}$	Energy needed to accelerate the actuator
F_{act}	Force affecting to the actuator
P	Pressure port of the hydraulic control valve
p_{pump}	Pressure in pump pressure line
p_+	Pressure in the upper cavity of the actuator
Q_+	Hydraulic flow in or out the upper cavity of the actuator
T	Tank port of the hydraulic control valve
t_{open}	Time of the open event
t_{stroke}	Time of the stroke event
v_{act}	Speed of the actuator

7. REFERENCES

1. Wang, Y., Introduction to Engine Valvetrains, (2007), SAE International, Warrendale.
2. Lunkes, Jr, J.H., van Doorn, IV, W., Donaldson, J., The Design and Simulation of a High Force Low Power Actuation System for Camless Engine, Proc. of Int. Mech. Eng. Congress and Exp. (IMECE2005), (2005), IMECE2005-81808, Orlando, Florida.
3. Herranen, M., Huhtala, K., Vilenius, M., The Electro-Hydraulic Valve Actuation (EHVA) for Medium Speed Diesel Engines – Development Steps with Simulations and Measurements, SAE 2007 World Congress, (2007), Detroit, Michigan.
4. <http://www.lmsintl.com/>
5. Findeisen, D., Findeisen, F., Ölhydraulik, Handbuch für die hydrostatische Leistungsübertragung in der Fluidtechnik, (1994), Springer-Verlag, Berlin Heidelberg New York.