E-mail: idei@lasti.u-hyogo.ac.jp

The LIGA (Lithografie, Galvanoformung, Abformung [German: lithography, electroplating, and molding]) process is one of the promising techniques for fabrication of microstructures having high aspect ratios. Microstructures as high as a few hundred μm or more are widely used for various devices, such as micro-actuators, micro-mechanisms, and micro-sensors. The key to reducing the microstructure fabrication cost of the LIGA process is by using micro replication technology. Hot embossing is attracting the attention of engineers as one such technology for economically mass-fabricating microstructures on thin plastic sheets. This technology is especially effective for precisely replicating micro patterns on relatively large sheets. This paper describes the results of research the authors recently carried out to find the optimal conditions for hot embossing in the atmosphere and in a vacuum. For a series of experiments, we prepared two types of Ni molds each containing an area of $33 \times 33 \text{ mm}^2$ distributed with hole or column patterns $60 \mu\text{m}$ in diameter and 1.0 in aspect ratio. The LIGA process using synchrotron radiation fabricated these patterns. From the experiments, we could determine the optimal conditions for replicating these patterns on PMMA sheets in a normal-atmosphere and vacuum environments.

P7: Analytical Prediction of Fatigue Life on Aluminum Alloy Die Castings for High Performance Parts

N. SUZUKI, K. KANAWAZA, Y. ISHII, Chiba Institute of Technology;
H. HIROYAMA, S. ECHIGO, Cast Research Co., Ltd.; K. KONAGAYA,
S. AOYAMA, Ahresty Corporation,
E-mail: kanaz@pf.it-chiba.ac.jp

In aluminum alloy die castings under cyclic load, a fatigue crack initiates at casting defect and propagates based on $\Delta K\text{-da/dN}$ relation. The prediction method of fatigue life of aluminum alloy die castings under complex cyclic load has been proposed theoretically and verified experimentally. The paper shows that the prediction method is effective to several shapes of aluminum alloy die castings and it can be applied to the automobile parts under cyclic high load by using the miniature model of actual automobile parts.

P8: Statistical Analysis of Optimum Friction Welding Condition of 5056 Aluminum Alloy Friction Welded Joint

R. TSUJINO, Osaka Institute of Technology; G. KAWAI, Osaka Sangyo University; H. OCHI, Osaka Institute of Technology; H. YAMAGUCHI,
K. OGAWA, Osaka Prefecture University; Y. YAMAMOTO, Setsunan University,
E-mail: tsujino@jc.oit.ac.jp

The optimum friction welding condition of 5056 Aluminum alloy was investigated. Tested conditions were selected from them showing different unit deformation heat input in the upset stage that can be the index of the soundness of the joint. Statistical analysis of many joints was conducted for judging the appropriateness of the friction welding condition. The results are as follows. (1) The optimum friction welding condition is the one with larger upset pressure after keeping a certain friction heat. (2) The shape parameter of Weibull distribution is the index for judging the appropriateness of the friction welding condition. (3) Clear relationship between the shape parameter and unit deformation heat input in the upset stage can be found. The value of the shape parameter of Weibull distribution for obtaining sound joint steadily is about 80.

P9: Investigation of High Strength Electroformed Ni for Microprobes

T. KIMURA, N. ARITA, H. FUKINBARA, Japan Electronic Materials CORP; T. HATTORI, University of Hyogo,
E-mail: kimura@jem-net.co.jp

According to higher function and higher density of rules of LSI, a num-

ber of pads becomes larger, and pad pitch of dies becomes finer. We have developed microprobe and have achieved low contact resistance under low contact force only for gold pads. However, an oxide layer formed on aluminum pad surface obstructs stable contacting, higher contact force with strong probe is required. The mechanical properties are tried to improve strength. It is said that downsizing of grain, functionally alloying and impurity addition can improve the material strength. In the electroforming, the additives to the bath are tried here because of its controllability of the process. It is said that the additives have characteristics to control the depositional phenomenon such as crystalline orientation. Alkylsulfonic acid sodium salt as the additive is tried. Next, the electroformed nickel is investigated about its mechanical properties. Main estimation factors are Vickers hardness and Young's modulus because of the material strength can be easily estimated by their values. Improved nickel has a much higher Vickers hardness of Hv600, than the one of Hv450 of the former nickel. And more, it is clarified that Young's modulus of $E=200\text{GPa}$ is much larger than the one of $E=150\text{GPa}$ of the former nickel. Thus, high strength of the electroformed probe can be successfully obtained. It was confirmed by the calculation that the contact force is raised about 1.33times as high as the former probe. So, stable contact with low electrical resistance should be achieved in touching on aluminum-copper pad.

P10: Development of Desk Size Superplastic Forming Machine and Several Trials

M. KIMURA, Tokyo National College of Technology,
E-mail: kimura@tokyo-ct.ac.jp

The superplastic forging machine of desktop size was developed, and superplastic processing of a superplastic aluminum alloy of 5083 and superplastic zinc alloy, embossing forming, coining forming and thermo plastic injection to superplastic formed products were performed. Rather than the simulation by the finite element method, the physical simulation by solder material is easy, is a short time, and has been realized at low cost. Metal die can be heated in 20 minutes to 520 degrees C of Al alloy superplastic temperature, and at least 850 degrees C of titanium alloy superplastic temperature can be heated in 1 hour by means of cartridge heaters were inserted metal die. The embossing product by using the same material for the superplastic aluminum alloy 5083 with a thickness of 0.5mm which has 3 times as much as height plate thickness with sharp corner was able to be obtained by carrying out 3min-20min holding of the 100kN load at 460 degrees C - 500 degrees C by using the same material as a backup material. The electronic-parts case and autparts of lightweight and complicated form were able to be obtained by embossing forming of a super-elasticity aluminum alloy. Although embossing forming at the room temperature of pure aluminum was performed for comparison, the corner of a plate thickness distribution or a cast was excellent in the direction of the super-elasticity aluminum alloy 5083. The electronic-parts case and auto parts of lightweight and complicated form were able to be obtained by embossing forming of a superplastic aluminum alloy. Although embossing forming at the room temperature of pure aluminum was performed for comparison, the corner of sharpness and thickness distribution or a forming was excellent in the direction of the superplastic aluminum alloy 5083.

P11: Superplastic Properties Evaluated at Each Small Gauge Part in a Tensile Specimen

A. KURUMADA, Y. MOTOHASHI, G. ITOH, Ibaraki University,
E-mail: kurumada@mech.ibaraki.ac.jp

Superplasticity is an interesting high temperature phenomenon that can occur in almost all of crystalline materials. Many studies relating to the microstructures and the occurrence of superplasticity in the materials have been performed. In particular, a number of studies concerning the low temperature or the high strain-rate superplasticity have been carried out from the viewpoint of practical applications. The local deformation such as a necking is easy to occur under the condition of the low temperature and the high strain-rate. Therefore it is important to analysis the superplastic behavior including the necking under these conditions.