Enhancing Localization Using Random Ferns Based Vision and Multi-Robot Collaboration

Youssef Ktiri, Tomoaki YOSHIKAI, and Masayuki INABA

Youssef Ktiri, The University of Tokyo, youssef@jsk.t.u-tokyo.ac.jp
Tomoaki YOSHIKAI, Masayuki INABA, The University of Tokyo

Humanoid robots sensory signals typically suffer from noise. In the typical case of indoor environment, small obstacles like carpets, books, or wires can make the odometry error degenerate which eventually results in severe inaccuracies during the localization process. In this paper, we describe a landmark based multi-robot localization architecture which handles robustly the self-localization problem of a team of small humanoid robots. The landmark detection under partial occlusion and affine transformations takes advantage of the real-time capabilities of a random ferns based vision system. The observations of a single robot and those of cooperating partners are merged through a particle filter-based method. In our approach, the absolute localization of every single robot is achieved in a robot-centric way. The relative localization is kept by a remote machine. Since all the team data is interfaced via the remote machine, every robot can act independently from the rest of the robot network.

Key Words: Multi-robot localization, Particle filter, Random Ferns

1 Introduction

Achieving accurate localization is a base prerequisite for a robot to achieve other various tasks such as mapping, manipulation or object tracking. For such a reason, the problem of self-localization of a single mobile robot has been extensively studied. The more sophisticated case of cooperative multi-robot localization has been gaining interest since collaboration between a team of robot is often a highly desirable behaviour that can exhibit same or better capabilities than a single complex robot unit, specially under the scope of collaborative exploration.

Two base prerequisites are essential to achieve collaborative localization. First of all, the cooperating robots must be able to sense each others with relatively good accuracy. Then, these observations must be communicated to the robots of concern. In such a configuration, every robot can refine its internal belief based on the observation of a team partner. Such an observation reduces drastically the uncertainty of the estimated location, specially in the scenario where observable landmarks are sparse and occasionally occluded by human activity, and where ground topology is maculated with small reliefs that make the uncertainty on odometry data rapidly degenerate.

Many approaches have been successfully introduced for the cooperative localization problem [1][2][3][4][5]. Many relied on a EKF to integrate relative observations. A mostly comprehensive approach can be found in [1]. In [2] the cooperative localization is derived using a particle filter-based algorithm by means of relative observations.

We also base our approach on particle filters. Large noise is added to our motion model to account for large deviations that can occur due to small randomly placed obstacles. A further step during the fusion process is added and which computes a trust coefficient since all relative robots observations may not be good to merge. This is specially the case when a "lost" robot observes a well localized partner.

We derive in section 2 the theoretical formalism to describe the multi-robot problem. We give in section 3 a

full description of the random ferns based algorithm that lies at the base of our vision system. Section 4 gives the overall declinat of our architecture. Finally we validate our approach by an experiment in section 5.

2 Multi-Robot Localization

We give in this section the mathematical formalism at the base of our multi-robot localization system. In the cooperative localization problem a single robot has access to three types of data :

- *The odometric data given by the motion sensors from now on denoted u_k at time k .
- *The environment observations given by the vision system denoted o_k at time k .
- *The observations by other robots denoted r_k at time k .

Without the later the robot acts merely as a single robot. We are interested in estimation the three dimensional position of the robot i denoted x_k^i at time k . In an attempt to cope with non-linear and multi-modal cases, the particle filter [6] is a popular approach to approximate the probability distribution through discrete samples. Such particles can in fact model complex distributions. One simple illustration is the observation of a landmark with two possible locations on the map without any prior knowledge of the actual position. Such distribution has two modes centred closely to the two possible landmark positions. The history of the state is denoted $X^k = \{x_0, x_1, \dots, x_k\}$, the history of the motion data $U^k = \{u_0, u_1, \dots, u_k\}$, the vector of landmark observations $O^k = \{o_0, o_1, \dots, o_k\}$ and finally the vector of robot detections by other robots $R^k = \{r_0^1, r_0^2, \dots, r_1^2, \dots, r_k^n\}$. Let us write down the update equations of our system.

For an odometry update, under the Markov property the total probability theorem gives :

$$P(x_k | O^{k-1}, U^k, x_0) =$$

$$\int P(x_k | x_{k-1}, u_k) P(x_{k-1} | O^{k-1}, U^{k-1}, x_0) dx_{k-1}$$

In case of an environment observation bayes rule gives :

$$P(x_k | O^k, U^k, x_0) = C P(o_k | x_k) P(x_k | O^{k-1}, U^k, x_0)$$

where C is a normalizing constant. This last equation applied to each particle gives the update rule for each weight. At this stage a resampling phase is performed where elements of the particle set are drawn according to their weight, hence the most likely particles in the sense of the up-to-date observation made are the more likely to be kept while the low weighted particle are generally dropped. On the top of that, we use an augmented particle procedure to adaptatively add new random poses as a mean of coping efficiently with localization failures [7]. Finally, let us consider the case of a robot being observed by other robot partners. As it has been said, our approach is essentially robot-centric. Each robot uses the detection made by a partner as a mere observation to refine its own localization. With no detection made, a robot obeys to the single robot model rules. The impact of such refinement is measured by a coefficient of trust computed by each robot and which depreciates when the self-localization loses compactness and hence becomes too noisy. In this sense every robot is made highly independant of the rest of the network. Let denote Z a general vector that can contain motion, landmark and robot observation data of the robots. Under such scenario, reasoning on all the robots, the following approximation is made :

$$P(x_k^1, x_k^2, \dots, x_k^n | Z^k) = P(x_k^1 | Z^k) P(x_k^2 | Z^k) \dots P(x_k^n | Z^k)$$

The robot centric-approach translates into an independence hypothesis in computing the belief of all robots locations. Let us take the case of two robots. One partner called robot j is observing a robot of concern robot i. Thus, the following holds :

$$\begin{aligned} P(x_k^i | Z^k) &= P(x_i | Z_i^k) P(x_i | Z_j^k) \\ &= P(x_i | Z_i^k) \int P(x_i | x_j, R_j^k) P(x_j | Z_j^k) dx_j \end{aligned}$$

The computation of such update is not straightforward in the case of particle filters since it requires the multiplication of two densities, represented in our case by different sets of randomly drawn samples. One solution to this problem can be found in [3] where a continuous density is recovered using density trees. In our approach an estimate of the pose of robot j is precomputed using appropriate clustering technique, a gaussian model error is applied with the variance depending on the trust coefficient. The last equation can effectively be computed by mere multiplication by the weighting of the observed robot. Such an hypothesis however requires that only the good estimates on the initial positions should be merged so not to depreciate the overall localization of robot i. This translates in our method into a larger variances in the observation model with the depreciation of trust. This approach generalizes easily in the case of more robots.

3 Random Ferns Landmark Detection Vision System

Our landmark detection system is based on a randomized fern algorithm presented in [8]. We try in this section

Fig. 1: RF Algorithm Performing under Affine Variations

to give a comprehensive description of the algorithm which we denote from now on RF. The RF algorithm originally aims at fast keypoint recognition under scale and six axis affine variations. A semi-baysian approach lies at its heart and essentially aims at making computation much faster. The keypoint correspondance is assessed on the basis of randomly chosen binary tests. For such reasons it is by extension robust against partial occlusion and illumination changes (due to randomness for the later). The RF algorithm lies at the center of our cognition system since it behaves remarkably well in real-time environment with comparable performances with "heavier" keypoint detection paradigms like SIFT descriptors. Further memory and speed/performances trade-offs can be made by adjusting the model parameters. During a training phase, patches surrounding the most significant keypoints of a training image are exposed to affine deformations. Let us call class the set of all deformations of a given keypoint. Given a class c_i a set of N randomly chosen binary tests f_i are computed over a class to try to find the most likely corresponding class. Formally this can be written :

$$\text{Find } c_i \text{ that verifies } \argmax P(C = c_i | f_1, \dots, f_n)$$

which reduces by bayes rules to $\argmax P(f_1, \dots, f_n | C = c_i)$ A complete naive baysian approach is to assume independence between all these features, estimating the probability distribution relies on 2^N parameters. The semi-naive baysian hypothesis aims at modeling some of the dependencies occuring between groups of features called ferns noted F_i . Under such hypothesis we can rewrite as follows :

$$P(f_1, \dots, f_n | C = c_i) = P(F_1 | C = c_i) \dots P(F_M | C = c_i)$$

Each ferns is now storing $2^{N/M}$ parameters. During runtime, after each observation, the correspondance between two keypoints is stated by a mere lookup at each fern and performing a multiplication to compute the whole probability. The step of computing the estimators from the

Fig. 2: General Architecture

training set is moved to the training phase. The final homography transform between the input and output images is computed from the matched keypoints using RANSAC. Fig. 1 shows an example of the RF algorithm performing on landmarks under various deformations.

4 General Architecture

Decentralized approaches has been successfully applied to the multi-robot problem. In contrast to this approach, we have been using a centralized approach. The central server acts as interface to all the rest of the robots, providing only the necessary and precomputed observations. Moreover, the central machine dedicates to keeping tracks of all the robots, which is found in the general case a prerequisite to more evaluate behaviors such as time efficient robot and robot avoidance or emergence of collaborative tasks achievement. These points lay out of the scope of this paper. Finally, this approach has quickly proven necessary since we have been highly constrained by the processing capabilities of the NAO robots [9] we have been using for our experiments and since keeping track of the rest of robots by very single robot can quickly become an onerous task with the number of robots growing. Even though, by means of interfacing, the robots acquire a higher degree of autonomy, a necessary drawback of such approach is that conversely, the robots are made highly dependant of the central server to fuse data. The fig. 2 shows our general architecture.

As shown in the figure every NAO Robot runs four modules implemented in our case as threads : cognition, motion, localization and communication. The cognition module runs the RF and robot detection algorithm. At the stage of this paper, the robot detection algorithm works on a color detection basis. More intelligent algorithm is to be implemented. The motion module gives controls inputs to robot actuators on the basis of ocalization data. The localization module runs a robot-centric localization particle filter. Finally the communication module is an open TCP/IP socket with the central server. The center on the other hand runs as a concurrent multithreaded server that gathers robots observations clusters, and sends back only the necessary data to fuse. It also recieves the up-to-date estimates from each robot.

5 Experimentation

An experiment involving three NAO robots has been conducted on a $8m^2$ ground littered with wires and small steps of $3mm$ high by means of creating severe disturbance into the odometry data. 3 landmarks have been disposed sparsely in the field. All the robots were given the map such that the landmarks position is known with enough precision. Fig. 3 shows our scenario. Robot 1 searches for landmark 2, robot 2 were taking random directions. The robots were given an initial position. Doing so we don't really lose generality. Otherwise, if no initial positions were to be given the robot distribution would have been

initialised uniformly on the field, after further stepping in random directions the robots would have eventually made relevant observations to refine their positions.

The noise added on the robot was large in order to absorb the effect of the small obstacles. Since no landmark was placed in the deviated trajectory its self-localization would have eventually failed without the observation made by robot 2 just as robot 3. On the top of that, the later observation by robot 3 has grossly no effect since the robot 3 holds a low trust coefficient. The robot 1 could reach the landmark 2 and hence its position has been further refined by the landmark observation.

6 Conclusion and Future Work

We have presented in this paper a full implementation of the multi-robot localization problem. In such approach recovery from severe disturbance could be achieved when the knowledge of each robot was augmented by that of other partners even in the case where no landmarks could be detected. Our central fusion approach however limitates the displacement of our robots. It is thus our concern to trade the current solution with a decentralized method and run tests in broader environment. Furthermore, simultaneous mapping lays in the natural continuity of our work. We shall pour our future work in handling scenarios where no prior knowledge about the map is given. Finally, our landmark vision system though very competitive in landmark detection under changing and partial views loses its real-time capabilities when the number of landmark to detect becomes significant, which proves it necessary to figure out a broader solution.

This work is supported by NEDO (New Energy and Industrial Technology Development Organization, Japan) project 'Intelligent RT Software Project'.

References

- [1] Andrew Howard, Maja J Mataric, and Gaurav S. Sukhatme. Putting the i in team: an ego-centric approach to cooperative localization. *International Conference on Robotics and Automation*, 2003.
- [2] Agostino Martinelli, Frederic Pont, and Roland Siegwart. Multi-robot localization using relative observations. *International Conference on Robotics and Automation*, 2005.
- [3] Dieter Fox, Wolfram Burgard, Hannes Kruppa, and Sebastian Thrun. A monte carlo algorithm for multi-robot localization. 1999.
- [4] J.R. Spletzer and C.J Taylor. A bounded uncertainty approach to multi-robot localization. *International Conference on Intelligent Robot and Systems*, 2003.
- [5] D. Fox, W. Burgard, and S. Thrun H. Kruppa. A probabilistic approach to collaborative multi-robot localization. In *Autonomous Robots*, Vol. 8, pp. 325–344, 2000.
- [6] S. Thrun, D. Fox, W. Burgard, and F. Dellaert. Robust monte carlo localization for mobile robots. *Artificial Intelligence*, 2000.
- [7] Jens-Steffen Gutmann and D. Fox. An experimental comparison of localization methods continued. *International Conference on Intelligent Robots and Systems*, 2002.
- [8] Mustafa Ozuyal, Michael Calonder, Vincent Lepetit, and Pascal Fua. Fast keypoint recognition using random ferns. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2010.
- [9] Aldebaran Robotics. www.aldebaran-robotics.com.

Fig. 3: A Multi-robot Localization Scenario Involving 3 NAO Robots