D 1 1 0

近傍乱流後流における3次元渦度の直交ウェーブレット変換

李鹿 輝[○] (山形大学), Tongming ZHOU (The University of Western Australia)
Yu ZHOU (The Hong Kong Polytechnic University)

Orthogonal Wavelet Transform of the Three Vorticity Components in a Turbulent near Wake

Akira RINOSHIKA, Tongming ZHOU and Yu ZHOU

ABSTRACT

The purpose of the present study is to examine the characteristics of the vortical structures using the orthogonal wavelet multi-resolution technique by decomposing the vorticity into a number of wavelet components based on different central frequencies. The three vorticity components were measured simultaneously using an eight-wire probe in the near wake of a circular cylinder at two Reynolds numbers, namely 6,500 and 10,000. It is found that the dominant contributions to the vorticity variances are from the intermediate and relatively small-scale structures. The contributions from the large and intermediate-scale structures to the vorticity variances decrease with the increase of Reynolds number, while the contributions from the small-scale structures to all three vorticity variances jump significantly, which is connected to previous observations in the near wake that there is a significant increase in the generation of small-scale structures. The result reinforces the conception that turbulence 'remembers' its origin.

Keywords: Orthogonal wavelet multi-resolution technique, Turbulence, Vorticity, Wake

1. Introduction

Flow around a circular cylinder is of significant importance for engineering applications. The topology and transport characteristics of the turbulent structure in the wake that depend on the initial conditions have been well established studied. Especially the Reynolds number has a significant effect on the formation of vortices behind the circular cylinder and attracted a large amount of investigation in the past several decades particularly in the range of $Re = 1,000$ to $10,000$ [1]. Recently, Yiu et al. [2] examined the Reynolds number effects on the turbulent near wake over the Re range of $2,500 - 10,000$ using a 4-X-wire 3-dimensional vorticity probe. They found that the streamwise vorticity component "jump" significantly as Re is increased from $5,000$ to $10,000$. Correspondingly, the contributions from the large-scale structures to the spanwise vorticity variance decline appreciably, suggesting an increased 3-dimensionality of the flow. However, due to the limitation of their detection scheme, they could not provide any information on the relationship between initial conditions and organized

structures other than the large-scale ones. One interesting question to be asked is how these variations with Re would affect the contribution of various scales to the three-dimensional vorticity in the near wake. This motivates the present investigation.

In the past decade there has been a growing interest in the use of wavelet analysis for extracting new information on the turbulence structures of various scales. Recently, an orthogonal wavelet multi-resolution technique was applied to the analysis of the turbulent structures of various scales in the near-wake of a circular cylinder by Rinoshika and Zhou [3]. It is observed for the first time that the spanwise vorticity contours of the wavelet component at the averaging frequency of Kármán vortices display a secondary spanwise structure near the saddle point in the near wake of a circular cylinder. Using the same technique, Rinoshika & Zhou [4, 5] further investigate the dependence of the turbulent structures of various scales on various wake-generating bodies in the near and far wakes. Their results indicate that the intermediate- as well as the large-scale structures depend on the initial conditions.

One objective of this work is to explore further the possible dependence of the near-wake turbulence on Re , in particular, focusing on the aspects of vorticity. For this purpose, a probe that used by Zhou et al. [6] was employed to measure the three-dimensional vorticity components simultaneously at two Reynolds numbers, namely 6,500 and 10,000. Vorticity is an important characteristic of turbulence that can provide fundamental information on multi-scale turbulent structures. Therefore, the second objective is to investigate the connection between the three-component vorticity and the multi-scale vortical structures, which is fundamentally important to the thorough understanding of the near-wake turbulence.

In the present study, the wavelet transform is used to decompose the measured three-component vorticity signals into a number of wavelet components based on their central frequencies, which are representative of the turbulent structures of different scales. The contributions from the turbulent structures of various scales to the vorticity variances are calculated. The Re dependence of large-, intermediate- and small-scale structures is documented in details in terms of the three-dimensional vorticity.

2. Experimental Details

The experiments were conducted in a closed loop wind tunnel with a test section of 1.2 m (width) $\times$ 0.8 m (height) and 2.4 m (length). The three-dimensional vorticity were measured simultaneously at three free stream velocities, i.e. 8 m/s and 12 m/s, corresponding to $Re (U_\infty d/\nu) = 6,500$ and 10,000, respectively. The measurement location is at $x/d = 40$, where $d = 12.7$ mm is the diameter of the stainless steel circular cylinder.

The probe consists of four X-probes and the details were described in Zhou et al. [6]. The output signals were subsequently sampled at a frequency f_s of 10,400 Hz. The sampling period is about 60 seconds. The three vorticity components are obtained from the u_i signals measured by the vorticity probe

3. Results

The spectra of the velocity signals, measured on the vortex center for the free stream velocities of 8 m/s and 12 m/s, exhibit strong peaks at frequencies of 132 Hz and 150 Hz, respectively. The peaks become more apparent as Re increases. These frequencies correspond to a Strouhal number $St (=fd/U_\infty)$ of about 0.2, which indicates a consequence of the occurrence of the

large-scale structure of Kármán vortices. These corresponding shedding frequencies will therefore be used as the basic frequencies f_0 in the wavelet analysis to represent the large-scale vortical structures.

3.1 Contributions to Vorticity Variances from Different Wavelet Components at Re of 6,500

In this section, results and discussion will be focused on the measurements at the velocity of 8 m/s (i. e. $Re = 6,500$) to study the contributions to vorticity variances from different wavelet components. The wavelet multi-resolution technique was used to decompose the three vorticity components into a number of orthogonal wavelet vorticity components by $\omega_{k,i}$, where k represents the vorticity components in the x_1 -, x_2 -, and x_3 -direction at the i th wavelet level. The wavelet level is based on the shedding frequency f_0 , which represent the large-scale structures in wavelet analysis, as basic frequency to multiple by a factor of 1/2, 2, 4, 8, 16 and 32 ($\equiv f_0/2, 2f_0, 4f_0, 8f_0, 16f_0$ and $32f_0$) for the wavelet analysis of the various scale of turbulent structures. Then the vorticity variances of the wavelet components,

$\langle \omega_k^2 \rangle_i$, may be calculated by $\langle \omega_k^2 \rangle_i = \frac{1}{n} \sum_{j=1}^n \omega_{j,k,i}^2$, where

n is the total number of data points.

The distributions of the time-averaged three vorticity variances obtained from the wavelet multi-resolution analysis at different wavelet levels or central frequencies are shown in Fig. 1. The values of $\langle \omega_k^2 \rangle_i$

are normalized by the maximum measured value of $\langle \omega_k^2 \rangle_{\max}$ to indicate the contribution from different central frequencies to the vorticity variance, where k ($\equiv 1, 2$ or 3) represents any component of the vorticity vector and $\langle \omega_k^2 \rangle_i$ represent the wavelet components at

i th level. The measured vorticity variances $\langle \omega_k^2 \rangle$ are also included in the figure for comparison. It can be seen in each figure that, both $\langle \omega_k^2 \rangle / \langle \omega_k^2 \rangle_{\max}$ and

$\langle \omega_k^2 \rangle_i / \langle \omega_k^2 \rangle_{\max}$ drop when the free stream is

approached. It needs to be noted that the maximum value of $\langle \omega_1^2 \rangle_i / \langle \omega_1^2 \rangle_{\max}$, corresponding to central

frequency of f_0 (Fig. 1a), accounts for about 12.3% of the maximum longitudinal vorticity variance. This value is much larger than that for $\langle \omega_2^2 \rangle_i / \langle \omega_2^2 \rangle_{\max}$

(6.5%, Fig. 1b) and $\langle \omega_3^2 \rangle_i / \langle \omega_3^2 \rangle_{\max}$ (8.9%, Fig. 1c),

indicating a relatively larger contribution to the longitudinal total vorticity variance from the large-scale structures than both to the transverse and to the spanwise vorticity components. This result seems to suggest that as the vortical structures evolve downstream, the spanwise and rib-like structures found in Rinoshika and Zhou [3] show different contributions to the three vorticity components. Figure 1 also shows that the turbulent structures with higher central frequencies tend to contribute more to the vorticity variances than those of lower ones since $\langle \omega_1^2 \rangle_i / \langle \omega_1^2 \rangle_{\max}$

is largest at $4f_0$, while the contributions to $\langle \omega_2^2 \rangle_i / \langle \omega_2^2 \rangle_{\max}$ and $\langle \omega_3^2 \rangle_i / \langle \omega_3^2 \rangle_{\max}$ are dominated by

structures with central frequency of $8f_0$. In Figs. 1 (b) and (c), it can be seen that contributions at $2f_0$, $4f_0$, $8f_0$ and $16f_0$ are all higher than that corresponding to f_0 . The total contribution from the included subsets ($2 \sim 32f_0$) takes about 76% of $\langle \omega_1^2 \rangle_{\max}$, 87% of $\langle \omega_2^2 \rangle_{\max}$ and

85% of $\langle \omega_3^2 \rangle_{\max}$, indicating that more transverse and

spanwise vorticity resides in the intermediate and small-scale structures than the longitudinal vorticity component. In addition, this result is consistent with the previous study [3] that compared with the large-scale turbulent structures (with central frequencies lower than $2f_0$), the intermediate and relatively small-scale structures contribute more to vorticity.

3.2 Reynolds Number Effect on the Contributions to Vorticity Variances from Different Wavelet Components

Figures 2 shows the vorticity variances of the wavelet components at the central frequencies $f_0/2$, f_0 , $2f_0$, $4f_0$, $8f_0$, $16f_0$ and $32f_0$. The structures with central frequencies of $f_0/4$ and $32f_0$ contribute least to the total energy with a percentage being smaller than 4%. Figure 1 (a) shows the vorticity variances from the wavelet components at the central frequencies of $f_0/2$ and f_0 , which represent the large-scale structures. Similar variations with Re are found for individual vorticity component and the wavelet contributions decrease with the increase of Re .

The contributions to vorticity variances from structures with central frequencies of $2f_0$, $4f_0$ and $8f_0$, which mainly represent the intermediate scale turbulent structures, are shown in Fig.1b. It can be seen that, the

contributions to $\langle \omega_1^2 \rangle$, $\langle \omega_2^2 \rangle$ and $\langle \omega_3^2 \rangle$ at $2f_0$

decrease by about 4.9%, 3.3% and 2.2%, respectively, when Re increases. At central frequency of $4f_0$, the decrease of contributions is about 2.8% for $\langle \omega_3^2 \rangle_i$. In

contrast to $\langle \omega_3^2 \rangle_i$, the decreases of $\langle \omega_1^2 \rangle_i$ and $\langle \omega_2^2 \rangle_i$

are larger, which are about 3.6% and 4.5%, respectively. The decreases of the contributions to vorticity variances at central frequencies of $8f_0$ are much smaller, which are about 2.2%, 2.9% and 0.9%, respectively.

The contributions to vorticity variances at central frequencies of $16f_0$ and $32f_0$, which mainly represent the small-scale structures, are shown in Fig. 2c, significant increases or jump of contributions to the three vorticity components are observed when Re increases, indicating a strong positive Re dependence over the present Re range (6,500~10,000). In Fig. 1c ($16f_0$), the increases of the contributions to $\langle \omega_1^2 \rangle$, $\langle \omega_2^2 \rangle$ and $\langle \omega_3^2 \rangle$ are 9.1%,

8.5% and 8.6%, respectively. The corresponding increases are also significant at $32f_0$, which are 5.6%, 6.3% and 6.0%. With the caveat of the experimental uncertainty associated with vorticity measurements, the changes of the wavelet contributions when Reynolds number is increased are still appreciable. This sudden "jump" of the contributions to vorticity variances from the turbulent structures with the central frequencies of $16f_0$ and $32f_0$ is probably due to the generation of small-scale structures in the near field [2]. This result indicates that the vorticity field in the wake depends not only on the initial conditions [4], but also on the Reynolds numbers, which reveals the "memory" effects to the Reynolds number change in the near field.

5. Conclusions

All three components of the vorticity vector in the near region of a cylinder wake were measured simultaneously by employing an eight hot-wire probe at two Reynolds numbers, namely 6,500 and 10,000. Using the wavelet multi-resolution technique, contributions to vorticity variances from different wavelet components are evaluated. It is found that the dominant contributions to the vorticity variances are from the intermediate and relatively small-scale structures. The contributions from the large and intermediate-scale structures to the vorticity variances decrease with the increase of Reynolds number, while the contributions from the small-scale structures to all

Figure 2 Vorticities of the wavelet components at various central frequencies for $Re = 6,500$ and $10,000$

Figure 1 Vorticities of the measured and the wavelet components at various central frequencies for $Re = 6,500$

References

- 1) Lin J. C., Towfigh J. and Rockwell D.: Instantaneous structure of the near-wake of a circular cylinder: on the effect of Reynolds number, *Journal of Fluids and Structures*, 9:409-418, 1995.
- 2) Yiu M. W., Zhou Y., Zhou T. and Cheng L.: Reynolds number effects on 3-D vorticity in a turbulent wake, *AIAA Journal*, 42:1009-1015, 2004.
- 3) Rinoschika A. and Zhou Y.: Orthogonal Wavelet Multi-Resolution Analysis of a Turbulent Cylinder Wake, *Journal of Fluid Mechanics*, 524, pp.229-248, 2005.
- 4) Rinoschika A. and Zhou Y.: Effects of Initial Conditions on a Wavelet-decomposed Turbulent Near-wake, *Physical Review E*, 71, 046303, pp.1-8, 2005.
- 5) Rinoschika A. and Zhou Y.: Effects of Initial Conditions on Wavelet Decomposed Self-Preserving Turbulent Structures, *International Journal of Heat and Fluid Flow*, 28, pp.948-962, 2007.
- 6) Zhou T., Rinoschika A., Hao Z., Zhou Y. and Chua L. P.: Wavelet multi-resolution analysis of the three vorticity components in a turbulent far wake, *Physical Review E*, 73, 036307, pp.1-12, 2006.

three vorticity variances jump significantly. The result reinforces the conception that turbulence 'remembers' its origin.