NUMERICAL MODELLING OF THREE-LEG JACKUP BEHAVIOUR SUBJECT TO HORIZONTAL LOAD

E. T. R. DEANⁱ⁾, R. G. JAMESⁱⁱ⁾, ANDREW N. SCHOFIELDⁱⁱ⁾ and YOSHIMICHI TSUKAMOTOⁱⁱⁱ⁾

ABSTRACT

This paper examines a method of numerical simulation of 3-leg jackup response to horizontal load. The method assumes variable rotational (moment) fixity, variable horizontal fixity, and complete vertical fixity. Numerical results are compared with centrifuge model test data. Consistently with Wong et al. (1993), it is shown that moment fixity increases with increasing spudcan rotational stiffness, increasing leg length, and decreasing leg flexural rigidity. It is further shown that fixity degrades with increasing horizontal load. Fixity with a longer leg under high horizontal load may become smaller than fixity with a shorter leg length under low horizontal load.

Key words: bearing capacity, footing, foundation, horizontal load, yield (IGC: H3/H1)

INTRODUCTION

Figure 1 shows features of an independent-leg offshore jackup platform. Typical operations and geotechnical considerations are described by McClelland et al. (1982), Young et al. (1984), Boswell (1986), Reardon (1986), Poulos (1988), Ahrendsen et al. (1989), Chaney and Demars (1991), Senner (1992), Boswell and D'Mello (1993, 1995), SNAME (1994). The unit is typically moved to location with its legs elevated. The legs are then jacked onto the seabed and the jacking systems are used to lift the hull out of the water. Water ballast may be taken on board to "preload" the foundation. The ballast is then discharged and the hull is raised further to provide adequate air-gap during subsequent operations.

Environmental loads include wind load (typically 25–35% of the total extreme lateral load), wave (typically 55–65%), and current (10%; Poulos, 1988, p. 255). Earthquake effects can be significant in seismic regions, but are not considered here. Control of net buoyant weight and of the position of its centroid is important. In this paper, considerations are restricted to loading in the plane of Fig. 1. Soil reactions at the i -th spudcan are vertical load V_i , horizontal load H_i , and moment M_i . The moments are important in serviceability and ultimate limit state calculations, and for fatigue, particularly at the spudcan-leg connections and for the jacking mechanisms (Santa Maria, 1988; Hambly, 1990; Tan, 1990; Murff et al., 1991; Houlsby and Martin, 1992).

Field data and analyses of cyclic loading are reported

by Hattori et al. (1982), Brekke et al. (1989, 1990), Stewart et al. (1989, 1991), Hambly et al. (1990), Hambly and Nicholson (1991), Liu et al. (1991), Hambly (1992), McCarron and Broussard (1992), Spidsøe and Karunakaran (1993), Springett et al. (1993), Weaver and Brinkmann (1995), and others. Centrifuge model test

Fig. 1. Three-leg jackup rig

ⁱ⁾ Soil Models Limited, UK.

ⁱⁱ⁾ Cambridge University, Engineering Department and Andrew N Schofield & Associates Limited, UK.

ⁱⁱⁱ⁾ Science University of Tokyo.

Manuscript was received for review on February 1, 1996.

Written discussions on this paper should be submitted before January 1, 1998 to the Japanese Geotechnical Society, Sugayama Bldg. 4F, Kanda Awaji-cho 2-23, Chiyoda-ku, Tokyo 101, Japan. Upon request the closing date may be extended one month.

data and analyses of spudcan and 3-leg jackup models on sand are reported by Silva-Perez (1982), Tanaka (1984), Lau (1988), James and Shi (1988), Shi (1988), Tan (1990), Osborne et al. (1991), Murff et al. (1991, 1992), Dean et al. (1992a-d; 1995a,b), Wong et al. (1993), Tsukamoto (1994), Hsu (1995), and others.

This paper describes and discusses a numerical simulation of the behaviour of a 3-leg jackup subject to horizontal load. The simulation incorporates variable horizontal fixity, as well as variable moment fixity. Results are compared to centrifuge data of drained loading reported in Dean et al. (1992b) and Tsukamoto (1994). A limitation of the work reported here is that, for field loading conditions, the soil may be only partially drained over the typical period of a single extreme design wave. Work on partially drained responses is reported by Dean et al. (1995a,b) and Hsu (1995).

A NUMERICAL SIMULATION OF 3-LEG JACKUP BEHAVIOUR

Schotman (1989) showed that displacements are important in numerical modelling of spudcan response to loads. Murff et al. (1991, 1992), Dean et al. (1992c, 1995a), and Wong et al. (1993) considered idealisations with complete vertical and horizontal fixity at each spudcan, and with variable moment fixity. In the following formulation, both moment and horizontal fixity are assumed to be variable. Complete vertical fixity is assumed, which means that the simulated jackup will not rotate with respect to the seabed during horizontal loading.

It is assumed here that the jackup has a rigid hull and elastic legs, as shown in the idealisation in Fig. 2. In the absence of environmental loads, the gravity load W is taken to be equally distributed to the three spudcans. Net horizontal environmental load H_T is assumed to act on a fixed point on the hull at height $L^* = L + S + Y$ above the spudcan load reference points (LRP's), which are the points on the spudcans at which spudcan loads are eval-

uated, where L is the leg length (hull-leg connection HLC to spudcan-leg connection SLC), S is the height of the rigid spudcans (SLC to LRP), and Y is the height of the line of action of H_T above the hull-leg connections. The total vertical load W is assumed constant. In plan view, the three legs typically form an equilateral triangle. Legs 2 and 3 are at symmetrical positions, and are assumed here to experience equal loads and displacements. Quantities for these legs are denoted either using the separate suffixes "2" and "3", or using suffix "23". For example, V_2 and V_3 are the vertical loads on the spudcans on legs 2 and 3 respectively. V_{23} is the average vertical load on these two legs, and $V_{23} = V_2 = V_3$.

If there is complete vertical fixity at the spudcans, and if the legs deform in bending only, then the idealised jackup hull moves horizontally, parallel to the seabed, when net horizontal load H_T is applied. Horizontal displacements of the hull are here denoted as h_{HULL} (Fig. 3). Horizontal displacements of the top of the legs relative to the spudcan load reference points are denoted as δ_1 and $\delta_{23} = \delta_2 = \delta_3$. Spudcan rotations are denoted by θ_1 and $\theta_{23} = \theta_2 = \theta_3$. Spudcan horizontal deflections relative to a fixed datum are h_1 and $h_{23} = h_2 = h_3$, assessed at the load reference points. Since the hull is rigid:

$$h_{HULL} = h_1 + \delta_1 = h_{23} + \delta_{23} \quad (1)$$

In the absence of dynamic acceleration effects, horizontal and vertical equilibrium of forces on the idealised jackup in Figs. 2 and 3 implies that:

$$H_T = H_1 + 2H_{23} \quad (2)$$

$$W = V_1 + 2V_{23} \quad (3)$$

where $H_{23} = H_2 = H_3$ and $V_{23} = V_2 = V_3$. By taking moments about appropriate points on the spudcans, Dean et al. (1992c) derived equations for spudcan vertical loads which, in the notation and with the sign conventions used in this paper, and noting that δ_1 and δ_{23} may be different, may be written as:

Fig. 2. Simple idealisation of geometry and loads for three-leg jackup rig

Fig. 3. Simple idealisation of displacements and rotations

$$V_1 = \frac{W \cdot ((D/3) + \delta_{23} - e_{23}) + H_T \cdot L^*}{D + (e_1 - e_{23}) - (\delta_1 - \delta_{23})} \quad (4)$$

$$V_{23} = \frac{W \cdot ((D/3) - (\delta_1/2) + (e_1/2)) - (H_T \cdot L^*/2)}{D + (e_1 + e_{23}) - (\delta_1 - \delta_{23})} \quad (5)$$

where D is the horizontal distance in elevation between leg 1 and legs 2 and 3, $e_1 = M_1/V_1$ is the load eccentricity at the spudcan on leg 1, and $e_{23} = M_{23}/V_{23}$ is the load eccentricity at the spudcans on legs 2 and 3.

Figure 4 shows the i -th leg and spudcan. It is assumed here that the rotation θ_i of a spudcan is related to the moment M_i at the spudcan by a secant rotational stiffness $K_{RS,i}$ as follows:

$$M_i = K_{RS,i} \cdot \theta_i \quad (6)$$

Assuming that the leg deflects in bending only, and taking (x, y) coordinates as shown in Fig. 4, with $x=0$ at the hull-leg connection, the leg deflection y relative to the hull-leg connection satisfies the following elastic bending equation:

$$EI d^2y/dx^2 = H_i \cdot (L + S - x) - M_i \quad (7)$$

where EI is the leg flexural rigidity. By integrating this expression once with respect to x , by evaluating the rotation dy/dx at $x=L$, then by substituting for the moment using Eq. (6) and re-arranging the result, it is found that:

$$\theta_i = \frac{H_i \cdot L^2}{2EI} \cdot \left(\frac{EI}{EI + K_{RS,i}L} \right) \cdot (1 + 2 \cdot (S/L)) \quad (8)$$

By integrating Eq. (7) twice, evaluating the relative deflection at $x=L$, and adding the relative deflection $\theta_i \cdot S$ due to the rotation of the spudcan about the load reference

point, substituting for the moment using Eq. (6), and substituting for the rotation using Eq. (8), it is found that:

$$\delta_i = \frac{H_i \cdot L^3}{12EI} \cdot \left[1 + 3 \cdot \left(\frac{EI}{EI + K_{RS,i}L} \right) \cdot (1 + 2 \cdot (S/L))^2 \right] \quad (9)$$

A number of authors have proposed various kinds of yield locus or limiting locus or envelope for combined loads of circular or strip footings, including Roscoe and Schofield (1956, 1957), James (1987), Georgiadis and Butterfield (1988), Schotman (1989), Nova and Montrasio (1991), Murff et al. (1991, 1992), Dean et al. (1992c), Gottardi and Butterfield (1993), Butterfield and Gottardi (1994). For the numerical simulation described in this paper, the following locus for the i -th spudcan is used. This locus is believed to be a modification of an earlier proposal by James (1987). It is described by Dean et al. (1992c), except that they do not use the suffices “ i ”:

$$\left[\left(\frac{M_i}{BV_{Mi}} \right)^2 + \beta^2 \cdot \left(\frac{H_i}{V_{Mi}} \right)^2 \right]^{1/2} = \alpha \cdot \frac{V_i}{V_{Mi}} \cdot \left(1 - \frac{V_i}{V_{Mi}} \right) \quad (10)$$

where B is the diameter of a circular spudcan, V_{Mi} is the current vertical bearing capacity of the footing, and α and β are dimensionless constants which depend on the geometry and roughness of the footing, and might also conceivably depend on vertical penetration depth, shear strength parameters of the soil, and other factors. The assumption of complete vertical fixity used in the present simulation is taken to imply that V_{Mi} is a constant. Dean et al. (1992c, p. 250) considered the values $\alpha=0.35$ and $\beta=0.625$. These values are used here. SNAME (1994, Section 6.3.4.1) use a similar formula, except for notation, but with $\alpha=0.3$ and $\beta=0.625$. The following expression, developed by Tsukamoto (1994) from an expression in Dean et al. (1992d), is assumed here for the relation between spudcan moment M_i and spudcan rotation θ_i at constant vertical spudcan load V_i :

$$M_i = M_{ULT,i} \left\{ 1 - \exp \left(\frac{-K_{RE,i} \cdot \theta_i}{M_{ULT,i}/B} \right) \right\} \quad (11)$$

where $M_{ULT,i}$ is obtained by re-arranging Eq. (10) and renaming the moment, as follows:

$$M_{ULT,i}/B = \alpha \cdot \frac{V_i}{V_{Mi}} \cdot \left(1 - \frac{V_i}{V_{Mi}} \right) \sqrt{1 + \left(\frac{\beta}{\zeta} \right)^2} \quad (12)$$

where $\zeta = (M_i/B)/H_i$, and where the value $K_{RE,i}$ is assumed to depend on the current vertical load V_i on the spudcan via a coefficient R_{RE} :

$$K_{RE,i} = R_{RE} \cdot \sqrt{V_i} \quad (13)$$

where $K_{RE,i}$ is in kN/degree when V_i is in kN. Because the vertical loads V_i on the spudcans change as horizontal load H_T is applied to the jackup, the stiffness $K_{RE,i}$ and the ultimate moment $M_{ULT,i}$ also change. In this simulation, this is taken to imply that the curve on which the current moment-rotation values lie would shift as the vertical load changes, as indicated in Fig. 5.

To evaluate the horizontal displacement h_i of the i -th spudcan, it is assumed in the numerical simulation that the normality rule of plasticity holds for incremental

Fig. 4. Linear elastic bending analysis of i -th leg (neglecting effect of V_i -times-deflection)

Fig. 5. Formulation of spudcan load-interaction and load-displacement behaviour

horizontal displacement and rotation. Consideration of Eq. (10) for a fixed value of vertical load V_i and a given V_{Mi} then implies that:

$$\Delta(B\theta_i)/\Delta(h_i/\beta) = (M_i/B)/(\beta H_i) \quad (14)$$

as illustrated in Fig. 5. In applying this rule, for simplicity, the total incremental displacements and rotations were used in the simulation. The incremental displacements and rotations were not split into elastic and plastic components.

COMPARISONS WITH CENTRIFUGE MODEL TEST DATA

Centrifuge modelling has played a major role in resolving geotechnical issues in the development of offshore structures (Rowe, 1983). Principles and practice of centrifuge modelling for a variety of onshore and offshore geotechnical applications are described by Schofield (1980, 1981), Craig (1984), Craig et al. (1988), Corte (1988), Ko and McLean (1991), Taylor (1994), Leung et al. (1994), and others.

In this section, simulation results are compared with centrifuge model test data for event 7 of test YT2-3L-C reported by Dean et al. (1992b) and Tsukamoto (1994). In this centrifuge test, a jackup model was landed and preloaded on a 119 mm deep layer of fine saturated Leighton Buzzard 100/170 silica sand. The soil layer rested on a rigid base. The centrifuge gravity varied from approximately 113 g at the soil surface to 128 g at the base

of the 119 mm thick soil layer. The vertical spudcan loads at the start of event 7 were $V_1 = V_{23} = W/3 = 0.7$ kN. During event 7, the centrifuge model was subjected to four slow two-way cycles of increasing amplitude of net horizontal load H_T , at approximately constant net vertical load $W = 2.1$ kN.

The centrifuge model is shown in elevation in Fig. 6. The model was hung from a support frame. The net loads consisted of (a) the model weight W^* in the centrifuge gravity, (b) an upthrust U from the hanger, and (c) a horizontal load H_{APP} applied by cables to the hull reference point marked "HRP". The model spudcans were flat based, with overall diameter $B = 57.8$ mm and with a small conical tip. The spudcans were instrumented to measure axial loads (P_i), shear loads (Q_i), and moment loads (M_i). The axial and shear loads could be resolved to obtain the spudcan vertical loads (V_i) and spudcan horizontal loads (H_i). The sum of the spudcan vertical loads was taken to be the net rig weight W . The sum of the spudcan horizontal loads was taken to be the net horizontal load H_T .

The legs of the model jackup were not equal in length. Model dimensions were in the ranges $S = 72.2 \pm 0.9$ mm, $L = 248.4 \pm 2$ mm, $Y = 34.3 \pm 2.3$ mm, and $L^* = 355 \pm 1.2$ mm. However, in the numerical simulation, it was assumed that $S = 0$, $L = L^* = 354.4$ mm, and $Y = 0$. The leg spacing D was 186 mm in the centrifuge test and in the simulation. The leg flexural rigidity in the simulation was taken as $EI = 0.234 \times 10^6$ kN·mm², based on the meas-

Fig. 6. 3-leg model jackup and support frame, model properties, directions of positive loads H_{APP} , W^* , and U , and directions of positive soil reactions P_i , Q_i , and M_i

ured leg cross-section dimensions and the value $E=70$ kN/mm² for the duraluminium material of which the physical model legs were made. The parameters α and β in Eqs. (10) and (12) were taken as $\alpha=0.35$ and $\beta=0.625$. The coefficient R_{RE} in Eq. (13) was taken as $0.7 \text{ kN}^{1/2} \text{ degree}$. The values $V_{M1}=V_{M23}=2.8 \text{ kN}$ were considered appropriate, based on estimates obtained using an extrapolation of the measured vertical load-penetration relations during preloading and on the measured average vertical penetration of the centrifuge model spudcans at the start and end of the sequence of horizontal load application in event 7 of the model test.

Figures 7–9, which are discussed below, show comparisons of the numerical simulation with centrifuge data.

Fig. 7. Comparison between simulation and centrifuge data – hull behaviour and loadsharing between spudcans

Fig. 8. Comparison between simulation and centrifuge data – spudcan loadpaths

Fig. 9. Comparison between simulation and centrifuge data – spudcan load-displacement and rotation responses

The sign conventions for load and displacement quantities in these figures are the same as the sign conventions illustrated in Figs. 2 and 3. For example, horizontal hull displacement h_{HULL} is taken positive when the hull translates rightwards in the simulation and in the centrifuge model. Checks confirmed that the loads on the spudcans on legs 2 and 3 in the centrifuge model were close to equal, and the suffix “23” in Figs. 7–9 denotes average values for these spudcans.

In the simulation and in the centrifuge test, the general behaviour of the spudcan loads was as follows. When the horizontal load H_T increased positively, so that the load was directed towards leg 1, the vertical load V_1 on the spudcan on leg 1 increased above 0.7 kN , and the vertical loads V_{23} on the spudcans on legs 2 and 3 decreased below 0.7 kN . When the horizontal load increased negatively, so that the load was directed towards legs 2 and 3, the vertical load V_1 on the spudcan on leg 1 decreased, and the vertical loads V_{23} on the spudcans on legs 2 and 3 increased. The terminology “heavily loaded” and “lightly loaded” is sometimes used, referring to vertical spudcan loads. The spudcan on leg 1 is “heavily loaded” when the net horizontal load H_T is positive, but is “lightly loaded” when H_T is negative. The spudcans on legs 2 and 3 are “lightly loaded” when the net horizontal load is positive, and are “heavily loaded” when H_T is negative.

Figure 7 shows aspects of the hull behaviour, and of the interactions between the spudcan on leg 1 and those on legs 2 and 3. Because the simulation assumes complete vertical fixity, the vertical settlement and rotation of the hull are not simulated, and only the predicted relation between net horizontal load and hull displacement is available. It may be seen that the simulation results indicate non-linear loadsharing between the spudcans, and that non-linear loadsharing occurred in the model test. When the net horizontal load H_T was applied towards leg 1, the

spudcan on leg 1 took a higher share of the horizontal load. When H_T was negative, the spudcans on legs 2 and 3 took a higher share of the load.

Figure 8 compares numerical simulations and centrifuge test data of the loadpaths at the spudcans. The simulation reproduces features of the non-linearity of the paths observed in the centrifuge test. The simulation shows lower peak values of moment-over-diameter, for all spudcans and for both the “lightly loaded” and the “heavily loaded” conditions. The simulation slightly over-predicts the changes of vertical loads at all spudcans.

Figure 9 compares simulations and data of the relations between spudcan moments and rotations, and spudcan horizontal displacements and horizontal loads. The observed values of spudcan displacements and rotations were inferred from measured data of hull displacement and rotations and data of measured spudcan loads, using an elastic analysis for the legs of the physical model similar to that described above for the simulation. The inferred spudcan rotations were relatively insensitive to small potential inaccuracies in the measurements of the dimensions and stiffness of the physical model. The inferred horizontal spudcan displacements were more sensitive to these potential inaccuracies (Tsukamoto, 1994).

Both the test data and the numerical simulation in Fig. 9 show noticeable spudcan horizontal displacements and rotations. The simulation results for horizontal displacements show sliding conditions for the spudcan on leg 1 only when the spudcan horizontal load reaches its maximum negative value. This occurs in the two-way load cycles when this spudcan is “lightly loaded”. For the spudcans on legs 2 and 3, the simulation shows sliding conditions only at maximum positive horizontal load. This occurs at the different times in the two-way load cycles when these spudcans are “lightly loaded”.

For the moment-rotation responses, both the simulation and the data show reductions in tangent stiffnesses at both ends of the load cycles, thus when the spudcans are “lightly loaded” and when they are “heavily loaded”. Wong et al. (1993) defined the “moment fixity”, which they denoted as “ x_{dy} ”, as the ratio of the moment M_i at a spudcan divided by the theoretical moment which would occur if all three spudcans behaved as encastred foundations. In this paper, the notation f is used for fixity, and fixity is defined separately for each spudcan. Assuming equal rotational stiffnesses at each spudcan, Wong et al. (1993) derived an equation which, in the notation of this paper, could be written:

$$f_i = K_{RS,i} / \{K_{RS,i} + (EI/L)\} \quad (15)$$

By using Eq. (8) to substitute for θ_i in Eq. (6), and noting that the theoretical moment for fully encastred conditions is $H_i \cdot ((L/2) + S)$, it may be verified that the analysis here would be consistent with Wong et al.’s (1993) finding if the analysis had assumed equal rotational stiffnesses at each spudcan. However, the data indicate that rotational stiffnesses were variable during load cycles. In the simulation, the rotational stiffnesses $K_{RS,i}$ at

the spudcans are linked to the spudcan vertical loads by Eq. (13), and the spudcan vertical loads given by Eqs. (4) and (5) are different when the net horizontal load H_T is non-zero.

In conclusion, it may be said that the numerical simulation provided a useful initial interpretation of the experimental data. There are areas where improvements might be useful. For example, the numerical simulation does not incorporate the hysteresis seen in the data.

PARAMETRIC STUDIES

Although Eq. (15) was derived assuming equal rotational stiffnesses at all three spudcans, it shows that moment fixity x_{dy} or f_i is not solely a property of the soil or the footing, but is a soil-structure interaction parameter depending on the footing rotational stiffness and on the effective leg rotational stiffness EI/L .

Figure 10 shows numerical simulation results illustrating effects of rotational stiffnesses $K_{RS,i}$, which from Eqs. (11) and (13) are related to $R_{RE} \cdot B \cdot \sqrt{V_i}$ in the simulation. Three values of the coefficient R_{RE} are used in Fig. 10, namely 0.5, 0.7, and 0.9 $\text{kN}^{1/2}/\text{degree}$, representing variations of about $\pm 30\%$ compared to the value $R_{RE}=0.7$ used in the comparisons with centrifuge data. In all three cases, the leg flexural rigidity is taken as $EI=0.234 \times 10^6 \text{ kN} \cdot \text{mm}^2$, and the height L^* of the line of action of the net horizontal load is taken as 354.4 mm. The simulations indicate that, in the vicinities of the parameter values that were used, horizontal displacements of the spudcans are relatively insensitive to the implied values

Fig. 10. Parametric investigation – numerical simulation of influence of foundation rotational stiffness

of rotational stiffness.

The reason for this is believed to be as follows. Differentiation of Eq. (11) gives $K_{RS,i} = K_{RE,i} \cdot B$ around $\theta_i = 0$ (ignoring differentials associated with change of vertical spudcan load). For $R_{RE} = 0.7 \text{ kN}^{1/2}/\text{degree}$ and an average spudcan vertical load of 0.7 kN , the stiffness $K_{RE,i}$ given by Eq. (13) is $0.7 \sqrt{0.7} = 0.6 \text{ kN/degree}$ or 33.6 kN/radian , so the rotational stiffness $K_{RS,i}$ is $33.6 \times 57.8 = 1942 \text{ kN}\cdot\text{mm/radian}$ for a spudcan diameter $B = 57.8 \text{ mm}$. For the parameters of the numerical simulation, the leg length L was taken equal to the height L^* , so EI/L was $0.234 \times 10^6 / 354.4 = 660 \text{ kN}\cdot\text{mm/radian}$. From Eq. (15), the fixity at small displacements was around $1942 / (1942 + 660) = 75\%$. As shown by Wong et al. (1993), differentiating Eq. (15) and re-arranging the result gives $(df_i/f_i) = (1 - f_i) \cdot dK_{RS,i}/K_{RS,i}$. If $f_i = 75\%$, a change $dK_{RS,i}/K_{RS,i} = 30\%$ in rotational stiffness produces a change df_i/f_i of only about $(1 - 0.75) \times 0.30 = 7.5\%$. From Eqs. (6), (8) and (15):

$$\frac{M_i/B}{H_i} = \frac{L + 2S}{2B} \cdot f_i \quad (16)$$

The slope of the loadpath in terms of spudcan moment-over-diameter and spudcan horizontal load is therefore altered by only about 7.5%. It seems reasonable to assume that the slopes of the vertical-horizontal loadpath will also be altered by only a small value. Therefore, a 30% change in rotational stiffness does not have much effect on the positions on the yield loci towards which the spudcan loadpaths move.

Figure 11 shows numerical simulation results illustrat-

Fig. 11. Parametric investigation - numerical simulation of influence of leg flexural rigidity

ing effects of leg flexural rigidity. Three values of EI were used in these calculations, namely 0.134×10^6 , 0.234×10^6 , and $0.334 \times 10^6 \text{ kN}\cdot\text{mm}^2$. These values correspond to variations of about $\pm 40\%$ around the value of $0.234 \times 10^6 \text{ kN}\cdot\text{mm}^2$ appropriate for the centrifuge model test. The coefficient R_{RE} was taken to be $0.7 \text{ kN}^{1/2}/\text{degree}$. L^* was taken equal to L , and was set at 354.4 mm . The simulation results show a small effect on the values of horizontal loads at which the horizontal load-displacement curves flatten. In these calculations, moment fixities have been evaluated separately for the spudcan on leg 1 (f_1) and the spudcans on legs 2 and 3 (f_{23}). The results show that, as the leg flexural rigidity decreases, the fixity at a given horizontal load increases, although the hull would then be subjected to larger horizontal displacements. It can be seen that moment fixity degrades as the horizontal loads increase.

Figure 12 shows numerical simulation results illustrating effects of leg length or height of horizontal load application. Three different values for L^* are considered, namely 304.4 mm , 354.4 mm , and 404.4 mm . This corresponds to a variation of about $\pm 14\%$ on the value of 354.4 mm . The leg flexural rigidity was taken as $EI = 0.234 \times 10^6 \text{ kN}\cdot\text{mm}^2$. The coefficient R_{RE} was taken to be $0.7 \text{ kN}^{1/2}/\text{degree}$. The simulation results indicate that there is a noticeable effect on the values of horizontal loads at which the horizontal load-displacement curves flatten, indicating onset of sliding conditions at one or other of the spudcans. The results show that, as the distance L^* increases, the fixity at a given horizontal load increases, but that degradation of fixity as the

Fig. 12. Parametric investigation - numerical simulation of influence of leg length or height of load application

horizontal loads increase is a more important effect.

CONCLUSIONS

This paper has described, and examined the performance of, a numerical simulation method for 3-leg jackups in which linear-elastic behaviour of the structure has been combined with a non-linear model for footing response incorporating one of the several yield surfaces that have been proposed in the literature. The simulation assumed that the footings could move horizontally, as well as rotate, but that no vertical spudcan displacements would occur.

Comparisons with centrifuge model test data showed that this simulation approach has good potential. Significant general features of the test data were observed in the simulation results, including the degradation of rotational stiffness and the possibility of sliding at a spudcan during those parts of a load cycle when the spudcan is "lightly loaded". A significant feature of the numerical simulation, not present in previous analyses, was that the rotational stiffnesses were allowed to be different at different spudcans as well as at different parts of a load cycle.

ACKNOWLEDGEMENTS

Test YT2-3L-C was part of a series of tests funded by Esso Exploration and Production UK Limited (EPUK) and carried out with the help of staff of Andrew N Schofield & Associates Limited at Cambridge University's Geotechnical Centrifuge Centre. We would also like to thank N. R. Sosdian of EPUK and J. D. Murff and P. C. Wong of Exxon Production Research Company. Any opinions in this paper are those of the authors, and do not purport to represent opinions of the acknowledgees or organisations involved.

NOTATION

B	footing diameter
d	differential
D	distance between leg 1 and legs 2 and 3 in side elevation
e	footing load eccentricity, M/V
EI	leg flexural rigidity
f	moment fixity
h	horizontal displacement relative to a fixed coordinate frame
H	horizontal load
HLC	hull-leg connection
HRP	hull reference point
K_{RE}	stiffness parameter (units of force/angle), see Eqs. (11) and (13)
K_{RS}	secant rotational stiffness (units of moment/angle)
L	leg length from hull-leg connection (HLC) to spudcan-leg connection (SLC)
L^*	$=L+S+Y$, height of horizontal load application above LRP's
LRP	load reference point on spudcan
M	moment
P	axial load
R_{RE}	coefficient for rotational stiffness, see Eq. (13)
S	height of idealised rigid spudcan
SLC	spudcan-leg connection

Q	shear load
U	upthrust applied to centrifuge model (see Fig. 6)
V	vertical load
V_M	vertical bearing capacity of footing
W	net rig weight
W^*	weight of model in centrifuge gravity (see Fig. 6)
x	coordinate along leg ($x=0$ at HLC , Fig. 4)
y	leg deflection at coordinate x relative to the hull
Y	height of line of action of total horizontal load H_T above the HLC 's
α, β	dimensionless factors in Eq. (10)
δ	displacement of hull relative to spudcan
Δ	differential change of (Eq. (14))
ζ	spudcan moment-over-diameter M/B divided by spudcan horizontal load H
θ	rotation
Subscripts	
APP	applied to the centrifuge model (H_{APP} =horizontal load applied by cables, see Fig. 6)
$HULL$	of the hull of the jackup
i	quantity for the spudcan on leg i
M	capacity (V_M =bearing capacity under vertical load at the spudcan on leg i)
RE	referring to calculation for rotational stiffness, see Eqs. (11) and (13)
RS	secant rotational (see K_{RS})
T	total, net (H_T =total horizontal load)
1	quantity for the spudcan on leg 1
23	average of quantities for the spudcans on legs 2 and 3

REFERENCES

- Ahrendsen, B. K., Dutt, R. N. and Ingram, W. B. (1989): "Jackup footing performance: an integrated approach to geotechnical assessment," Paper OTC 6027, Offshore Technology Conference, Vol. 2, pp. 525-534.
- Boswell, L. F. (ed.) (1986): The Jackup Drilling Platform, Collins.
- Boswell, L. F. and D'Mello, C. (eds.) (1993): The Jackup Platform: Design, Construction, and Operation, Proc. 4th Int. Conf., Bentham Press, London.
- Boswell, L. F. and D'Mello, C. (eds.) (1995): The Jackup Platform: Design, Construction, and Operation, Proc. 5th Int. Conf., Bentham Press, London.
- Brekke, J. N., Murff, J. D., Campbell, R. B. and Lamb, W. C. (1989): "Calibration of a jackup leg foundation model using full-scale structural measurements," Paper OTC 6127, Offshore Technology Conference, Vol. 4, pp. 49-58.
- Brekke, J. N., Campbell, R. B., Lamb, W. C. and Murff, J. D. (1990): "Calibration of a jackup structural analysis procedure using field measurements from a North Sea jackup," Paper OTC 6465, Offshore Technology Conference, Vol. 4, pp. 357-368.
- Butterfield, R. and Gottardi, G. (1994): "A complete three-dimensional failure envelope for shallow footings on sand," *Geotechnique*, Vol. 44, No. 1, pp. 181-184.
- Chaney, R. C. and Demars, K. R. (1991): "Offshore Structure Foundations," Chapter 18 of *Foundation Engineering Handbook*, Second Edition, Fang, H-Y. (ed.), Chapman & Hall, pp. 679-734.
- Corte, J-F. (ed.) (1988): Centrifuge 88, Proc. Int. Conf. Geotechnical Centrifuge Modelling, Balkema.
- Craig, W. H. (ed.) (1984): Application of Centrifuge Modelling Techniques to Geotechnical Design, Balkema.
- Craig, W. H., James, R. G. and Schofield, A. N. (eds.) (1988): Centrifuges in Soil Mechanics, Balkema.
- Dean, E. T. R., James, R. G., Schofield, A. N. and Tsukamoto, Y. (1992a): "Combined vertical, horizontal, and moment loading of circular spudcans on dense sand foundations: Data report for drum centrifuge tests YT1-1L-A thru-G and YT2-1L-G thru-Y," Technical Report CUED/D-Soils/TR244, Cambridge Univ. Engineering Department.

- 13) Dean, E. T. R., James, R. G., Schofield, A. N. and Tsukamoto, Y. (1992b): Contract EP-022R Task Order 3-022, Report by Andrew N Schofield & Associates Limited to Esso Exploration and Production UK Limited, Phase 5 Volume 1.
- 14) Dean, E. T. R., James, R. G., Schofield, A. N., Tan, F. S. C. and Tsukamoto, Y. (1992c): "The bearing capacity of conical footings on sand in relation to the behaviour of spudcan footings of jack-ups," Predictive Soil Mechanics, Proc. Wroth. Mem. Symp., Thomas Telford, pp. 230-253.
- 15) Dean, E. T. R., James, R. G. and Schofield, A. N. (1992d): "A new procedure for assessing fixity of spudcans on sand," Report by Andrew N Schofield & Associates Limited to Noble Denton Consultancy Services Limited.
- 16) Dean, E. T. R., Hsu, Y., James, R. G., Schofield, A. N., Murff, J. D. and Wong, P. C. (1995a): "Centrifuge modelling of 3-leg jack-ups with non-skirted and skirted spudcans on partially drained sand," Paper OTC 7839, Offshore Technology Conference, Vol. 3, pp. 319-332.
- 17) Dean, E. T. R., Hsu, Y. S., James, R. G., Sasakura, T., Schofield, A. N. and Tsukamoto, Y. (1995b): "Centrifuge modelling of jack-ups and spudcans on drained and partially drained silica sand," Paper presented at the 5th. Int. Conf. The Jackup Platform, City University 26-27 September; Technical Report CUED/D-Soils/TR291, Cambridge Univ. Engineering Department.
- 18) Georgiadis, M. and Butterfield, R. (1988): "Displacements of footings on sand under eccentric and inclined loads," Can. Geotech. J., Vol. 25, pp. 199-212.
- 19) Gottardi, G. and Butterfield, R. (1993): "On the bearing capacity of surface footings on sand under general planar loads," Soils and Foundations, Vol. 33, No. 3, pp. 68-79.
- 20) Hambly, E. C. (1990): "Overturning Instability," ASCE Jour. of Geotech. Engrg., Vol. 116, No. 4, pp. 704-709.
- 21) Hambly, E. C. (1992): "Jackup sliding/bearing resistance on sand," BOSS 92, Behaviour of Offshore Structures, Vol. 2, pp. 989-1000.
- 22) Hambly, E. C. and Nicholson, B. A. (1991): "Jackup dynamic stability under extreme storm conditions," Paper OTC 6590, Offshore Technology Conference, Vol. 2, pp. 261-272.
- 23) Hambly, E. C., Imm, G. R. and Stahl, B. (1990): "Jackup performance and foundation fixity under developing storm conditions," Paper OTC 6466, Offshore Technology Conference, Vol. 4, pp. 369-380.
- 24) Hattori, Y., Ishihama, T., Matsumoto, K., Arima, K., Sakata, N. and Ando, A. (1982): "Full-scale measurement of natural frequency and damping ratio of jackup rigs and some theoretical considerations," Paper OTC 4287, Offshore Technology Conference, Vol. 2, pp. 661-670.
- 25) Houlsby, G. T. and Martin, C. M. (1992): "Modelling the behaviour of foundations of jackup units on clay," Predictive Soil Mechanics, Proc. Wroth. Mem. Symp., Thomas Telford, pp. 339-358.
- 26) Hsu, Y. (1995): forthcoming Ph. D thesis, Cambridge Univ.
- 27) James, R. G. (1987): "Cambridge University Research," Appendix B of Foundation Fixity of Jackup Units, Report by Noble Denton to Joint Industry Sponsors.
- 28) James, R. G. and Shi, Q. (1988): "Centrifuge modelling of the behaviour of surface footings under combined loading," Centrifuge 88, Corte, J-F. (ed.), Balkema, pp. 307-311.
- 29) Ko, H-Y. and McLean, F. G., (eds.) (1991): Centrifuge 91, Proc. Int. Conf. Geotechnical Centrifuge Modelling, Balkema.
- 30) Lau, C. K. (1988): "Scale effects in tests on footings," Ph. D thesis, Cambridge Univ.
- 31) Leung, C. F., Lee, F. H. and Tan, G. T. S. (1994): Centrifuge 94, Proc. Int. Conf. Geotechnical Centrifuge Modelling, Balkema.
- 32) Liu, P., Massie, W. W., Wolters, J. G. and Blaauwendraad, J. (1991): "Response of jackup models to irregular waves," Paper OTC 6591, Offshore Technology Conference, Vol. 2, pp. 273-282.
- 33) McCarron, W. O. and Broussard, M. D. (1992): "Measured jack-up response and spudcan-seafloor interaction for an extreme storm event," BOSS 92, Vol. 1, pp. 349-361.
- 34) McClelland, B., Young, A. G. and Remmes, B. D. (1982): "Avoiding Jackup rig foundation failures," Geotechnical Engineering, Vol. 13, pp. 151-188; also Proc. Symp. Geotechnical Aspects of Offshore and Nearshore Structures, Balkema, pp. 139-157.
- 35) Murff, J. D., Hamilton, J. M., Dean, E. T. R., James, R. G., Kusakabe, O. and Schofield, A. N. (1991): "Centrifuge testing of foundation behavior using full jackup rig models," Paper OTC 6516, Offshore Technology Conference, Vol. 1, pp. 165-178.
- 36) Murff, J. D., Prins, M. D., Dean, E. T. R., James, R. G. and Schofield, A. N. (1992): "Jackup rig foundation modeling," Paper OTC 6807, Proc. 24th Offshore Technology Conference, Vol. 1, pp. 35-46.
- 37) Nova, R. and Montrasio, L. (1991): "Settlements of shallow foundations on sand," Géotechnique, Vol. 41, No. 2, pp. 243-256.
- 38) Osborne, J. J., Trickey, J. C., Houlsby, G. T. and James, R. G. (1991): "Findings from a joint industry study on foundation fixity of jackup units," Paper OTC 6615, Offshore Technology Conference, Vol. 2, pp. 517-533.
- 39) Poulos, H. G. (1988): Marine Geotechnics, Unwin Hyman.
- 40) Reardon, M. J. (1986): "Review of the geotechnical aspects of jack-up unit operations," Ground Engineering, Vol. 19, No. 7.
- 41) Roscoe, K. H. and Schofield, A. N. (1956): "The stability of short pier foundations in sand," British Welding Journal, August, pp. 343-354.
- 42) Roscoe, K. H. and Schofield, A. N. (1957): Discussion on "The stability of short pier foundations in sand," British Welding Journal, January, pp. 12-19.
- 43) Rowe, P. W. (1983): "Use of large centrifugal models for offshore and nearshore works," Proc. Int. Symp. Geotechnical Aspects of Coastal and Offshore Structures, Bangkok, Yubdhir and Balasubranianiam, A. S. (eds.), Balkema, pp. 21-33.
- 44) Santa Maria, P. E. L. de. (1988): "Behaviour of footings for offshore structures under combined loading", Ph. D thesis, Oxford Univ.
- 45) Schofield, A. N. (1980): "Cambridge geotechnical centrifuge operations," Géotechnique, Vol. 30, No. 3, pp. 227-268.
- 46) Schofield, A. N. (1981): "Dynamic and earthquake geotechnical centrifuge modelling," Proc. Int. Conf. Recent Advances in Soil Dynamics and Earthquake Engineering, Missouri.
- 47) Schotman, G. J. M. (1989): "The effect of displacements on the stability of jackup spudcan-can foundations," OTC 6026, Offshore Technology Conference, Vol. 2, pp. 515-524.
- 48) Senner, D. W. F. (1992): "Analysis of long-term jackup rig foundation performance," Offshore Site Investigation and Foundation Behaviour, Ardu, D. A., Clare, D., Hill, A., Hobbs, R., Jardine, R. J. and Squire, J. M. (eds.) Society for Underwater Technology, Kluwer Academic Publishers, pp. 691-716.
- 49) Shi, Q. (1988): "Centrifuge modelling of surface footings subject to combined loading," Ph. D thesis, Cambridge Univ.
- 50) Silva-Perez, A. A. (1982): "Conical footings under combined loads," M. Phil thesis, Cambridge Univ.
- 51) SNAME, (1994): Site Specific Assessment of Mobile Jackup Units, Technical and Research Bulletin 5-5A, Society of Naval Architects and Marine Engineers, Jersey City, NJ.
- 52) Spidsøe, N. and Karunakaran, D. (1993): "Non-linear dynamic behaviour of jackup platforms," Proc. 4th Int. Conf., The Jackup Platform, Boswell, L. F. and D'Mello, C. (eds.), Bentham Press, London.
- 53) Springett, C. N., Stonor, R. W. P. and Wu, X. (1993): "Results of a jackup measurement programme in the North Sea and the comparison with the structural analysis," Proc. 4th Int. Conf. The Jackup Platform, Boswell, L. F. and D'Mello, C. (eds.), Bentham Press, London.
- 54) Stewart, W. P., White, R. M., Rapoport, V. and Devoy, S. D. (1989): "On-bottom stability of jackups," Paper OTC 6125, Offshore Technology Conference, Vol. 4, pp. 29-38.
- 55) Stewart, W. P., Rapoport, V. and Oser, M. (1991): "Observed storm stability of jackup boats (liftboats)," Paper OTC 6611, Offshore Technology Conference, Vol. 2, pp. 483-492.
- 56) Tan, F. S. C. (1990): "Centrifuge and theoretical modelling of conical footings on sand," Ph. D thesis, Cambridge Univ.

- cal footings on sand," Ph. D thesis, Cambridge Univ.
- 57) Tanaka, H. (1984): "Bearing capacity of footings for jackup platforms," M. Phil thesis, Cambridge Univ.
- 58) Taylor, R. N. (ed.) (1994): *Geotechnical Centrifuge Technology*, Blackie Academic & Scientific.
- 59) Tsukamoto, Y. (1994): "Drum centrifuge tests of three-leg jackups on sand," Ph. D thesis, Cambridge Univ.
- 60) Weaver, T. O. and Brinkmann, C. R. (1995): "Calibration of a dynamic analysis procedure using measurements from a North Sea jackup," Paper OTC 7840, Offshore Technology Conference, Vol. 3, pp. 333-341.
- 61) Wong, P. C., Chao, J. C., Murff, J. D., Dean, E. T. R., James, R. G., Schofield, A. N. and Tsukamoto, Y. (1993): "Jackup rig foundation modelling II," Paper OTC 7303, Offshore Technology Conference.
- 62) Young, A. G., Remmes, B. D. and Meyer, B. J. (1984): "Foundation performance of offshore jackup rig drilling ships," ASCE, J. of Geotech. Engrg., Vol. 110, No. 7, pp. 841-859.