AN ELASTO-VISCOPLASTIC CONSTITUTIVE MODEL WITH STRAIN SOFTENING

TOSHIHISA ADACHIⁱ⁾, FUSAO OKAⁱⁱ⁾ and FENG ZHANGⁱⁱⁱ⁾

ABSTRACT

In this paper, an elasto-viscoplastic constitutive model with strain softening is proposed based on Adachi-Oka's model. In the model, a time measure, instead of strain measure adopted in a previous model, is introduced as an internal variable to account for not only stress history but also time change. The yielding function is defined in the way that the structural deterioration of geologic materials with time is considered. The application of the model to the experimental results for soft sedimentary rock indicates that the model can not only describe the time dependency, such as strain rate dependency, creep and stress relaxation to some extent, but also the strain softening behavior of geologic materials.

Key words: constitutive model, creep, relaxation, strain softening, time dependency (IGC: E1/G1)

INTRODUCTION

It is commonly known that soft sedimentary rock can be linked to many geotechnical engineering problems, such as the instability of cut slopes and foundations. Generally speaking, the mechanical behavior of soft sedimentary rock is elasto-plastic, dilatant, strain hardening-strain softening and time dependent. Physically, soft sedimentary rock has an unconfined compressive strength of 1 ~ 10 MPa and its mechanical behavior exists between the behavior of soil and rock. Its cementation plays an important role in its shear strength. Compared to other geological materials formed in the same geologic era, the void ratio is relatively large and a special structure was formed during sedimentation. Its mechanical behavior during shear is largely dependent on the confined stress and the pore-water pressure. The cementation which existed in the structure, deteriorates due to the breakdown of the structure. Such a breakdown is caused by various processes, such as large shearing deformation, cyclic drying-wetting or stress relaxation. The softening behavior of soft sedimentary rock becomes a very important factor in the long-term stability in geotechnical engineering problems. With regard to time dependent behavior, three aspects are involved, namely, the strain rate effect, creep and stress relaxation. Many models have been proposed to describe the time dependency of geologic materials. They are found in the studies by Andersland

and Al-Nouri (1970), Ting (1983). Singh and Mitchell (1968) clarified the mechanism of creep for soil under undrained condition; Saito and Uezawa (1961) gave an empirical prediction of creep failure time. Oka (1985) proposed a viscoplastic model with memory and an internal variable based on the generalized theory of Wang (1969) and Perzyna (1980). Adachi et al. (1990) proposed a viscoplastic model which can describe both the strain rate effect and strain softening of frozen sand.

With regard to softening behavior, there are two different viewpoints on the subject.

In the first viewpoint, the softening behavior of geologic materials is considered to be an inherited characteristics in a stress-strain relationship, that is, strain softening or material softening. The researchers who share with this viewpoint try to establish a constitutive model that can describe strain softening.

As some researchers have pointed out, however, when a strain softening model is applied to finite element analysis, the stiff matrix will become negative in the softening region and the boundary value problem cannot be defined and solved uniquely. Such a problem was considered by some researchers, for example, Aifantis (1984), Bazant and Pijaudier-Cabot (1988).

In the second viewpoint, the softening behavior is regarded as a consequence of non-uniform deformation occurring in a material which has undergone loading, in other words, the result of localization in deformation.

ⁱ⁾ Professor, Civil Engineering Department, Kyoto University, Yoshida-Honmachi, Sakyo-ku, Kyoto, 606-8317.

ⁱⁱ⁾ Professor, Civil Engineering Department, Gifu University, 1-1, Yanagido, Gifu, 501-1112.

ⁱⁱⁱ⁾ Ph.D., Chuo Fukken Consultants Co., Ltd., 1-8-29 MB32, Nishi-Miyahara, Yodogawa-ku, Osaka, 532-0004.

Manuscript was received for review on May 19, 1995.

Written discussions on this paper should be submitted before January 1, 1999 to the Japanese Geotechnical Society, Sugayama Bldg. 4F, Kanda Awaji-cho 2-23, Chiyoda-ku, Tokyo 101-0063, Japan. Upon request the closing date may be extended one month.

The researchers who share this viewpoint insist that softening is related to localization where a decrease of apparent stress occurs not by strain softening but by a reduction of effective area due to the coalescence of void and micro cracks, and that strain-hardening is the inherited characteristic of geologic materials. Since the localization of deformation is the main cause of softening behavior, the softening behavior can be illustrated by solving the boundary value problems based on strain hardening models.

It is difficult, however, to say that softening behavior can be fully described by analyses based on strain hardening models. The decline of strength caused by structural deterioration in geologic materials can never be neglected. It seems reasonable to say, that the softening behavior is caused both by localization in deformation and structural deterioration in geologic materials. For an engineering approach, the choice of a procedure for providing a drop in nominal stress with strain can be based on convenience because a rigorous development of the methods based on two different viewpoints should provide the same results on a macroscopic basis.

Adachi et al. (1991) published in their research that Adachi-Oka's model with strain softening was applicable to the numerical analyses of the strain-hardening and the strain-softening behaviors of geological materials. Based on the model, the finite element analysis can lead to a unique solution for initial value problems in Valanis's sense (1985) and the analytical results have only a very small dependency on the mesh size. In this paper, a new type of elasto-viscoplastic model is proposed to describe not only strain softening but also strain rate dependency, creep and stress relaxation.

ELASTO-VISCOPLASTIC MODEL WITH STRAIN SOFTENING

Adachi et al. (1990) proposed an elasto-viscoplastic model for frozen sand exhibiting strain softening, using a time measure which is similar to that proposed by Valanis (1971). In this paper, however, the definition of a new incremental time measure is introduced in following form:

$$dz = C \exp(-(z - z_1)/C) dt \quad (1)$$

where dz is an incremental time measure, t is real time and C is the parameter of time dependency which will be discussed in detail later. z_1 is the initial time measure. In the present study, the stress history tensor is expressed by introducing a single exponential type of kernel function similar to that in the previous work by Adachi and Oka (1990), namely,

$$\sigma_{ij}^* = \frac{1}{\tau} \int_0^z \exp(-(z - z')/\tau) \sigma_{ij}(z') dz' \quad (2)$$

where τ is a material parameter which expresses the retardation of stress with respect to the time measure. The total strain increment tensor is composed of the elastic and plastic components:

$$d\epsilon_{ij} = d\epsilon_{ij}^e + d\epsilon_{ij}^p \quad (3)$$

The viscoplastic strain increment is assumed to be determined by the non-associated flow rule,

$$d\epsilon_{ij}^p = H(\partial f_p / \partial \sigma_{ij}) df_y, \quad (4)$$

where f_p is the plastic potential function, f_y is the yield function and H is the loading index describing the hardening-softening characteristics. The subsequent yield function is defined by

$$f_y = \eta^* - \kappa = 0 \quad (5)$$

$$\eta^* = \sqrt{S_{ij}^* S_{ij}^*} / (\sigma_m^* + b) \quad (6)$$

where S_{ij}^* is the deviatoric stress history tensor, b is the plastic potential parameter which can be determined from the assumption that the stress ratio η is kept constant in the over-consolidated region along the M_m -line. σ_m^* is the mean stress history and κ is the strain hardening-softening parameter. The strain hardening-softening parameter is assumed to be given by the following evolutive equation for strain hardening and softening:

$$\dot{\kappa} = \dot{\gamma}^p G' (M_f^* + \kappa)^2 / M_f^{*2} \quad (7)$$

where $\dot{\gamma}^p = (\dot{\epsilon}_{ij}^p \dot{\epsilon}_{ij}^p)^{1/2}$. In the case of proportional loading, it can be integrated as

$$\kappa = M_f^* G' \gamma^p / (M_f^* + G' \gamma^p) \quad (8)$$

where γ^p is the second invariant of the deviatoric plastic strain, that is, $\gamma^p = (e_{ij}^p e_{ij}^p)^{1/2}$. G' and M_f^* are strain hardening-softening parameters. M_f^* was supposed to be constant in the previous study by Adachi et al. (1991). In this paper, it was assumed to change with time because of the structural deterioration of geologic materials. M_f^* takes the form of

$$M_f^* = M_{f\infty}^* + (M_{f0}^* - M_{f\infty}^*) e^{-A(z - z_1)} \quad (9)$$

where $M_{f\infty}^*$ is the residual value of $\eta^* = \sqrt{2J_2^*} / (\sigma_m^* + b)$. A is a material parameter and can be determined by triaxial drained creep tests. M_{f0}^* is dependent on the initial stress and is defined as

$$M_{f0}^* = \begin{cases} \sqrt{2J_2} / \sigma_m|_{at=t=0} & \text{if } \sqrt{2J_2} / \sigma_m|_{at=t=0} > M_{f\infty}^* \\ M_{f\infty}^* & \text{if } \sqrt{2J_2} / \sigma_m|_{at=t=0} \leq M_{f\infty}^* \end{cases} \quad (10)$$

Equation (9) illustrates the deterioration of the shear strength of a given material with the time measure. Figure 1 shows schematically how the failure line changes in relation to time measure in stress history space. The loading conditions are given by the following relationship:

$$d\epsilon_{ij}^p = \begin{cases} \neq 0 & \text{if } f_y = 0, df_y > 0 \quad \text{loading} \\ = 0 & \text{if } f_y = 0, df_y = 0 \quad \text{neutral} \\ = 0 & \text{if } f_y = 0, df_y < 0 \quad \text{unloading} \end{cases} \quad (11)$$

It was assumed that plastic potential function is expressed by the relationship:

$$f_p = \bar{\eta} + \bar{M} \ln [(\sigma_m + b) / (\sigma_{mb} + b)] = 0 \quad (12)$$

where $\bar{\eta} = (S_{ij} S_{ij} / (\sigma_m + b)^2)^{1/2}$, in which S_{ij} is the deviator-

Fig. 1. Variation of M_f^* with time measure

ic stress tensor, σ_m is the mean stress and $\bar{M}$ is the parameter that controls the development of the volumetric strain. σ_{mb} , the plastic potential parameter, is determined by isotropic consolidation tests and takes the value of the pre-consolidated stress.

The concept of boundary surface, introduced in previous studies, is expressed by the following relationship:

$$f_p = \bar{\eta} + \bar{M}_m \ln [(\sigma_m + b)/(\sigma_{mb} + b)] = 0. \quad (13)$$

Based on this relationship, the value of $\bar{M}$ can be determined by considering the following condition:

$$\left\{ \begin{array}{l} \bar{M} = -\bar{\eta} / \ln [(\sigma_m + b)/(\sigma_{mb} + b)] \bar{M} = \bar{M}_m \quad f_b \leq 0 \\ \bar{M} = \bar{M}_m \quad f_b > 0 \end{array} \right\} \quad (14)$$

Combining Eqs. (4), (5), (12), (13), (14), we can derive the following equation for the viscoplastic strain increment tensor:

$$d\epsilon_{ij}^p = \Lambda \left[\frac{\eta_{ij}}{\bar{\eta}} + (\bar{M} - \bar{\eta}) \frac{\delta_{ij}}{3} \right] d\eta^*$$

or

$$d\epsilon_{ij}^p = \Lambda \left[\frac{\bar{\eta}_{ij}}{\bar{\eta}} + (\bar{M} - \bar{\eta}) \frac{\delta_{ij}}{3} \right] \left[\frac{\eta_{kl}^*}{\bar{\eta}^*} - \eta^* \frac{\delta_{kl}}{3} \right] \frac{d\sigma_{kl}^*}{\sigma_m^* + b} \quad (15)$$

where

$$\Lambda = \frac{M_f^{*2}}{G'(M_f^* - \eta^*)^2}, \quad \bar{\eta}_{ij} = S_{ij}/(\sigma_m + b), \quad \eta_{kl}^* = S_{kl}^*/(\sigma_m^* + b). \quad (16)$$

Finally, the elastic strain increment is evaluated by

$$d\epsilon_{ij}^e = d\sigma_{ij}/2G + d\sigma_m \delta_{ij}/3K. \quad (17)$$

APPLICATION TO DRAINED CREEP TESTS ON SOFT ROCK

In drained triaxial creep tests, the stress is kept constant, that is, $\Delta\sigma_{ij} = 0$, $\sqrt{J_2} = \text{const.}$ and $\sigma_m = \text{const.}$ By integrating Eq. (1), the expression for the time measure can

be given in Eq. (18) if we take into consideration the fact that the initial time measure, $z|_{t=0} = z_1$, is usually not equal to zero, namely,

$$z - z_1 = C \ln(1 + t). \quad (18)$$

Here z_1 is the time measure for the time at which the creep tests begin. In drained creep tests, the stress is not applied all at once to the specimens. The loading process from zero to a certain stress state usually takes some time. It is reasonable, therefore, to conclude that the initial time measure is not equal to zero, which means that the stress history tensor will also not be equal to zero. Its value is dependent on the loading rate and the loading path. It can be assumed that the load increases proportionally to time measure z during the interval $[0, z_1]$. The stress history tensor can then be calculated in the following manner:

$$\sigma_{ij}^* = \sigma_{ij1}^* + \sigma_{ij2}^* \quad (19)$$

where

$$\begin{aligned} \sigma_{ij1}^* &= \frac{1}{\tau} \int_0^{z_1} \exp(-(z - z')/\tau) \sigma_{ij}(z') dz' \\ &= \sigma_{ij} \frac{e^{-z/\tau}}{z_1} \int_0^{z_1} e^{z'/\tau} \frac{z'}{\tau} dz' \\ &= \sigma_{ij} e^{-(z - z_1)/\tau} \frac{\tau}{z_1} \left(\frac{z_1}{\tau} - 1 + e^{-z_1/\tau} \right), \end{aligned} \quad (20)$$

is the initial stress history at $t=0$ resulted in the loading process before creep. In creep tests, the stress is kept constant, namely,

$$\begin{aligned} \sigma_{ij2}^* &= \frac{1}{\tau} \int_{z_1}^z \exp(-(z - z')/\tau) \sigma_{ij}(z') dz' \\ &= \sigma_{ij} (1 - e^{-(z - z_1)/\tau}) \end{aligned} \quad (21)$$

$$\sigma_{ij}^* = \sigma_{ij1}^* + \sigma_{ij2}^* = \sigma_{ij} [1 - e^{-(z - z_1)/\tau} g(z_1)] = \sigma_{ij} f(z) \quad (22)$$

$$f(z) = 1 - e^{-(z - z_1)/\tau} g(z_1), \quad g = g(z_1) = \frac{\tau}{z_1} (1 - e^{-z_1/\tau}). \quad (23)$$

In axisymmetric condition, the detailed expression for the deviatoric and the volumetric components of viscoplastic strain can be given algebraically

$$de_{11}^p = \frac{2}{3G} \frac{M_f^{*2}}{(M_f^* - \eta^*)^2} g(z_1) \frac{b q e^{-(z - z_1)/\tau} dz}{(\sigma_m^* + b)^2 \tau} \quad (24)$$

$$dv^p = \Lambda \left(\bar{M} - \frac{\sqrt{2/3} q}{\sigma_m + b} \right) d\eta^* = \left(\bar{M} - \frac{\sqrt{2/3} q}{\sigma_m + b} \right) \sqrt{3/2} de_{11}^p \quad (25)$$

where, $q = \sqrt{3/2} \sqrt{2J_2} = \sqrt{3/2} \sqrt{2/6} (\sigma_1 - \sigma_3) = (\sigma_1 - \sigma_3)$. Equation (24) can be rewritten as

$$\dot{\epsilon}_{11} = \dot{\epsilon}_{11}^p = \frac{2bq}{3G'\tau} g(z_1) \frac{M_f^{*2}}{(M_f^* - \eta^*)^2 (\sigma_m^* + b)^2} \dot{z}(t). \quad (26)$$

Substituting Eq. (18) into Eq. (26), we obtain

$$\begin{aligned} \ln \dot{\epsilon}_{11} &= \ln \frac{2qCg(z_1)}{3G'b\tau} - \frac{C}{\tau} \ln(1 + t) \\ &\quad + 2 \ln \left(\frac{M_f^*}{M_f^* - \eta^*} \frac{b}{\sigma_m^* + b} \frac{1}{\sqrt{1 + t}} \right). \end{aligned} \quad (27)$$

Fig. 2. Time dependent behavior

In Eq. (27), the first term on the right-hand side is constant with respect to time and can be regarded as the initial strain rate. The second and third terms correspond to steady creep and accelerating creep, respectively.

Figure 2 shows schematically the general process of creep failure. From the figure, parameter α , the initial value of the gradient of strain rate with time, can be defined as

$$\alpha = d \ln e_{11} / d \ln (1+t)_{at t=0}. \quad (28)$$

The value of C is defined here as

$$C = \alpha \tau \quad (29)$$

so that,

$$\dot{e}_{11}^0 = \frac{2q\alpha}{3G'b} g \frac{M_f^{*2}}{(M_f^* - \eta_0^*)^2 (\sigma_{m0}^* + b)^2}. \quad (30)$$

In Eq. (31), $\dot{e}_{11}^0 = \dot{e}_{11}|_{t=0}$, and

$$\eta_0^* = \frac{\sqrt{2J_2}(1-g)}{\sigma_m(1-g)+b}, \quad (31)$$

$$\sigma_{m0}^* = \sigma_m(1-g) \quad (32)$$

$$\frac{M_f^{*2}}{(M_f^* - \eta_0^*)^2 (\sigma_{m0}^* + b)^2} = \left\{ \frac{M_f^* b}{M_f^* b + (\sigma_m M_f^* - \sqrt{2J_2})(1-g)} \right\}^2. \quad (33)$$

Because $M_{f,at t=0}^* = M_{f0}^* = \sqrt{2J_2} / \sigma_m$, Eq. (33) will become

$$\frac{M_f^{*2}}{(M_f^* - \eta_0^*)^2 (\sigma_{m0}^* + b)^2} = 1 \quad (34)$$

Based on Eqs. (10), (30), (31), (32), (33), (34), the expression for the initial creep rate is obtained as

$$\dot{e}_{11}^0 = \frac{2q\alpha g(z_1)}{3G'b} = g(z_1) = \frac{3G'b}{2q\alpha} \dot{e}_{11}^0 \quad (35)$$

Based on Eq. (35), parameter $g(z_1)$ can be determined from triaxial drained creep tests. Equation (27) can be rewritten as

$$\ln \dot{e}_{11} = \ln \dot{e}_{11}^0 - \alpha \ln (1+t) + \ln h(t) \quad (36)$$

In Eq. (36), the first term on the right-hand side of the equation represents the initial deviatoric strain creep rate. Because it is difficult to measure the strain rate immediately after the creep stress is applied, the initial deviatoric strain creep rate is determined in such a way that the rate measured one minute after the creep stress state completed its shearing process from zero to the prescribed creep stress coincides with the calculated results. The second term stands for the steady creep strain in the decreasing stage, which can also be called the secondary consolidation. The third term can be regarded as the ac-

(a) deviatoric creep strain rate vs. time

(b) volumetric creep strain rate vs. time

Fig. 3. Comparison between theoretical and experimental results for creep strain rates

celeration of creep strain at rupture. The expression for the accelerating creep strain is

$$h(t) = \left(\frac{M_f^{*2}}{M_f^* - \eta^*} \frac{b}{\sigma_m^* + b} \frac{1}{\sqrt{1+t}} \right)^2 \quad (37)$$

It is known from Eq. (10) that when $\sqrt{2J_2}/\sigma_m|_{at=0} < M_{f\infty}^*$, $M_{f\infty}^* = M_f^*$ is valid. In addition, in a drained creep test, $\sqrt{2J_2}^*/\sigma_m^* = \sqrt{2J_2}/\sigma_m$ is valid. Therefore, when the initial stress ratio is $\sqrt{2J_2}/\sigma_m|_{at=0} < M_{f\infty}^*$, then

$$\eta^* = \frac{\sqrt{2J_2}^*}{\sigma_m^* + b} < \frac{\sqrt{2J_2}^*}{\sigma_m^*} = \frac{\sqrt{2J_2}}{\sigma_m} < M_{f\infty}^* = M_f^* \quad (38)$$

which means that the right-hand side of Eq. (26) will

never become infinite. In other words, creep failure never occurs when the stress ratio $\sqrt{2J_2}/\sigma_m|_{at=0}$ is less than $M_{f\infty}^*$.

In actual application, the drained creep test results for a saturated sample of Ohya stone (porous tuff) deposited in the Miocene Epoch of Tertiary Period were analyzed with the present model. The material parameters of the model are listed in Table 1.

In this study, the results of drained creep tests under confining pressure of 0.1 MPa were considered. Figures 3 and 4 show a comparison between the theoretical and the experimental results for deviatoric and volumetric creep strain rates at a confining pressure of 0.1 MPa. It was

(a) deviatoric creep strain vs. time

(b) volumetric creep strain vs. time

Fig. 4. Comparison between theoretical and experimental results

Table 1. Material parameters of Ohya stone (confining pressure $\sigma_3 = 0.1$ MPa)

K (MPa)	440.3	a	-0.101
G (MPa)	502.9	α	0.614
b (MPa)	2.0	g	0.924
σ_{mb} (MPa)	11.0	G'	1563.0
$\bar{M}_m$	1.694	τ	14.15
		$M_{f\infty}^*$	0.392

Table 2. Comparison of theoretical and experimental results

q (kgf/cm ²)	Creep failure time t , (min)		Minimum strain rate (10 ⁻⁶ %/min)	
	experiment	theory	experiment	theory
40	2923	3765	0.410	0.17
45	253	242	6.0	9.33
50	40	64	26.0	31.5

found that the general characteristics of creep behavior, such as the initial creep rate, the steady creep stage and the creep rupture, can be well simulated.

Table 2 lists the theoretical and experimental results for creep failure times and minimum strain rates.

APPLICATION TO TRIAXIAL SHEAR TESTS ON SOFT ROCK

Drained triaxial shear tests at a constant strain rate are next considered, where, the initial time measure is equal to zero. Equation (18) therefore becomes $z = C \ln(1+t)$. In strain-controlled conventional triaxial tests at a constant strain rate, the following relationships exist:

$$\dot{\epsilon}_{ij} = \dot{\epsilon}_{ij}^e + \dot{\epsilon}_{ij}^p = \text{const} \quad (39)$$

$$\dot{\epsilon}_{ij}^e = \frac{s_{ij}}{2G}, \quad \dot{\epsilon}_v^e = \frac{\sigma_m}{K}, \quad \dot{\epsilon}_{ij}^p = \dot{\epsilon}_{ij}^e + \delta_{ij} \dot{\epsilon}_v^e \quad (40)$$

By considering the relation of $d\sigma_{ij}^* = (\sigma_{ij} - \sigma_{ij}^*)dz/\tau$ (see Appendix I) and Eq. (15), we obtain

$$\begin{aligned} \dot{\epsilon}_{ij}^p = A \left[\frac{\bar{\eta}_{ij}}{\bar{\eta}} + (\bar{M} - \bar{\eta}) \frac{\delta_{ij}}{3} \right] \left[\frac{\eta_{kl}^*}{\eta^*} - \eta^* \frac{\delta_{kl}}{3} \right] \\ \times \frac{1}{\sigma_m^* + b} (\sigma_{kl} - \sigma_{kl}^*) \frac{C}{1+t}. \end{aligned} \quad (41)$$

For this case, unlike the creep, the stress history tensor cannot be integrated explicitly and should be solved by associated differential equations as indicated in Eqs. (39) ~ (41).

The parameter of time dependency C in for this case was determined in the following way. By differentiating Eq. (18), the following relationship was determined

$$dz = \frac{C}{1+t} dt. \quad (42)$$

It is known from experimental results that parameter C is dependent on the shear strain rate. As a reference, the stress history parameter τ was initially determined for the conditions of $\dot{\epsilon}_{11} = \dot{\epsilon}_0 = 1\%/min$, assuming that $C=1$. The value of τ here is denoted by τ_0 . Secondly, by using the curve fitting method, the values of τ at an arbitrary shearing strain rates $\dot{\epsilon}_{11}$ with the same assumption of $C=1$ are evaluated. τ is evaluated in such a way that the theoretical peak strength is the most suitable for comparison with the experimental results. Through this analysis, it was determined for arbitrary shearing strain rates $\dot{\epsilon}_{11}$ and the correspondent τ , that the following relationship exists,

$$\tau = (\dot{\epsilon}_{11} / \dot{\epsilon}_0)^a \tau_0. \quad (43)$$

where a is called the parameter of strain-rate-dependency. By comparing the following two relationship,

$$dz/\tau_0 = dt/\tau_0 / (1+t); \quad dz/\tau = C dt/\tau / (1+t) \quad (44)$$

it can be determined that if the parameter for time dependency C takes the form expressed in Eq. (45), the values of dz/τ will become independent of the strain rate.

$$C = (\dot{\epsilon}_{11} / \dot{\epsilon}_0)^a \quad (45)$$

The proposed model was used to analyze the behavior of Tomuro stone (Koike, 1997), a type of Ohya stone, under a different constant axial strain rate. The strain-controlled conventional triaxial tests was conducted on the specimen at different strain rates with a confining pressure of 0.1 MPa. Figure 5 shows a comparison for stress difference ($q = \sigma_{11} - \sigma_{33}$)-deviatoric strain relation and peak stress difference. The material parameters are listed in Table 3. It was found from the figure that the rate dependency of the sedimentary soft rock can be well simulated. Both the peak value of strength and the residual value of strength can be simulated. It was also found that the theoretical result agreed with the experimental one until the peak value, while in the post peak area, the strain softening predicted by the model is much sharper than the experimental result.

APPLICATION TO DRAINED TRIAXIAL STRESS RELAXATION TESTS

In drained triaxial stress relaxation tests, strain is kept constant. Therefore, $\dot{\epsilon}_{ij} = 0 \Rightarrow \dot{\epsilon}_{ij}^p = -\dot{\epsilon}_{ij}^e$. Being similar to the drained triaxial shearing tests at a constant strain rate, the stress history tensor cannot be integrated explicitly and should be solved by associated differential equations. Since the stress is not applied all at once to the specimen, the loading process from zero to a certain stress state will take some time. In calculating the stress history tensor, therefore, the time spent on the loading process should be considered. For the present case, the stress history tensor σ_{ij}^* cannot be integrated explicitly. It has to be evaluated by solving the associated differential equations. Since it is different from a drained creep test where the starting time $t=0$ is set at the beginning of

Fig. 5. Strain rate dependency

Table 3. Material parameters of Tomuro stone (confining pressure $\sigma_3 = 0.1$ MPa)

K (MPa)	340.2	a	-0.01
G (MPa)	151.1	α	0.614
b (MPa)	0.94	g	0.924
σ_{mb} (MPa)	8.1	G'	803.0
$\bar{M}_m$	1.194	τ	3.16
		$M_{f\infty}^*$	0.676

creep, the starting time here is set at the beginning of loading. It was found that parameter C is dependent on the strain rate in the process where the specimen is loaded to the prescribed stress state. C can then be determined by drained triaxial shear tests.

The proposed model is used to simulate drained triaxial stress relaxation tests. Since drained triaxial stress relaxation tests were not made on Ohya stone, only a theoretical estimate of the stress relaxation could be determined. Figure 6 shows the estimated stress relaxation behavior of Ohya stone using the present model. The

Fig. 6. Stress relaxation

sample was first loaded to a deviatoric stress state of 4 MPa with a confining pressure of 0.1 MPa, the strain ϵ_{11} at the moment being 0.415%.

In order to investigate the influence of the initial strain rate, stress-time relationships at three different values of C were evaluated, that is, $C=2.29$, 2.88 and 3.63, which correspond to the strain rates of 0.025%/min., 0.0025%/min. and 0.00025%/min. at constant strain-rate shearing respectively. It is found from the figure that at shearing process, the stress-time relations show no much difference for different strain rates, with only one-order shift in time axis. Such behavior is thought to be reasonable if comparing it with Fig. 5 in which the stress-strain relations before peak strength also show no much difference. In the process of stress relaxation, the stresses decreases almost linearly at the beginning in stress-logarithmic time axes. After decreased to a certain value, the stress almost remain unchanged. If the value is called as relaxed stress, then the higher the initial strain rate is, the lower the relaxed stress will be. Under the present conditions, the stress relaxation will almost be completed within 10^4 minutes after the relaxation starts and the stress will decrease from 4.0 MPa to 3.6 MPa after 10^7 minutes.

DETERMINATION OF THE PARAMETERS IN THE MODEL

Eleven material parameters are involved in the model, that is, G , K : Young's modules; b , σ_{mb} : plastic potential parameters; G' , A , $M_{f\infty}^*$ strain hardening-softening parameters; τ : stress history parameter; $\bar{M}_m$: parameter of over-consolidated boundary; C : parameters of time dependency and g : parameter of the initial time measure.

Young's modulus and the bulk modulus are determined directly by measuring the tangent to the deviatoric stress-strain curve and the tangent to the volumetric

Fig. 7. Value of C in creep, constant shearing and relaxation

stress-strain curve at the initial stage of loading. The parameter of the over-consolidated boundary, M_m , takes the value of stress ratio $\sqrt{S_{ij}S_{ij}}/(\sigma_m + b)$ at the point where the maximum contraction occurs in the shearing process.

Stress history parameter τ is determined by a process of trial and error using the peak shearing strength. Strain hardening-softening parameter $M_{f\infty}^*$ is determined as the value of η^* for the residual state. G' can be determined as the initial gradient of the stress-strain curve in the unloading-reloading process at the residual state. For parameter A , it was found from creep tests that it increases linearly with stress ratio $\bar{\eta}$ and can be given as $A = A_0 + \bar{\eta}A_1$, where, the value of A_0 is evaluated to be -0.664 and A_1 to be 0.854 based on creep tests at a confining pressure of 0.1 MPa.

For a time dependent constitutive model, the influence on the time measure defined in Eq. (1) from creep, strain rate dependency and stress relaxation of geologic materials should be considered synthetically. Based on previous discussions, the expression for parameter C can be given as

$$C = C(\dot{\epsilon}_{ij}). \quad (46)$$

which means that parameter C is dependent on strain rate tensor $\dot{\epsilon}_{ij}$. Figure 7 shows the values of parameter C for Ohya stone in creep, constant-strain shearing and relaxation. It can be seen from this figure that the value of C in a drained creep test is different from the ones in the drained triaxial shear tests and the drained triaxial stress relaxation tests. The discrepancy is thought to be the result of the assumption that the gradient of the strain rate for the steady state of a drained creep test is kept constant. Further study should be done on this point.

CONCLUSION

In this paper, an elasto-viscoplastic model with memory is proposed for geologic materials. A comparison of the analytical results and the experimental results indicates that it is not only able to describe all the aspects of

time dependency, such as strain rate dependency, creep and stress relaxation, but also the strain softening behavior of geologic materials. Due to the fact, that this model is based on previous work by Oka and Adachi (1985), most of the parameters involved in the model can be determined in the same way as those in the previous work. The new parameters introduced in this model can be determined from triaxial and drained creep tests.

APPENDIX I

For a function expressed as

$$F(x) = \int_{\phi(x)}^{\psi(x)} f(x, t) dt, \quad (a-1)$$

its differential is given by the following relationship

$$F'(x) = f(x, \psi(x))\psi'(x) - f(x, \phi(x))\phi'(x) + \int_{\phi(x)}^{\psi(x)} f'_x(x, t) dt. \quad (a-2)$$

Based on Eqs. (a-2) and (2), it is easy to obtain the relationship given below.

$$\frac{d\sigma_{ij}^*}{dz} = \frac{1}{\tau} (\sigma_{ij} - \sigma_{ij}^*) \quad (a-3)$$

NOTATION

G	elastic shearing modulus
K	elastic volumetric modulus
τ	parameter of stress history tensor
$M_{f\infty}^*$	strain hardening-softening parameters
G'	strain hardening-softening parameters
A	strain hardening-softening parameters
b	plastic potential parameters
σ_{mb}	plastic potential parameters
$\bar{M}_m$	boundary surface parameter
z	time measure
C	time dependent parameter
g	parameter of initial time measure
e_{ij}	deviatoric strain tensor
S_{ij}	deviatoric stress tensor
S_{ij}^*	deviatoric stress history tensor
f_p	plastic potential function
f_y	yield function
f_b	overconsolidated boundary surface
η^*	stress history tensor ratio
η	stress ratio
κ_s	hardening-softening parameter
α	initial gradient of strain rate vs. time at creep
a	parameter of strain-rate-dependency
M_{f0}^*	initial stress ratio

REFERENCES

- Adachi, T., Oka, F. and Poorooshasb, H. B. (1990): "A constitutive model for frozen sand," Trans. of ASME, Vol. 112, pp. 208-212.
- Adachi, T. and Yoshida, N. (1993): "Analysis of excavation in clay shales with high K_0 stress states," Proc. Int. Symp. on Application of Comp. Meth. in Rock Mech. and Engng., Xian, China, pp. 835-842.
- Adachi, T., Zhang, F., Oka, F. and Yashima, A. (1991): "Finite element analysis with strain-softening constitutive model," Proc. 7th Int. Conf. on Computer Methods and Advances in Geomechan-

- ics, Cairns, pp. 535-540.
- 4) Adachi, T., Oka, F. and Yashima, A. (1991): "A finite element analysis of strain localization for soft rock using a constitutive equation with strain softening," *Archive of Applied Mechanics*, No. 61, pp. 183-191.
 - 5) Adachi, T., Zhang, F., Oka, F. and Yashima, A. (1991): "A FEM analysis of strain localization using a non-local strain-softening plasticity," *Proc. 3th Int. Conf. on Constitutive Laws for Engineering Materials, Theory and Application*, Tucson, USA, pp. 83-94.
 - 6) Aifantis, E. C. (1984): "On the microstructural origin of certain inelastic models," *Trans. ASME, J. Mat. Eng. Tech.*, Vol. 106, pp. 326-330.
 - 7) Andersland, O. B. and Al-Nouri, I. (1970): "Time dependent strength behavior of frozen soils," *J. of Mechanics and Foundation Division, ASCE*, Vol. 96, No. SM(4), pp. 1249-1265.
 - 8) Bazant, Z. P. and Pijaudier-Cabot, G. (1988): "Non-local continuum damage, localization, instability and convergence," *J. Appl. Mech.*, ASME, Vol. 55, pp. 287-293.
 - 9) Koike, M. (1997): "Elasto-viscoplastic constitutive model with strain softening for soft rock", Master thesis, Kyoto Univ.
 - 10) Oka, F. (1985): "Elasto/viscoplastic constitutive equation with memory and internal variables," *Computer and Geomechanics*, 1, pp. 59-69.
 - 11) Oka, F. and Adachi, T. (1985): "A constitutive equation of geologic materials with memory," *Proc. 5th Int. Conf. on Numerical Method in Geomechanics*, 1, pp. 293-300.
 - 12) Perzyna, P. (1980): "Memory effects and internal changes of a material," *Int. J. of Nonlinear Mechanics*, Vol. 6, pp. 707-716.
 - 13) Saito, M. and Uezawa, H. (1961): "Failure of soil due to creep," *Proc. 5th Int. Conf. on SMFE, Paris*, pp. 315-318.
 - 14) Singh, A. and Mitchell, J. K. (1968): "General stress-strain-time function for soils," *Proc. ASCE*, Vol. 94, No. SM1, pp. 21-46.
 - 15) Ting, J. M. (1983): "Tertiary creep model for frozen sands," *ASCE J. of Geotechnical Engineering*, Vol. 109, No. 7, pp. 932-945.
 - 16) Valanis, K. C. (1971): "A theory of viscoplasticity without a yielding surface," *Arch. Mech. Stos.* Vol. 23, No. 4, pp. 517-533.
 - 17) Valanis, K. C. (1985): "On the uniqueness of solution of the initial value problem in softening materials," *J. Appl. Mech.*, Vol. 52, pp. 649-653.
 - 18) Wang, C. C. (1969): "Generalized simple bodies," *Arch. Rational Mech. Analysis*, Vol. 32, pp. 1-30.