Studies on the Compounds Related to PCB (VI)

Determination of Polychlorinated Quaterphenyl (PCQ) in Kanemi Rice Oil Caused the "Yusho" and Investigation on the PCQ Formation

(Received January 20, 1978)

Hideaki MIYATA, Yasuyuki MURAKAMI and Takashi KASHIMOTO

(Osaka Prefectural Institute of Public Health: 3-69, Nakamichi 1-chome, Higashinari-ku, Osaka)

Our earlier study revealed that unknown organochlorinated compounds, which were mainly composed of polychlorinated quaterphenyl (PCQ), were present largely in Kanemi rice oil caused the "Yusho."

In this report, in order to determine PCQ in Kanemi rice oil, a simple analytical method for PCQ was established and PCQ standard was prepared.

The actual PCQ level in the oil was 490 to 866 ppm, equivalent to 0.88~3.46 times more than the actual PCB level found in the oil.

Moreover, the chlorine concentration of PCQ in the oil was 207 to 450 ppm by MCD-GC. From this result, it was confirmed that PCQ occupied 72~89% of the unknown in the oil.

In addition to clarify the cause why large quantities of PCQ was present in the oil, Kanechlor 400 (KC-400), which had been used as the thermotransfer media, was analysed for PCQ. Consequently, it became clear that PCQ had generated at level of 690~31,000 ppm in the thermotransfer media.

Therefore, it was investigated whether PCQ would be generated thermochemically from PCB.

KC-400, Japanese commercial PCB preparation containing 48% chlorine, was poured in a glass ampoule. After the ampoule was sealed, it was heated under various conditions. Consequently, it was confirmed that PCQ was generated thermochemically from KC-400 by heating KC-400 at high temperature in a glass ampoule. The PCQ level in KC-400 increased by heating KC-400 at higher temperature and during longer period. Moreover, it was clear that the PCQ formation was more accelerated by heating under the presence of stainless steel and water, and consequently the PCQ concentration in heated KC-400 became the maximum level, 47,000 ppm.

1. Introduction

Previously, we reported that organochlorinated compounds, which were free from PCB and PCDF, were detected largely in Kanemi rice oil caused the "Yusho" and that the chlorine concentration of them was 287 to 537 ppm, equivalent to 1.1~4.1 times more than the chlorine level of PCB in the oil, by neutron activation analysis.^{1),2)} Moreover, GC-MS analysis revealed that the unknown was mainly

composed of polychlorinated quaterphenyls (PCQs).^{1),2)}

In this paper, in order to determine the actual PCQ concentration in Kanemi rice oil, it was attempted to prepare the PCQ standard for the PCQ determination and to establish a simple analytical method for PCQ in samples.

On the other hand, until the present there was only a report that PCQ was generated photochemically from original PCB by irradiating PCB

with UV lamps and sunlight.⁸⁾ However, the result couldn't be applied to the PCQ formation in the Kanemi rice oil.

Therefore, the PCQ formation by heating PCB was investigated.

2. Materials and Methods

2.1 Materials

KC-400: It was distributed to our laboratory in 1972 by the Ministry of Health and Welfare.

Kanemi rice oils: The oils were manufactured on February 5th, 9th, and 10th in 1968, and their lot no. were 821119079, 15520, and 16793, respectively.

KC-400 used as the thermotransfer media: H-1 was used for 1958 to 1972 at 180 to 270°C at a chemical factory. It was opaque dark brown and high viscous liquid. It also had a irritant order which was different from PCB-like order. The brown substance which was not dissolved with *n*-hexane was present in it. H-2

was used for *ca.* 3 years at 200 to 220°C at a factory where the rice oil was produced. It was transparent pale brown liquid and had PCB-like order. H-3 was opaque dark brown and high viscous liquid and had PCB-like order. The temperature and period used were not clear.

2.2 Reagents

Florisil of 60 to 80 mesh was activated overnight at 130°C. Silica gel TLC plate was Wakogel FM Plate (20×20 cm) of Wako Pure Chemical Co. Ltd. Methylene dichloride, ethanol, diethyl ether, *n*-hexane and anhydrous sodium sulfate were reagent for PCB analysis of Wako Pure Chemical Co. Ltd.

2.3 Methods

1) Preparation of PCQ standard

As shown in Scheme 1, PCQ in H-3 was purified by repeating of Florisil column and silica gel thin layer chromatography, checking by gel permeation chromatography (GPC). One

Scheme 1. Procedure for the purification of PCQ in KC-400 used as the thermotransfer medium (H-3)

gram of H-3 was dissolved with 25 ml of *n*-hexane, and each of 1/5 aliquot was put on a Florisil column (20 g, 1.8 cm i.d.) and eluted with: successive 130 ml of *n*-hexane, 50 ml of 2% diethyl ether in *n*-hexane and 100 ml of 5% diethyl ether in *n*-hexane solution. The five third fractions were collected, concentrated and rechromatographed over a Florisil column (20 g, 1.8 cm i.d.). The third fraction was concentrated and purified further by silica gel TLC. Sample was spotted on twelve silica gel plates and developed with *n*-hexane. The portion of UV band corresponding to PCQ in each plate was scraped off, extracted with benzene, concentrated and dried. The residue was dissolved with 3 ml of *n*-hexane and chromatographed with successive 100 ml of *n*-hexane and 100 ml of 5% diethyl ether in *n*-hexane solution on a Florisil column (10 g, 1.5 cm i.d.). The five percentage diethyl ether in *n*-hexane fraction was concentrated, placed on a Florisil column (20 g, 1.8 cm i.d.) and rechromatographed with successive 130 ml of *n*-hexane, 50 ml on 2% diethyl ether in *n*-hexane and 100 ml of 5% diethyl ether in *n*-hexane solution. The third fraction (purified PCQ fraction) was concentrated, dried, kept in a constant temperature box at 85°C, and weighed once an hour until the weight reached a constant value. The impurities in the purified PCQ fraction were examined by FID-GC, ECD-GC and GC-MS.

GC-MS analysis was carried out on a Shimadzu LKB-9000 B equipped with the computer system. GC-MS condition showed following: Column, 1 m×3 mm glass column packed with 2% OV-210 on Gaschrom Q(100/120 mesh); Column, Injector, Ionsorce and Separator temp., 220, 250, 280 and 290°C, respectively; Electron energy, 20 eV; Accel. volt., 3.5 kV; Carrier gas, He (30 ml/min); Scanning, once every ten seconds; Scanning range, 300 to 700 *m/e*. Moreover, the chlorine in the fraction was determined by MCD-GC. MCD-GC condition showed following: Column, 70 cm×2 mm glass column packed with 2% SE-30 on Gaschrom Q(100/120 mesh); Injection temp., 240°C; Detector temp., 250°C; Column temp., programmed from 225 to 250°C (20°C/min); Carrier gas, N₂(35 ml/min); Transfer, Reaction and Outlet temp., 650, 840 and 840°C, respectively; Range, 50 ohm; Reactant gas, O₂ (100 ml/min); Bias volt., 250 mV; Gain, high 360.

2) Purification and determination of PCQ in Kanemi rice oil

Sample was saponified, extracted and concentrated according to the method described previously.²⁾ Ten concentrated extract was put on a Florisil column (20 g, 1.8 cm i.d.) and eluted successively with 130 ml of *n*-hexane, 50 ml of 2% diethyl ether in *n*-hexane and 100 ml of 5% diethyl ether in *n*-hexane solution. The third fraction was analysed By MCD-GC (for the determination of the chlorine content of PCQ) and ECD-GC (for the determination of PCQ). The determination of PCQ was carried out by comparing the total areas in the gas chromatogram of the PCQ fraction with that of PCQ standard.

Fig. 1. Gel permeation chromatograms of Kanemi rice oil eluant from Florisil column with 5% diethyl ether in *n*-hexane solution and the PCQ fraction separated from KC-400 used as the thermotransfer medium¹(H-3)

The ECD-GC condition was described previously.²⁾

3) *Purification and determination of PCQ in KC-400s used as the thermotransfer media and in heated KC-400*

A tenth gram of sample was dissolved with 3 ml of *n*-hexane and chromatographed over a Florisil column (20 g, 1.8 cm i.d.) using to the same method described in (Method-2). The five percentage diethyl ether in *n*-hexane fraction was concentrated, spotted on a silica gel plate and developed with *n*-hexane. The portion of UV band corresponding to PCQ was scraped off, extracted with benzene and concentrated. The extract was analysed for the determination of PCQ.

4) *Heat treatment of KC-400*

KC-400 which had been heated before⁴⁾ was used in this study. KC-400 (2.6 ml) was poured into 8 cm × 1.5 cm i.d. a pyrex glass ampoule. After sealing, it was heated in the electric furnace under various conditions indicated in Table 3.

3. Results and Discussion

3.1 PCQ standard

Fig. 1-A showed the GPC chromatogram of KC-400 used as the thermotransfer medium (H-3). Peak Q, first eluted from the column, might be organochlorinated compounds with higher molecular weight than that of PCQ.

As shown in Fig. 1B, the most of PCB was removed by the first Florisil column-clean up, but the PCQ fraction (5% diethyl ether in *n*-hexane eluant) was fairly contaminated with PCB.

Therefore, the fraction was rechromatographed over a Florisil column, but polar PCB remained in the PCQ fraction (Fig. 1-C).

Then, the PCQ fraction was purified by silica gel thin layer chromatography.

Figure 2 showed the TLC chromatogram of standards and the PCQ fraction. The lowest UV spot (spot Q) corresponded to the peak Q shown in Fig. 1-A. The portion of UV band corresponding to PCQ was scraped off and extracted with benzene. However, the extract was still contaminated with the large amount of hydrocarbons from the adsorbent of the thin layer.

Therefore, the fraction was purified by two more Florisil column chromatographies. As shown

Fig. 2. Thin layer chromatogram of PCB (KC-400), PCT (Aroclor 5460) and the PCQ fraction of H-3 after the second Florisil column-clean up TLC plate, Wakogel FM Plate; mobile phase, *n*-hexane

Fig. 3. Total ion current chromatogram (by GC-MS with the computer system) of the final PCQ fraction

in Fig. 1-D, PCB and the compounds with the higher molecular weight were not shown in the final PCQ fraction, and the weight of the fraction was 18 mg.

However, FID-GC and ECD-GC analysis

revealed that the fraction contained 2% as the impurity.

Figure 3 showed the total ion current chromatogram of the final PCQ fraction.

Figure 4-A, B, C, and D showed the mass

Fig. 4. Mass spectra of scanning No. 10, 45, 120 and 230 as shown in Fig. 3 A, B, C and D showed mass spectrum of scanning No. 10, 45, 120 and 230, respectively.

PeCQ, HxCQ, HpCQ, OCQ, NCQ and DCQ showed penta-, hexa-, hepta-, octa-, nona- and deca-chlorinated quaterphenyl, respectively.

Fig. 5. Possible structure for $M^+(406)$, $M^+(440)$ and $M^+(474)$ in Fig. 4 A and B $n=3\sim5$

spectra of scanning No. 10, 45, 120, and 230, respectively, in Fig. 3. The fragments of PCQ as well as PCB and PCT showed the strong peak at the molecular ion (M^+) and minor peaks at (M^+-70), a fragment eliminated of double chlorine atoms from (M^+). Figure 4A showed that penta- to hepta-chlorinated quaterphenyl were present in the scanning No. 10.

It was supposed that $M^+(406)$, $M^+(440)$ and $M^+(474)$ in Fig. 4-A and B might be cyclic structures of the type depicted in Fig. 5.

Figure 4 also showed that the ratio of the higher chlorinated PCQ increased with increasing of scanning number.

GC-MS analysis became clear that the final PCQ fraction contained bits of unknown compounds but that the fraction mainly composed of penta- to deca-chlorinated quaterphenyls.

Moreover, MCD-GC revealed that the chlorine content of the PCQ fraction was 45.5%.

The PCQ fraction was used as PCQ standard for the determination of PCQ in samples by ECD-GC.

3.2 The PCQ level in Kanemi rice oil caused the "Yusho"

As shown in Fig. 1-E, *n*-hexane extract from

saponified Kanemi rice oil which was manufactured on February 10th in 1968 contained large quantities of non-chlorinated hydrocarbons and PCB. The hydrocarbons and the most amount of PCB were eliminated from the extract by Florisil column-clean up.

As shown in Fig. 1-F, the PCQ fraction contained unknown materials which were appeared to be chlorinated compounds with the higher molecular weight than PCQ, but the unknown didn't disturb the PCQ determination by ECD-GC and MCD-GC analysis because they eluted later than PCQ from GC-column (2% OV-210 on Gaschrom Q).

As shown in Table 1, the chlorine concentration of PCQ in the oil was 207 to 450 ppm.

The values were equivalent to 72~89% of organochlorine compounds, which were free from PCB and PCDF, in the oil reported previously.^{1),2)}

It was supposed that 11~28% of organochlorine compounds might attribute to unknown materials.

The actual PCQ level in the oil also was determined by ECD-GC. As shown in Table 1, the PCQ level in the oil was 490 to 866 ppm, equivalent to 0.88~3.46 times more than the actual PCB level in the oil.

It had been considered that all the chlorine in Kanemi rice oil was derived from PCB, and consequently the PCB concentration was calculated from the total chloride level in the oil in 1969 to 1970.^{8),9)}

However, this study revealed that the estimated PCB concentration was the level which contained

Table 1. The Chlorine Concentration of PCQ, PCB and PCDF in Kanemi Rice Oils Caused the "Yusho"

Production date	Concentration of chlorine (ppm)				PCB ^{e) 5), 6)}	PCDF ^{5), 6)}	PCQ/PCB (g/g)	PCDF/PCB (g/g)
	Original sample	Hexane extract ^{a)}	OC ^{b) 1), 2)}	PCQ				
Feb. 5th, 1968	1,485	997	537	450 (866)	500 (983)	3.98 (7.40)	0.88	0.008
Feb. 9th, 1968	554	443	287	207 (490)	80 (151)	0.95 (1.90)	3.25	0.013
Feb. 10th, 1968	446	462	343	248 (536)	83 (155)	1.15 (2.25)	3.46	0.015
Feb. 21st, 1968	11	13						

^{a)} Hexane extract from the saponified sample

^{b)} Organochlorinated compounds in the hexane extracts from saponified oils that were not PCB nor PCDF

^{c)} The values were calculated from the concentration of PCB with the method of the author *et al.*⁷⁾ The figures in parenthesis show the concentration of each compound.

Table 2. The Concentration of PCQ and PCDF in KC-400s Used as the Thermotransfer Media

Sample	Used temp. (°C)	Used period (year)	Concentration of PCQ (ppm)	Concentration of PCDF (ppm)
H-1	180~270	14	31,000	510
H-2	200~220	ca. 3	690	277
H-3	not clear	not clear	28,000	20

PCB, PCQ, PCDF and bits of unknown organochlorinated compounds. It also became clear that the actual PCB level in the oil was barely as 1/3 to 1/7 times as the estimated PCB level and that the PCQ concentration in the oil was 0.88 to 3.46 times more than the actual PCB level.

3.3 The PCQ formation

It was considered that all organochlorinated compounds in Kanemi rice oil were derived from KC-400 used as the thermotransfer medium, which had leaked out into Kanemi rice oil in the deodorized tank.

Therefore, KC-400s which had been used as

the thermotransfer media were analysed for PCQ.

As shown in Table 2, PCQ was detected in all thermotransfer media, and the PCQ level in them was 690 to 31,000 ppm.

It was supposed that PCQ might generate from KC-400 during the period when KC-400 was used as the thermotransfer media because PCQ wasn't detected in the commercial KC-400 preparation.

In regard to the PCQ formation, there was only a report which PCQ generated photochemically from original PCB by irradiating PCB with UV lamps or sunlight.⁸⁾ Therefore, it was investigated whether PCQ would generate thermo-

Table 3. The Concentration of PCQ and PCDF in Heated KC-400

Heating temp. (°C)	Heating period (day)	Additive	Concentration of PCQ (ppm)	Concentration of PCDF (ppm) ^{a)}
Room temp.	0		0	33
180	5		450	41
250	5		710	40
300	5		2,000	
"	6		5,700	35
"	10		4,000	34
"	15		3,300	41
"	30		11,000	
360	2		7,400	84
"	10		7,300	94
"	20		14,000	65
300	3	S ^{a)}	3,500	55
"	5	S	1,800	46
360	2	S	13,000	188
"	5	S	14,000	182
"	10	S	25,000	205
"	20	S	23,000	77
"	2	W ^{b)}	20,000	223
"	20	W	37,000	212
"	2	S+W	3,800	101
"	20	S+W	47,000	71

^{a)} Stainless steel

^{b)} Water

Fig. 6. Gas chromatograms of PCQ in KC-400 used as the thermotransfer medium (H-3), Kanemi rice oil and heated KC-400s

chemically from PCB by heating KC-400 in a glass ampoule.

As shown in Table 3, it was confirmed that PCQ generated from original KC-400 when KC-400 was heated at high temperature in a glass ampoule. It also became clear that the PCQ level in KC-400 increased by heating at higher temperature and during longer period.

Moreover, the PCQ level increased when KC-400 was heated under the addition of stainless steel. It was supposed that stainless steel might act catalytically on the PCQ formation.

The PCQ level also increased by heating under the addition of water. Perhaps, water increased the pressure in a ampoule, and consequently the PCQ formation might be accelerated.

Therefore, when KC-400 was heated for 20 days at 360°C under the addition of stainless steel and water, the PCQ concentration became the maximum level, 47,000 ppm.

In addition, as shown in Fig. 6, the gas

chromatogram of PCQ in heated KC-400 was more or less different according to the heating condition, especially the additive, *i.e.*, the PCQ composition varied according to the heating condition.

When KC-400 was heated under additives, the ratio of less chlorinated quaterphenyl increased in comparison with PCQ in KC-400 heated only (Fig. 6).

The gas chromatogram of PCQ in Kanemi rice oil was similar to that of PCQ in KC-400 heated only, and also the gas chromatogram of the PCQ standard resembled that of PCQ in KC-400 heated under the addition of stainless steel and water (Fig. 6).

On the other hand, it wasn't correlative between the PCQ and PCDF concentration in the thermotransfer media and in heated KC-400 as shown in Table 2 and 3. This result suggested that the mechanism for the PCQ formation was different from that of the PCDF formation.

From the results described above, it became clear that PCQ generated from original KC-400 during the period when KC-400 was used as the thermotransfer media.

However, the ratios of PCQ/PCB and PCDF/PCB in the thermotransfer media were fairly lower than those of Kanemi rice oil. The difference might be explained as follows: After KC-400 which was used as the thermotransfer medium leaked out into Kanemi rice oil in the deodorization tank, the ratios of PCQ/PCB and PCDF/PCB in the oil might become extraordinarily high by deodorizing.

The authors are currently working to identify additional unknown organochlorinated compounds in Kanemi rice oil and the thermotransfer media, and also to resolve the high ratios of PCQ/PCB and PCDF/PCB in the oil.

References

- 1) Miyata, H., Kashimoto, T., Kunita, N.: J. Food Hyg. Soc. Japan, **19**, 126 (1978).
- 2) Miyata, H., Kashimoto, T., Kunita, N.: *ibid.*, **19**, 364 (1978).
- 3) Hutzinger, O., Jamieson, W.D., Safe, S., MacNeil, D., Zikto, V.: "The Chemistry of PCBs," p. 121 (1974), CRC Press, Ohio.
- 4) Miyata, H., Kashimoto, T.: J. Food Hyg. Soc. Japan, **19**, 78 (1978).

-
- 5) Miyata, H., Kashimoto, T., Kunita, N.: *ibid.*, **18**, 260 (1977).
 - 6) Miyata, H., Watanabe, I., Kashimoto, T., Kunita, N.: Osaka Prefectural Institute of Public Health, ED. of Food Sanitation, **8**, 87 (1977).
 - 7) Ugawa, M., Nakamura, A., Kashimoto, T.: J. Food Hyg. Soc. Japan, **14**, 415 (1973).
 - 8) Tukamoto, H. *et al.*: Fukuoka Acta Med., **60**, 496 (1969).
 - 9) Special report on the prevention, diagnosis and treatment for the "Yusho," Science and Technology Agency, p. 19 (1970).