Dynamic Bayesian Network Model for Production and Inventory Control of Automobile Parts

Ji-Sun Shin, Yeong-Hwa Park, Hee-Hyol Lee

Graduate School of Information, Production and Systems, Waseda University
2-7 Hibikino, Wakamatsu-ku, Kitakyushu, Fukuoka, 808-0135, Japan

E-mail: shinjs1220@ruri.waseda.jp

Abstract

In the manufacturing business, the delivery guarantee of quantities is a prerequisite for improving the credit of corporation and securing profit. However, the delivery quantity, the production quantity, and the inventory is changed according to various unexpected reasons. Then the prediction of production and inventory which can cope with such irregular fluctuations is required. This paper deals with an adjusting production method using the Dynamic Bayesian Network (DBN) for all factors which influence the production quantity, the delivery quantity, and the inventory quantity for an automobile parts production process. This study also provides an adjusting production schedule algorithm that adjusts sequentially the production schedule for appropriate guarantee of the deadline. Furthermore, an adjusting rule of the production quantities to maintain the delivery guarantee is provided.

1 Introduction

In real world applications like intellectual information processing system, it is necessary to cope with uncertain events and observations. Therefore, modeling uncertain relationships among many kinds of variables and predicting such variables are important issues. The Bayesian networks by now are widely accepted as powerful tools for representing and reasoning with uncertainty in decision-support systems.

The Bayesian Network can represent the dependence and the causal relation between uncertain variables by a directed acyclic graph and it is paid to attention recently out of necessity to construct the model based on probabilistic data. The Bayesian Network is a stochastic model that shows the qualitative dependence between two or more random variables by a graph structure and indicates the quantitative relations between individual variable by the conditional probability. And in the Bayesian Network, the variables are represented by nodes, whereas the directed edges are used to express assumed relationships among the nodes. Both nodes and edges are combined in order to form a directed acyclic graph, or a digraph for short.

This paper deals with the production and inventory

control using the Bayesian Network. The production quantities and delivered goods are changed randomly in this problem, and then the total stock is also changed randomly under these conditions. Firstly, the probabilistic distribution of the total stock is calculated through the propagation of the probability on the network. Furthermore, an adjusting rule of the production quantities to maintain the probability of the lower limit and upper bound value of the total stock to a certain value is shown.

2 Construction of DBN model for production and inventory control in an automobile parts production process

The production quantities and the delivered goods are changed randomly in real problem, and then the total stock is also changed irregularly under these conditions.

Dynamic Bayesian Network is applied to the production and inventory control of the automobile part that calculate the probabilistic distribution of the total stock through the propagation of the probability on the network. The target production system is as that:

· Item of the production: :

Automobile engine valve lifter

· Max of production quantity: 1,000,000ea/month

· Actual data period: JAN.2003 ~ DEC.2005

Production quantity for each month is decided by the inventory of previous month and the delivery quantity of the month. However, the production quantity must take into consideration the conditions at the production site. The reason is that the production quantity can be changed according to the trouble of equipments and the outbreak cancels, etc. And, the delivered goods is also assumed that it can be changed randomly according to the order-change, the control of inventory quantities, and the manufacturing trouble, etc. The production process is as follows.

· Production quantities : A_t

· Delivery quantities : D_t

· Total stock : S_t

· Its forecast and an adjustment period of the production schedule hold between m months

($t=1,2,\dots,l$ l : forecast adjustment months).

- Thus, the total stock of the product S_i of i th month can be expressed as eq. (1)

$$S_t = S_{t-1} + A_t - D_t \quad (1)$$

The stochastic model of the production and the inventory control considering the practical dependence of the productions, deliveries, and inventories changed randomly is illustrated in Fig.1. In addition, each factor which corresponds to each node is shown in Table 1.

Fig. 1. Stochastic model of production and inventory by Dynamic Bayesian Network

Table1. The stochastic variable of delivered goods and production

S_i	Inventory quantities	$RACAF_i$	An external diameter processing
D_i	Delivered goods	$RACB_i$	Inferior of B2
RDA_i	The cause of external	$RACBA_i$	Lathe processing
$RDAA_i$	A poor outbreak process	$RACBB_i$	Dimensional check
$RDAB_i$	A poor delivery inspection	$RACBC_i$	An external diameter processing
RDB_i	The cause of in-company	$RACBD_i$	The inside diameter processing
$RDBA_i$	Strike of customer	$RACC_i$	Inferior of DPL
$RDBB_i$	Order-change of A/S products	$RACCA_i$	DPL-lathe processing
$RDBC_i$	Change of production schedule	$RACCB'$	Crowning
A_i	production quantities	$RACCC_i$	Hole-processing
RAA_i	The cause of external	$RACCD_i$	An external diameter processing
$RAAA_i$	Order-change	$RACCE_i$	Hole polishing
RAB_i	The cause of in-company	$RACCF_i$	An external diameter processing
$RABA_i$	Control of Inventory quantity (+)	$RACD_i$	Inferior of assembling
$RABB_i$	Control of Inventory quantity (-)	$RACDA_i$	HOLE -CHECK
RAC_i	Inferior a manufacturing process	$RACDB_i$	CLIP Insertion
$RACA_i$	Inferior of B 1	$RACDC'$	DPL-assembling
$RACAA_i$	Body-lathe processing	$RACDD_i$	Stratification

$RACAB_t$	Hole-processing	$RACDE_t$	Stratification
$RACAC_t$	An external diameter processing	$RACDF_t$	Assembling
$RACAD_t$	Crowning	$RACDG_t$	OIL-pouring
$RACAE_t$	Swaging	$RACE_t$	Product inspection

3 Maintenance of appropriate inventory through production adjusting algorithm

3.1 Prior Probabilistic Distribution

Actual data on the production and delivery for 36 months are shown in Fig.2. Also, Fig.3 represents all factors related to the production and delivery.

Fig.2. Schedule and actual data of production, delivered good and inventory quantities

Fig. 3. Main cause of change

Delivery quantity is changed according to various factors such as the order-change and the manufacturing trouble postponement of delivery. Here, the prior probability on the change of delivery quantity is calculated based on the actual data from January 2003 to December 2005 (36 months). The prior probability is calculated using the quantity and frequency of each factor, and is set as shown in Fig.4.

The prior probability of the internal trouble is shown in Fig.7, and the prior probability of the order change can be founded shown in Fig.8. In addition, the actual production quantity for each month has to take account of the change which results from various factors including the order change, the inventory control and the defect in the process.

These prior probabilities are calculated based on the past data as shown in Fig.9, Fig.10, and Fig.11.

The prior probability of the internal trouble is shown in Fig.7, and the prior probability of the order change can be founded shown in Fig.8. In addition, the actual production quantity for each month has to take account of the change which results from various factors including the order change, the inventory control and the defect in the process. These prior probabilities are calculated based on the past data as shown in Fig.9, Fig.10, and Fig.11.

Fig.4. Prior probability of delivered goods

Fig.5. Prior probability of production quantities

Fig.6. Prior probability of inventory quantities

Fig.7. Prior probability of internal trouble

Fig.8. Prior probability of change of outbreak

Fig.9. Prior probability of order change

Fig.10. Prior probability of control inventory quantity

Fig.11. Prior probability of trouble-amount

Therefore, the probability distribution for the amount of the product A_i in stock of the i th month can be calculated as that:

$$P(S_t^i) = \sum_{S_{t-1}^i} \sum_{A_t^i} \sum_{D_t^i} \sum_{RA\alpha_t}^C \sum_{RD\kappa_t}^B \sum_{RA\alpha\beta}^E \sum_{RD\kappa\lambda}^C \sum_{RA\alpha\beta\gamma}^U \sum_{RA\alpha\beta\gamma\zeta_t}^G \quad (2)$$

$$P(S_t^i | S_{t-1}^i, A_t^i, D_t^i, RA\alpha_t, RD\kappa_t, RA\alpha\beta_t, RD\kappa\lambda_t, RA\alpha\beta\gamma_t, RA\alpha\beta\gamma\zeta_t) \\ P(S_t^i, S_{t-1}^i, A_t^i, D_t^i, RA\alpha_t, RD\kappa_t, RA\alpha\beta_t, RD\kappa\lambda_t, RA\alpha\beta\gamma_t, RA\alpha\beta\gamma\zeta_t) \\ = P(S_t^i | S_{t-1}^i, A_t^i, D_t^i) P(S_{t-1}^i) P(A_t^i) P(D_t^i) \\ \times P(A_t^i | RA\alpha_t, RA\alpha\beta_t, RA\alpha\beta\gamma_t, RA\alpha\beta\gamma\zeta_t) \\ \times P(D_t^i | RD\kappa_t, RD\kappa\lambda_t) \\ \times P(RA\alpha_t | RA\alpha\beta_t, RA\alpha\beta\gamma_t, RA\alpha\beta\gamma\zeta_t) P(RA\alpha_t) \\ \times P(RD\kappa_t | RD\kappa\lambda_t) P(RD\kappa_t) \\ \times P(RA\alpha\beta_t | RA\alpha\beta\gamma_t, RA\alpha\beta\gamma\zeta_t) \\ \times P(RA\alpha\beta_t) P(RD\kappa\lambda_t) P(RA\alpha\beta\gamma_t | RA\alpha\beta\gamma\zeta_t) \\ \times P(RA\alpha\beta\gamma_t) P(RA\alpha\beta\gamma\zeta_t) \quad (3)$$

$$P(S_t^i) = \sum_{S_{t-1}^i} \sum_{A_t^i} \sum_{D_t^i} \sum_{RA\alpha_t}^C \sum_{RD\kappa_t}^B \sum_{RA\alpha\beta}^E \sum_{RD\kappa\lambda}^C \sum_{RA\alpha\beta\gamma}^U \sum_{RA\alpha\beta\gamma\zeta_t}^G \\ P(S_t^i, S_{t-1}^i, A_t^i, D_t^i, RA\alpha_t, RD\kappa_t, RA\alpha\beta_t, RD\kappa\lambda_t, RA\alpha\beta\gamma_t, RA\alpha\beta\gamma\zeta_t) \\ = \sum_{S_{t-1}^i} \sum_{A_t^i} \sum_{D_t^i} \sum_{RA\alpha_t}^C \sum_{RD\kappa_t}^B \sum_{RA\alpha\beta}^E \sum_{RD\kappa\lambda}^C \sum_{RA\alpha\beta\gamma}^U \sum_{RA\alpha\beta\gamma\zeta_t}^G \\ P(S_t^i | S_{t-1}^i, A_t^i, D_t^i) \\ \times P(A_t^i | RA\alpha_t, RA\alpha\beta_t, RA\alpha\beta\gamma_t, RA\alpha\beta\gamma\zeta_t) \\ \times P(D_t^i | RD\kappa_t, RD\kappa\lambda_t) \\ \times P(RA\alpha_t | RA\alpha\beta_t, RA\alpha\beta\gamma_t, RA\alpha\beta\gamma\zeta_t) \\ \times P(RA\alpha\beta_t | RA\alpha\beta\gamma_t, RA\alpha\beta\gamma\zeta_t) \\ \times P(RA\alpha\beta\gamma_t | RA\alpha\beta\gamma\zeta_t) P(RD\kappa_t | RD\kappa\lambda_t) \\ \times P(S_{t-1}^i) P(A_t^i) P(D_t^i) P(RA\alpha_t) P(RA\alpha\beta_t) \\ \times P(RA\alpha\beta\gamma_t) P(RA\alpha\beta\gamma\zeta_t) P(RD\kappa_t) P(RD\kappa\lambda_t) \quad (4)$$

Eq.(2) is simplified as eq.(3) by the D-separation which is the feature of Dynamic Bayesian Network. Therefore, the probability distributions of the inventory quantity are calculable from eq.(4).

3.2 Adjusting Algorithm of Production Schedule

The total stock is decided by an amount of stock of the previous month, delivered goods, and production quantities on the month. But, it is necessary to consider a large amount of the shipment after the month, and to keep more than a certain amount. Then, an adjusting rule of the production schedule to maintain the probability of the lower limit and upper limit value of the total stock to a certain value is necessary.

As an example, the production schedule is improved as that the probabilities of more than the lower limit and upper bound of the total stock don't exceed 5%. Here the lower limit and the upper bound of the amount for the total stock A_i are 100,000 and 1,000,000, respectively.

The algorithm of the improvement rule is shown in Fig.12. The production schedule can be updated automatically by the algorithm.

Fig.12. Adjusting rule of flow chart

3.3 Predictive Distribution of Inventory

The probability distribution of the total stock of one year(2006) based on the initial production schedule of Table 2 is shown in Fig.13.

The production schedule updated by the adjusting algorithm based on the prior probabilities is shown in Fig.14. The new probabilistic distribution of the total stock by this corrected production schedule is as shown in Fig.15.

As the results, it is understood that the probability for the stock to be 100,000 or less has become small more than 5% as shown in Fig.16. And also the probability for the stock to be 1,000,000 or more has become small more than

5% as shown in Fig.16.

The inventory quantity before adjustment and after adjustment is compared with no adjustment as shown in Fig.17. As the results, the actual inventory don't exceed target inventory (200,000 ~ 300,000 products). Therefore, the delivery guarantee goods and the maintenance of appropriate inventory can be achieved by considering the probabilistic changes in the delivery quantity and production quantity using the adjusting production algorithm.

Table 2. Schedule of production (2006year)

Month-Year	Jan-06	Feb-06	Mar-06	Apr-06
Schedule of Delivered goods	800,000	500,000	500,000	600,000
Schedule of Production	550,000	500,000	500,000	500,000
Month-Year	May-06	Jun-06	Jul-06	Aug-06
Schedule of Delivered goods	750,000	700,000	100,000	550,000
Schedule of Production	450,000	500,000	300,000	450,000
Month-Year	Sep-06	Oct-06	Nov-06	Dec-06
Schedule of Delivered goods	600,000	750,000	700,000	700,000
Schedule of Production	750,000	700,000	400,000	450,000

Fig.13. Probability distribution of production schedule

Fig.14. Adjustment of production schedule

Fig.15. Adjustment of probability distribution of production schedule

Fig.16. Adjustment of the lower limit

Fig.17 Inventory quantities of adjusted production and Actual production

4 Conclusions

This paper dealt with the production and inventory control of the automobile part process using the Dynamic Bayesian Network. We consider the real situation in which the production quantities and delivered goods are changed randomly, then the total stock is also changed randomly.

Firstly, the probabilistic distribution of the total stock was calculated through the propagation of the probability on the network. Furthermore, the adjusting rule of the production quantities to maintain the probability of the lower limit and upper bound value of the total stock to a certain value was deduced.

As the result, the production schedule could be updated so as not to exceed the probability of the lower bound value and upper bound value of the amount of stock specified. By this method, the reduction in costs from the excessive production and the expense of the inventory management expense can be expected.

References

- [1] A. Biedermann, F. Taron, Bayesian networks and probabilistic reasoning about scientific evidence when there is a lack of data, *Forensic Science International* 157(2006)
- [2] P. Seferlis N. F. Giannelos: A Tow-lauered Optimization-based Control Strategy for Multi-echelon Supply Chain Networks, *Computers and chemical Engineering*, Vol.28, pp.799-809, 2004
- [3] Takao SUGURO, Mitsuru KURODA: Safety Stock and Reorder Pont for Reordering Pont System with Variable Lead Times, *Journal of Japan Inustrial Management Association*, vol.55, 89-94 (2004)
- [4] Richard E.Neapolitan : *Learning Bayesian Networks* , Prentice Hall (2003)
- [5] Tsuchiya K (1995), Model dynamics and function of a complex system (in Japanese). *Control inf* 39(1):29-34
- [6] Han-Ying Kao, Shia-Hui Huang, Han-Lin Li : Supply chain diagnostics with dynamic Bayesian Networks. *Computers &Industrial Engineering* Vol.49, pp.339-347, (2005)
- [7] Edward A. Siver et al. : *Inventory Managemaent and Production Planning and Scheduling*, John Wiley & Sons Inc (1998)
- [8] Tsuchiya K (1995), Model dynamics and function of a complex system (in Japanese). *Control inf* 39(1):29-34